



Certificate #4301.01

Prüfbericht-Nr.: Test Report No.:	CN22VZ0B 001	Auftrags-Nr.: Order No.:	244434826	Seite 1 von 19 Page 1 of 19
Kunden-Referenz-Nr.: Client Reference No.:	1288983	Auftragsdatum: Order date.:	2022-07-06	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: Test item:	STRÅLA Birch tree with light 60" floor			
Bezeichnung / Typ-Nr.: Identification / Type No.:	J2229 STRÅLA			
Auftrags-Inhalt: Order content:	TÜV Rheinland EMC service			
Prüfgrundlage: Test specification:	FCC 47 CFR Part 15, Subpart B:2020 Class B ICES-005:2018			
Wareneingangsdatum: Date of receipt:	2022-06-26	Refer to the EUT photos file		
Prüfmuster-Nr.: Test sample No.:	A003282875-006			
Prüfzeitraum: Testing period:	Refer to test report			
Ort der Prüfung: Place of testing:	Refer to clause 1.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: / tested by: Jessie Xu		genehmigt von: / authorized by: Hexiong Liu		
Datum: / Date: 2022-08-11 <i>Jessie Xu</i>		Datum: / Date: 2022-08-11 <i>Hexiong Liu</i>		
Stellung: / Position: Project manager		Stellung: / Position: Department manager		
Sonstiges / Other:	FCC ID: FHO-J2229 Test Firm Registration Number: 958801			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V05

Prüfbericht - Nr.: CN22VZ0B 001

Test Report No.:

Seite 2 von 19

Page 2 of 19

TEST SUMMARY

5.1.1 CONDUCTED EMISSION

*Result:**Passed*

5.2.1 RADIATED EMISSION

*Result:**Passed*

Contents

1	TEST SITES	4
1.1	TEST FACILITIES	4
2	GENERAL PRODUCT INFORMATION	5
2.1	PRODUCT FUNCTION AND INTENDED USE	5
2.2	RATINGS AND SYSTEM DETAILS	5
2.3	INDEPENDENT OPERATION MODES	5
2.4	DESCRIPTION OF INTERCONNECTING CABLES	5
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS	5
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES	5
2.7	SUBMITTED DOCUMENTS	5
3	TEST SET-UP AND OPERATION MODES	6
3.1	PRINCIPLE OF CONFIGURATION SELECTION	6
3.2	EQUIPMENT AND CABLE ARRANGEMENT	6
3.3	TEST SOFTWARE	7
3.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	7
3.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	7
4	CONFORMITY DECISION RULE	8
5	TEST RESULTS EMISSION	9
5.1	EMISSION IN THE FREQUENCY RANGE UP TO 30 MHz	9
5.1.1	Conducted emission	9
5.2	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz	13
5.2.1	Radiated emission	13
6	PHOTOGRAPHS OF THE TEST SET-UP	17
7	LIST OF TEST AND MEASUREMENT INSTRUMENTS	18
8	LIST OF FIGURES	19

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:

Seite 4 von 19
Page 4 of 19

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.

Address: No.177, 178, Lane 777 West Guangzhong Road, Jing'an District, Shanghai, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 7 for test and measurement instruments.

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:Seite 5 von 19
Page 5 of 19

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is the ordinary portable luminaire for lighting and similar use. For the further information, refer to the user's manual.

2.2 Ratings and System Details

Product	:	STRÅLA Birch tree with light 60" floor
Model	:	J2229 STRÅLA
Rated input	:	DC 24 V
Rated power	:	3 W
Protection class	:	III
The product was powered by approved SELV LED driver. LED driver information: ICPSW24-3-2, Input: AC 100-240 V, 50/60 Hz, 0,05 A, 4 W; Output: DC 24 V, 0.125 mA, 3 W max.		

2.3 Independent Operation Modes

The basic operation modes are: "ON" and "OFF".

2.4 Description of interconnecting cables

No.	Interface and name	Shielded or not	Specified length (m)
1	Input line of switch	Unshielded	0.95
2	Output line of switch	Unshielded	3

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is less than 108 MHz.

2.7 Submitted Documents

Circuit diagram, user's manual and rating label.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:

1. Radiated emission tests were performed on 2022-07-13.
2. Conducted emission tests were performed on 2022-07-12.

3.2 Equipment and cable arrangement

Block diagram for both conducted emission and radiated emission tests is as follows:



Also refer to photographs on clause 6 for test setups for both conducted emission test and radiated emission test.

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:

Seite 7 von 19
Page 7 of 19

3.3 Test Software

No special test software was used during the tests.

3.4 Special Accessories and Auxiliary Equipment

None.

3.5 Countermeasures to achieve EMC Compliance

No other special measure is employed to achieve the requirement.

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:**Seite 8 von 19**
Page 8 of 19

4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results EMISSION

5.1 Emission in the Frequency Range up to 30 MHz

5.1.1 Conducted emission

Result:		Passed
Date of testing	: 2022-07-12	
Test procedure	: FCC 47 CFR Part 15, Subpart B:2020, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-1	
Frequency range	: 0.15 – 30 MHz	
Limits	: Quasi-peak limit: 0.15 – 0.5 MHz, 66 to 56 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 56 dB μ V; 5 – 30 MHz, 60 dB μ V Average limit: 0.15 – 0.5 MHz, 56 to 46 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 46 dB μ V; 5 – 30 MHz, 50 dB μ V	
Bandwidth of EMI receiver for final measurement	: 9 kHz	
Measurement time for final measurement	: 1 s	
Kind of test site	: Shielded room	
Input voltage	: AC 120 V, 60 Hz	
Operational mode	: Lighting on	
Ambient condition	: Temperature: 24.6 °C; Relative humidity: 42.3 %	
Expanded measurement uncertainty ($k=2$)	: 3.39 dB	

The measurement setup was made according to ANSI C63.4-2014 in a shielded room.

The measurement equipment like test receivers, quasi-peak detector and artificial mains network (AMN) are in compliance with CISPR 16-1 series standards.

The tested object was set-up on a wooden support. The EUT was set 0.8 m away from the AMN. The cord longer than necessary to be connected to the AMN was folded forth and back parallel so as to form a bundle with a length between 0.3 m and 0.4 m.

The disturbance voltage test was performed on the neutral line and phase line of the power supply of the EUT respectively.

The following figures and tables were those measured by an automatic measuring system. Both quasi-peak and average measurements were performed. In the following spectral diagram, “*”

Prüfbericht - Nr.: CN22VZ0B 001

Test Report No.:

Seite 10 von 19

Page 10 of 19

means Quasi-Peak Value and “*” means Average Value results.


Notes on following tables of conducted emission results and conversions:

Level (dB μ V): final measurement results by using quasi-peak detector and average detector

Transd (dB): transducer factor including cable loss, insertion loss of artificial mains network and gain of pre-amplifier (if used)

Margin: Limit (dB μ V) - Level (dB μ V)

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L




Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.898125	34.73	56.00	21.27	L1	9.6
3.901875	35.51	56.00	20.49	L1	9.7
0.785625	35.87	56.00	20.13	L1	9.6
0.369375	41.77	58.52	16.74	L1	9.6
0.358125	42.80	58.77	15.97	L1	9.6
0.189375	44.11	64.06	19.96	L1	9.5

Final Average measurement result:

Frequency (MHz)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166875	34.73	55.12	20.38	L1	9.5
3.901875	24.47	46.00	21.53	L1	9.7
0.886875	23.46	46.00	22.54	L1	9.6
0.369375	28.77	48.52	19.75	L1	9.6
0.785625	24.48	46.00	21.52	L1	9.6
0.346875	31.31	49.04	17.73	L1	9.6

Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
15.601875	26.27	60.00	33.73	N	10.0
3.980625	30.65	56.00	25.35	N	9.6
0.886875	31.65	56.00	24.35	N	9.6
0.875625	31.71	56.00	24.29	N	9.6
0.346875	37.19	59.04	21.85	N	9.6
0.189375	44.03	64.06	20.04	N	9.5

Final Average measurement result:

Frequency (MHz)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
3.935625	21.87	46.00	24.13	N	9.6
0.886875	21.76	46.00	24.24	N	9.6
0.346875	29.61	49.04	19.42	N	9.6
0.166875	34.52	55.12	20.60	N	9.5
0.785625	22.17	46.00	23.83	N	9.6
0.369375	26.70	48.52	21.81	N	9.6

5.2 Emission in the Frequency Range above 30 MHz

5.2.1 Radiated emission

Result:	Passed
----------------	---------------

Date of testing	: 2022-07-13
Test procedure	: FCC 47 CFR Part 15, Subpart B:2020, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-2
Product classification	: Class B
Frequency range	: 30 – 1000 MHz (see Note 1)
Limits	: Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dB μ V/m; 88 – 216 MHz, 43.5 dB μ V/m; 216 – 1000 MHz, 46 dB μ V/m (see Note 2)
Bandwidth of EMI receiver for final measurement	: 120 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Semi-anechoic chamber
Input voltage	: AC 120 V, 60 Hz
Operational mode	: Lighting on
Ambient condition	: Temperature: 24.5 °C; Relative humidity: 45.2 %
Expanded measurement uncertainty (k=2)	: 5.49 dB

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on an 80 cm wooden support above the reference ground plane. The wooden support was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, “×” means quasi-peak test results.

Note 1: The highest frequency in the EUT is less than 108 MHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 1000 MHz.

Note 2: The class B limits of ICES-005:2018 is stricter than those FCC 47 CFR Part 15, Subpart B:2020 for 3 m test distance. Therefore, the former limits are used in following figures and tables.

Prüfbericht - Nr.: CN22VZ0B 001

Test Report No.:

Seite 14 von 19

Page 14 of 19

Notes on following tables of radiated emission results and conversions:

QuasiPeak (dB μ V/m): final measurement results by using quasi-peak detector


Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit (dB μ V/m) - QuasiPeak (dB μ V/m)

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:

Seite 15 von 19
Page 15 of 19


Figure 3: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
30.808333	22.6	1000.0	120.000	120.0	H	150.0	25.0	17.4	40.0
128.746000	16.1	1000.0	120.000	100.0	H	120.0	18.7	27.4	43.5
574.299333	24.9	1000.0	120.000	100.0	H	120.0	26.1	21.1	46.0
713.074000	25.5	1000.0	120.000	100.0	H	120.0	26.2	20.6	46.0
789.122000	26.0	1000.0	120.000	100.0	H	120.0	27.6	20.0	46.0
947.490667	27.4	1000.0	120.000	100.0	H	120.0	28.3	18.6	46.0

Figure 4: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
31.034667	22.9	1000.0	120.000	160.0	V	11.0	24.9	17.2	40.0
139.222000	21.3	1000.0	120.000	100.0	V	174.0	18.1	22.2	43.5
455.927000	22.3	1000.0	120.000	100.0	V	-32.0	24.3	23.7	46.0
683.456667	24.9	1000.0	120.000	100.0	V	-32.0	26.2	21.1	46.0
726.718667	26.2	1000.0	120.000	100.0	V	-32.0	26.6	19.8	46.0
895.110667	27.4	1000.0	120.000	100.0	V	-32.0	28.4	18.6	46.0

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:

Seite 17 von 19
Page 17 of 19

6 Photographs of the Test Set-Up

Refer to the test setup file.

Prüfbericht - Nr.: CN22VZ0B 001
Test Report No.:Seite 18 von 19
Page 18 of 19

7 List of Test and Measurement Instruments

Equip.	Description	Model	Manufacturer	Last Date	Due Date
				DD.MM.YYYY	DD.MM.YYYY
9023229	EMI test receiver	ESR3	Rohde&Schwarz	22.03.2021	31.08.2022
G1811403	Artificial mains network	ENV216	Rohde&Schwarz	04.11.2021	04.11.2022
G1824248	Dual display multimeter	F45	Fluke	18.09.2020	18.09.2022
G1811378	3m modified semi-anechoic chamber	SAC3	Frankonia	27.06.2019	31.08.2022
9042162	EMI test receiver	ESR7	Rohde&Schwarz	02.03.2022	02.03.2023
G1811425	Bilog antenna	CBL 6112D	Teseq	10.03.2020	10.03.2023
G1824845	EMC measurement software	EMC32 (Ver 10.20.01)	Rohde&Schwarz	N/A	N/A

Prüfbericht - Nr.: CN22VZ0B 001

Test Report No.:

Seite 19 von 19

Page 19 of 19

8 List of Figures

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L.....	11
Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N	12
Figure 3: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization.....	15
Figure 4: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization.....	16

End of test report