

5 FCC §2.1091, FCC §15.247(i) & ISED RSS-102 – RF Exposure

5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

According to ISED RSS-102 Issue 5:

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Note: According to MIMO FCC KDB 662911 D02 MIMO with Cross Polarized Antenna v01, Where an FCC rule specifies limits in radiated terms such as EIRP or ERP, the limits apply to the maximum emission that would be observed by a linearly polarized measurement antenna. Therefore, the highest output power from single antenna power was selected to calculate in this section.

5.3 RF exposure evaluation for FCC

BLE:

<u>Maximum output power at antenna input terminal (dBm):</u>	<u>8.90</u>
<u>Maximum output power at antenna input terminal (mW):</u>	<u>7.76</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>2402</u>
<u>Maximum Directional Antenna Gain, typical (dBi):</u>	<u>1.9</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1.55</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.002</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device is compliant with the requirement FCC MPE limit for uncontrolled exposure. The maximum power density at the distance of 20cm is 0.002 mW/cm². Limit is 1.0 mW/cm².

Colocation evaluation: BLE ratio + Wifi ratio < 1

2.4Wifi colocation: $0.002/1 + 0.08/1 = 0.082 < 1$

5Wifi colocation: $0.002/1 + 0.04/1 = 0.042 < 1$

Note: refer to R2402274-247-01 for 2.4Wifi (FCC ID: 2BFSEG400W, IC: 32309-G400W)

Note: refer to R2402274-407 for 5Wifi (FCC ID: 2BFSEG400W, IC: 32309-G400W)

5.4 RF exposure evaluation exemption for IC

BLE

Maximum EIRP power = 8.90 dBm + 1.9 dBi = 10.8 dBm which is lesser than $1.31 \times 10^{-2} f^{0.6834} = 2.68 \text{ W} = 34.28 \text{ dBm}$.

Therefore, the RF exposure Evaluation is exempt.