

SAR TEST REPORT

for

Acer Incorporated

Notebook Computer

Model No.: N24B4; Aspire Lite 15; AL15-41P; AL15-42P; GW15-41P

Brand: acer; Gateway

FCC ID: HLZGW1541P

IC: 1754F-GW1541P

The MAX SAR(1g)	
Body SAR	0.899W/Kg

Maximum SAR Test distance: 0mm

Prepared for : Acer Incorporated

8F., No.88, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City
221 Taiwan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Kefeng Road, Science & Technology Park,
Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Fax: (0755) 26632877



Report Number : ACS-SF25001

Date of Test : Dec.30, 2024 ~ Jan.03, 2025

Date of Report : Jan.20, 2025

TABLE OF CONTENTS

Description	Page
SAR TEST REPORT.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Equipment Under Test.....	5
2. GENERAL DESCRIPTION.....	6
2.1. Product Description For EUT.....	6
2.2. Applied Standards	6
2.3. Device Category and SAR Limits	6
2.4. Test Conditions	7
2.5. Exposure Positions Consideration.....	8
2.6. Standalone SAR Test Exclusion Considerations.....	9
2.7. Block Diagram of connection between EUT and simulators	10
2.8. Test Equipments.....	11
2.9. Laboratory Environment	12
2.10. Measurement Uncertainty	12
3. MEASURE PROCEDURES.....	14
3.1. General description of test procedures	14
4. SAR MEASUREMENTS SYSTEM	15
4.1. SAR Measurement Set-up	15
4.2. ELI Phantom	16
4.3. Device Holder for SAM Twin Phantom.....	17
4.4. DASY5 E-field Probe System.....	18
4.5. E-field Probe Calibration	19
4.6. Scanning procedure	20
5. DATA STORAGE AND EVALUATION	22
5.1. Data Storage	22
5.2. Data Evaluation by SEMCAD	22
6. SYSTEM CHECK.....	24
7. TEST RESULTS.....	26
7.1. Output power.....	26
7.2. System Check & Tissue simulating liquid	32
7.3. Dielectric Performance for Body Tissue simulating liquid.....	37
7.4. Test Results	41
APPENDIX A (Graph Result –WIFI 2.4GHz & WIFI 5GHz)	
APPENDIX B (EUT Photos)	
APPENDIX C (Test Photos)	
APPENDIX D (Calibration Certificate)	

SAR TEST REPORT

Applicant : Acer Incorporated
Manufacturer : Acer Incorporated
Product : Notebook Computer
Model No. : N24B4; Aspire Lite 15; AL15-41P; AL15-42P; GW15-41P
Brand : acer; Gateway
Test Voltage : DC 11.4V

Measurement Standard Used:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- IEC/IEEE 62209-1528: 2020
- IEC62209-1:2016
- IEC62209-2:2010
- IEEE1528-2013
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- RSS-102, Issue 6: 2023
- FCC KDB 447498 D04 v01
- FCC KDB 865664 D01/D02
- FCC KDB 248227 D01 v02r02
- KDB 616217 D04 v01r02
- KDB 941225 D06 v02r01

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. This report contains data that are not covered by the NVLAP accreditation. Also, this report shows that the EUT is technically compliant with the FCC and RSS-102 test requirements.

This report applies to single evaluation of one sample of above mentioned product. And shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd..

Date of Test : Dec.30, 2024 ~ Jan.03, 2025 Date of Report: Jan.20, 2025

Prepared by : April Zeng Reviewed by : Thomas Chen
April Zeng / Assistant Thomas Chen / Assistant Manager



Approved & Authorized Signer :

Signature: _____

REPORT REVISION HISTORY

Edition No.	Revision	Issue Date	Report No.
Original	Initial issue of report	Jan.20, 2025	ACS-SF25001

1. GENERAL INFORMATION

1.1.Description of Equipment Under Test

Applicant	Acer Incorporated	
Applicant Address	8F., No.88, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221 Taiwan	
Manufacturer	Acer Incorporated	
Manufacturer Address	8F., No.88, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221 Taiwan	
Product	Notebook Computer	
Model No.	N24B4; Aspire Lite 15; AL15-41P; AL15-42P; GW15-41P Model Difference declared by applicant: marketing purpose or color deviation	
Brand	acer; Gateway	
FCC ID	HLZGW1541P	
IC	1754F-GW1541P	
Sample Type	Prototype production	
Date of Receipt	Nov.19, 2024	
Date of Test	Dec.30, 2024 ~ Jan.03, 2025	
Operating Mode	BT,WLAN	
Frequency Range	Bluetooth	2402-2480MHz
	802.11 b/g/n(HT20/HT40)	2412MHz~2462MHz
	802.11 a	5150 MHz~5250 MHz
	802.11n(HT20/HT40)	5250 MHz~5350MHz
	802.11ac(VHT20/ VHT40/ VHT80)	5470 MHz~5725 MHz
		5725 MHz~5850 MHz

Antenna Information	
Type of Antenna	FPC Antenna
Antenna Peak Gain	BT Peak Gain:2.93dBi WIFI 2.4GHz Peak Gain: Ant 1:3.63dBi; Ant 2: 2.93dBi WIFI 5 GHz Peak Gain: Ant 1:3.25dBi; Ant 2: 3.77dBi
Remark: This report is for SAR evaluation only. EUT also supports other radio specification as below listed: BDR+EDR (Test report No. ACS-F25001) BLE (Test report No. ACS-F25002) WiFi 2.4GHz (Test report No. ACS-F25003) WiFi 5GHz (Test report No. ACS-F25004) SAR (Test report No. ACS-SF25001) DFS (Test report No. ACS-F25008)	

2. GENERAL DESCRIPTION

2.1. Product Description For EUT

Please refer to section 1.1

2.2. Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- IEC/IEEE 62209-1528: 2020
- IEC62209-1:2016
- IEC62209-2:2010
- IEEE1528-2013
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- RSS-102, Issue 6: 2023
- FCC KDB 447498 D04 v01
- FCC KDB 865664 D01/D02
- FCC KDB 248227 D01 v02r02
- KDB 616217 D04 v01r02
- KDB 941225 D06 v02r01

2.3. Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General

Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

2.4. Test Conditions

2.4.1. Ambient Condition

Ambient Temperature	20 to 24 °C
Humidity	< 60 %

2.4.2. Test Configuration


The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests.

2.4.3 Simultaneous Transmission Description

No.	Type
1.	WLAN2.4G ANT 1+ WLAN2.4G ANT 2+BT ANT 2
2.	WLAN5G ANT 1+ WLAN5G ANT 2+ BT ANT 2

Note: 2.4G and 5G can transmit RF signals at the same time

2.5.Exposure Positions Consideration



Test Sides for SAR tests						
Band	Body					
	Back	Front	Top	Bottom	Left	Right
ANT 1	✓	✓	X	X	X	X
ANT 2	✓	X	X	✓	X	X

Note:

1. The side which has a distance larger than 2.5cm from antenna can be excluded from SAR measurement.

2.6. Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

According to the KDB447498 appendix A, the SAR test exclusion threshold listed as below

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

According to RSS-102 Issue 6 Table 11, the SAR test exclusion threshold for 2450MHz at 0mm test separation distances is 3mW, 5.8GHz is 1mW.

Frequency (MHz)	≤ 5 mm (mW)	10 mm (mW)	15 mm (mW)	20 mm (mW)	25 mm (mW)	30 mm (mW)	35 mm (mW)	40 mm (mW)	45 mm (mW)	> 50 mm (mW)
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296
835	21	32	41	54	72	96	129	172	228	298
1900	6	10	18	33	57	92	138	194	257	323
2450	3	7	16	32	56	89	128	170	209	245
3500	2	6	15	29	50	72	94	114	134	158
5800	1	5	13	23	32	41	54	74	102	128

2.7. Block Diagram of connection between EUT and simulators



(EUT: Notebook Computer)

2.8. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date	Calibration Body
1.	DASY5 SAR Test System	Speag	TX60 L speag	F09/5B1H1/01	NCR	NCR	N/A
2.	ENA SERIES NETWORK ANALYZER	Agilent	E5071C	MY46316760	2024.09.15	2025.09.14	CCIC
3.	Power Meter	Anritsu	ML2487A	6K00003262	2024.06.19	2025.06.18	CCIC
4.	Power Sensor	Anritsu	MA2491A	032516	2024.06.19	2025.06.18	CCIC
5.	Signal Generator	Rohde&Schwarz	SMB100A	181375	2024.03.16	2025.03.15	CCIC
6.	Amplifier	Milmega	ZHL-42W	C620601316	NCR	NCR	N/A
7.	Dipole Validation Kits	Speag	D2450V2	862	2023.05.18	2026.05.17	CCTL
8.	Dipole Validation Kits	Speag	D5GHzV2	1102	2023.05.19	2026.05.18	CCTL
9.	Attenuator	N/A	1527	001	2024.09.15	2025.09.14	CCIC
10.	Date Acquisition Electronics	Speag	DAE4	899	2024.06.06	2025.06.05	CCTL
11.	E-Field Probe	Speag	EX3DV4	3767	2024.08.01	2025.07.31	CCTL
12.	Test Software	Schmid&Partner Englinnering AG	DASY5	52.8.7.1137	NCR	NCR	NCR
13.	Radio Communication Analyzer	Anritsu	MT8821C	6201547828	2024.03.16	2025.03.15	CCIC
14.	Radio Communication Analyzer	Rohde & Schwarz	CMW500	103249	2024.09.15	2025.09.14	CCIC

Note 1: Calibration Method

- a): Calibration conducted by the National Institute of Information and Communications Technology ~ NICT ~ or a designated calibration agency under Article 102-18 paragraph (1) ~ TELEC Engineering Center, Intertek Japan K.K., Keysight Technologies, Inc ~.
- b): Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992) ~ Japan Calibration Service System ~
- c): Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1) ~ TELEC Engineering Center, Intertek Japan K.K., Keysight Technologies, Inc ~.
- d): Calibration conducted by using other equipment that listed above from a) to c)

Note 2: CCIC (Shenzhen) Metrology & Testing Service Co., Ltd

Addr : ShengHui Hongxing Chuangzhi Square, Tongren Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen

2.9.Laboratory Environment

Temperature	Min:20℃,Max.25℃
Relative humidity	Min. = 45%, Max. = 70%
Note: Ambient noise is checked and found very low and in compliance with requirement of standards.	

2.10.Measurement Uncertainty

Test Item	Uncertainty
Uncertainty for SAR test	1g: ±21.2
	10g: ±20.7
Uncertainty for SAR tissue fluid	1g: ±21.1(Conductivity)
	10g: ±20.6(Dielectric properties)
Uncertainty for test site temperature and humidity	±0.6℃

Source	Type	Uncertainty Value (%)	Probability Distribution	K	C1(1g)	C1(10g)	Standard uncertainty u _i (%)1g	Standard uncertainty u _i (%)10g	Degree of freedom V _{eff} or V _i
Measurement system repeatability	A	0.5	N	1		1	0.5	0.5	9
Probe calibration	B	5.9	N	1	1	1	5.9	5.9	∞
Isotropy	B	4.7	R	√3	1	1	2.7	2.7	∞
Linearity	B	4.7	R	√3	1	1	2.7	2.7	∞
Probe modulation response	B	0	R	√3	1	1	0	0	∞
Detection limits	B	1.0	R	√3	1	1	0.6	0.6	∞
Boundary effect	B	1.9	R	√3	1	1	1.1	1.1	∞
Readout electronics	B	1.0	N	1	1	1	1.0	1.0	∞
Response time	B	0	R	√3	1	1	0	0	∞
Integration time	B	4.32	R	√3	1	1	2.5	2.5	∞
RF ambient conditions – noise	B	0	R	√3	1	1	0	0	∞
RF ambient conditions – reflections	B	3	R	√3	1	1	1.73	1.73	∞
Probe positioner mech. restrictions	B	0.4	R	√3	1	1	0.2	0.2	∞
Probe positioning with respect to phantom shell	B	2.9	R	√3	1	1	1.7	1.7	∞
Post-processing	B	0	R	√3	1	1	0	0	∞
Test sample related									
Device holder uncertainty	A	2.94	N	1	1	1	2.94	2.94	M-1
Test sample positioning	A	4.1	N	1	1	1	4.1	4.1	M-1
Power scaling	B	5.0	R	√3	1	1	2.9	2.9	∞
Drift of output power (measured SAR drift)	B	5.0	R	√3	1	1	2.9	2.9	∞
Phantom and set-up									
Phantom uncertainty (shape and thickness tolerances)	B	4.0	R	√3	1	1	2.3	2.1	∞
Algorithm for correcting SAR for deviations in permittivity and conductivity	B	1.9	N	1	1	0.84	1.9	1.6	∞
Liquid conductivity (meas.)	A	0.55	N	1	0.78	0.71	0.24	0.21	M-1
Liquid permittivity (meas.)	A	0.19	N	1	0.23	0.26	0.09	0.06	M
Liquid permittivity – temperature uncertainty	A	5.0	R	√3	0.78	0.71	1.4	1.1	∞
Liquid conductivity – temperature uncertainty	A	5.0	R	√3	0.23	0.26	1.2	0.8	∞
Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^{23} c_i^2 u_i^2}$						10.57	10.32	
Expanded uncertainty (95 % conf. interval)	$u_E = 2u_c$		N	K=2			21.14	20.64	

3. MEASURE PROCEDURES

3.1. General description of test procedures

For the 802.11b/g SAR body tests, a communication link is set up with the test mode software for WIFI mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate. Testing at higher data rates is not required when the maximum average output power is less than 0.25dB higher than those measured at the lowest data rate. SAR is not required for 802.11g channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels. The same test procedure for 802.11a/n/ac mode.

4. SAR MEASUREMENTS SYSTEM

4.1. SAR Measurement Set-up

DASY5 system for performing compliance tests consists of the following items:

- (1) A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- (2) A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage. It issues simulating liquid. The probe is equipped with an optical surface detector system.
- (3) A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- (4) A unit to operate the optical surface detector which is connected to the EOC.
- (5) The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- (6) The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.
- (7) DASY5 software and SEMCAD data evaluation software.
- (8) Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- (9) The generic twin phantom enabling the testing of left-hand and right-hand usage.
- (10) The device holder for handheld mobile phones.
- (11) Tissue simulating liquid mixed according to the given recipes.
- (12) System validation dipoles allowing to validate the proper functioning of the system.




Figure 4.1 SAR Lab Test Measurement Set-up

4.2.ELI Phantom

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.




Figure 4.2 Top View of Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Wooden Support	SPEAG standard phantom table

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters.

On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

The phantom can be used with the following tissue simulating liquids:

*Water-sugar based liquid

*Glycol based liquids

4.3. Device Holder for SAM Twin Phantom

The SAR in the Phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source in 5 mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. An accurate device position is therefore crucial for accurate and repeatable measurement. The position in which the devices must be measured, are defined by the standards.

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r=3$ and loss tangent $\tan \delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.




Figure 4.3 Device Holder

4.4.DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.



Figure 4.4 EX3DV4 E-field Probe

5.4.1. EX3DV4 Probe Specification

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: PRS-T2 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

4.5.E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (Norm X, Norm Y, Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),
 C = Heat capacity of tissue (brain or muscle),
 ΔT = Temperature increase due to RF exposure.
Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:
 σ = Simulated tissue conductivity,
 ρ = Tissue density (kg/m^3).

4.6. Scanning procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the EUT's output power and should vary max. $\pm 5\%$.

The "surface check" measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles.

The difference between the optical surface detection and the actual surface depends on the Probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged.

After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

Zoom Scan

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x7 points within a cube whose base is centered around the maxima found in the preceding area scan.

Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Sheppard's method for extrapolation. For a grid using 7x7x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10g cubes.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x7 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

5. DATA STORAGE AND EVALUATION

5.1.Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.2.Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi
- Diode compression point	Dcpi

Device parameters: - Frequency
- Crest factor cf

Media parameters: - Conductivity
- Density

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the millimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c_f / d_{cpi}$$

With V_i = compensated signal of channel i ($i = x, y, z$)

U_i = input signal of channel i ($i = x, y, z$)

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: $E_i = (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2}$

H-field probes: $H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1} f + a_{i2} f^2) / f$

With V_i = compensated signal of channel i ($i = x, y, z$)

Norm_i = sensor sensitivity of channel i ($i = x, y, z$)

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

= conductivity in [mho/m] or [Siemens/m]

= equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \quad \text{or} \quad P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

6. SYSTEM CHECK

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulates, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the ANNEX A.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.




Figure 6.1: System Check Set-up




Figure 6.3: photos of system

7. TEST RESULTS

7.1. Output power

Bluetooth

Mode	Channel	Output Power (dBm)	Tune UP (dBm)
GFSK	0	5.350	7.000
	39	6.191	7.000
	78	6.228	7.000
8-DPSK	0	8.188	10.000
	39	8.956	10.000
	78	9.009	10.000
BLE1M	0	5.942	7.000
	19	6.193	7.000
	39	6.816	7.000
BLE2M	0	5.501	7.000
	19	6.200	7.000
	39	6.469	7.000

WiFi 2.4GHz

Mode	Channel	Output Power(dBm)		Tune UP (dBm)
		Chain 0	Chain 1	
11b	CH1	15.680	15.780	16.000
	CH6	15.600	15.530	16.000
	CH11	15.470	15.470	16.000
11g	CH1	12.820	12.240	13.000
	CH6	12.410	12.400	13.000
	CH11	12.620	11.840	13.000
11n20	CH1	12.490	11.670	13.000
	CH6	12.280	11.780	13.000
	CH11	12.220	12.070	13.000
11n40	CH3	9.780	9.660	10.000
	CH6	9.370	9.710	10.000
	CH9	9.090	9.760	10.000
11ax20	CH1	11.620	11.070	12.000
	CH6	11.870	11.140	12.000
	CH11	11.240	11.500	12.000
11ax40	CH3	9.350	9.220	10.000
	CH6	8.980	8.990	10.000
	CH9	8.790	9.080	10.000

WiFi 5GHz

Mode	Channel	Output Power(dBm)		Tune UP (dBm)
		Chain 0	Chain 1	
11a	CH36	12.05	12.93	13.500
	CH40	11.97	12.60	13.500
	CH48	12.85	13.47	13.500
11n20	CH36	11.86	12.69	13.500
	CH40	11.59	12.40	13.500
	CH48	12.60	13.39	13.500
11n40	CH38	11.80	12.37	13.500
	CH46	12.35	13.04	13.500
11ac20	CH36	11.92	12.69	13.500
	CH40	11.65	12.45	13.500
	CH48	12.65	13.29	13.500
11ac40	CH38	11.67	12.25	13.500
	CH46	12.27	12.94	13.500
11ac80	CH42	12.01	12.63	13.500
11ax20	CH36	12.03	12.64	13.500
	CH40	11.76	12.32	13.500
	CH48	12.66	13.31	13.500
11ax40	CH38	11.83	12.35	13.500
	CH46	12.37	13.01	13.500
11ax80	CH42	12.15	12.77	13.500

Mode	Channel	Output Power(dBm)		Tune UP (dBm)
		Chain 0	Chain 1	
11a	CH52	13.18	13.09	13.500
	CH60	12.18	11.95	13.500
	CH64	12.81	12.35	13.500
11n20	CH52	13.09	12.94	13.500
	CH60	12.38	11.86	13.500
	CH64	12.80	12.26	13.500
11n40	CH54	12.68	12.72	13.500
	CH62	12.45	12.08	13.500
11ac20	CH52	13.09	12.94	13.500
	CH60	12.41	11.82	13.500
	CH64	12.83	12.31	13.500
11ac40	CH54	12.68	12.66	13.500
	CH62	12.45	11.98	13.500
11ac80	CH58	12.27	12.20	13.500
11ax20	CH52	13.06	13.09	13.500
	CH60	12.39	11.95	13.500
	CH64	12.77	12.31	13.500
11ax40	CH54	12.77	12.69	13.500
	CH62	12.52	12.02	13.500
11ax80	CH58	12.45	12.33	13.500

Mode	Channel	Output Power(dBm)		Tune UP (dBm)
		Chain 0	Chain 1	
11a	CH100	12.33	12.39	13.500
	CH120	12.57	12.43	13.500
	CH140	12.80	13.39	13.500
11n20	CH100	12.28	12.40	13.500
	CH120	12.58	12.39	13.500
	CH140	12.77	13.44	13.500
11n40	CH102	12.44	12.28	13.500
	CH118	12.41	12.34	13.500
	CH134	12.30	12.86	13.500
11ac20	CH100	12.29	12.41	13.500
	CH120	12.60	12.42	13.500
	CH140	12.67	13.41	13.500
11ac40	CH102	12.44	12.38	13.500
	CH118	12.42	12.43	13.500
	CH134	12.32	12.84	13.500
11ac80	CH106	11.97	12.14	13.500
	CH122	11.98	12.00	13.500
11ax20	CH100	12.37	12.47	13.500
	CH120	12.63	12.36	13.500
	CH140	12.78	13.38	13.500
11ax40	CH102	12.44	12.43	13.500
	CH118	12.42	12.47	13.500
	CH134	12.32	13.02	13.500
11ax80	CH106	12.14	12.37	13.500
	CH122	12.15	12.40	13.500

Mode	Channel	Output Power(dBm)		Tune UP (dBm)
		Chain 0	Chain 1	
11a	CH149	12.16	12.75	13.500
	CH157	12.86	12.70	13.500
	CH165	12.04	12.44	13.500
11n20	CH149	12.07	12.38	13.500
	CH157	12.70	12.62	13.500
	CH165	11.89	12.37	13.500
11n40	CH151	12.41	12.37	13.500
	CH159	12.72	12.70	13.500
11ac20	CH149	12.06	12.40	13.500
	CH157	12.74	12.63	13.500
	CH165	11.94	12.31	13.500
11ac40	CH151	12.41	12.38	13.500
	CH159	12.72	12.71	13.500
11ac80	CH155	12.31	12.32	13.500
11ax20	CH149	12.12	12.46	13.500
	CH157	12.78	12.67	13.500
	CH165	11.83	12.41	13.500
11ax40	CH151	12.45	12.44	13.500
	CH159	12.76	12.75	13.500
11ax80	CH155	12.53	12.49	13.500

7.2.System Check & Tissue simulating liquid

Frequency	Description	SAR		Dielectric Parameters (±10% for window)		Temp
		1g	10g	σ (s/m)	ϵ_r	℃
2450MHz	Recommended value	13.5 10.962-16.038	6.29 5.11377-7.46623	1.80 1.62-1.98	39.2 35.28-43.12	/
	Measurement value 2024-12-30	12.4	5.51	1.818	39.440	22.05
5250MHz	Recommended value	8.20 6.1992-10.2008	2.32 1.75856-2.88144	5.07 4.563-5.577	35.5 31.95-39.05	/
	Measurement value 2024-12-31	8.34	2.53	4.52	35.49	22.03
5600MHz	Recommended value	8.20 6.1992-10.2008	2.32 1.75856-2.88144	5.07 4.563-5.577	35.5 31.95-39.05	/
	Measurement value 2025-01-02	7.43	2.17	4.851	35.134	22.03
5750MHz	Recommended value	8.20 6.1992-10.2008	2.32 1.75856-2.88144	5.07 4.563-5.577	35.5 31.95-39.05	/
	Measurement value 2025-01-03	7.21	2.36	5.29	35.211	22.03

Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CW 2450

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:862

Communication System: UID 0, CW (0); Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.818$ S/m; $\epsilon_r = 39.440$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1112
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CW 2450MHz/Area Scan (61x71x1): Interpolated grid: $dx=2.000$ mm, $dy=2.000$ mm

Maximum value of SAR (interpolated) = 16.6 W/kg

Configuration/CW 2450MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 79.77 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 25.7 W/kg

SAR(1 g) = 12.4 W/kg; SAR(10 g) = 5.51 W/kg

Maximum value of SAR (measured) = 14.3 W/kg



Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CW 5250

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1102

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5250 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.52$ S/m; $\epsilon_r = 35.49$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.5, 5.5, 5.5); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1112
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CW 5250MHz/Area Scan (61x71x1): Interpolated grid: $dx=2.000$ mm, $dy=2.000$ mm

Maximum value of SAR (interpolated) = 9.40 W/kg

Configuration/CW 5250MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 42.21 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 27.9 W/kg

SAR(1 g) = 8.34 W/kg; SAR(10 g) = 2.53 W/kg

Maximum value of SAR (measured) = 9.44 W/kg



Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CW 5600

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1102

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.851$ S/m; $\epsilon_r = 35.134$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.85, 4.85, 4.85); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1112
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CW 5600MHz/Area Scan (61x71x1): Interpolated grid: $dx=2.000$ mm, $dy=2.000$ mm

Maximum value of SAR (interpolated) = 8.11 W/kg

Configuration/CW 5600MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 37.57 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 27.7 W/kg

SAR(1 g) = 7.43 W/kg; SAR(10 g) = 2.17 W/kg

Maximum value of SAR (measured) = 8.73 W/kg



Test Laboratory: Audix SAR Lab

Date: 03/01/2025

CW 5750

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1102

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5750 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5750$ MHz; $\sigma = 5.29$ S/m; $\epsilon_r = 35.211$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.91, 4.91, 4.91); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1112
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CW 5750MHz/Area Scan (61x71x1): Interpolated grid: $dx=2.000$ mm, $dy=2.000$ mm

Maximum value of SAR (interpolated) = 8.55 W/kg


Configuration/CW 5750MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 33.99 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 23.9 W/kg

SAR(1 g) = 7.21 W/kg; SAR(10 g) = 2.36 W/kg

Maximum value of SAR (measured) = 8.58 W/kg



7.3.Dielectric Performance for Body Tissue simulating liquid

Frequency		Description	Dielectric Parameters (±10% window)		Temp
			σ (s/m)	ϵ_r	℃
WiFi 2.4GHz (Ant 1)	2412MHz (Back)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.841	38.849	22.05
	2412MHz (Front)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.841	38.849	22.05
	2437MHz (Back)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.873	38.753	22.05
	2462MHz (Back)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.899	38.666	22.05
WiFi 2.4GHz (Ant 2)	2412MHz (Back)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.841	38.849	22.05
	2412MHz (Bottom)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.841	38.849	22.05
	2437MHz (Bottom)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.873	38.753	22.05
	2462MHz (Bottom)	Recommended value	1.80 1.62-1.98	39.20 35.28-43.12	/
		Measurement value 2024-12-30	1.899	38.666	22.05
WiFi 5GHz Band 1 (Ant 1)	5210MHz (Back)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2024-12-31	4.253	37.132	22.03
	5210MHz (Front)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2024-12-31	4.253	37.132	22.03
WiFi 5GHz Band 1 (Ant 2)	5210MHz (Back)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2024-12-31	4.253	37.132	22.03
	5210MHz (Bottom)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2024-12-31	4.253	37.132	22.03

Frequency		Description	Dielectric Parameters (±10% window)		Temp
			σ (s/m)	ϵ_r	°C
WiFi 5GHz Band 2 (Ant 1)	5290MHz (Back)	Recommended value	4.71 4.239-5.181	35.9 32.31-39.49	/
		Measurement value 2025-12-31	4.489	37.049	22.03
	5290MHz (Front)	Recommended value	4.71 4.239-5.181	35.9 32.31-39.49	/
		Measurement value 2025-12-31	4.489	37.049	22.03
WiFi 5GHz Band 2 (Ant 2)	5290MHz (Back)	Recommended value	4.71 4.239-5.181	35.9 32.31-39.49	/
		Measurement value 2025-12-31	4.489	37.049	22.03
	5290MHz (Bottom)	Recommended value	4.71 4.239-5.181	35.9 32.31-39.49	/
		Measurement value 2025-12-31	4.489	37.049	22.03
WiFi 5GHz Band 3 (Ant 1)	5530MHz (Back)	Recommended value	5.07 4.563-5.577	35.5 31.95-39.05	/
		Measurement value 2025-01-02	4.659	36.764	22.03
	5610MHz (Front)	Recommended value	5.07 4.563-5.577	35.5 31.95-39.05	/
		Measurement value 2025-01-02	4.923	35.994	22.03
	5610MHz (Back)	Recommended value	5.07 4.563-5.577	35.5 31.95-39.05	/
		Measurement value 2025-01-02	4.923	35.994	22.03
WiFi 5GHz Band 3 (Ant 2)	5530MHz (Back)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2025-01-02	4.659	36.764	21.04
	5610MHz (Back)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2025-01-02	4.923	35.994	21.04
	5610MHz (Bottom)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2025-01-02	4.923	35.994	21.04

WiFi 5GHz Band 4 (Ant 1)	5775MHz (Back)	Recommended value	4.71 4.239-5.181	35.9 32.31-39.49	/
		Measurement value 2025-01-03	5.125	34.861	21.04
	5775MHz (Front)	Recommended value	4.71 4.239-5.181	35.9 32.31-39.49	/
		Measurement value 2025-01-03	5.12	34.54	21.04
WiFi 5GHz Band 4 (Ant 2)	5775MHz (Back)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2025-01-03	5.125	34.861	21.04
	5775MHz (Bottom)	Recommended value	4.71 4.239 - 5.181	35.90 32.31- 39.49	/
		Measurement value 2025-01-03	5.125	34.861	21.04




Figure 4.4: Liquid depth in the Flat Phantom

7.4. Test Results

Test Mode: WIFI 2.4GHz

SAR Test Record For WIFI 2.4G + BT

SAR Test Record For WIFI 2.4G + BT												
/	Test Mode					Measure			/	Power(dBm)		Report SAR (W/kg)
Remark	Test Position	distance	Band	Mode	Test CH	SAR (W/kg) 1g	SAR (W/kg) 10g	Power Drift (dB)	Duty cycle	Conducted	Tune up	SAR 1g
Ant1	Back	0mm	2.4G	11b	1	0.16	0.077	0.17	0.78	15.68	16	0.221
Ant1	Back	0mm	2.4G	11b	6	0.167	0.08	0.08	0.78	15.6	16	0.235
Ant1	Back	0mm	2.4G	11b	11	0.169	0.081	0.16	0.78	15.47	16	0.245
Ant1	Front	0mm	2.4G	11b	1	0.011	0.00822	-0.12	0.78	15.68	16	0.015
Ant2	Bottom	0mm	2.4G	11b	1	0.209	0.109	0.14	0.78	15.78	16	0.282
Ant2	Back	0mm	2.4G	11b	1	0.112	0.058	0.17	0.78	15.53	16	0.16
Ant2	Bottom	0mm	2.4G	11b	6	0.21	0.108	0.19	0.78	15.53	16	0.3
Ant2	Bottom	0mm	2.4G	11b	11	0.208	0.109	0.07	0.78	15.47	16	0.301
Ant2-BT	Back	0mm	BT	3DH5	78	0.0364	0.00997	0.01	0.95	9.009	10	0.048
Ant2-BT	Bottom	0mm	BT	3DH5	78	0.0411	0.0101	0.01	0.95	9.009	10	0.054

Test Mode: WIFI 5GHz

SAR Test Record For WIFI 5G

SAR Test Record For WIFI 5G												
/	Test Mode					Measure			/	Power(dBm)		Report SAR (W/kg)
Remark	Test Position	distance	Band	Mode	Test CH	SAR (W/kg) 1g	SAR (W/kg) 10g	Power Drift (dB)	Duty cycle	Conducted	Tune up	SAR 1g
Ant1	Back	0mm	Band1	11ax80	42	0.354	0.141	0.09	1	12.15	13.5	0.483
Ant1	Back	0mm	Band2	11ax80	58	0.333	0.137	-0.08	1	12.45	13.5	0.424
Ant1	Back	0mm	Band3	11ax80	106	0.404	0.158	-0.11	1	12.14	13.5	0.553
Ant1	Back	0mm	Band3	11ax80	122	0.412	0.163	0.16	1	12.15	13.5	0.562
Ant1	Back	0mm	Band4	11ax80	155	0.389	0.161	0.15	1	12.53	13.5	0.486
Ant1	Front	0mm	Band1	11ax80	42	0.077	0.048	0.18	1	12.15	13.5	0.105
Ant1	Front	0mm	Band2	11ax80	58	0.077	0.047	-0.19	1	12.45	13.5	0.098
Ant1	Front	0mm	Band3	11ax80	122	0.094	0.055	0.1	1	12.15	13.5	0.128
Ant1	Front	0mm	Band4	11ax80	155	0.097	0.054	0.17	1	12.53	13.5	0.121
Ant2	Bottom	0mm	Band1	11ax80	42	0.149	0.075	-0.17	1	12.77	13.5	0.176
Ant2	Back	0mm	Band1	11ax80	42	0.156	0.082	0.18	1	12.77	13.5	0.185
Ant2	Back	0mm	Band2	11ax80	58	0.125	0.073	0.09	1	12.33	13.5	0.164
Ant2	Bottom	0mm	Band2	11ax80	58	0.121	0.072	0.14	1	12.33	13.5	0.158
Ant2	Back	0mm	Band3	11ax80	106	0.229	0.107	-0.2	1	12.37	13.5	0.297
Ant2	Back	0mm	Band3	11ax80	122	0.229	0.109	-0.13	1	12.4	13.5	0.295
Ant2	Bottom	0mm	Band3	11ax80	122	0.173	0.086	0.06	1	12.4	13.5	0.223
Ant2	Back	0mm	Band4	11ax80	155	0.152	0.085	0.19	1	12.49	13.5	0.192
Ant2	Bottom	0mm	Band4	11ax80	155	0.148	0.081	-0.15	1	12.49	13.5	0.187

Total SAR:

WLAN 2.4G			Total SAR 1g	Limit
Position	Ant1	Ant2		
Back	0.245	0.160	0.405	1.6W/kg
Bottom	-	0.301	0.301	
Front	0.015	-	0.015	

WLAN 2.4G+BT			Total SAR 1g	Limit
Position	BT	Ant1+2		
Back	0.040	0.405	0.445	1.6W/kg
Bottom	0.054	0.301	0.355	
Front	-	0.015	0.015	

WLAN 5G			Total SAR 1g	Limit
Position	Band1			
	Ant1	Ant2		
Back	0.483	0.185	0.668	1.6W/kg
Bottom	-	0.176	0.176	
Front	0.105	-	0.105	

WLAN 5G			Total SAR 1g	Limit
Position	Band2			
	Ant1	Ant2		
Back	0.424	0.164	0.588	1.6W/kg
Bottom	-	0.158	0.158	
Front	0.098	-	0.098	

WLAN 5G			Total SAR 1g	Limit
Position	Band3			
	Ant1	Ant2		
Back	0.562	0.297	0.859	1.6W/kg
Bottom	-	0.223	0.223	
Front	0.128	-	0.128	

WLAN 5G			Total SAR 1g	Limit
Position	Band4			
	Ant1	Ant2		
Back	0.486	0.192	0.678	1.6W/kg
Bottom	-	0.187	0.187	
Front	0.121	-	0.121	

WLAN 5G+BT			Total SAR 10g	Limit
Position	Band1			
	Ant1+2	BT		
Back	0.668	0.040	0.708	1.6W/kg
Bottom	0.176	0.054	0.230	
Front	0.105	-	0.105	

WLAN 5G+BT			Total SAR 10g	Limit
Position	Band2			
	Ant1+2	BT		
Back	0.588	0.040	0.628	1.6W/kg
Bottom	0.158	0.054	0.212	
Front	0.098	-	0.098	

WLAN 5G+BT			Total SAR 10g	Limit
Position	Band3			
	Ant1+2	BT		
Back	0.859	0.040	0.899	1.6W/kg
Bottom	0.223	0.054	0.277	
Front	0.128	-	0.128	

WLAN 5G+BT			Total SAR 10g	Limit
Position	Band4			
	Ant1+2	BT		
Back	0.678	0.040	0.718	1.6W/kg
Bottom	0.187	0.054	0.241	
Front	0.121	-	0.121	

APPENDIX A

Graph Results (WIFI 2.4GHz & WIFI 5GHz)

Test Mode: WIFI 2.4GHz(ANT1):

Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH1(2412MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz), Frequency: 2412 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.841$ S/m; $\epsilon_r = 38.849$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH1(2412MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.191 W/kg

Configuration/CH1(2412MHz Back)/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.723 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.341 W/kg

SAR(1 g) = 0.160 W/kg; SAR(10 g) = 0.077 W/kg

Maximum value of SAR (measured) = 0.177 W/kg



Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH6(2437MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz); Frequency: 2437

MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.873$ S/m; $\epsilon_r = 38.753$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH6(2437MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.196 W/kg

Configuration/CH6(2437MHz Back)/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.896 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.364 W/kg

SAR(1 g) = 0.167 W/kg; SAR(10 g) = 0.080 W/kg

Maximum value of SAR (measured) = 0.187 W/kg



Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH11(2462MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz); Frequency: 2462 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 1.899 \text{ S/m}$; $\epsilon_r = 38.666$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH11(2462MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.191 W/kg

Configuration/CH11(2462MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.705 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.388 W/kg

SAR(1 g) = 0.169 W/kg; SAR(10 g) = 0.081 W/kg

Maximum value of SAR (measured) = 0.184 W/kg



Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH1(2412MHz Front)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz); Frequency: 2412 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.841 \text{ S/m}$; $\epsilon_r = 38.849$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH1(2412MHz Front)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.0123 W/kg

Configuration/CH1(2412MHz Front)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.200 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.0240 W/kg

SAR(1 g) = 0.011 W/kg; SAR(10 g) = 0.00822 W/kg

Maximum value of SAR (measured) = 0.0126 W/kg



Test Mode: WIFI 2.4GHz(ANT2):

Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH1(2412MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz), Frequency: 2412 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.841$ S/m; $\epsilon_r = 38.849$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH1(2412MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.110 W/kg

Configuration/CH1(2412MHz Back)/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.878 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.267 W/kg

SAR(1 g) = 0.112 W/kg; SAR(10 g) = 0.058 W/kg

Maximum value of SAR (measured) = 0.121 W/kg



Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH1(2412MHz Bottom)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz); Frequency: 2412 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.841 \text{ S/m}$; $\epsilon_r = 38.849$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH1(2412MHz Bottom)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.242 W/kg

Configuration/CH1(2412MHz Bottom)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.653 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.512 W/kg

SAR(1 g) = 0.209 W/kg; SAR(10 g) = 0.109 W/kg

Maximum value of SAR (measured) = 0.232 W/kg



Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH6(2437MHz Bottom)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz); Frequency: 2437

MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.873$ S/m; $\epsilon_r = 38.753$; $\rho =$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH6(2437MHz Bottom)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.245 W/kg

Configuration/CH6(2437MHz Bottom)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.643 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.514 W/kg

SAR(1 g) = 0.210 W/kg; SAR(10 g) = 0.108 W/kg

Maximum value of SAR (measured) = 0.232 W/kg



Test Laboratory: Audix SAR Lab

Date: 30/12/2024

CH11(2462MHz Bottom)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps) (0);

Communication System Band: ISM 2.4GHz Band (2400.0-2483.5MHz); Frequency: 2462 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 1.899 \text{ S/m}$; $\epsilon_r = 38.666$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.6, 7.6, 7.6); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH11(2462MHz Bottom)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.242 W/kg

Configuration/CH11(2462MHz Bottom)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.724 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.512 W/kg

SAR(1 g) = 0.208 W/kg; SAR(10 g) = 0.109 W/kg

Maximum value of SAR (measured) = 0.232 W/kg



Test Mode: WIFI 5GHz-Band 1(ANT1):

Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH42(5210MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.2GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.2GHz; Frequency: 5210 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5210 \text{ MHz}$; $\sigma = 4.253 \text{ S/m}$; $\epsilon_r = 37.132$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.5, 5.5, 5.5); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH42(5210MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.427 W/kg

Configuration/CH42(5210MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.86 V/m ; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.354 W/kg ; SAR(10 g) = 0.141 W/kg

Maximum value of SAR (measured) = 0.418 W/kg



Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH42(5210MHz Front)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.2GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.2GHz; Frequency: 5210 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5210 \text{ MHz}$; $\sigma = 4.253 \text{ S/m}$; $\epsilon_r = 37.132$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.5, 5.5, 5.5); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH42(5210MHz Front)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.0847 W/kg

Configuration/CH42(5210MHz Front)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.012 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.183 W/kg

SAR(1 g) = 0.077 W/kg; SAR(10 g) = 0.048 W/kg

Maximum value of SAR (measured) = 0.0860 W/kg



Test Mode: WIFI 5GHz-Band 1(ANT2):

Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH42(5210MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.2GHz (0); Communication

System Band: IEEE 802.11ax80 WiFi 5.2GHz; Frequency: 5210 MHz; Communication

System PAR: 0 dB

Medium parameters used: $f = 5210 \text{ MHz}$; $\sigma = 4.253 \text{ S/m}$; $\epsilon_r = 37.132$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.5, 5.5, 5.5); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH42(5210MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.138 W/kg

Configuration/CH42(5210MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.513 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.389 W/kg

SAR(1 g) = 0.156 W/kg; SAR(10 g) = 0.082 W/kg

Maximum value of SAR (measured) = 0.169 W/kg



Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH42(5210MHz Bottom)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.2GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.2GHz; Frequency: 5210 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5210 \text{ MHz}$; $\sigma = 4.253 \text{ S/m}$; $\epsilon_r = 37.132$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.5, 5.5, 5.5); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH42(5210MHz Bottom)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.160 W/kg

Configuration/CH42(5210MHz Bottom)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.961 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.384 W/kg

SAR(1 g) = 0.149 W/kg; SAR(10 g) = 0.075 W/kg

Maximum value of SAR (measured) = 0.184 W/kg



Test Mode: WIFI 5GHz-Band 2(ANT1):

Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH58(5290MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.3GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.3GHz ; Frequency: 5290 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5290 \text{ MHz}$; $\sigma = 4.489 \text{ S/m}$; $\epsilon_r = 37.049$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.32, 5.32, 5.32); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH58(5290MHz Front)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.399 W/kg

Configuration/CH58(5290MHz Front)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.706 V/m ; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.333 W/kg ; SAR(10 g) = 0.137 W/kg

Maximum value of SAR (measured) = 0.374 W/kg



Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH58(5290MHz Front)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.3GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.3GHz ; Frequency: 5290 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5290 \text{ MHz}$; $\sigma = 4.489 \text{ S/m}$; $\epsilon_r = 37.049$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.32, 5.32, 5.32); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH58(5290MHz Front)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.0828 W/kg

Configuration/CH58(5290MHz Front)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.239 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.181 W/kg

SAR(1 g) = 0.077 W/kg; SAR(10 g) = 0.047 W/kg

Maximum value of SAR (measured) = 0.0876 W/kg



Test Mode: WIFI 5GHz-Band 2(ANT2):

Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH58(5290MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.3GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.3GHz ; Frequency: 5290 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5290 \text{ MHz}$; $\sigma = 4.489 \text{ S/m}$; $\epsilon_r = 37.049$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.32, 5.32, 5.32); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH58(5290MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.121 W/kg

Configuration/CH58(5290MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.869 V/m ; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.301 W/kg

SAR(1 g) = 0.125 W/kg ; SAR(10 g) = 0.073 W/kg

Maximum value of SAR (measured) = 0.148 W/kg



Test Laboratory: Audix SAR Lab

Date: 31/12/2024

CH58(5290MHz Bottom)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.3GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.3GHz ; Frequency: 5290 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5290 \text{ MHz}$; $\sigma = 4.489 \text{ S/m}$; $\epsilon_r = 37.049$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.32, 5.32, 5.32); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH58(5290MHz Bottom)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.142 W/kg

Configuration/CH58(5290MHz Bottom)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.699 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.407 W/kg

SAR(1 g) = 0.121 W/kg; SAR(10 g) = 0.072 W/kg

Maximum value of SAR (measured) = 0.179 W/kg



Test Mode: WIFI 5GHz- Band 3(ANT1):

Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CH106(5530MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.5GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.5GHz; Frequency: 5530 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5530 \text{ MHz}$; $\sigma = 4.659 \text{ S/m}$; $\epsilon_r = 36.764$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.93, 4.93, 4.93); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH106(5530MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.505 W/kg

Configuration/CH106(5530MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.206 V/m ; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.404 W/kg ; SAR(10 g) = 0.158 W/kg

Maximum value of SAR (measured) = 0.484 W/kg



Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CH122(5610MHz Front)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.5GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.5GHz; Frequency: 5610 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5610 \text{ MHz}$; $\sigma = 4.923 \text{ S/m}$; $\epsilon_r = 35.994$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.85, 4.85, 4.85); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH122(5610MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.193 W/kg

Configuration/CH122(5610MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 0 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.094 W/kg; SAR(10 g) = 0.055 W/kg

Maximum value of SAR (measured) = 0.104 W/kg



Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CH122(5610MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.5GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.5GHz; Frequency: 5610 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5610 \text{ MHz}$; $\sigma = 4.923 \text{ S/m}$; $\epsilon_r = 35.994$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.85, 4.85, 4.85); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH122(5610MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.515 W/kg

Configuration/CH122(5610MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.848 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.412 W/kg; SAR(10 g) = 0.163 W/kg

Maximum value of SAR (measured) = 0.478 W/kg



Test Mode: WIFI 5GHz- Band 3(ANT2):

Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CH106(5530MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.5GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.5GHz; Frequency: 5530 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5530 \text{ MHz}$; $\sigma = 4.659 \text{ S/m}$; $\epsilon_r = 36.764$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.93, 4.93, 4.93); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH106(5530MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.229 W/kg

Configuration/CH106(5530MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.334 V/m ; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 0.600 W/kg

SAR(1 g) = 0.229 W/kg ; SAR(10 g) = 0.107 W/kg

Maximum value of SAR (measured) = 0.266 W/kg



Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CH122(5610MHz Back)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.5GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.5GHz; Frequency: 5610 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5610 \text{ MHz}$; $\sigma = 4.923 \text{ S/m}$; $\epsilon_r = 35.994$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.85, 4.85, 4.85); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH122(5610MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.241 W/kg

Configuration/CH122(5610MHz Back)/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.375 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.588 W/kg

SAR(1 g) = 0.229 W/kg; SAR(10 g) = 0.109 W/kg

Maximum value of SAR (measured) = 0.242 W/kg



Test Laboratory: Audix SAR Lab

Date: 02/01/2025

CH122(5610MHz Bottom)

DUT: Notebook Computer M/N:N24B4

Communication System: UID 0, IEEE 802.11ax80 WiFi 5.5GHz (0); Communication System Band: IEEE 802.11ax80 WiFi 5.5GHz; Frequency: 5610 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 5610 \text{ MHz}$; $\sigma = 4.923 \text{ S/m}$; $\epsilon_r = 35.994$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.85, 4.85, 4.85); Calibrated: 01/08/2024;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2024
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: xxxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Configuration/CH122(5610MHz Back)/Area Scan (51x71x1): Interpolated grid:

$dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.168 W/kg

Configuration/CH122(5610MHz Back)/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.437 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.477 W/kg

SAR(1 g) = 0.173 W/kg; SAR(10 g) = 0.086 W/kg

Maximum value of SAR (measured) = 0.206 W/kg

