

FCC 47 CFR MPE REPORT

Shenzhen KingChuang Smart Navi Technology Co.,Ltd.

Robot Vacuum Cleaner

Model Number: SL68

Additional Model:

SL40,SL68 Plus,SL68 Plus+,SL68 Pro,SL68 Pro+,SL68 Max,SL68 Max+,SL68 Pure,
SL68 Ultra,SL68 MaxV,B12,B12 Plus,B12 Plus+,B12 Pro,B12 Pro+,B12 Max,B12 Max+,
B12 Pure,B12 Ultra,B12 MaxV,SL40A,SL40B,SL40C SL40D,SDL40,SDL40A,SDL40B,
SDL40C,SDL40D,Mars01,Mars01 Pro,Mars01 Nex,V9,V9 Pro,V9 SE,M500L,L9S,L8000,
L8000 Pro,L8500,L8500 Pro,L8000 Plus,L8000 Pro Plus,L8500 Plus,L8500 Pro Plus,
L8000 +,L8000 Pro +,L8500 +,L8500 Pro +,V-RVCLM40A

FCC ID: 2BA3GKFTYRM24

Applicant:	Shenzhen KingChuang Smart Navi Technology Co.,Ltd.
Address:	Building 10, Furong Industrial Zone, 177 Furong Avenue, Xinqiao Street, Baoan District, Shenzhen, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2309161-2
Date of Test:	Aug. 07, ~Sep. 21, 2023
Date of Report:	Jan. 31, 2024

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
BLE 1M	2402	-1.04	0.787
	2440	-1.57	0.697
	2480	-1.76	0.667
IEEE 802.11b	2412	14.02	25.235
	2437	13.74	23.659
	2462	13.68	23.335
IEEE 802.11g	2412	14.35	27.227
	2437	14.46	27.925
	2462	14.24	26.546
IEEE 802.11n HT20	2412	14.33	27.102
	2437	14.44	27.797
	2462	14.13	25.882
IEEE 802.11n HT40	2422	14.65	29.174
	2437	14.65	29.174
	2452	14.34	27.164

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
				(dBi)	(Linear)			
2.4G Band								
BLE 1M	-1.04	-1±1	0	4.5	2.818	0.00056	1	Complies
IEEE 802.11b	14.02	14±1	15	4.5	2.818	0.01773	1	Complies
IEEE 802.11g	14.46	14±1	15	4.5	2.818	0.01773	1	Complies
IEEE 802.11n HT20	14.44	14±1	15	4.5	2.818	0.01773	1	Complies
IEEE 802.11n HT40	14.65	14±1	15	4.5	2.818	0.01773	1	Complies

End of Test Report