



中国认可
国际互认
检测
TESTING
CNAS L5313



DEKRA

RF Exposure Evaluation Declaration

Product Name : Xiaomi Router 3 Pro

Model No. : R3P

FCC ID : 2AIMRMIWIFIR3P

Applicant : Beijing Xiaomi Electronics Co.,Ltd

Address : Room 707,7F, Building 5, No 58, JinghaiWulu Road,
Beijing, China

Date of Receipt : Apr. 26 , 2017

Test Date Apr. 26 , 2017~ May. 25, 2017

Issued Date : Aug. 16, 2017

Report No. : 1742141R-RF-US-P20V01

Report Version : V1.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Aug. 16, 2017

Report No. : 1742141R-RF-US-P20V01



Product Name : Xiaomi Router 3 Pro

Applicant : Beijing Xiaomi Electronics Co.,Ltd

Address : Room 707,7F, Building 5, No 58, JinghaiWulu Road,
Beijing, China

Manufacturer : Nanning Fugui Precision Industrial Co.,Ltd.Shajing
Branch

Address : No. 51 Tongle Road, Foxconn Industrial Park .District
Jiangnan .NanNing City,GuangXi China

Model No. : R3P

FCC ID : 2AIMRMIWIFIR3P

Brand Name : MI

EUT Voltage : DC12V, 1.5A

Applicable Standard : KDB 447498D01V06
FCC Part1.1310

Test Result : Complied

Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.
Corporation - Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,
215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By :



(Adm. Specialist: Kitty Li)

Reviewed By :



(Senior Engineer: Frank He)

Approved By :



(Engineering Manager : Harry Zhao)

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	Xiaomi Router 3 Pro
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Antenna Information:

2.4G:

Antenna manufacturer	Dongguan renfeng electronic technology co., LTD												
Antenna Delivery	☒	1*TX+1*RX		☒	2*TX+2*RX		☐	3*TX+3*RX		☒	4*TX+4*RX		
Antenna technology	☒	SISO											
	☒	MIMO	☐	Basic									
			☐	Sectorized antenna systems									
			☐	Cross-polarized antennas									
			☐	Unequal antenna gains, with equal transmit powers									
			☐	Spatial Multiplexing									
			☒	CDD									
			☒	Beam-forming									
Antenna Type	☒	External		☒	Dipole								
	☐	Internal	☐	PIFA									
			☐	PCB									
			☐	Ceramic Chip Antenna									
			☐	Metal plate type F antenna									
			☐	Cross-polarize Antenna									
	Antenna Gain 0		1.47dBi										
	Antenna Gain 1		1.46dBi										
Antenna Gain 2		1.42dBi											
Antenna Gain 3		1.43dBi											
Beamforming Antenna Gain		7.47dBi											

5G:

Model No.	N/A							
Antenna manufacturer	Dongguan renfeng electronic technology co., LTD							
Frequency Range	2400-2483.5MHz,5150-5350MHz,5725-5850MHz							
Antenna Delivery	☒ 1*TX+1*RX	☐ 2*TX+2*RX	☐ 3*TX+3*RX	☒ 4*TX+4*RX				
Antenna technology	☒ SISO ☐ MIMO <table border="1" style="margin-left: 20px;"> <tr> <td>☐ Basic</td> </tr> <tr> <td>☒ CDD</td> </tr> <tr> <td>☒ Beam-forming</td> </tr> </table>				☐ Basic	☒ CDD	☒ Beam-forming	
☐ Basic								
☒ CDD								
☒ Beam-forming								
Antenna Type	☒ External ☒ Dipole ☐ Internal <table border="1" style="margin-left: 20px;"> <tr> <td>☐ PIFA</td> </tr> <tr> <td>☐ PCB</td> </tr> <tr> <td>☐ Ceramic Chip Antenna</td> </tr> <tr> <td>☐ Metal plate type F antenna</td> </tr> </table>				☐ PIFA	☐ PCB	☐ Ceramic Chip Antenna	☐ Metal plate type F antenna
☐ PIFA								
☐ PCB								
☐ Ceramic Chip Antenna								
☐ Metal plate type F antenna								
Antenna Gain 0	1.77dBi							
Antenna Gain 1	1.77dBi							
Antenna Gain 2	1.76dBi							
Antenna Gain 3	1.77dBi							
Beamforming Antenna Gain	7.77dBi							

- Output Power into Antenna & RF Exposure Evaluation Distance:

Standalone modes

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
802.11b/g/n(20MHz)	2412 ~ 2462 MHz	26.96	7.47	0.5517	1.0
802.11n(40MHz)	2422 ~ 2452 MHz	26.86	7.47	0.5392	1.0
802.11a/n/ac (20MHz)	5180-5240MHz 5745-5825 MHz	19.57	7.77	0.1078	1.0
802.11n/ac (40MHz)	5190-5230MHz 5755-5795 MHz	18.29	7.77	0.0803	1.0
802.11ac(80MHz)	5210MHz 5775MHz	13.17	7.77	0.0247	1.0

Simultaneous transmission:

Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
2412 ~ 2462	26.96	7.47	0.5517	1.0
5180-5240 5745-5825	19.57	7.77	0.1078	1.0
Simultaneous transmission power density			0.6595	1.0

Note: The simultaneous transmission power density is 0.6595mW/cm² for Xiaomi Router 3 Pro without any other radio equipment.

_____ The End _____