

RF Exposure Evaluation

E.U.T. : Transmitter

Model Number : 151SP


Applicant : **Nutek Corporation**

Address : NO. 167, Lane 235, Bauchiau Rd., Xindian District,
New Taipei City 23145, Taiwan


Issued By : Interocean EMC Technology Corp.

LAB Location : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,
Taiwan 244, R.O.C.

Report Issued : 2016/08/22

Project Engineer : 

Elli Chang

Approved: 

Jerry Liu

1 RF Exposure Evaluation

Portable Device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio

frequency energy level in excess of the Commission's guidelines.

According to KDB 447498_D01_V06 4.3.1(a)

SAR exclusion thresholds by:

$$[\text{max. power of channel, including tune-up tolerance, mW}]/(\text{min, test separation distances, mm}) \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR}$$

and ≤ 7.5 for 10-g extremity SAR.

Maximum measured transmitter power

Frequency Range (MHz)	Maximum measured transmitter power (dBm)	Tune-up power tolerance (dB)	Total Maximum power (dBm)	Total Maximum power (mW)
909.6	2.46	(±)2	4.46	2.79254
913.8	2.21	(±)2	4.21	2.63633
918.0	1.94	(±)2	3.94	2.47742

$$(2.79254/5) \cdot (\sqrt{0.9096}) = 0.53267 \leq 3$$

Conclusion: No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A