



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM171101209101
Page: 1 of 17

TEST REPORT

Application No.: SZEM1711012091CR
Applicant: Spigen Korea Co., Ltd.
Address of Applicant: NO. 1709 STX-V Tower, 128, Gasan digital 1-ro, Geumcheon-gu, Seoul, 08507, Republic of Korea, Seoul, South Korea
Manufacturer: Spigen Korea Co., Ltd.
Address of Manufacturer: NO. 1709 STX-V Tower, 128, Gasan digital 1-ro, Geumcheon-gu, Seoul, 08507, Republic of Korea, Seoul, South Korea
Factory: Spigen Korea Co., Ltd.
Address of Factory: NO. 1709 STX-V Tower, 128, Gasan digital 1-ro, Geumcheon-gu, Seoul, 08507, Republic of Korea, Seoul, South Korea
Equipment Under Test (EUT):
EUT Name: Fast Wireless Charger
Model No.: F301W
Trade mark: Spigen
FCC ID: 2AFKNF301W
Standard(s) : 47 CFR PART 18
Date of Receipt: 2017-12-07
Date of Test: 2017-12-07 to 2018-1-29
Date of Issue: 2018-1-29

Test Result:	Pass*
---------------------	-------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM171101209101
Page: 2 of 17

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-1-29		

Authorized for issue by:				
				
		Moon Zhang /Project Engineer		
				
		Eric Fu /Reviewer		



2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Class / Severity	Result
Radiated Emissions (9kHz-30MHz)	47 CFR PART 18	FCC OST/ MP-5:1986	18.305(b)	Pass
Conducted Emission (150 kHz to 30 MHz)	47 CFR PART 18	FCC OST/ MP-5:1986	18.307(a)	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST	7
6 RADIO SPECTRUM MATTER TEST RESULTS	8
6.1 RADIATED EMISSIONS (9kHz-30MHz)	8
6.1.1 E.U.T. Operation	8
6.1.2 Test Setup Diagram	9
6.1.3 Measurement Procedure and Data	9
6.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz)	13
6.1.1 E.U.T. Operation	13
6.1.2 Test Setup Diagram	13
6.1.3 Measurement Data	13
7 PHOTOGRAPHS	16
7.1 RADIATED EMISSIONS (9kHz-30MHz) TEST SETUP	16
7.2 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz) TEST SETUP	16
7.3 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	17



4 General Information

4.1 Details of E.U.T.

Power supply:	Adaptor: APS-FW018W1-G Input: 100-240V~50/60Hz 0.5A MAX Output:DC 5.0V/3A ;9V/2A; 12V/1.5A Total output: 18W Fast Wireless Charger F301W Input: 5V/1A 9V /1.8A Output: 5V/1A;9V/1A
Cable:	USB Cable: 120cm unshielded
EUT Function:	wireless charging transmitter
Carrier Frequency	110-205kHz
Antenna Type	Loop antenna
Modulation type:	Load modulation

4.2 Description of Support Units

The EUT has been tested as an independent unit.

Description	Manufacturer	Model No.
Full load receiver	Provided by Client	10W
Adjustable load receiver	Provided by Client	0-10W
Samsung phone	Provided by Client	SM-G9500

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25×10^{-8}
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz) 4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (Below 1GHz) 4.8dB (Above 1GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Radiated Emissions (9kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017-05-10	2018-05-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2017-07-13	2018-07-12
EMI Test Receiver (9kHz-3GHz)	Rohde & Schwarz	ESR	SEM004-03	2017-04-14	2018-04-13
Trilog-Broadband Antenna(30MHz-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-01-26	2019-01-25
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2017-06-05	2018-06-04
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2017-05-10	2018-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2017-07-13	2018-07-12
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2017-04-14	2018-04-13

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-17



6 Radio Spectrum Matter Test Results

6.1 Radiated Emissions (9kHz-30MHz)

Test Requirement: 47 CFR PART 18
Test Method: FCC OST/ MP-5:1986
Test Site: Measurement Distance: 10m (Semi-Anechoic Chamber)
Receiver Setup:

Frequency	Detector	RBW	VBW
9kHz~150kHz	Quasi-peak	200Hz	≥RBW
150kHz~30MHz	Quasi-peak	9kHz	≥RBW
30MHz~1GHz	Quasi-peak	100kHz	≥RBW

Frequency	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009-30MHz	53.0	Quasi-peak	10
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-1000MHz	46.0	Quasi-peak	3

Limit:

Remark: According to the article 18.305(b), The operating frequency is non-ISM frequency; the RF Power generated by equipment is below 500(watts); According to the clause 18.305(c), the EUT belongs to Consumer equipment.


6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1020 mbar
a: Normal Working_ Keep EUT working at normal working.

Test mode: Test were conducted in three load modes (low, medium and high load mode) and only the worst case is submitted.

6.1.2 Test Setup Diagram




6.1.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.



Mode a: (DC 9V, 1.0A)



Condition: 10m


Job No. : 12091CR

Test Mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0.01	0.29	19.57	32.32	49.98	37.52	53.06	-15.54
2	0.02	0.21	14.93	32.49	53.75	36.40	53.06	-16.66
3	0.04	0.15	13.14	32.50	50.87	31.66	53.06	-21.40
4	0.07	0.09	12.18	32.51	54.00	33.76	53.06	-19.30
5	0.11	0.06	11.90	32.51	56.06	35.51	53.06	-17.55
6 pp	0.14	0.06	11.75	32.50	59.80	39.11	53.06	-13.95



Mode a: (DC 9V, 1.0A)



Condition: 10m
Job No. : 12091CR
Test Mode: a

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp	0.18	0.07	11.82	32.51	53.81	33.19	53.06	-19.87
2		0.54	0.12	11.75	32.49	52.15	31.53	53.06	-21.53
3		0.81	0.19	12.00	32.46	44.42	24.15	53.06	-28.91
4		2.35	0.35	12.14	32.46	41.18	21.21	53.06	-31.85
5		12.72	0.55	10.52	32.50	26.97	5.54	53.06	-47.52
6		17.94	0.64	9.84	32.52	23.98	1.94	53.06	-51.12

Remark:

1: The loop antenna rotated about both Vertical and Horizontal to find the maximum emission, So only the worst position(Horizontal) was report.

2: According to the clause 2.3 of MP-5:1986, the highest frequency is 205kHz, So the Range of frequency measurements is 9kHz to 30MHz.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM171101209101

Page: 12 of 17

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_{300} / L_{10} = D_{10} / D_{300}$$

Note:

L₃₀₀: Level @ 300m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃₀₀: 300m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 300m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 300m (uV/m)	Level @ 300m (dBuV/m)	Limit @ 300m (dBuV/m)	Margin (dB)
0.01	37.52	75.16	2.51	7.99	23.52	-15.53
0.02	36.40	66.07	2.20	6.85	23.52	-16.67
0.04	31.66	38.28	1.28	2.14	23.52	-21.38
0.07	33.76	48.70	1.62	4.19	23.52	-19.33
0.11	35.51	59.57	1.99	5.98	23.52	-17.54
0.14	39.11	59.63	1.99	5.98	23.52	-17.54
0.18	33.19	45.66	1.52	3.64	23.52	-19.88
0.54	31.53	37.71	1.26	2.01	23.52	-21.51
0.81	24.15	16.13	0.54	-5.35	23.52	-28.87
2.35	21.21	11.49	0.38	-8.40	23.52	-31.92
12.72	5.54	1.89	0.06	-24.44	23.52	-47.96
17.94	1.94	1.25	0.04	-27.96	23.52	-51.48

6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement:	47 CFR Part 15, Subpart B:2016
Test Method:	ANSI C63.4
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz


6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 35.8 % RH Atmospheric Pressure: 1020 mbar
a: Normal Working_ Keep EUT working at normal working.

Test mode: Test were conducted in three load modes (low, medium and high load mode) and only the worst case is submitted.

6.1.2 Test Setup Diagram




6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.



Mode:a; Line:Live Line



Site : Shielding Room

Condition: Line


Job No. : 12091CR

Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15	0.02	9.51	41.80	51.33	56.00	-4.67	Peak
2	0.19	0.02	9.51	39.03	48.56	54.06	-5.50	Peak
3	0.22	0.02	9.50	38.11	47.63	52.88	-5.25	Peak
4	0.35	0.01	9.50	32.81	42.32	49.00	-6.68	Peak
5	0.65	0.02	9.51	29.20	38.73	46.00	-7.27	Peak
6	0.94	0.02	9.49	29.24	38.75	46.00	-7.25	Peak



Mode:a; Line:Neutral Line




Site : Shielding Room
Condition: Neutral
Job No. : 12091CR
Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17	0.02	9.59	40.07	49.68	54.99	-5.31	Peak
2	0.22	0.02	9.57	36.32	45.91	52.79	-6.88	Peak
3	0.27	0.01	9.58	35.10	44.69	50.98	-6.29	Peak
4	0.33	0.01	9.58	32.76	42.35	49.57	-7.22	Peak
5	0.67	0.02	9.62	27.15	36.79	46.00	-9.21	Peak
6	1.74	0.02	9.64	25.31	34.97	46.00	-11.03	Peak

7 Photographs

7.1 Radiated Emissions (9kHz-30MHz) Test Setup



7.2 Conducted Emissions at Mains Terminals (150kHz-30MHz) Test Setup





7.3 EUT Constructional Details (EUT Photos)

Refer to EUT external and internal photos.

- End of the Report -