



# RF Exposure Evaluation Declaration

Report No.: S20230809559508-G1 Issue Date: 01-02-2024

**Applicant:** IGEN TECH CO.,Ltd.

Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. Address:

China

FCC ID: 2A4FR-MW-4E

**Product:** WiFi Module

Model No.: MW-4E

Trade Mark: /

CFR 47, FCC Part 2.1091 Radio frequency radiation

FCC Rule Part(s):

exposure evaluation: mobile devices.

Item Receipt date: Aug. 24, 2023

**Test Date:** Sep. 13~ Sep. 17, 2023

Compiled By

(Guangze Ding) Senior Test Engineer

Approved By

(Line Chen)

Engineer Manager

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

Page Number: 1 of 5



# **Revision History**

Report No.	Version	Description	Issue Date	
S20230809559508	Rev. 01	1	10-07-2023	
S20230809559508-G1	Rev. 02	1. This report shall be replaced by report S20230809559508, which shall be invalid immediately upon the issuance of this report. 2. The initial issuance date of report S20230809559508 was Oct 07, 2023, and the first amendment to the report was made on Dec 29, 2023, change the address to Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. China on page 1.	01-02-2024	



# 1. PRODUCT INFORMATION

# 1.1. Equipment Description

Product Name:	WiFi Module
Model Name:	MW-4E
Trade Mark:	/
Input Voltage Range:	DC 5V
Wi-Fi Specification:	802.11b/g/n20
Bluetooth Version:	5.0

# 1.2. Product Specification Subjective to this Report

Frequency Range:	WIFI:802.11b/g/n20: 2412 ~ 2462MHz
	BLE:2402~2480MHz
Channel Number:	802.11b/g/n20: 11
	BLE:40
Type of Modulation:	802.11b: DSSS
	802.11g/n: OFDM
	BLE:GFSK
Data Rate:	802.11b: 1/2/5.5/11Mbps
	802.11g: 6/9/12/18/24/36/48/54Mbps
	802.11n/: MCS0~MCS7
	BLE:1Mbps
Antenna Type:	Rod antenna
Antenna Gain:	3.16 dBi

Page Number: 3 of 5



## 2. RF Exposure Evaluation

#### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field Power Density Averag		Average Time	
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm <sup>2</sup> )	(Minutes)	
(A) Limits for Occupational/ Control Exposures					
300-1500		f/300		6	
1500-100,000			5	6	
(B) Limits for General Population/ Uncontrolled Exposures					
300-1500		f/1500		6	
1500-100,000		1		30	

f= Frequency in MHz

Calculation Formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



## 2.2. Test Result of RF Exposure Evaluation

Product	WiFi Module
Test Item	RF Exposure Evaluation

Mode	Frequency (MHz)	Maximum Conducted OutputPower (dBm)	Antenna Gain (dBi)	(dBm)	G (mW)	MPE (mW/cm²)	MPE Limits (mW/cm²)
WIFI	2412~2462	16.46	3.16	19.62	91.6	0.06	1.00
BLE	2402~2480	9.86	3.16	13.02	20.0	0.01	1.00

Remark: 1. MPE use distance is 20cm from manufacturer declaration of user manual.

Remark: 2.Use the maximum gain of all bands when evaluating

Remark: 3.BT and 5G wifi can't transmit simultaneously.

#### **CONCULISON:**

The Max Power Density at R (20 cm) = 0.06mW/cm<sup>2</sup> < 1mW/cm<sup>2</sup>. So the EUT complies with the requirement.

———— The End	