


FCC SAR Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2127-1
FCC ID : IHDT56ZM4
STANDARD : FCC 47 CFR Part 2 (2.1093)

The product was received on Oct. 20, 2020 and testing was started from Nov. 11, 2020 and completed on Dec. 02, 2020. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.



Reviewed by: Hank Huang / Supervisor



Approved by: Johnny Chen / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China

Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Applied	5
4. Equipment Under Test (EUT) Information	6
4.1 General Information.....	6
4.2 General LTE SAR Test and Reporting Considerations	7
5. Proximity Sensor Triggering Test.....	9
5.1 Proximity sensor triggering distances(Per KDB616217\$6.2).....	9
6. RF Exposure Limits.....	15
6.1 Uncontrolled Environment	15
6.2 Controlled Environment.....	15
7. Specific Absorption Rate (SAR)	16
7.1 Introduction	16
7.2 SAR Definition	16
8. System Description and Setup.....	17
8.1 E-Field Probe	18
8.2 Data Acquisition Electronics (DAE)	18
8.3 Phantom.....	19
8.4 Device Holder.....	20
9. Measurement Procedures.....	21
9.1 Spatial Peak SAR Evaluation	21
9.2 Power Reference Measurement.....	22
9.3 Area Scan.....	22
9.4 Zoom Scan.....	23
9.5 Volume Scan Procedures.....	23
9.6 Power Drift Monitoring.....	23
10. Test Equipment List	24
11. System Verification	25
11.1 Tissue Simulating Liquids	25
11.2 Tissue Verification.....	26
11.3 System Performance Check Results	27
12. RF Exposure Positions	29
12.1 Ear and handset reference point	29
12.2 Definition of the cheek position	30
12.3 Definition of the tilt position	31
12.4 Body Worn Accessory	32
12.5 Product Specific 10g SAR Exposure	33
12.6 Wireless Router.....	33
13. Conducted RF Output Power (Unit: dBm).....	34
14. Antenna Location	42
15. SAR Test Results	43
15.1 Head SAR	46
15.2 Hotspot SAR	49
15.3 Body Worn Accessory SAR.....	53
15.4 Product specific 10g SAR.....	57
15.5 Repeated SAR Measurement	60
16. Simultaneous Transmission Analysis	61
16.1 Head Exposure Conditions.....	62
16.2 Hotspot Exposure Conditions.....	63
16.3 Body-Worn Accessory Exposure Conditions	64
16.4 Product specific 10g SAR Exposure Conditions.....	65
16.5 SPLSR Evaluation and Analysis.....	66
17. Uncertainty Assessment.....	72
18. References.....	73
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	
Appendix E. Conducted RF Output Power Table	



Report No. : FA0O2013-01

Revision History

[illegible]

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, XT2127-1**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 5mm)	Body-worn (Separation 5mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.50	1.26	1.26	1.59
		GSM1900	0.29	1.30	1.22	
	WCDMA	Band V	0.45	1.18	1.18	
		Band IV	0.32	1.37	1.36	
		Band II	0.27	1.21	1.21	
	LTE	Band 5	0.44	1.36	1.36	
		Band 66/Band 4	0.29	1.44	1.44	
		Band 2	0.27	1.44	1.44	
		Band 7	0.26	1.44	1.21	
DTS	WLAN	2.4GHz WLAN	0.58	0.38	0.38	1.59
NII		5GHz WLAN	1.11	0.89	1.00	1.59
DSS	Bluetooth	2.4GHz Bluetooth	0.14	<0.10	<0.10	1.53
Highest 10g SAR Summary						
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)		Highest Simultaneous Transmission 10g SAR (W/kg)	
Licensed	GSM	GSM850	1.80		3.86	
		GSM1900	3.59			
	WCDMA	Band V	3.31			
		Band IV	3.50			
		Band II	3.17			
	LTE	Band 5	2.41			
		Band 66/Band 4	3.57			
		Band 2	3.07			
		Band 7	3.41			
NII	WLAN	5GHz WLAN	2.72		3.86	
Date of Testing:				2020/11/11~2020/12/2		
Remark: This device supports LTE B4 and B66. Since the supported frequency span for LTE B4 falls completely within the supports frequency span for LTE B66, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE B66.						

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory		
Test Firm	Sporton International (Shenzhen) Inc.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1256	421272

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2127-1
FCC ID	IHDT56ZM4
IMEI Code	IMEI 1: 356465220019298 IMEI 2: 356465220019306
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is not supported) LTE: QPSK, 16QAM, 64QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT2
SW Version	RRB31.30
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Production Unit
Remark: 802.11n-HT40 is not supported in 2.4GHz WLAN. - This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation. - This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications. - This device 2.4GHz WLAN/5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only). - This device does not support DTM operation and supports GRPS/EGRPS mode up to multi-slot class 12. - The device implements Proximity sensors/receiver detect mechanism/hotspot trigger reduced power for the power management for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity). - The device will invoke corresponding work scenarios power level, which are provided in the operational description. - For Some WWAN bands, sensor on reduced power level higher than hotspot reduced power level, so front/back sensor on SAR can represent hotspot conservatively. - There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to perform all tests. - For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will	

- be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
11. The device has five headsets, only supplier is different, so we chose headset 1 to perform full SAR testing, and headset 2/3/4/5 only verified the worst case of headset 1.

4.2 General LTE SAR Test and Reporting Considerations


Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	IHDT56ZM4							
Equipment Name	Mobile Cellular Phone							
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz							
Channel Bandwidth	LTE Band 2:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 4:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
uplink modulations used	QPSK / 16QAM / 64QAM							
LTE Voice / Data requirements	Voice and Data							
LTE Release Version	R12, Cat5							
CA Support	Not supported							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
	256 QAM	≥ 1						≤ 5
	LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)						
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
Power reduction applied to satisfy SAR compliance	Yes, head/body-worn/ hotspot/extremity will trigger reduced power for some LTE bands, the detail please referred to section 13.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829	20450	829	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844	20600	844	20600	844
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510	20850	2510	20850	2510
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560	21350	2560	21350	2560
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

5. Proximity Sensor Triggering Test



5.1 Proximity sensor triggering distances(Per KDB616217§6.2)



- Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency (5720MHz) and lowest (850MHz) frequency was used for proximity sensor triggering testing.
- Capacitive proximity sensor placed coincident with antenna elements at the bottom end of the phone are utilized to determine when the device comes in proximity of the user's body at the front or back or bottom or left side surface of the device. There is no need to do sensor coverage testing for the proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.
- When the proximity sensor is active, GSM850/1900, WCDMA band II/IV/V, LTE band 2/4/5/7/66 and WLAN5.5GHz reduced power will be active for front/ back body worn SAR.
- P-sensor can detect handheld state, WCDMA band II/IV and LTE B2/4/7/66 for front/back/bottom sides of product specific 10g SAR condition reduced powers will be active for handheld SAR.
- The proximity sensors used to detect the proximity of the user's body at the front or back or bottom side surface of the device use a detection threshold distance. The data shown in the sections below shows the distance(s).
- For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for body worn:
Front: [12 mm](#)
Back: [20 mm](#)
- For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for handheld:
Front: [9 mm](#)
Back: [13 mm](#)
Bottom side: [10 mm](#)



<P-Sensor>



Proximity Sensor Triggering Distance (mm)				
Position	Front		Back	
	Moving towards	Moving away	Moving towards	Moving away
Minimum	13	14	21	23









<Handheld>

Position	Front		Back		Bottom Side	
	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Minimum	10	12	14	17	11	14







6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE

8.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

8.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d162	Dec. 05, 2018	Nov. 24, 2021
SPEAG	1750MHz System Validation Kit	D1750V2	1137	Jul. 30, 2018	Jul. 22, 2021
SPEAG	1900MHz System Validation Kit	D1900V2	5d182	Dec. 07, 2018	Nov. 24, 2021
SPEAG	2450MHz System Validation Kit	D2450V2	924	Sep. 02, 2020	Sep. 01, 2021
SPEAG	2600MHz System Validation Kit	D2600V2	1070	Dec. 07, 2018	Nov. 24, 2021
SPEAG	5000MHz System Validation Kit	D5GHzV2	1167	Aug. 03, 2018	Aug. 02, 2021
SPEAG	Data Acquisition Electronics	DAE4	1210	Jul. 27, 2020	Jul. 26, 2021
SPEAG	Data Acquisition Electronics	DAE4	1437	Nov. 19, 2019	Nov. 18, 2020
SPEAG	Data Acquisition Electronics	DAE3	528	Mar. 16, 2020	Mar. 15, 2021
SPEAG	Dosimetric E-Field Probe	EX3DV4	7576	Jan. 22, 2020	Jan. 21, 2021
SPEAG	Dosimetric E-Field Probe	EX3DV4	3826	May 20, 2020	May 19, 2021
SPEAG	Dosimetric E-Field Probe	ES3DV3	3241	May 14, 2020	May 13, 2021
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1671	NCR	NCR
SPEAG	SAM Twin Phantom	SAM V5.0	1795	NCR	NCR
SPEAG	SAM Twin Phantom	SAM V4.0	1576	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201300653	Jul. 21, 2020	Jul. 20, 2021
Anritsu	Radio communication analyzer	MT8821C	6201588577	Mar. 26, 2020	Mar. 25, 2021
Agilent	Wireless Communication Test Set	E5515C	MY50267224	Jul. 21, 2020	Jul. 20, 2021
Agilent	Network Analyzer	E5071C	MY46523671	Oct. 15, 2020	Oct. 14, 2021
Speag	Dielectric Assessment KIT	DAK-3.5	1138	May 19, 2020	May 18, 2021
Agilent	Signal Generator	N5181A	MY50145381	Dec. 26, 2019	Dec. 25, 2020
Anritsu	Power Sensor	MA2411B	1306099	Jul. 21, 2020	Jul. 20, 2021
Anritsu	Power Meter	ML2495A	1349001	Jul. 21, 2020	Jul. 20, 2021
Anritsu	Power Sensor	MA2411B	1207253	Dec. 26, 2019	Dec. 25, 2020
Anritsu	Power Meter	ML2495A	1218010	Dec. 26, 2019	Dec. 25, 2020
R&S	CBT BLUETOOTH TESTER	CBT	100963	Dec. 26, 2019	Dec. 25, 2020
R&S	Spectrum Analyzer	FSP7	100818	Jul. 21, 2020	Jul. 20, 2021
TES	Hygrometer	1310	200505600	Jul. 30, 2020	Jul. 29, 2021
Anymetre	Thermo-Hygrometer	JR593	2015030904	Jul. 21, 2020	Jul. 20, 2021
AR	Amplifier	5S1G4	0333096	Note	
mini-circuits	Amplifier	ZVE-3W-83+	599201528	Note	
ARRA	Power Divider	A3200-2	N/A	Note	
PASTERNAK	Dual Directional Coupler	PE2214-10	N/A	Note	
Agilent	Dual Directional Coupler	778D	50422	Note	
MCL	Attenuator 1	BW-S10W5	N/A	Note	
Weinschel	Attenuator 2	3M-20	N/A	Note	
Zhongjilianhe	Attenuator 3	MVE2214-03	N/A	Note	

Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check.
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

11. System Verification

11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.2.




Fig 11.1 Photo of Liquid Height for Head SAR




Fig 11.2 Photo of Liquid Height for Body SAR

11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	22.4	0.929	41.793	0.90	41.50	3.22	0.71	±5	2020/11/11
835	Head	22.4	0.938	42.518	0.90	41.50	4.22	2.45	±5	2020/11/15
1750	Head	22.6	1.373	41.392	1.37	40.10	0.22	3.22	±5	2020/11/11
1750	Head	22.3	1.406	41.525	1.37	40.10	2.63	3.55	±5	2020/11/12
1900	Head	22.5	1.455	40.068	1.40	40.00	3.93	0.17	±5	2020/11/11
1900	Head	22.5	1.453	39.146	1.40	40.00	3.79	-2.14	±5	2020/11/12
2450	Head	22.7	1.809	37.604	1.80	39.20	0.50	-4.07	±5	2020/11/18
2600	Head	22.4	1.992	40.445	1.96	39.00	1.63	3.71	±5	2020/11/12
2600	Head	22.3	2.053	38.007	1.96	39.00	4.74	-2.55	±5	2020/11/13
5250	Head	22.8	4.595	36.652	4.71	35.95	-2.44	1.95	±5	2020/11/19
5250	Head	22.6	4.597	36.241	4.71	35.95	-2.40	0.81	±5	2020/11/27
5600	Head	22.6	5.002	36.115	5.07	35.50	-1.34	1.73	±5	2020/11/20
5600	Head	22.7	4.954	35.793	5.07	35.50	-2.29	0.83	±5	2020/11/30
5750	Head	22.6	5.170	35.843	5.22	35.35	-0.96	1.39	±5	2020/11/22
5750	Head	22.5	5.119	35.497	5.22	35.35	-1.93	0.42	±5	2020/12/2

11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/11/11	835	Head	250	4d162	7576	528	2.36	9.61	9.44	-1.77
2020/11/15	835	Head	250	4d162	3826	1210	2.52	9.61	10.08	4.89
2020/11/11	1750	Head	250	1137	3826	1210	9.39	36.50	37.56	2.90
2020/11/12	1750	Head	250	1137	3241	1437	9.66	36.50	38.64	5.86
2020/11/11	1900	Head	250	5d182	3826	1210	10.50	39.60	42	6.06
2020/11/12	1900	Head	250	5d182	3241	1437	10.60	39.60	42.4	7.07
2020/11/18	2450	Head	250	924	3826	1210	13.80	51.40	55.2	7.39
2020/11/12	2600	Head	250	1070	3826	1210	14.40	58.10	57.6	-0.86
2020/11/13	2600	Head	250	1070	3241	1437	15.80	58.10	63.2	8.78
2020/11/19	5250	Head	100	1167	3826	1210	8.20	77.00	82	6.49
2020/11/27	5250	Head	100	1167	3826	1210	7.42	77.00	74.2	-3.64
2020/11/20	5600	Head	100	1167	3826	1210	8.12	80.80	81.2	0.50
2020/11/30	5600	Head	100	1167	3826	1210	7.96	80.80	79.6	-1.49
2020/11/22	5750	Head	100	1167	3826	1210	8.32	76.90	83.2	8.19
2020/12/2	5750	Head	100	1167	3826	1210	7.39	76.90	73.9	-3.90

<10g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2020/11/11	835	Head	250	4d162	7576	528	1.54	6.35	6.16	-2.99
2020/11/15	835	Head	250	4d162	3826	1210	1.65	6.35	6.6	3.94
2020/11/11	1750	Head	250	1137	3826	1210	4.99	19.50	19.96	2.36
2020/11/12	1750	Head	250	1137	3241	1437	5.27	19.50	21.08	8.10
2020/11/11	1900	Head	250	5d182	3826	1210	5.34	20.70	21.36	3.19
2020/11/12	1900	Head	250	5d182	3241	1437	5.49	20.70	21.96	6.09
2020/11/18	2450	Head	250	924	3826	1210	6.17	24.00	24.68	2.83
2020/11/12	2600	Head	250	1070	3826	1210	6.17	26.10	24.68	-5.44
2020/11/13	2600	Head	250	1070	3241	1437	6.84	26.10	27.36	4.83
2020/11/19	5250	Head	100	1167	3826	1210	2.28	22.00	22.8	3.64
2020/11/27	5250	Head	100	1167	3826	1210	2.04	22.00	20.4	-7.27
2020/11/20	5600	Head	100	1167	3826	1210	2.22	23.20	22.2	-4.31
2020/11/30	5600	Head	100	1167	3826	1210	2.16	23.20	21.6	-6.90
2020/11/22	5750	Head	100	1167	3826	1210	2.35	21.60	23.5	8.80
2020/12/2	5750	Head	100	1167	3826	1210	2.03	21.60	20.3	-6.02




Fig 11.3.1 System Performance Check Setup



Fig 11.3.2 Setup Photo

12. RF Exposure Positions

12.1 Ear and handset reference point

Figure 12.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 12.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 12.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 12.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 12.1.1 Front, back, and side views of SAM twin phantom




Fig 12.1.2 Close-up side view of phantom showing the ear region.




Fig 12.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 12.2.1 and Figure 12.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 12.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the handset. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 12.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 12.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 12.2.3. The actual rotation angles should be documented in the test report.




Fig 12.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 12.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 12.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

12.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 12.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 12.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 12.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 12.4 Body Worn Position

12.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

12.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

13. Conducted RF Output Power (Unit: dBm)

The detailed conducted power table can refer to Appendix E.

<GSM Conducted Power>

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850/GSM1900 are considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$. Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$. Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases. Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.							

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration


<WCDMA Conducted Power>**General Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B5 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE B4 SAR test was covered by B66; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM


<WLAN Conducted Power>

General Note:

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz Bluetooth>
General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 77.36 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation





14. Antenna Location

The detailed antenna location information can refer to SAR Test Setup Photos.

15. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN/Bluetooth signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For BT/WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. Per KDB648474 D04v01r03, when the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset. When headset SAR is less than or equal than without headset SAR, no need to verify the remaining channels for headset SAR.
5. The device implements Proximity sensors/receiver detect mechanism/hotspot trigger reduced power for the power management for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity).
6. The device will invoke corresponding work scenarios power level, which are provided in the operational description.
7. For Some WWAN bands, sensor on reduced power level higher than hotspot reduced power level, so front/back sensor on SAR can represent hotspot conservatively.
8. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power (for handheld on state, the maximum full power means reduced power), including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.
 - a. For this device SAR for WWAN transmitter scaled to maximum output power mode for product specific 10g SAR is higher than 1.2W/kg of GSM850/1900, WCDMA Band II/IV/V, LTE Band 2/4/5/7/66 therefore product specific 10g SAR is necessary.
 - b. WLAN 5.3/5.5GHz tested the product specific 10g SAR since it has no hotspot mode.
 - c. When 10-g product specific 10g SAR is considered, SAR thresholds is specified in the procedures for SAR test reduction and exclusion should be multiplied by 2.5.
9. The device has five headsets, only supplier is different, so we chose headset 1 to perform full SAR testing, and headset 2/3/4/5 only verified the worst case of headset 1.
10. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for body worn:
Front: [12 mm](#)
Back: [20 mm](#)
11. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed for handheld:
Front: [9 mm](#)
Back: [13 mm](#)
Bottom side: [10 mm](#)

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850/GSM1900 are considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

WCDMA Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 / B5 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE B4 SAR test was covered by LTE B66; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	GSM850	GPRS(2 Tx slots)	Right Cheek	Full	251	848.8	31.09	32.00	1.233	0.05	0.402	0.496
	GSM850	GPRS(2 Tx slots)	Right Tilted	Full	251	848.8	31.09	32.00	1.233	0.07	0.210	0.259
	GSM850	GPRS(2 Tx slots)	Left Cheek	Full	251	848.8	31.09	32.00	1.233	-0.05	0.390	0.481
	GSM850	GPRS(2 Tx slots)	Left Tilted	Full	251	848.8	31.09	32.00	1.233	-0.05	0.219	0.270
	GSM1900	GPRS(2 Tx slots)	Right Cheek	Full	661	1880	28.25	29.50	1.334	-0.08	0.189	0.252
	GSM1900	GPRS(2 Tx slots)	Right Tilted	Full	661	1880	28.25	29.50	1.334	0.05	0.105	0.140
02	GSM1900	GPRS(2 Tx slots)	Left Cheek	Full	661	1880	28.25	29.50	1.334	0.13	0.216	0.288
	GSM1900	GPRS(2 Tx slots)	Left Tilted	Full	661	1880	28.25	29.50	1.334	-0.12	0.161	0.215

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	WCDMA V	RMC 12.2Kbps	Right Cheek	Full	4182	836.4	23.13	24.00	1.222	0.01	0.366	0.447
	WCDMA V	RMC 12.2Kbps	Right Tilted	Full	4182	836.4	23.13	24.00	1.222	-0.07	0.196	0.239
	WCDMA V	RMC 12.2Kbps	Left Cheek	Full	4182	836.4	23.13	24.00	1.222	0.07	0.333	0.407
	WCDMA V	RMC 12.2Kbps	Left Tilted	Full	4182	836.4	23.13	24.00	1.222	-0.05	0.197	0.241
04	WCDMA IV	RMC 12.2Kbps	Right Cheek	Full	1413	1732.6	23.04	24.00	1.247	0.18	0.257	0.321
	WCDMA IV	RMC 12.2Kbps	Right Tilted	Full	1413	1732.6	23.04	24.00	1.247	-0.07	0.101	0.126
	WCDMA IV	RMC 12.2Kbps	Left Cheek	Full	1413	1732.6	23.04	24.00	1.247	0.01	0.183	0.228
	WCDMA IV	RMC 12.2Kbps	Left Tilted	Full	1413	1732.6	23.04	24.00	1.247	0.01	0.136	0.170
	WCDMA II	RMC 12.2Kbps	Right Cheek	Full	9538	1907.6	23.22	24.00	1.197	-0.14	0.224	0.268
	WCDMA II	RMC 12.2Kbps	Right Tilted	Full	9538	1907.6	23.22	24.00	1.197	0.06	0.102	0.122
05	WCDMA II	RMC 12.2Kbps	Left Cheek	Full	9538	1907.6	23.22	24.00	1.197	0.06	0.228	0.273
	WCDMA II	RMC 12.2Kbps	Left Tilted	Full	9538	1907.6	23.22	24.00	1.197	0.01	0.159	0.190

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	LTE Band 5	10M	QPSK	1	25	Right Cheek	Full	20525	836.5	23.25	24.00	1.189	-0.11	0.371	0.441
	LTE Band 5	10M	QPSK	1	25	Right Tilted	Full	20525	836.5	23.25	24.00	1.189	0.05	0.191	0.227
	LTE Band 5	10M	QPSK	1	25	Left Cheek	Full	20525	836.5	23.25	24.00	1.189	-0.14	0.339	0.403
	LTE Band 5	10M	QPSK	1	25	Left Tilted	Full	20525	836.5	23.25	24.00	1.189	0.07	0.176	0.209
	LTE Band 5	10M	QPSK	25	12	Right Cheek	Full	20525	836.5	22.05	23.00	1.245	0.19	0.213	0.265
	LTE Band 5	10M	QPSK	25	12	Right Tilted	Full	20525	836.5	22.05	23.00	1.245	0.01	0.112	0.139
	LTE Band 5	10M	QPSK	25	12	Left Cheek	Full	20525	836.5	22.05	23.00	1.245	-0.15	0.189	0.235
	LTE Band 5	10M	QPSK	25	12	Left Tilted	Full	20525	836.5	22.05	23.00	1.245	-0.03	0.104	0.129
07	LTE Band 66	20M	QPSK	1	49	Right Cheek	Full	132322	1745	23.10	24.00	1.230	0.06	0.236	0.290
	LTE Band 66	20M	QPSK	1	49	Right Tilted	Full	132322	1745	23.10	24.00	1.230	-0.13	0.099	0.121
	LTE Band 66	20M	QPSK	1	49	Left Cheek	Full	132322	1745	23.10	24.00	1.230	-0.02	0.180	0.221
	LTE Band 66	20M	QPSK	1	49	Left Tilted	Full	132322	1745	23.10	24.00	1.230	0.04	0.134	0.165
	LTE Band 66	20M	QPSK	50	24	Right Cheek	Full	132322	1745	22.55	23.00	1.109	-0.15	0.189	0.210
	LTE Band 66	20M	QPSK	50	24	Right Tilted	Full	132322	1745	22.55	23.00	1.109	0.09	0.082	0.091
	LTE Band 66	20M	QPSK	50	24	Left Cheek	Full	132322	1745	22.55	23.00	1.109	0.04	0.127	0.141
	LTE Band 66	20M	QPSK	50	24	Left Tilted	Full	132322	1745	22.55	23.00	1.109	-0.17	0.117	0.130
	LTE Band 2	20M	QPSK	1	49	Right Cheek	Full	18900	1880	23.09	24.00	1.233	0.03	0.206	0.254
	LTE Band 2	20M	QPSK	1	49	Right Tilted	Full	18900	1880	23.09	24.00	1.233	-0.08	0.106	0.131
08	LTE Band 2	20M	QPSK	1	49	Left Cheek	Full	18900	1880	23.09	24.00	1.233	0.02	0.218	0.269
	LTE Band 2	20M	QPSK	1	49	Left Tilted	Full	18900	1880	23.09	24.00	1.233	0.05	0.168	0.207
	LTE Band 2	20M	QPSK	50	0	Right Cheek	Full	18900	1880	21.90	23.00	1.288	-0.09	0.121	0.156
	LTE Band 2	20M	QPSK	50	0	Right Tilted	Full	18900	1880	21.90	23.00	1.288	0.03	0.063	0.081
	LTE Band 2	20M	QPSK	50	0	Left Cheek	Full	18900	1880	21.90	23.00	1.288	0.03	0.127	0.164
	LTE Band 2	20M	QPSK	50	0	Left Tilted	Full	18900	1880	21.90	23.00	1.288	0.02	0.103	0.133
	LTE Band 7	20M	QPSK	1	49	Right Cheek	Full	21100	2535	23.29	24.00	1.178	-0.1	0.123	0.145
	LTE Band 7	20M	QPSK	1	49	Right Tilted	Full	21100	2535	23.29	24.00	1.178	0.17	0.065	0.077
09	LTE Band 7	20M	QPSK	1	49	Left Cheek	Full	21100	2535	23.29	24.00	1.178	0.08	0.218	0.257
	LTE Band 7	20M	QPSK	1	49	Left Tilted	Full	21100	2535	23.29	24.00	1.178	-0.05	0.086	0.101
	LTE Band 7	20M	QPSK	50	0	Right Cheek	Full	21100	2535	22.37	23.00	1.156	0.02	0.118	0.136
	LTE Band 7	20M	QPSK	50	0	Right Tilted	Full	21100	2535	22.37	23.00	1.156	0.15	0.066	0.076
	LTE Band 7	20M	QPSK	50	0	Left Cheek	Full	21100	2535	22.37	23.00	1.156	-0.03	0.189	0.219
	LTE Band 7	20M	QPSK	50	0	Left Tilted	Full	21100	2535	22.37	23.00	1.156	0.18	0.081	0.093

<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.12	0.233	0.295
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.11	0.292	0.370
10	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	Full	11	2462	18.50	19.50	1.259	99.31	1.007	-0.11	0.461	0.584
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.12	0.458	0.581

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.12	0.388	0.604
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Tilted	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.11	0.428	0.666
11	WLAN5.3GHz	802.11n-HT40 MCS0	Left Cheek	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.16	0.568	0.884
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.03	0.535	0.833
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Cheek	Full	62	5310	15.72	17.00	1.343	96.32	1.038	0.04	0.413	0.576
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	Full	62	5310	15.72	17.00	1.343	96.32	1.038	0.05	0.379	0.528
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	Reduced	122	5610	15.54	17.00	1.400	92.79	1.078	0.05	0.326	0.492
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Tilted	Reduced	122	5610	15.54	17.00	1.400	92.79	1.078	-0.02	0.413	0.623
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	Reduced	122	5610	15.54	17.00	1.400	92.79	1.078	0.06	0.556	0.839
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	Reduced	122	5610	15.54	17.00	1.400	92.79	1.078	0.01	0.520	0.785
12	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	Reduced	138	5690	15.49	17.00	1.416	92.79	1.078	-0.09	0.724	1.105
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.12	0.160	0.230
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Tilted	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.11	0.196	0.282
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Cheek	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.13	0.224	0.322
13	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.17	0.241	0.346

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Right Cheek	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.11	0.030	0.047
	Bluetooth	DH5 1Mbps	Right Tilted	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.03	0.039	0.061
14	Bluetooth	DH5 1Mbps	Left Cheek	Full	39	2441	11.20	12.00	1.202	77.36	1.293	-0.13	0.090	0.140
	Bluetooth	DH5 1Mbps	Left Tilted	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.04	0.073	0.114

15.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS(2 Tx slots)	Front	5mm	Reduced	251	848.8	29.84	30.50	1.164	-0.13	0.555	0.646
15	GSM850	GPRS(2 Tx slots)	Back	5mm	Reduced	251	848.8	29.84	30.50	1.164	0.15	1.080	1.257
	GSM850	GPRS(2 Tx slots)	Left Side	5mm	Reduced	251	848.8	29.84	30.50	1.164	-0.02	0.211	0.246
	GSM850	GPRS(2 Tx slots)	Right Side	5mm	Reduced	251	848.8	29.84	30.50	1.164	-0.05	0.382	0.445
	GSM850	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	251	848.8	29.84	30.50	1.164	-0.08	0.361	0.420
	GSM850	GPRS(2 Tx slots)	Back	5mm	Reduced	128	824.2	29.56	30.50	1.242	0.05	0.888	1.103
	GSM850	GPRS(2 Tx slots)	Back	5mm	Reduced	189	836.4	29.81	30.50	1.172	-0.13	0.933	1.094
	GSM1900	GPRS(2 Tx slots)	Front	5mm	Reduced	810	1909.8	26.44	27.50	1.276	0.02	0.629	0.803
	GSM1900	GPRS(2 Tx slots)	Back	5mm	Reduced	810	1909.8	26.44	27.50	1.276	-0.17	0.740	0.945
	GSM1900	GPRS(2 Tx slots)	Left Side	5mm	Reduced	810	1909.8	25.00	26.00	1.259	0.04	0.242	0.305
	GSM1900	GPRS(2 Tx slots)	Right Side	5mm	Reduced	810	1909.8	25.00	26.00	1.259	0.02	0.072	0.090
	GSM1900	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	810	1909.8	25.00	26.00	1.259	0.15	0.820	1.032
16	GSM1900	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	512	1850.2	24.87	26.00	1.297	0.02	1.000	1.297
	GSM1900	GPRS(2 Tx slots)	Bottom Side	5mm	Reduced	661	1880	24.90	26.00	1.288	0.01	0.876	1.129
	GSM1900	GPRS(2 Tx slots)	Front	5mm	Reduced	512	1850.2	26.14	27.50	1.368	-0.13	0.783	1.071
	GSM1900	GPRS(2 Tx slots)	Front	5mm	Reduced	661	1880	26.42	27.50	1.282	-0.14	0.732	0.939
	GSM1900	GPRS(2 Tx slots)	Back	5mm	Reduced	512	1850.2	26.14	27.50	1.368	-0.13	0.888	1.215
	GSM1900	GPRS(2 Tx slots)	Back	5mm	Reduced	661	1880	26.42	27.50	1.282	-0.14	0.842	1.080

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	5mm	Reduced	4132	826.4	22.35	23.00	1.161	0.16	0.526	0.611
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4132	826.4	22.35	23.00	1.161	-0.15	0.940	1.092
	WCDMA V	RMC 12.2Kbps	Left Side	5mm	Reduced	4132	826.4	22.35	23.00	1.161	-0.04	0.230	0.267
	WCDMA V	RMC 12.2Kbps	Right Side	5mm	Reduced	4132	826.4	22.35	23.00	1.161	-0.08	0.339	0.394
	WCDMA V	RMC 12.2Kbps	Bottom Side	5mm	Reduced	4132	826.4	22.35	23.00	1.161	-0.02	0.263	0.305
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4182	836.4	22.33	23.00	1.167	-0.03	0.964	1.125
17	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4233	846.6	22.18	23.00	1.208	-0.1	0.980	1.184
	WCDMA IV	RMC 12.2Kbps	Front	5mm	Reduced	1413	1732.6	18.09	19.00	1.233	-0.1	0.740	0.912
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Reduced	1413	1732.6	18.09	19.00	1.233	-0.12	1.000	1.233
	WCDMA IV	RMC 12.2Kbps	Left Side	5mm	Reduced	1413	1732.6	17.13	18.00	1.222	0.03	0.124	0.152
	WCDMA IV	RMC 12.2Kbps	Right Side	5mm	Reduced	1413	1732.6	17.13	18.00	1.222	0.02	0.094	0.114
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	Reduced	1413	1732.6	17.13	18.00	1.222	0.05	1.110	1.356
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	Reduced	1312	1712.4	16.99	18.00	1.262	-0.08	1.020	1.287
18	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	Reduced	1513	1752.6	17.12	18.00	1.225	-0.12	1.120	1.372
	WCDMA IV	RMC 12.2Kbps	Front	5mm	Reduced	1312	1712.4	18.04	19.00	1.247	-0.01	0.657	0.820
	WCDMA IV	RMC 12.2Kbps	Front	5mm	Reduced	1513	1752.6	17.99	19.00	1.262	-0.13	0.741	0.935
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Reduced	1312	1712.4	18.04	19.00	1.247	-0.18	0.962	1.200
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Reduced	1513	1752.6	17.99	19.00	1.262	-0.07	1.080	1.363
	WCDMA II	RMC 12.2Kbps	Front	5mm	Reduced	9538	1907.6	20.06	21.00	1.242	0.06	0.736	0.914
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	20.06	21.00	1.242	-0.11	0.782	0.971
	WCDMA II	RMC 12.2Kbps	Left Side	5mm	Reduced	9538	1907.6	17.69	18.50	1.205	0.08	0.173	0.208
	WCDMA II	RMC 12.2Kbps	Right Side	5mm	Reduced	9538	1907.6	17.69	18.50	1.205	0.05	0.031	0.037
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9538	1907.6	17.69	18.50	1.205	-0.02	0.781	0.941
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9262	1852.4	17.63	18.50	1.222	0.02	0.952	1.163
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9400	1880	17.66	18.50	1.213	-0.1	0.858	1.041
	WCDMA II	RMC 12.2Kbps	Front	5mm	Reduced	9262	1852.4	19.90	21.00	1.288	0.03	0.754	0.971
	WCDMA II	RMC 12.2Kbps	Front	5mm	Reduced	9400	1880	20.01	21.00	1.256	0.06	0.727	0.913
19	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9262	1852.4	19.90	21.00	1.288	-0.13	0.936	1.206
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9400	1880	20.01	21.00	1.256	-0.19	0.851	1.069

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
20	LTE Band 5	10M	QPSK	1	25	Front	5mm	Reduced	20525	836.5	22.81	23.50	1.172	0.05	0.603	0.707
	LTE Band 5	10M	QPSK	1	25	Back	5mm	Reduced	20525	836.5	22.81	23.50	1.172	-0.16	1.160	1.360
	LTE Band 5	10M	QPSK	1	25	Left Side	5mm	Reduced	20525	836.5	22.81	23.50	1.172	0.05	0.336	0.394
	LTE Band 5	10M	QPSK	1	25	Right Side	5mm	Reduced	20525	836.5	22.81	23.50	1.172	-0.07	0.477	0.559
	LTE Band 5	10M	QPSK	1	25	Bottom Side	5mm	Reduced	20525	836.5	22.81	23.50	1.172	-0.08	0.338	0.396
	LTE Band 5	10M	QPSK	25	12	Front	5mm	Reduced	20525	836.5	21.61	22.50	1.227	-0.09	0.319	0.392
	LTE Band 5	10M	QPSK	25	12	Back	5mm	Reduced	20525	836.5	21.61	22.50	1.227	-0.14	0.620	0.761
	LTE Band 5	10M	QPSK	25	12	Left Side	5mm	Reduced	20525	836.5	21.61	22.50	1.227	-0.16	0.196	0.241
	LTE Band 5	10M	QPSK	25	12	Right Side	5mm	Reduced	20525	836.5	21.61	22.50	1.227	-0.18	0.273	0.335
	LTE Band 5	10M	QPSK	25	12	Bottom Side	5mm	Reduced	20525	836.5	21.61	22.50	1.227	-0.06	0.189	0.232
21	LTE Band 5	10M	QPSK	50	0	Back	5mm	Reduced	20525	836.5	21.50	22.50	1.259	-0.07	0.616	0.775
	LTE Band 66	20M	QPSK	1	49	Front	5mm	Reduced	132322	1745	18.26	19.00	1.186	0.02	0.778	0.923
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Reduced	132322	1745	18.26	19.00	1.186	0.06	1.150	1.364
	LTE Band 66	20M	QPSK	1	49	Left Side	5mm	Reduced	132322	1745	17.01	17.50	1.119	-0.11	0.106	0.119
	LTE Band 66	20M	QPSK	1	49	Right Side	5mm	Reduced	132322	1745	17.01	17.50	1.119	0.08	0.103	0.115
	LTE Band 66	20M	QPSK	1	49	Bottom Side	5mm	Reduced	132322	1745	17.01	17.50	1.119	0.05	1.020	1.142
	LTE Band 66	20M	QPSK	1	49	Bottom Side	5mm	Reduced	132072	1720	16.55	17.50	1.245	-0.02	0.906	1.128
	LTE Band 66	20M	QPSK	1	49	Bottom Side	5mm	Reduced	132572	1770	16.77	17.50	1.183	0.02	1.020	1.207
	LTE Band 66	20M	QPSK	1	49	Front	5mm	Reduced	132072	1720	17.80	19.00	1.318	-0.1	0.686	0.904
	LTE Band 66	20M	QPSK	1	49	Front	5mm	Reduced	132572	1770	18.22	19.00	1.197	0.03	0.791	0.947
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Reduced	132072	1720	17.80	19.00	1.318	0.06	1.020	1.345
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Reduced	132572	1770	18.22	19.00	1.197	-0.13	1.110	1.328
	LTE Band 66	20M	QPSK	50	24	Front	5mm	Reduced	132322	1745	18.15	19.00	1.216	0.06	0.765	0.930
	LTE Band 66	20M	QPSK	50	24	Front	5mm	Reduced	132072	1720	17.78	19.00	1.324	-0.13	0.678	0.898
	LTE Band 66	20M	QPSK	50	24	Front	5mm	Reduced	132572	1770	17.93	19.00	1.279	-0.19	0.751	0.961
	LTE Band 66	20M	QPSK	50	24	Back	5mm	Reduced	132322	1745	18.15	19.00	1.216	-0.06	1.140	1.386
	LTE Band 66	20M	QPSK	50	24	Back	5mm	Reduced	132072	1720	17.78	19.00	1.324	-0.07	0.952	1.261
	LTE Band 66	20M	QPSK	50	24	Back	5mm	Reduced	132572	1770	17.93	19.00	1.279	0.05	1.030	1.318
	LTE Band 66	20M	QPSK	50	24	Left Side	5mm	Reduced	132322	1745	16.90	17.50	1.148	-0.02	0.107	0.123
	LTE Band 66	20M	QPSK	50	24	Right Side	5mm	Reduced	132322	1745	16.90	17.50	1.148	0.02	0.100	0.115
	LTE Band 66	20M	QPSK	50	24	Bottom Side	5mm	Reduced	132322	1745	16.90	17.50	1.148	-0.1	1.030	1.183
	LTE Band 66	20M	QPSK	50	24	Bottom Side	5mm	Reduced	132072	1720	16.53	17.50	1.250	0.03	0.905	1.131
	LTE Band 66	20M	QPSK	50	24	Bottom Side	5mm	Reduced	132572	1770	16.68	17.50	1.208	0.06	1.040	1.256
	LTE Band 66	20M	QPSK	100	0	Front	5mm	Reduced	132322	1745	18.14	19.00	1.219	0.03	0.836	1.019
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Reduced	132322	1745	18.14	19.00	1.219	-0.17	1.180	1.438
	LTE Band 66	20M	QPSK	100	0	Bottom Side	5mm	Reduced	132322	1745	16.77	17.50	1.183	0.05	1.030	1.219



FCC SAR Test Report

Report No. : FA002013-01

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	19100	1900	21.42	22.00	1.143	0.03	0.872	0.997
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	19100	1900	21.42	22.00	1.143	0.07	1.160	1.326
	LTE Band 2	20M	QPSK	1	49	Left Side	5mm	Reduced	19100	1900	18.68	19.50	1.208	0.02	0.242	0.292
	LTE Band 2	20M	QPSK	1	49	Right Side	5mm	Reduced	19100	1900	18.68	19.50	1.208	-0.07	0.068	0.082
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	19100	1900	18.68	19.50	1.208	0.05	0.940	1.135
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	18700	1860	18.61	19.50	1.227	-0.02	1.140	1.399
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	18900	1880	18.59	19.50	1.233	0.15	1.020	1.258
	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	18700	1860	21.41	22.00	1.146	0.02	1.150	1.317
	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	18900	1880	21.27	22.00	1.183	0.08	0.920	1.088
22	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18700	1860	21.41	22.00	1.146	-0.04	1.260	1.443
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18900	1880	21.27	22.00	1.183	0.04	1.160	1.372
	LTE Band 2	20M	QPSK	50	24	Front	5mm	Reduced	19100	1900	21.16	22.00	1.213	-0.03	0.799	0.969
	LTE Band 2	20M	QPSK	50	24	Front	5mm	Reduced	18700	1860	21.14	22.00	1.219	0.07	0.851	1.037
	LTE Band 2	20M	QPSK	50	24	Front	5mm	Reduced	18900	1880	21.09	22.00	1.233	0.02	0.808	0.996
	LTE Band 2	20M	QPSK	50	24	Back	5mm	Reduced	19100	1900	21.16	22.00	1.213	-0.07	0.992	1.204
	LTE Band 2	20M	QPSK	50	24	Back	5mm	Reduced	18700	1860	21.14	22.00	1.219	0.05	1.160	1.414
	LTE Band 2	20M	QPSK	50	24	Back	5mm	Reduced	18900	1880	21.09	22.00	1.233	-0.02	1.040	1.282
	LTE Band 2	20M	QPSK	50	24	Left Side	5mm	Reduced	19100	1900	18.56	19.50	1.242	0.08	0.243	0.302
	LTE Band 2	20M	QPSK	50	24	Right Side	5mm	Reduced	19100	1900	18.56	19.50	1.242	0.05	0.068	0.085
	LTE Band 2	20M	QPSK	50	24	Bottom Side	5mm	Reduced	19100	1900	18.56	19.50	1.242	-0.02	0.944	1.172
	LTE Band 2	20M	QPSK	50	24	Bottom Side	5mm	Reduced	18700	1860	18.54	19.50	1.247	0.11	1.130	1.410
	LTE Band 2	20M	QPSK	50	24	Bottom Side	5mm	Reduced	18900	1880	18.49	19.50	1.262	0.13	1.010	1.274
	LTE Band 2	20M	QPSK	100	0	Front	5mm	Reduced	19100	1900	21.14	22.00	1.219	-0.02	0.722	0.880
	LTE Band 2	20M	QPSK	100	0	Back	5mm	Reduced	19100	1900	21.14	22.00	1.219	0.05	1.010	1.231
	LTE Band 2	20M	QPSK	100	0	Bottom Side	5mm	Reduced	19100	1900	18.54	19.50	1.247	0.06	1.060	1.322
	LTE Band 7	20M	QPSK	1	49	Front	5mm	Reduced	21100	2535	16.34	17.00	1.164	0.02	0.419	0.488
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	21100	2535	16.34	17.00	1.164	-0.1	0.919	1.070
	LTE Band 7	20M	QPSK	1	49	Left Side	5mm	Reduced	21100	2535	15.54	16.00	1.112	-0.02	0.111	0.123
	LTE Band 7	20M	QPSK	1	49	Right Side	5mm	Reduced	21100	2535	15.54	16.00	1.112	0.06	0.041	0.045
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	21100	2535	15.54	16.00	1.112	0.01	1.250	1.390
23	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	20850	2510	15.51	16.00	1.119	-0.16	1.290	1.444
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	21350	2560	15.31	16.00	1.172	0.03	1.040	1.219
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	20850	2510	16.32	17.00	1.169	-0.04	1.030	1.205
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	21350	2560	16.21	17.00	1.199	-0.19	0.815	0.978
	LTE Band 7	20M	QPSK	50	24	Front	5mm	Reduced	21100	2535	16.26	17.00	1.186	0.08	0.428	0.508
	LTE Band 7	20M	QPSK	50	24	Back	5mm	Reduced	21100	2535	16.26	17.00	1.186	0.05	0.870	1.032
	LTE Band 7	20M	QPSK	50	24	Back	5mm	Reduced	20850	2510	16.19	17.00	1.205	0.04	0.939	1.132
	LTE Band 7	20M	QPSK	50	24	Back	5mm	Reduced	21350	2560	16.16	17.00	1.213	0.03	0.788	0.956
	LTE Band 7	20M	QPSK	50	24	Left Side	5mm	Reduced	21100	2535	15.50	16.00	1.122	-0.01	0.110	0.123
	LTE Band 7	20M	QPSK	50	24	Right Side	5mm	Reduced	21100	2535	15.50	16.00	1.122	0.08	0.041	0.046
	LTE Band 7	20M	QPSK	50	24	Bottom Side	5mm	Reduced	21100	2535	15.50	16.00	1.122	0.1	1.150	1.290
	LTE Band 7	20M	QPSK	50	24	Bottom Side	5mm	Reduced	20850	2510	15.49	16.00	1.125	-0.04	1.250	1.406
	LTE Band 7	20M	QPSK	50	24	Bottom Side	5mm	Reduced	21350	2560	15.16	16.00	1.213	-0.19	1.030	1.250
	LTE Band 7	20M	QPSK	100	0	Back	5mm	Reduced	21100	2535	16.23	17.00	1.194	-0.04	0.858	1.024
	LTE Band 7	20M	QPSK	100	0	Bottom Side	5mm	Reduced	21100	2535	15.23	16.00	1.194	0.06	1.130	1.349

<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.08	0.234	0.297
24	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.02	0.301	0.382
	WLAN2.4GHz	802.11b 1Mbps	Left Side	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.14	0.037	0.047
	WLAN2.4GHz	802.11b 1Mbps	Right Side	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.15	0.251	0.318
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.11	0.253	0.321

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.2GHz	802.11n-HT40 MCS0	Front	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.11	0.270	0.405
25	WLAN5.2GHz	802.11n-HT40 MCS0	Back	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.06	0.594	0.891
	WLAN5.2GHz	802.11n-HT40 MCS0	Back	5mm	Full	38	5190	17.28	19.00	1.486	96.32	1.038	0.1	0.301	0.464
	WLAN5.2GHz	802.11n-HT40 MCS0	Left Side	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.12	0.000	0.000
	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	-0.1	0.104	0.156
	WLAN5.2GHz	802.11n-HT40 MCS0	Top Side	5mm	Full	46	5230	17.40	19.00	1.445	96.32	1.038	0.04	0.444	0.666
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.12	0.162	0.233
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	Full	155	5775	12.25	13.50	1.334	92.79	1.078	-0.1	0.325	0.467
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Side	5mm	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.13	0.010	0.015
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	5mm	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.14	0.112	0.161
26	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Full	155	5775	12.25	13.50	1.334	92.79	1.078	-0.19	0.525	0.755

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Front	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.03	0.040	0.062
27	Bluetooth	DH5 1Mbps	Back	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	-0.15	0.053	0.082
	Bluetooth	DH5 1Mbps	Left Side	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.04	0.004	0.006
	Bluetooth	DH5 1Mbps	Right Side	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.11	0.043	0.066
	Bluetooth	DH5 1Mbps	Top Side	5mm	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.06	0.038	0.058

15.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS(2 Tx slots)	Front	5mm	-	Reduced	251	848.8	29.84	30.50	1.164	-0.13	0.555	0.646
28	GSM850	GPRS(2 Tx slots)	Back	5mm	-	Reduced	251	848.8	29.84	30.50	1.164	0.15	1.080	1.257
	GSM850	GPRS(2 Tx slots)	Back	5mm	-	Reduced	128	824.2	29.56	30.50	1.242	0.05	0.888	1.103
	GSM850	GPRS(2 Tx slots)	Back	5mm	-	Reduced	189	836.4	29.81	30.50	1.172	-0.13	0.933	1.094
	GSM850	GPRS(2 Tx slots)	Back	5mm	Headset 1	Reduced	251	848.8	29.84	30.50	1.164	0.15	1.010	1.176
	GSM850	GPRS(2 Tx slots)	Front	12mm	-	Full	251	848.8	31.09	32.00	1.233	0.1	0.367	0.453
	GSM850	GPRS(2 Tx slots)	Back	20mm	-	Full	251	848.8	31.09	32.00	1.233	0.02	0.403	0.497
	GSM1900	GPRS(2 Tx slots)	Front	5mm	-	Reduced	810	1909.8	26.44	27.50	1.276	0.02	0.629	0.803
	GSM1900	GPRS(2 Tx slots)	Front	5mm	-	Reduced	512	1850.2	26.14	27.50	1.368	-0.13	0.783	1.071
	GSM1900	GPRS(2 Tx slots)	Front	5mm	-	Reduced	661	1880	26.42	27.50	1.282	-0.14	0.732	0.939
	GSM1900	GPRS(2 Tx slots)	Back	5mm	-	Reduced	810	1909.8	26.44	27.50	1.276	-0.17	0.740	0.945
29	GSM1900	GPRS(2 Tx slots)	Back	5mm	-	Reduced	512	1850.2	26.14	27.50	1.368	-0.13	0.888	1.215
	GSM1900	GPRS(2 Tx slots)	Back	5mm	-	Reduced	661	1880	26.42	27.50	1.282	-0.14	0.842	1.080
	GSM1900	GPRS(2 Tx slots)	Back	5mm	Headset 1	Reduced	512	1850.2	26.14	27.50	1.368	0.02	0.878	1.201
	GSM1900	GPRS(2 Tx slots)	Front	12mm	-	Full	512	1850.2	28.21	29.50	1.346	0.03	0.610	0.821
	GSM1900	GPRS(2 Tx slots)	Back	20mm	-	Full	512	1850.2	28.21	29.50	1.346	0.07	0.276	0.371

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	5mm	-	Reduced	4132	826.4	22.35	23.00	1.161	0.16	0.526	0.611
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4132	826.4	22.35	23.00	1.161	-0.15	0.940	1.092
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4182	836.4	22.33	23.00	1.167	-0.03	0.964	1.125
30	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4233	846.6	22.18	23.00	1.208	-0.1	0.980	1.184
	WCDMA V	RMC 12.2Kbps	Front	12mm	-	Full	4132	826.4	23.09	24.00	1.233	0.03	0.385	0.475
	WCDMA V	RMC 12.2Kbps	Back	20mm	-	Full	4233	846.6	22.94	24.00	1.276	0.12	0.387	0.494
	WCDMA IV	RMC 12.2Kbps	Front	5mm	-	Reduced	1413	1732.6	18.09	19.00	1.233	-0.1	0.740	0.912
	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	Reduced	1413	1732.6	18.09	19.00	1.233	-0.12	1.000	1.233
	WCDMA IV	RMC 12.2Kbps	Front	5mm	-	Reduced	1312	1712.4	18.04	19.00	1.247	-0.01	0.657	0.820
	WCDMA IV	RMC 12.2Kbps	Front	5mm	-	Reduced	1513	1752.6	17.99	19.00	1.262	-0.13	0.741	0.935
	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	Reduced	1312	1712.4	18.04	19.00	1.247	-0.18	0.962	1.200
31	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	Reduced	1513	1752.6	17.99	19.00	1.262	-0.07	1.080	1.363
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	1513	1752.6	17.99	19.00	1.262	0.14	1.010	1.274
	WCDMA IV	RMC 12.2Kbps	Front	12mm	-	Full	1513	1752.6	23.03	24.00	1.250	0.07	0.728	0.910
	WCDMA IV	RMC 12.2Kbps	Back	20mm	-	Full	1513	1752.6	23.03	24.00	1.250	0.03	0.449	0.561
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9538	1907.6	20.06	21.00	1.242	0.06	0.736	0.914
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9538	1907.6	20.06	21.00	1.242	-0.11	0.782	0.971
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9262	1852.4	19.90	21.00	1.288	0.03	0.754	0.971
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9400	1880	20.01	21.00	1.256	0.06	0.727	0.913
32	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9262	1852.4	19.90	21.00	1.288	-0.13	0.936	1.206
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9400	1880	20.01	21.00	1.256	-0.19	0.851	1.069
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset 1	Reduced	9262	1852.4	19.90	21.00	1.288	-0.06	0.923	1.189
	WCDMA II	RMC 12.2Kbps	Front	12mm	-	Full	9262	1852.4	23.09	24.00	1.233	0.02	0.680	0.839
	WCDMA II	RMC 12.2Kbps	Back	20mm	-	Full	9262	1852.4	23.09	24.00	1.233	0.06	0.377	0.465



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
33	LTE Band 5	10M	QPSK	1	25	Front	5mm	-	Reduced	20525	836.5	22.81	23.50	1.172	0.05	0.603	0.707
	LTE Band 5	10M	QPSK	1	25	Back	5mm	-	Reduced	20525	836.5	22.81	23.50	1.172	-0.16	1.160	1.360
	LTE Band 5	10M	QPSK	1	25	Back	5mm	Headset 1	Reduced	20525	836.5	22.81	23.50	1.172	0.08	1.100	1.289
	LTE Band 5	10M	QPSK	1	25	Front	12mm	-	Full	20525	836.5	23.25	24.00	1.189	0.11	0.373	0.443
	LTE Band 5	10M	QPSK	1	25	Back	20mm	-	Full	20525	836.5	23.25	24.00	1.189	0.12	0.416	0.494
	LTE Band 5	10M	QPSK	25	12	Front	5mm	-	Reduced	20525	836.5	21.61	22.50	1.227	-0.09	0.319	0.392
	LTE Band 5	10M	QPSK	25	12	Back	5mm	-	Reduced	20525	836.5	21.61	22.50	1.227	-0.14	0.620	0.761
	LTE Band 5	10M	QPSK	50	0	Back	5mm	-	Reduced	20525	836.5	21.50	22.50	1.259	-0.07	0.616	0.775
	LTE Band 66	20M	QPSK	1	49	Front	5mm	-	Reduced	132322	1745	18.26	19.00	1.186	0.02	0.778	0.923
	LTE Band 66	20M	QPSK	1	49	Back	5mm	-	Reduced	132322	1745	18.26	19.00	1.186	0.06	1.150	1.364
	LTE Band 66	20M	QPSK	1	49	Front	5mm	-	Reduced	132072	1720	17.80	19.00	1.318	-0.1	0.686	0.904
	LTE Band 66	20M	QPSK	1	49	Front	5mm	-	Reduced	132572	1770	18.22	19.00	1.197	0.03	0.791	0.947
	LTE Band 66	20M	QPSK	1	49	Back	5mm	-	Reduced	132072	1720	17.80	19.00	1.318	0.06	1.020	1.345
	LTE Band 66	20M	QPSK	1	49	Back	5mm	-	Reduced	132572	1770	18.22	19.00	1.197	-0.13	1.110	1.328
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	132322	1745	18.26	19.00	1.186	-0.19	1.020	1.209
	LTE Band 66	20M	QPSK	1	49	Front	12mm	-	Full	132572	1770	23.02	24.00	1.253	0.04	0.694	0.870
	LTE Band 66	20M	QPSK	1	49	Back	20mm	-	Full	132322	1745	23.10	24.00	1.230	-0.01	0.421	0.518
	LTE Band 66	20M	QPSK	50	24	Front	5mm	-	Reduced	132322	1745	18.15	19.00	1.216	0.06	0.765	0.930
	LTE Band 66	20M	QPSK	50	24	Front	5mm	-	Reduced	132072	1720	17.78	19.00	1.324	-0.13	0.678	0.898
	LTE Band 66	20M	QPSK	50	24	Front	5mm	-	Reduced	132572	1770	17.93	19.00	1.279	-0.19	0.751	0.961
	LTE Band 66	20M	QPSK	50	24	Back	5mm	-	Reduced	132322	1745	18.15	19.00	1.216	-0.06	1.130	1.374
	LTE Band 66	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	132322	1745	18.15	19.00	1.216	-0.06	1.140	1.386
	LTE Band 66	20M	QPSK	50	24	Back	5mm	-	Reduced	132072	1720	17.78	19.00	1.324	-0.07	0.952	1.261
	LTE Band 66	20M	QPSK	50	24	Back	5mm	-	Reduced	132572	1770	17.93	19.00	1.279	0.05	1.030	1.318
	LTE Band 66	20M	QPSK	50	24	Front	12mm	-	Full	132572	1770	22.33	23.00	1.167	0.02	0.510	0.595
	LTE Band 66	20M	QPSK	50	24	Back	20mm	Headset 1	Full	132322	1745	22.55	23.00	1.109	0.08	0.361	0.400
	LTE Band 66	20M	QPSK	100	0	Front	5mm	-	Reduced	132322	1745	18.14	19.00	1.219	0.03	0.836	1.019
	LTE Band 66	20M	QPSK	100	0	Back	5mm	-	Reduced	132322	1745	18.14	19.00	1.219	-0.17	1.180	1.438
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Headset 1	Reduced	132322	1745	18.14	19.00	1.219	-0.17	1.150	1.402
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Headset 2	Reduced	132322	1745	18.14	19.00	1.219	0.02	1.130	1.377
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Headset 3	Reduced	132322	1745	18.14	19.00	1.219	-0.05	1.130	1.377
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Headset 4	Reduced	132322	1745	18.14	19.00	1.219	0.01	1.120	1.365
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Headset 5	Reduced	132322	1745	18.14	19.00	1.219	-0.04	1.130	1.377
	LTE Band 66	20M	QPSK	100	0	Front	12mm	-	Full	132322	1745	22.52	23.00	1.117	0.01	0.490	0.547
	LTE Band 66	20M	QPSK	100	0	Back	20mm	-	Full	132322	1745	22.52	23.00	1.117	0.09	0.355	0.396



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	19100	1900	21.42	22.00	1.143	0.03	0.872	0.997
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	19100	1900	21.42	22.00	1.143	0.07	1.160	1.326
	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	18700	1860	21.41	22.00	1.146	0.02	1.150	1.317
	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	18900	1880	21.27	22.00	1.183	0.08	0.920	1.088
35	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	18700	1860	21.41	22.00	1.146	-0.04	1.260	1.443
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	18900	1880	21.27	22.00	1.183	0.04	1.160	1.372
	LTE Band 2	20M	QPSK	1	49	Front	5mm	Headset 1	Reduced	18700	1860	21.41	22.00	1.146	0.06	1.110	1.272
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	18700	1860	21.41	22.00	1.146	0.03	1.210	1.386
	LTE Band 2	20M	QPSK	1	49	Front	12mm	-	Full	18700	1860	23.03	24.00	1.250	-0.02	0.590	0.738
	LTE Band 2	20M	QPSK	1	49	Back	20mm	-	Full	18700	1860	23.03	24.00	1.250	-0.07	0.328	0.410
	LTE Band 2	20M	QPSK	50	24	Front	5mm	-	Reduced	19100	1900	21.16	22.00	1.213	-0.03	0.799	0.969
	LTE Band 2	20M	QPSK	50	24	Front	5mm	-	Reduced	18700	1860	21.14	22.00	1.219	0.07	0.851	1.037
	LTE Band 2	20M	QPSK	50	24	Front	5mm	-	Reduced	18900	1880	21.09	22.00	1.233	0.02	0.808	0.996
	LTE Band 2	20M	QPSK	50	24	Back	5mm	-	Reduced	19100	1900	21.16	22.00	1.213	-0.07	0.992	1.204
	LTE Band 2	20M	QPSK	50	24	Back	5mm	-	Reduced	18700	1860	21.14	22.00	1.219	0.05	1.160	1.414
	LTE Band 2	20M	QPSK	50	24	Back	5mm	-	Reduced	18900	1880	21.09	22.00	1.233	-0.02	1.040	1.282
	LTE Band 2	20M	QPSK	50	24	Back	5mm	Headset 1	Reduced	18700	1860	21.14	22.00	1.219	0.02	1.130	1.377
	LTE Band 2	20M	QPSK	100	0	Front	5mm	-	Reduced	19100	1900	21.14	22.00	1.219	-0.02	0.722	0.880
	LTE Band 2	20M	QPSK	100	0	Back	5mm	-	Reduced	19100	1900	21.14	22.00	1.219	0.05	1.010	1.231
	LTE Band 2	20M	QPSK	100	0	Back	5mm	Headset 1	Reduced	19100	1900	21.14	22.00	1.219	0.01	1.000	1.219
	LTE Band 7	20M	QPSK	1	49	Front	5mm	-	Reduced	21100	2535	16.34	17.00	1.164	0.02	0.419	0.488
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	21100	2535	16.34	17.00	1.164	-0.1	0.919	1.070
36	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	20850	2510	16.32	17.00	1.169	-0.04	1.030	1.205
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	21350	2560	16.21	17.00	1.199	-0.19	0.815	0.978
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Headset 1	Reduced	20850	2510	16.32	17.00	1.169	0.02	1.010	1.181
	LTE Band 7	20M	QPSK	1	49	Front	12mm	-	Full	21100	2535	23.29	24.00	1.178	0.08	0.410	0.483
	LTE Band 7	20M	QPSK	1	49	Back	20mm	-	Full	20850	2510	22.90	24.00	1.288	-0.02	0.458	0.590
	LTE Band 7	20M	QPSK	50	24	Front	5mm	-	Reduced	21100	2535	16.26	17.00	1.186	0.08	0.428	0.508
	LTE Band 7	20M	QPSK	50	24	Back	5mm	-	Reduced	21100	2535	16.26	17.00	1.186	0.05	0.870	1.032
	LTE Band 7	20M	QPSK	50	24	Back	5mm	-	Reduced	20850	2510	16.19	17.00	1.205	0.04	0.939	1.132
	LTE Band 7	20M	QPSK	50	24	Back	5mm	-	Reduced	21350	2560	16.16	17.00	1.213	0.03	0.788	0.956
	LTE Band 7	20M	QPSK	100	0	Back	5mm	-	Reduced	21100	2535	16.23	17.00	1.194	-0.04	0.858	1.024

<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	-	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.08	0.234	0.297
37	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	-	Full	11	2462	18.50	19.50	1.259	99.31	1.007	0.02	0.301	0.382

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	5mm	-	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.1	0.292	0.455
38	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	-	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.11	0.614	0.956
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	-	Full	62	5310	15.72	17.00	1.343	96.32	1.038	0.1	0.532	0.741
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	5mm	-	Reduced	122	5610	13.54	15.00	1.400	92.79	1.078	0.02	0.256	0.386
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	122	5610	13.54	15.00	1.400	92.79	1.078	0.03	0.575	0.868
39	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	138	5690	13.49	15.00	1.416	92.79	1.078	-0.03	0.656	1.001
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	12mm	-	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.08	0.202	0.305
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	20mm	-	Full	138	5690	17.49	19.00	1.416	92.79	1.078	0.02	0.439	0.670
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	-	Full	155	5775	12.25	13.50	1.334	92.79	1.078	0.12	0.162	0.233
40	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Full	155	5775	12.25	13.50	1.334	92.79	1.078	-0.1	0.325	0.467

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Front	5mm	-	Full	39	2441	11.20	12.00	1.202	77.36	1.293	0.03	0.040	0.062
41	Bluetooth	DH5 1Mbps	Back	5mm	-	Full	39	2441	11.20	12.00	1.202	77.36	1.293	-0.15	0.053	0.082

15.4 Product specific 10g SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
42	GSM850	GPRS(2 Tx slots)	Back	0mm	Full	251	848.8	31.09	32.00	1.233	0.15	1.460	1.800
43	GSM1900	GPRS(2 Tx slots)	Bottom Side	0mm	Full	661	1880	28.25	29.50	1.334	-0.14	2.690	3.587
	GSM1900	GPRS(2 Tx slots)	Bottom Side	0mm	Full	810	1909.8	28.24	29.50	1.337	-0.03	2.620	3.502
	GSM1900	GPRS(2 Tx slots)	Bottom Side	0mm	Full	512	1850.2	28.21	29.50	1.346	-0.07	2.660	3.580
	GSM1900	GPRS(2 Tx slots)	Front	0mm	Full	661	1880	28.25	29.50	1.334	0.06	1.470	1.960
	GSM1900	GPRS(2 Tx slots)	Back	0mm	Full	661	1880	28.25	29.50	1.334	-0.05	1.870	2.494
	GSM1900	GPRS(2 Tx slots)	Back	0mm	Full	810	1909.8	28.24	29.50	1.337	0.1	2.090	2.793
	GSM1900	GPRS(2 Tx slots)	Back	0mm	Full	512	1850.2	28.21	29.50	1.346	-0.15	1.890	2.544

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4182	836.4	23.13	24.00	1.222	-0.07	2.290	2.798
	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4132	826.4	23.09	24.00	1.233	-0.02	2.280	2.811
44	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4233	846.6	22.94	24.00	1.276	0.04	2.590	3.306
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Reduced	1413	1732.6	20.67	21.50	1.211	0.05	1.790	2.167
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Reduced	1312	1712.4	20.58	21.50	1.236	0.04	1.670	2.064
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Reduced	1513	1752.6	20.59	21.50	1.233	0.03	1.740	2.146
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Reduced	1413	1732.6	20.67	21.50	1.211	0.04	2.650	3.208
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Reduced	1312	1712.4	20.58	21.50	1.236	0.01	2.610	3.226
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Reduced	1513	1752.6	20.59	21.50	1.233	0.06	2.400	2.959
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1413	1732.6	20.67	21.50	1.211	0.11	2.780	3.365
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	20.58	21.50	1.236	-0.02	2.690	3.325
45	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1513	1752.6	20.59	21.50	1.233	-0.08	2.840	3.502
	WCDMA IV	RMC 12.2Kbps	Front	9mm	Full	1413	1732.6	23.04	24.00	1.247	0.04	0.686	0.856
	WCDMA IV	RMC 12.2Kbps	Back	13mm	Full	1312	1712.4	22.90	24.00	1.288	-0.07	0.650	0.837
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	Full	1513	1752.6	23.03	24.00	1.250	0.02	1.020	1.275
	WCDMA II	RMC 12.2Kbps	Front	0mm	Reduced	9538	1907.6	21.16	22.00	1.213	-0.06	1.320	1.602
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9538	1907.6	21.16	22.00	1.213	0.14	1.540	1.869
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9538	1907.6	21.16	22.00	1.213	0.07	2.230	2.706
46	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9262	1852.4	21.09	22.00	1.233	-0.17	2.570	3.169
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9400	1880	21.12	22.00	1.225	-0.16	2.450	3.000
	WCDMA II	RMC 12.2Kbps	Front	9mm	Full	9538	1907.6	23.22	24.00	1.197	0.12	0.553	0.662
	WCDMA II	RMC 12.2Kbps	Back	13mm	Full	9538	1907.6	23.22	24.00	1.197	0.02	0.403	0.482
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	Full	9262	1852.4	23.09	24.00	1.233	-0.03	0.672	0.829



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
47	LTE Band 5	10M	QPSK	1	25	Back	0mm	Full	20525	836.5	23.25	24.00	1.189	0.08	2.030	2.413
	LTE Band 5	10M	QPSK	25	12	Back	0mm	Full	20525	836.5	22.05	23.00	1.245	0.07	1.170	1.456
	LTE Band 5	10M	QPSK	50	0	Back	0mm	Full	20525	836.5	21.94	23.00	1.276	0.07	1.150	1.468
	LTE Band 66	20M	QPSK	1	49	Front	0mm	Reduced	132322	1745	20.98	21.50	1.127	0.02	1.850	2.085
	LTE Band 66	20M	QPSK	1	49	Front	0mm	Reduced	132072	1720	20.61	21.50	1.227	-0.1	1.560	1.915
	LTE Band 66	20M	QPSK	1	49	Front	0mm	Reduced	132572	1770	20.78	21.50	1.180	0.03	1.660	1.959
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Reduced	132322	1745	20.98	21.50	1.127	0.06	2.740	3.089
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Reduced	132072	1720	20.61	21.50	1.227	-0.13	2.380	2.921
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Reduced	132572	1770	20.78	21.50	1.180	-0.19	2.230	2.632
	LTE Band 66	20M	QPSK	1	49	Bottom Side	0mm	Reduced	132322	1745	20.98	21.50	1.127	-0.06	2.890	3.258
	LTE Band 66	20M	QPSK	1	49	Bottom Side	0mm	Reduced	132072	1720	20.61	21.50	1.227	-0.07	2.770	3.400
	LTE Band 66	20M	QPSK	1	49	Bottom Side	0mm	Reduced	132572	1770	20.78	21.50	1.180	-0.04	2.940	3.470
	LTE Band 66	20M	QPSK	1	49	Front	9mm	Full	132322	1745	23.10	24.00	1.230	0.02	0.595	0.732
	LTE Band 66	20M	QPSK	1	49	Back	13mm	Full	132322	1745	23.10	24.00	1.230	0.06	0.544	0.669
	LTE Band 66	20M	QPSK	1	49	Bottom Side	10mm	Full	132572	1770	23.02	24.00	1.253	0.01	1.070	1.341
	LTE Band 66	20M	QPSK	50	24	Front	0mm	Reduced	132322	1745	20.93	21.50	1.140	-0.07	1.840	2.098
	LTE Band 66	20M	QPSK	50	24	Front	0mm	Reduced	132072	1720	20.52	21.50	1.253	0.05	1.550	1.942
	LTE Band 66	20M	QPSK	50	24	Front	0mm	Reduced	132572	1770	20.75	21.50	1.189	-0.02	1.660	1.973
	LTE Band 66	20M	QPSK	50	24	Back	0mm	Reduced	132322	1745	20.93	21.50	1.140	0.08	2.510	2.862
	LTE Band 66	20M	QPSK	50	24	Back	0mm	Reduced	132072	1720	20.52	21.50	1.253	0.05	2.430	3.045
	LTE Band 66	20M	QPSK	50	24	Back	0mm	Reduced	132572	1770	20.75	21.50	1.189	-0.02	2.140	2.543
	LTE Band 66	20M	QPSK	50	24	Bottom Side	0mm	Reduced	132322	1745	20.93	21.50	1.140	0.02	3.130	3.569
	LTE Band 66	20M	QPSK	50	24	Bottom Side	0mm	Reduced	132072	1720	20.52	21.50	1.253	0.03	2.850	3.571
	LTE Band 66	20M	QPSK	50	24	Bottom Side	0mm	Reduced	132572	1770	20.75	21.50	1.189	0.06	2.970	3.530
	LTE Band 66	20M	QPSK	50	24	Front	9mm	Full	132322	1745	22.55	23.00	1.109	0.03	0.450	0.499
	LTE Band 66	20M	QPSK	50	24	Back	13mm	Full	132072	1720	22.37	23.00	1.156	0.01	0.400	0.462
	LTE Band 66	20M	QPSK	50	24	Bottom Side	10mm	Full	132072	1720	22.37	23.00	1.156	0.07	0.860	0.994
	LTE Band 66	20M	QPSK	100	0	Front	0mm	Reduced	132322	1745	20.91	21.50	1.146	0.03	1.780	2.039
	LTE Band 66	20M	QPSK	100	0	Back	0mm	Reduced	132322	1745	20.91	21.50	1.146	0.14	2.750	3.150
48	LTE Band 66	20M	QPSK	100	0	Bottom Side	0mm	Reduced	132322	1745	20.91	21.50	1.146	0.11	3.120	3.574
	LTE Band 66	20M	QPSK	100	0	Front	9mm	Full	132322	1745	22.52	23.00	1.117	0.02	0.430	0.480
	LTE Band 66	20M	QPSK	100	0	Back	13mm	Full	132322	1745	22.52	23.00	1.117	0.09	0.394	0.440
	LTE Band 66	20M	QPSK	100	0	Bottom Side	10mm	Full	132322	1745	22.52	23.00	1.117	0.03	0.810	0.905
	LTE Band 2	20M	QPSK	1	49	Front	0mm	Reduced	19100	1900	21.91	22.50	1.146	0.04	1.520	1.741
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	19100	1900	21.91	22.50	1.146	0.02	1.760	2.016
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	18700	1860	21.88	22.50	1.153	0.11	1.740	2.007
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	18900	1880	21.78	22.50	1.180	0.13	1.680	1.983
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	19100	1900	21.91	22.50	1.146	0.12	2.510	2.875
49	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	18700	1860	21.88	22.50	1.153	-0.11	2.660	3.068
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	18900	1880	21.78	22.50	1.180	-0.13	2.590	3.057
	LTE Band 2	20M	QPSK	1	49	Front	9mm	Full	19100	1900	23.01	24.00	1.256	0.02	0.563	0.707
	LTE Band 2	20M	QPSK	1	49	Back	13mm	Full	19100	1900	23.01	24.00	1.256	-0.03	0.413	0.519
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	Full	18700	1860	23.03	24.00	1.250	0.07	0.776	0.970
	LTE Band 2	20M	QPSK	50	24	Front	0mm	Reduced	19100	1900	21.76	22.50	1.186	0.06	1.160	1.375
	LTE Band 2	20M	QPSK	50	24	Back	0mm	Reduced	19100	1900	21.76	22.50	1.186	-0.13	1.360	1.613
	LTE Band 2	20M	QPSK	50	24	Bottom Side	0mm	Reduced	19100	1900	21.76	22.50	1.186	-0.19	2.050	2.431
	LTE Band 2	20M	QPSK	50	24	Bottom Side	0mm	Reduced	18700	1860	21.58	22.50	1.236	-0.06	2.220	2.744
	LTE Band 2	20M	QPSK	50	24	Bottom Side	0mm	Reduced	18900	1880	21.68	22.50	1.208	-0.07	2.180	2.633
	LTE Band 2	20M	QPSK	100	0	Back	0mm	Reduced	19100	1900	21.72	22.50	1.197	0.08	1.370	1.640
	LTE Band 2	20M	QPSK	100	0	Bottom Side	0mm	Reduced	19100	1900	21.72	22.50	1.197	0.05	2.050	2.453

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	49	Front	0mm	Reduced	21100	2535	18.83	19.50	1.167	-0.19	1.000	1.167
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	21100	2535	18.83	19.50	1.167	-0.06	2.750	3.209
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	20850	2510	18.78	19.50	1.180	-0.07	2.850	3.364
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	21350	2560	18.81	19.50	1.172	-0.02	2.600	3.048
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	21100	2535	18.83	19.50	1.167	0.08	2.320	2.707
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	20850	2510	18.78	19.50	1.180	-0.19	2.430	2.868
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	21350	2560	18.81	19.50	1.172	-0.06	2.150	2.520
	LTE Band 7	20M	QPSK	1	49	Front	9mm	Full	21100	2535	23.29	24.00	1.178	0.11	0.282	0.332
	LTE Band 7	20M	QPSK	1	49	Back	13mm	Full	20850	2510	22.90	24.00	1.288	0.05	0.514	0.662
	LTE Band 7	20M	QPSK	1	49	Bottom Side	10mm	Full	20850	2510	22.90	24.00	1.288	0.04	1.040	1.340
	LTE Band 7	20M	QPSK	50	24	Front	0mm	Reduced	21100	2535	18.75	19.50	1.189	0.12	0.979	1.164
	LTE Band 7	20M	QPSK	50	24	Back	0mm	Reduced	21100	2535	18.75	19.50	1.189	0.11	2.670	3.173
50	LTE Band 7	20M	QPSK	50	24	Back	0mm	Reduced	20850	2510	18.66	19.50	1.213	-0.06	2.810	3.410
	LTE Band 7	20M	QPSK	50	24	Back	0mm	Reduced	21350	2560	18.70	19.50	1.202	-0.07	2.600	3.126
	LTE Band 7	20M	QPSK	50	24	Bottom Side	0mm	Reduced	21100	2535	18.75	19.50	1.189	-0.04	2.340	2.781
	LTE Band 7	20M	QPSK	50	24	Bottom Side	0mm	Reduced	20850	2510	18.66	19.50	1.213	0.06	2.480	3.009
	LTE Band 7	20M	QPSK	50	24	Bottom Side	0mm	Reduced	21350	2560	18.70	19.50	1.202	-0.13	2.150	2.585
	LTE Band 7	20M	QPSK	50	0	Front	9mm	Full	21100	2535	22.37	23.00	1.156	0.11	0.219	0.253
	LTE Band 7	20M	QPSK	50	0	Back	13mm	Full	20850	2510	22.09	23.00	1.233	0.05	0.470	0.580
	LTE Band 7	20M	QPSK	50	0	Bottom Side	10mm	Full	20850	2510	22.09	23.00	1.233	0.04	0.840	1.036
	LTE Band 7	20M	QPSK	100	0	Back	0mm	Reduced	21100	2535	18.68	19.50	1.208	-0.07	2.760	3.334
	LTE Band 7	20M	QPSK	100	0	Bottom Side	0mm	Reduced	21100	2535	18.68	19.50	1.208	0.05	2.300	2.778

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	0mm	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.03	0.224	0.349
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	0mm	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.1	0.399	0.621
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Side	0mm	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.12	0.003	0.004
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Full	54	5270	17.24	19.00	1.500	96.32	1.038	0.14	0.115	0.179
51	WLAN5.3GHz	802.11n-HT40 MCS0	Top Side	0mm	Full	54	5270	17.24	19.00	1.500	96.32	1.038	-0.01	0.709	1.104
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	0mm	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.02	0.394	0.594
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	0mm	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.04	0.961	1.450
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.01	0.037	0.055
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Full	122	5610	17.54	19.00	1.400	92.79	1.078	-0.03	0.373	0.563
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Full	122	5610	17.54	19.00	1.400	92.79	1.078	0.05	1.400	2.112
52	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Full	138	5690	17.49	19.00	1.416	92.79	1.078	-0.08	1.780	2.717

15.5 Repeated SAR Measurement

<1g>

No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	LTE Band 5	10M	QPSK	1	25	Back	5mm	Reduced	20525	836.5	22.81	23.50	1.172	-0.16	1.160	1	1.360
2nd	LTE Band 5	10M	QPSK	1	25	Back	5mm	Reduced	20525	836.5	22.81	23.50	1.172	-0.02	1.060	1.094	1.243
1st	LTE Band 66	20M	QPSK	100	0	Back	5mm	Reduced	132322	1745	18.14	19.00	1.219	-0.17	1.180	1	1.438
2nd	LTE Band 66	20M	QPSK	100	0	Back	5mm	Reduced	132322	1745	18.14	19.00	1.219	0.08	1.140	1.035	1.390
1st	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18700	1860	21.41	22.00	1.146	-0.04	1.260	1	1.443
2nd	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18700	1860	21.41	22.00	1.146	0.11	1.250	1.008	1.432
1st	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	20850	2510	15.51	16.00	1.119	-0.16	1.290	1	1.444
2nd	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	20850	2510	15.51	16.00	1.119	0.02	1.240	1.040	1.388

<10g>

No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	GSM1900	-	-	-	-	GPRS(2 Tx slots)	Bottom Side	0mm	Full	661	1880	28.25	29.50	1.334	-0.14	2.690	1	3.587
2nd	GSM1900	-	-	-	-	GPRS(2 Tx slots)	Bottom Side	0mm	Full	661	1880	28.25	29.50	1.334	0.19	2.550	1.055	3.400
1st	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Full	4233	846.6	22.94	24.00	1.276	0.04	2.590	1	3.306
2nd	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Full	4233	846.6	22.94	24.00	1.276	0.02	2.480	1.044	3.166
1st	LTE Band 66	20M	QPSK	50	24	-	Bottom Side	0mm	Reduced	132322	1745	20.93	21.50	1.140	0.02	3.130	1	3.569
2nd	LTE Band 66	20M	QPSK	50	24	-	Bottom Side	0mm	Reduced	132322	1745	20.93	21.50	1.140	-0.1	3.040	1.030	3.466
1st	LTE Band 7	20M	QPSK	1	49	-	Back	0mm	Reduced	20850	2510	18.78	19.50	1.180	-0.07	2.850	1	3.364
2nd	LTE Band 7	20M	QPSK	1	49	-	Back	0mm	Reduced	20850	2510	18.78	19.50	1.180	0.05	2.820	1.011	3.329

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
3. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The ratio is the difference in percentage between original and repeated *measured SAR*.
5. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product specific 10g SAR
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes
5.	GSM Voice + WLAN5.3/5.5GHz	Yes	Yes		Yes
6.	GPRS/EDGE + WLAN5.3/5.5GHz	Yes	Yes		Yes
7.	WCDMA + WLAN5.3/5.5GHz	Yes	Yes		Yes
8.	LTE + WLAN5.3/5.5GHz	Yes	Yes		Yes
9.	GSM Voice + WLAN5.2/5.8GHz	Yes	Yes		Yes
10.	GPRS/EDGE + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
11.	WCDMA + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
12.	LTE + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
13.	GSM Voice + Bluetooth	Yes	Yes		Yes
14.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes	Yes
15.	WCDMA + Bluetooth	Yes	Yes	Yes	Yes
16.	LTE + Bluetooth	Yes	Yes	Yes	Yes

General Note:

- This device supports VoIP in GPRS, EGPRS, WCDMA, and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.
- EUT will choose each GSM, WCDMA and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
- This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.
- This device 2.4GHz WLAN/ 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only).
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment though they have independent antenna.
- WLAN 2.4GHz and Bluetooth share the same antenna so can't transmit simultaneously.
- According to the EUT character, WLAN 5GHz and Bluetooth can't transmit simultaneously.
- Chose the worst zoom scan SAR of WLAN correspondingly for co-located with WWAN analysis.
- The reported SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
 - $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.
 - The SPLSR calculated results please refer to section 16.5.

16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	4	6	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.496	0.295	0.604	0.047	0.79	1.10	0.54
		Right Tilted	0.259	0.370	0.666	0.061	0.63	0.93	0.32
		Left Cheek	0.481	0.584	1.105	0.140	1.07	1.59	0.62
		Left Tilted	0.270	0.581	0.833	0.114	0.85	1.10	0.38
	GSM1900	Right Cheek	0.252	0.295	0.604	0.047	0.55	0.86	0.30
		Right Tilted	0.140	0.370	0.666	0.061	0.51	0.81	0.20
		Left Cheek	0.288	0.584	1.105	0.140	0.87	1.39	0.43
		Left Tilted	0.215	0.581	0.833	0.114	0.80	1.05	0.33
WCDMA	WCDMA V	Right Cheek	0.447	0.295	0.604	0.047	0.74	1.05	0.49
		Right Tilted	0.239	0.370	0.666	0.061	0.61	0.91	0.30
		Left Cheek	0.407	0.584	1.105	0.140	0.99	1.51	0.55
		Left Tilted	0.241	0.581	0.833	0.114	0.82	1.07	0.36
	WCDMA IV	Right Cheek	0.321	0.295	0.604	0.047	0.62	0.93	0.37
		Right Tilted	0.126	0.370	0.666	0.061	0.50	0.79	0.19
		Left Cheek	0.228	0.584	1.105	0.140	0.81	1.33	0.37
		Left Tilted	0.170	0.581	0.833	0.114	0.75	1.00	0.28
	WCDMA II	Right Cheek	0.268	0.295	0.604	0.047	0.56	0.87	0.32
		Right Tilted	0.122	0.370	0.666	0.061	0.49	0.79	0.18
		Left Cheek	0.273	0.584	1.105	0.140	0.86	1.38	0.41
		Left Tilted	0.190	0.581	0.833	0.114	0.77	1.02	0.30
LTE	LTE Band 5	Right Cheek	0.441	0.295	0.604	0.047	0.74	1.05	0.49
		Right Tilted	0.227	0.370	0.666	0.061	0.60	0.89	0.29
		Left Cheek	0.403	0.584	1.105	0.140	0.99	1.51	0.54
		Left Tilted	0.209	0.581	0.833	0.114	0.79	1.04	0.32
	LTE Band 66	Right Cheek	0.290	0.295	0.604	0.047	0.59	0.89	0.34
		Right Tilted	0.121	0.370	0.666	0.061	0.49	0.79	0.18
		Left Cheek	0.221	0.584	1.105	0.140	0.81	1.33	0.36
		Left Tilted	0.165	0.581	0.833	0.114	0.75	1.00	0.28
	LTE Band 2	Right Cheek	0.254	0.295	0.604	0.047	0.55	0.86	0.30
		Right Tilted	0.131	0.370	0.666	0.061	0.50	0.80	0.19
		Left Cheek	0.269	0.584	1.105	0.140	0.85	1.37	0.41
		Left Tilted	0.207	0.581	0.833	0.114	0.79	1.04	0.32
	LTE Band 7	Right Cheek	0.145	0.295	0.604	0.047	0.44	0.75	0.19
		Right Tilted	0.077	0.370	0.666	0.061	0.45	0.74	0.14
		Left Cheek	0.257	0.584	1.105	0.140	0.84	1.36	0.40
		Left Tilted	0.101	0.581	0.833	0.114	0.68	0.93	0.22



16.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1 WWAN 1g SAR (W/kg)	2 2.4GHz WLAN 1g SAR (W/kg)	4 5GHz WLAN 1g SAR (W/kg)	6 Bluetooth 1g SAR (W/kg)	1+2 Summed 1g SAR (W/kg)	Case No	SPLSR	1+4 Summed 1g SAR (W/kg)	Case No	SPLSR	1+6 Summed 1g SAR (W/kg)
GSM	GSM850	Front	0.646	0.297	0.405	0.062	0.94			1.05			0.71
		Back	1.257	0.382	0.891	0.082	1.64	#01	0.01	2.15	#10	0.02	1.34
		Left side	0.246	0.047	0.015	0.006	0.29			0.26			0.25
		Right side	0.445	0.318	0.161	0.066	0.76			0.61			0.51
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	0.420				0.42			0.42			0.42
	GSM1900	Front	1.071	0.297	0.405	0.062	1.37			1.48			1.13
		Back	1.215	0.382	0.891	0.082	1.60	#02	0.01	2.11	#11	0.02	1.30
		Left side	0.305	0.047	0.015	0.006	0.35			0.32			0.31
		Right side	0.090	0.318	0.161	0.066	0.41			0.25			0.16
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	1.297				1.30			1.30			1.30
WCDMA	WCDMA V	Front	0.611	0.297	0.405	0.062	0.91			1.02			0.67
		Back	1.184	0.382	0.891	0.082	1.57			2.08	#12	0.02	1.27
		Left side	0.267	0.047	0.015	0.006	0.31			0.28			0.27
		Right side	0.394	0.318	0.161	0.066	0.71			0.56			0.46
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	0.305				0.31			0.31			0.31
	WCDMA IV	Front	0.935	0.297	0.405	0.062	1.23			1.34			1.00
		Back	1.363	0.382	0.891	0.082	1.75	#04	0.02	2.25	#13	0.02	1.45
		Left side	0.152	0.047	0.015	0.006	0.20			0.17			0.16
		Right side	0.114	0.318	0.161	0.066	0.43			0.28			0.18
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	1.372				1.37			1.37			1.37
	WCDMA II	Front	0.971	0.297	0.405	0.062	1.27			1.38			1.03
		Back	1.206	0.382	0.891	0.082	1.59			2.10	#14	0.02	1.29
		Left side	0.208	0.047	0.015	0.006	0.26			0.22			0.21
		Right side	0.037	0.318	0.161	0.066	0.36			0.20			0.10
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	1.163				1.16			1.16			1.16
LTE	LTE Band 5	Front	0.707	0.297	0.405	0.062	1.00			1.11			0.77
		Back	1.360	0.382	0.891	0.082	1.74	#06	0.02	2.25	#15	0.02	1.44
		Left side	0.394	0.047	0.015	0.006	0.44			0.41			0.40
		Right side	0.559	0.318	0.161	0.066	0.88			0.72			0.63
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	0.396				0.40			0.40			0.40
	LTE Band 66	Front	1.019	0.297	0.405	0.062	1.32			1.42			1.08
		Back	1.438	0.382	0.891	0.082	1.82	#07	0.02	2.33	#16	0.02	1.52
		Left side	0.123	0.047	0.015	0.006	0.17			0.14			0.13
		Right side	0.115	0.318	0.161	0.066	0.43			0.28			0.18
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	1.256				1.26			1.26			1.26
	LTE Band 2	Front	1.317	0.297	0.405	0.062	1.61	#19	0.01	1.72	#20	0.01	1.38
		Back	1.443	0.382	0.891	0.082	1.83	#08	0.02	2.33	#17	0.02	1.53
		Left side	0.302	0.047	0.015	0.006	0.35			0.32			0.31
		Right side	0.085	0.318	0.161	0.066	0.40			0.25			0.15
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	1.410				1.41			1.41			1.41
	LTE Band 7	Front	0.508	0.297	0.405	0.062	0.81			0.91			0.57
		Back	1.205	0.382	0.891	0.082	1.59			2.10	#18	0.02	1.29
		Left side	0.123	0.047	0.015	0.006	0.17			0.14			0.13
		Right side	0.046	0.318	0.161	0.066	0.36			0.21			0.11
		Top side		0.321	0.755	0.058	0.32			0.76			0.06
		Bottom side	1.444				1.44			1.44			1.44

16.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	4	6	1+2 Summed 1g SAR (W/kg)	Case No	SPLSR	1+4 Summed 1g SAR (W/kg)	Case No	SPLSR	1+6 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)							
GSM	GSM850	Front	0.646	0.297	0.455	0.062	0.94			1.10			0.71
		Back	1.257	0.382	1.001	0.082	1.64	#01	0.01	2.26	#26	0.02	1.34
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.176				1.18			1.18			1.18
	GSM1900	Front	1.071	0.297	0.455	0.062	1.37			1.53			1.13
		Back	1.215	0.382	1.001	0.082	1.60	#02	0.01	2.22	#27	0.02	1.30
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.201				1.20			1.20			1.20
WCDMA	WCDMA V	Front	0.611	0.297	0.455	0.062	0.91			1.07			0.67
		Back	1.184	0.382	1.001	0.082	1.57			2.19	#28	0.02	1.27
		Front with Headset					0.00			0.00			0.00
		Back with Headset					0.00			0.00			0.00
	WCDMA IV	Front	0.935	0.297	0.455	0.062	1.23			1.39			1.00
		Back	1.363	0.382	1.001	0.082	1.75	#04	0.02	2.36	#29	0.02	1.45
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.274				1.27			1.27			1.27
	WCDMA II	Front	0.971	0.297	0.455	0.062	1.27			1.43			1.03
		Back	1.206	0.382	1.001	0.082	1.59			2.21	#30	0.02	1.29
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.189				1.19			1.19			1.19
LTE	LTE Band 5	Front	0.707	0.297	0.455	0.062	1.00			1.16			0.77
		Back	1.360	0.382	1.001	0.082	1.74	#06	0.02	2.36	#31	0.02	1.44
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.289				1.29			1.29			1.29
	LTE Band 66	Front	1.019	0.297	0.455	0.062	1.32			1.47			1.08
		Back	1.438	0.382	1.001	0.082	1.82	#07	0.02	2.44	#32	0.02	1.52
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.402				1.40			1.40			1.40
	LTE Band 2	Front	1.317	0.297	0.455	0.062	1.61	#19	0.01	1.77	#35	0.01	1.38
		Back	1.443	0.382	1.001	0.082	1.83	#08	0.02	2.44	#33	0.02	1.53
		Front with Headset	1.272				1.27			1.27			1.27
		Back with Headset	1.386				1.39			1.39			1.39
	LTE Band 7	Front	0.508	0.297	0.455	0.062	0.81			0.96			0.57
		Back	1.205	0.382	1.001	0.082	1.59			2.21	#34	0.02	1.29
		Front with Headset					0.00			0.00			0.00
		Back with Headset	1.181				1.18			1.18			1.18

16.4 Product specific 10g SAR Exposure Conditions

WWAN Band		Exposure Position	1	4	1+4 Summed 10g SAR (W/kg)	Case No	SPLSR
			WWAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)			
GSM	GSM850	Front		0.594	0.59		
		Back	1.800	1.450	3.25		
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side			0.00		
	GSM1900	Front	1.960	0.594	2.55		
		Back	2.793	1.450	4.24	#21	0.06
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side	3.587		3.59		
WCDMA	WCDMA V	Front		0.594	0.59		
		Back	3.306	1.450	4.76	#22	0.07
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side			0.00		
	WCDMA IV	Front	2.167	0.594	2.76		
		Back	3.226	1.450	4.68	#23	0.07
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side	3.502		3.50		
	WCDMA II	Front	1.602	0.594	2.20		
		Back	1.869	1.450	3.32		
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side	3.169		3.17		
LTE	LTE Band 5	Front		0.594	0.59		
		Back	2.413	1.450	3.86		
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side			0.00		
	LTE Band 66	Front	2.098	0.594	2.69		
		Back	3.150	1.450	4.60	#24	0.07
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side	3.574		3.57		
	LTE Band 2	Front	1.741	0.594	2.34		
		Back	2.016	1.450	3.47		
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side	3.068		3.07		
	LTE Band 7	Front	1.167	0.594	1.76		
		Back	3.410	1.450	4.86	#25	0.07
		Left side		0.055	0.06		
		Right side		0.563	0.56		
		Top side		2.717	2.72		
		Bottom side	3.009		3.01		


Remark:

1. For Bluetooth Product specific 10g stand-alone SAR is not required for a transmitter or antenna, due to 1g hotspot SAR is <1.2W/kg.
2. If SPLSR ≤ 0.10 for 10g SAR, simultaneously transmission SAR measurement is not necessary.


16.5 SPLSR Evaluation and Analysis

General Note:


1. When standalone SAR is measured for both antennas in the pair, the peak location separation distance is computed by the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates in the area scans or extrapolated peak SAR locations in the zoom scans, as appropriate.
2. $SPLSR = (SAR1 + SAR2)1.5 / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.




Front for WWAN+WLAN2.4GHz_5mm




Back for WWAN+WLAN2.4GHz_5mm



Front for WWAN+ WLAN5GHz_5mm



Back for WWAN+WLAN5GHz_5mm



Back for WWAN+WLAN5GHz_0mm

Back 5mm (wwan+2.4G)-Hotspot/Body worn											
Case 1 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	GSM 850	Back	1.257	5	-0.0245	-0.0805	-0.208				
WLAN2.4GHz	0.382		5	-0.0422	0.0684	-0.207					
Case 2 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	GSM 1900	Back	1.215	5	0.001	-0.0815	-0.207				
WLAN2.4GHz	0.382		5	-0.0422	0.0684	-0.207					
Case 4 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	WCDMA IV	Back	1.363	5	-0.023	-0.0715	-0.208				
WLAN2.4GHz	0.382		5	-0.0422	0.0684	-0.207					
Case 6 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	LTE Band 5	Back	1.36	5	-0.0245	-0.0805	-0.208				
WLAN2.4GHz	0.382		5	-0.0422	0.0684	-0.207					
Case 7 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	LTE Band 66	Back	1.438	5	-0.0095	-0.082	-0.207				
WLAN2.4GHz	0.382		5	-0.0422	0.0684	-0.207					
Case 8 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	LTE Band 2	Back	1.443	5	-0.0255	-0.0795	-0.206				
WLAN2.4GHz	0.382		5	-0.0422	0.0684	-0.207					
Front 5mm (wwan+2.4G)-Hotspot/Body worn											
Case 19 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	LTE Band 2	Front	1.317	5	-0.035	-0.0795	-0.206				
WLAN2.4GHz	0.297		5	0.046	0.0672	-0.207					
Front 5mm (wwan+5G)-Hotspot											
Case 20 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
			(mm)	X	Y	Z					
	LTE Band 2	Front	1.317	5	-0.035	-0.0795	-0.206				
WLAN5GHz	0.405		5	0.006	0.076	-0.208					

Back 5mm (wwan+5G)-Hotspot											
Case 10 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM 850	Back	1.257	5	-0.0245	-0.0805	-0.208	158.1	2.15	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 11 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM 1900	Back	1.215	5	0.001	-0.0815	-0.207	165.6	2.11	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 12 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V	Back	1.184	5	-0.0205	-0.0765	-0.208	154.9	2.08	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 13 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Back	1.363	5	-0.023	-0.0715	-0.208	149.5	2.25	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 14 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II Cube 0	Back	1.206	5	-0.0135	-0.082	-0.207	161.9	2.10	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II Cube 1	Back	1.189	5	-0.0135	-0.0835	-0.207	163.4	2.08	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 15 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 5	Back	1.36	5	-0.0245	-0.0805	-0.208	158.1	2.25	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 16 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 66	Back	1.438	5	-0.0095	-0.082	-0.207	162.9	2.33	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 17 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Back	1.443	5	-0.0255	-0.0795	-0.206	157.0	2.33	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
Case 18 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7 Cube 0	Back	1.205	5	-0.0086	-0.088	-0.207	169.0	2.10	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				
	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7 Cube 1	Back	1.138	5	-0.014	-0.088	-0.207	167.6	2.03	0.02	Not required
	WLAN5GHz		0.891	5	-0.053	0.075	-0.209				

Back 5mm (wwan+5G)-Body worn											
Case 26 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	GSM 850	Back	1.257	(mm)	X	Y	Z	158.3	2.26	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 27 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	GSM 1900	Back	1.215	(mm)	X	Y	Z	164.9	2.22	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 28 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA V	Back	1.184	(mm)	X	Y	Z	155.0	2.19	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 29 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA IV	Back	1.363	(mm)	X	Y	Z	149.6	2.36	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 30 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II Cube 0	Back	1.206	(mm)	X	Y	Z	161.7	2.21	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
	WCDMA II Cube 1	Back	1.189	(mm)	X	Y	Z	163.2	2.19	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 31 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 5	Back	1.36	(mm)	X	Y	Z	158.3	2.36	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 32 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Back	1.438	(mm)	X	Y	Z	162.6	2.44	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 33 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Back	1.443	(mm)	X	Y	Z	157.1	2.44	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
Case 34 Plot No	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 7 Cube 0	Back	1.205	(mm)	X	Y	Z	168.7	2.21	0.02	Not required
	WLAN5GHz		1.001	5	-0.048	0.076	-0.208				
	LTE Band 7 Cube 1	Back	1.138	(mm)	X	Y	Z	167.5	2.14	0.02	Not required
WLAN5GHz	1.001		5	-0.048	0.076	-0.208					

Front 5mm (wwan+5G)-Body worn											
Case 35 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Front	1.317	5	-0.035	-0.0795	-0.206	167.8	1.77	0.01	Not required
	WLAN5GHz		0.455	5	0.02	0.079	-0.207				

Back 0mm (wwan+5G)											
Case 21 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM 1900 Cube 0	Back	2.793	0	0.0025	-0.075	-0.207	152.3	4.24	0.06	Not required
	WLAN5GHz		1.45	0	-0.041	0.071	-0.208				
	GSM 1900 Cube 1	Back	2.433	0	-0.023	-0.0765	-0.207	148.6	3.88	0.05	Not required
	WLAN5GHz		1.45	0	-0.041	0.071	-0.208				

Case 22 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V	Back	3.306	0	-0.026	-0.082	-0.207	153.7	4.76	0.07	Not required
	WLAN5GHz		1.45	0	-0.041	0.071	-0.208				

Case 23 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Back	3.226	0	-0.027	-0.074	-0.207	145.7	4.68	0.07	Not required
	WLAN5GHz		1.45	0	-0.041	0.071	-0.208				

Case 24 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 66	Back	3.15	0	-0.027	-0.074	-0.207	145.7	4.60	0.07	Not required
	WLAN5GHz		1.45	0	-0.041	0.071	-0.208				

Case 25 Plot No	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7	Back	3.41	0	-0.0062	-0.0796	-0.207	154.6	4.86	0.07	Not required
	WLAN5GHz		1.45	0	-0.041	0.071	-0.208				

Test Engineer : Changlin Huang, Bin He, Mengming Dai

17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [6] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [7] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [8] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [9] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [10] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [11] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [12] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [13] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.

-----THE END-----



Appendix A. Plots of System Performance Check

The plots are shown as follows.

System Check_Head_835MHz

DUT: D835V2-SN:4d162

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL_835_201111 Medium parameters used: $f = 835$ MHz; $\sigma = 0.929$ S/m; $\epsilon_r = 41.793$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.09 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.30 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 3.53 W/kg

SAR(1 g) = 2.36 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (measured) = 3.14 W/kg



System Check_Head_835MHz

DUT: D835V2-SN:4d162

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL_835_201115 Medium parameters used: $f = 835$ MHz; $\sigma = 0.938$ S/m; $\epsilon_r = 42.518$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(9.12, 9.12, 9.12); Calibrated: 2020.05.20;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.23 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 60.32 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 3.81 W/kg

SAR(1 g) = 2.52 W/kg; SAR(10 g) = 1.65 W/kg

Maximum value of SAR (measured) = 3.22 W/kg



System Check_Head_1750MHz**DUT: D1750V2-SN:1137**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL_1750_201111 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.373$ S/m; $\epsilon_r = 41.392$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(7.98, 7.98, 7.98); Calibrated: 2020.05.20;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.2 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 92.43 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 16.9 W/kg

SAR(1 g) = 9.39 W/kg; SAR(10 g) = 4.99 W/kg

Maximum value of SAR (measured) = 13.3 W/kg



System Check_Head_1750MHz**DUT: D1750V2-SN:1137**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL_1750_201112 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.406$ S/m; $\epsilon_r = 41.525$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.22, 5.22, 5.22); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 12.0 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 92.62 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 9.66 W/kg; SAR(10 g) = 5.27 W/kg

Maximum value of SAR (measured) = 12.0 W/kg



0 dB = 12.0 W/kg

System Check_Head_1900MHz**DUT: D1900V2-SN:5d182**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL_1900_201111 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.455$ S/m; $\epsilon_r = 40.068$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(7.67, 7.67, 7.67); Calibrated: 2020.05.20;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.2 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 101.4 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 19.7 W/kg

SAR(1 g) = 10.5 W/kg; SAR(10 g) = 5.34 W/kg

Maximum value of SAR (measured) = 15.1 W/kg



System Check_Head_1900MHz**DUT: D1900V2-SN:5d182**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL_1900_201112 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.453$ S/m; $\epsilon_r = 39.146$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.04, 5.04, 5.04); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.7 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 99.04 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 19.7 W/kg

SAR(1 g) = 10.6 W/kg; SAR(10 g) = 5.49 W/kg

Maximum value of SAR (measured) = 13.4 W/kg



0 dB = 13.4 W/kg

System Check_Head_2450MHz**DUT: D2450V2-SN:924**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL_2450_201118 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.809$ S/m; $\epsilon_r = 37.604$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(7.12, 7.12, 7.12); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 23.7 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 105.6 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 30.4 W/kg

SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.17 W/kg

Maximum value of SAR (measured) = 24.0 W/kg



System Check_Head_2600MHz**DUT: D2600V2-SN:1070**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL_2600_201112 Medium parameters used: $f = 2600$ MHz; $\sigma = 1.992$ S/m; $\epsilon_r = 40.445$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(6.94, 6.94, 6.94); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 26.0 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 118.7 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 33.4 W/kg

SAR(1 g) = 14.4 W/kg; SAR(10 g) = 6.17 W/kg

Maximum value of SAR (measured) = 26.0 W/kg



System Check_Head_2600MHz**DUT: D2600V2-SN:1070**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL_2600_201113 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.053$ S/m; $\epsilon_r = 38.007$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(4.42, 4.42, 4.42); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 21.5 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 105.8 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 35.1 W/kg

SAR(1 g) = 15.8 W/kg; SAR(10 g) = 6.84 W/kg

Maximum value of SAR (measured) = 21.3 W/kg



0 dB = 21.3 W/kg

System Check_Head_5250MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: HSL_5250_201119 Medium parameters used: $f = 5250$ MHz; $\sigma = 4.595$ S/m; $\epsilon_r = 36.652$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(5.09, 5.09, 5.09); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 20.8 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.40 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 33.7 W/kg

SAR(1 g) = 8.2 W/kg; SAR(10 g) = 2.28 W/kg

Maximum value of SAR (measured) = 20.5 W/kg



System Check_Head_5250MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: HSL_5250_201127 Medium parameters used: $f = 5250$ MHz; $\sigma = 4.597$ S/m; $\epsilon_r = 36.241$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(5.09, 5.09, 5.09); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.5 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 44.13 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 30.6 W/kg

SAR(1 g) = 7.42 W/kg; SAR(10 g) = 2.04 W/kg

Maximum value of SAR (measured) = 18.3 W/kg



System Check_Head_5600MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL_5600_201120 Medium parameters used: $f = 5600$ MHz; $\sigma = 5.002$ S/m; $\epsilon_r = 36.115$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(4.66, 4.66, 4.66); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 24.9 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 73.72 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 43.2 W/kg

SAR(1 g) = 8.12 W/kg; SAR(10 g) = 2.22 W/kg

Maximum value of SAR (measured) = 24.1 W/kg



System Check_Head_5600MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL_5600_201130 Medium parameters used: $f = 5600$ MHz; $\sigma = 4.954$ S/m; $\epsilon_r = 35.793$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(4.66, 4.66, 4.66); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 20.9 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 45.65 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 36.0 W/kg

SAR(1 g) = 7.96 W/kg; SAR(10 g) = 2.16 W/kg

Maximum value of SAR (measured) = 20.2 W/kg



System Check_Head_5750MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: HSL_5750_201122 Medium parameters used: $f = 5750$ MHz; $\sigma = 5.17$ S/m; $\epsilon_r = 35.843$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(4.68, 4.68, 4.68); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 5.71 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 35.06 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 10.3 W/kg

SAR(1 g) = 8.32 W/kg; SAR(10 g) = 2.35 W/kg

Maximum value of SAR (measured) = 5.70 W/kg



System Check_Head_5750MHz**DUT: D5GHzV2-SN:1167**

Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: HSL_5750_201202 Medium parameters used: $f = 5750$ MHz; $\sigma = 5.119$ S/m; $\epsilon_r = 35.497$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(4.68, 4.68, 4.68); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.9 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 46.55 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 34.2 W/kg

SAR(1 g) = 7.39 W/kg; SAR(10 g) = 2.03 W/kg

Maximum value of SAR (measured) = 19.1 W/kg





Appendix B. Plots of High SAR Measurement

The plots are shown as follows.

01_GSM850_GPRS(2 Tx slots)_Right Cheek_Ch251


Communication System: UID 0, GPRS/EDGE10 (0); Frequency: 848.8 MHz; Duty Cycle: 1:4.15
Medium: HSL_835_201111 Medium parameters used: $f = 849$ MHz; $\sigma = 0.941$ S/m; $\epsilon_r = 41.625$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch251/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.492 W/kg

Ch251/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.252 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.512 W/kg
SAR(1 g) = 0.402 W/kg; SAR(10 g) = 0.308 W/kg
Maximum value of SAR (measured) = 0.477 W/kg



02_GSM1900_GPRS(2 Tx slots)_Left Cheek_Ch661

Communication System: UID 0, GPRS/EDGE10 (0); Frequency: 1880 MHz; Duty Cycle: 1:4.15
Medium: HSL_1900_201112 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.432$ S/m; $\epsilon_r = 39.215$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.04, 5.04, 5.04); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch661/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.258 W/kg


Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.897 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.337 W/kg

SAR(1 g) = 0.216 W/kg; SAR(10 g) = 0.136 W/kg

Maximum value of SAR (measured) = 0.253 W/kg



03_WCDMA V_RMC 12.2Kbps_Right Cheek_Ch4182

Communication System: UID 0, UMTS (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_201111 Medium parameters used: $f = 836.5$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 41.777$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch4182/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.444 W/kg


Ch4182/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.201 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.461 W/kg

SAR(1 g) = 0.366 W/kg; SAR(10 g) = 0.283 W/kg

Maximum value of SAR (measured) = 0.427 W/kg



04_WCDMA IV_RMC 12.2Kbps_Right Cheek_Ch1413

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1
Medium: HSL_1750_201112 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.386$ S/m; $\epsilon_r = 41.592$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.22, 5.22, 5.22); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch1413/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.310 W/kg


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.742 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.376 W/kg

SAR(1 g) = 0.257 W/kg; SAR(10 g) = 0.164 W/kg

Maximum value of SAR (measured) = 0.292 W/kg



05_WCDMA II_RMC 12.2Kbps_Left Cheek_Ch9538


Communication System: UID 0, WCDMA (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium: HSL_1900_201112 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.462$ S/m; $\epsilon_r = 39.116$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.04, 5.04, 5.04); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch9538/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.264 W/kg

Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.921 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.354 W/kg
SAR(1 g) = 0.228 W/kg; SAR(10 g) = 0.143 W/kg
Maximum value of SAR (measured) = 0.269 W/kg



06_LTE Band 5_10M_QPSK_1RB_25Offset_Right Cheek_Ch20525

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: HSL_835_201111 Medium parameters used: $f = 836.5$ MHz; $\sigma = 0.93$ S/m; $\epsilon_r = 41.777$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7576; ConvF(10.45, 10.45, 10.45); Calibrated: 2020.01.22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn528; Calibrated: 2020.03.16
- Phantom: SAM (Front) with CRP v5.0; Type: QD000P40CD; Serial: TP:1795
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch20525/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.439 W/kg


Ch20525/Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.853 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.473 W/kg

SAR(1 g) = 0.371 W/kg; SAR(10 g) = 0.286 W/kg

Maximum value of SAR (measured) = 0.436 W/kg



07_LTE Band 66_20M_QPSK_1RB_49Offset_Right Cheek_Ch132322

Communication System: UID 0, LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: HSL_1750_201112 Medium parameters used: $f = 1745$ MHz; $\sigma = 1.401$ S/m; $\epsilon_r = 41.539$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.22, 5.22, 5.22); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch132322/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.288 W/kg


Ch132322/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.495 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.342 W/kg

SAR(1 g) = 0.236 W/kg; SAR(10 g) = 0.152 W/kg

Maximum value of SAR (measured) = 0.273 W/kg



08_LTE Band 2_20M_QPSK_1RB_49Offset_Left Cheek_Ch18900

Communication System: UID 0, LTE (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL_1900_201112 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.432$ S/m; $\epsilon_r = 39.215$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(5.04, 5.04, 5.04); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch18900/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.263 W/kg


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.481 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.339 W/kg

SAR(1 g) = 0.218 W/kg; SAR(10 g) = 0.137 W/kg

Maximum value of SAR (measured) = 0.257 W/kg



09_LTE Band 7_20M_QPSK_1RB_49Offset_Left Cheek_Ch21100

Communication System: UID 0, LTE (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: HSL_2600_201113 Medium parameters used: $f = 2535$ MHz; $\sigma = 1.978$ S/m; $\epsilon_r = 38.292$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3241; ConvF(4.42, 4.42, 4.42); Calibrated: 2020.05.14;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2019.11.19
- Phantom: SAM with CRP v4.0(Left); Type: QD000P40CC; Serial: TP:1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch21100/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.306 W/kg


Ch21100/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.605 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.410 W/kg

SAR(1 g) = 0.218 W/kg; SAR(10 g) = 0.110 W/kg

Maximum value of SAR (measured) = 0.280 W/kg



10_WLAN2.4GHz_802.11b 1Mbps_Left Cheek_Ch11

Communication System: UID 0, WIFI (0); Frequency: 2462 MHz; Duty Cycle: 1:1.007

Medium: HSL_2450_201118 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.884$ S/m; $\epsilon_r = 38.072$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(7.12, 7.12, 7.12); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch11/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.770 W/kg


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.70 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.461 W/kg; SAR(10 g) = 0.223 W/kg

Maximum value of SAR (measured) = 0.705 W/kg



11_WLAN5GHz_802.11n-HT40 MCS0_Left Cheek_Ch54

Communication System: UID 0, WIFI (0); Frequency: 5270 MHz; Duty Cycle: 1:1.038

Medium: HSL_5250_201119 Medium parameters used: $f = 5270$ MHz; $\sigma = 4.631$ S/m; $\epsilon_r = 36.171$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(5.09, 5.09, 5.09); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch54/Area Scan (101x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.27 W/kg


Ch54/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 5.442 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 0.568 W/kg; SAR(10 g) = 0.172 W/kg

Maximum value of SAR (measured) = 1.41 W/kg



12_WLAN5GHz_802.11ac-VHT80 MCS0_Left Cheek_Ch138

Communication System: UID 0, WIFI (0); Frequency: 5690 MHz; Duty Cycle: 1:1.078

Medium: HSL_5600_201120 Medium parameters used: $f = 5690$ MHz; $\sigma = 5.08$ S/m; $\epsilon_r = 35.672$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3826; ConvF(4.66, 4.66, 4.66); Calibrated: 2020.05.20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2020.07.27
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch138/Area Scan (101x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.00 W/kg

Ch138/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 12.62 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 3.53 W/kg

SAR(1 g) = 0.724 W/kg; SAR(10 g) = 0.231 W/kg

Maximum value of SAR (measured) = 1.94 W/kg


Ch138/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 12.62 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 2.50 W/kg

SAR(1 g) = 0.581 W/kg; SAR(10 g) = 0.187 W/kg

Maximum value of SAR (measured) = 1.40 W/kg



0 dB = 1.40 W/kg