

LARK C1

User Manual






LARK C1

* The quantity is based on the product's various model and is subject to the actual quantity of equipment purchased.

PACKING LIST

LARK C1 SOLO (TX*1 to RX*1) Wireless Microphone System



^{*} The quantity is based on the product's various model and is subject to the actual quantity of equipment purchased,

PACKING LIST

LARK DUO (TX*2 to RX*1) Wireless Microphone System with Charging Case




^{*} The quantity is based on the product's various model and is subject to the actual quantity of equipment purchased.


PRODUCTION INTRODUCTION







- Blue LED Flashing: Device disconnected / HearClear(Denoise) Off Blue LED Stavs On: Device connected /
- HearClear(Noise Reduction) Off by default Red LED Flashing:



PRODUCTION INSTALLATION



① The TX (transmitter) automatically turns ② Connect the RX to the smartphone. ③ Charge the Smartphone via the RX, or when takes it out from the charging case. Simply clip the TX (transmitter) to a shift collist.

PRODUCTION FUNCTION

Noise Cancellation Function



- ⊕ Blue LED Stays On : Device disconnected HearClear(Noise Reduction) Off by default
 - ◆ Green LED Stays On: HearClear(Noise Reduction) ON
 Press the TVs valve by through the notion to the HearClear(Noise Reduction).

Press the TX's yellow button to turn on the HearClear(Noise Reduction) function. When activated, the indicator LED turns green.

Charging Case Battery Level




(2) ◆ LED Flashing: Charging◆ LED Stays On: Fully charged

| One Light Flashing | •000 | 25% |
|-----------------------|------|------|
| Two Lights Flashing | ••• | 50% |
| Three Lights Flashing | ••• | 75% |
| Four Lights Flashing | •••• | 100% |

PRODUCTION FUNCTION

Manual Pairing



After the receiver is connected to the smartphone, long press TX's 'בּשַע'\unionia button for 3s and then long press PX's 'דמקו' for 3s pairing.

* The device has been paired in the factory before shipping. The product needs to pair again when there is disconnection.

PARAMETERS

| Wireless Transmission | 2.4GHz Adaptive Frequency Hopping(AFH) | |
|-----------------------|--|--|
| Transmission Range | 130ft(40m)(NLOS), 650ft(200m)(LOS) | |
| Built-in Microphone | Polar Pattern: Omnidirectional | |
| | Frequency Range:20Hz≈20KHz | |
| Maximum SPL | 110dB SPL | |
| Input Dynamic Range | 86dB | |
| Battery Capacity | TX: 140mAh (0.518Wh) | |
| | Charging Case: 1400mAh (5.18Wh) | |
| Runtime | TX: 8H | |
| | Charging Case: Maximum 3 times charging for 2 TX | |
| Charging Time | TX: 1.5H | |
| | Charging Case: 1.5H | |
| Dimensions | TX: 48x21.5x10mm (1.89"x0.85"x0.4") | |
| | RX: 48.3x27.6x9mm (1.9"x1.1"x0.35") | |
| | Charging Case: 83x60x30mm (3.3"x2.4"x1.2") | |
| Weight | TX: 11.5g (0.4oz) | |
| | RX: 7g (0.25oz) | |
| | Charging Case: 85.5g (3oz) | |

SUPPORT |

If any problems are encountered using the product, please follow these options for receiving technical support:

- f HolMand Products User Group
- HollylandTech
- HollylandTech
- Support@ hollyland-tech.com
- www.hollyland-tech.com

Note:

The frequency range and wireless transmit power of the device vary based on theregulations of different countries and regions.

Safety Precautions

Do not place the product near or inside heating devices (including but not limited to microwave ovens, induction cookers, electric ovens electric heaters, pressure cookers, water heaters, gas stoves) to prevent the battery from overheating and exploding.

Never use non-original charging cases, cables, and batteries with the product,

The use of non-original spare parts may cause electric shock, fire, explosion, or otherdangers.

FCC Requirement

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1)this device may not cause harmful interference.

(2)this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement:

The device has been tested and comply with FCC SAR limits.

Note:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide research to provide research to the provider rese

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

 Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.