



# RF Exposure Evaluation Report

**FOR:**

Motive Technologies, Inc.

**Brand:**

Motive Technologies, Inc.

**Marketing Name:**

Omnica™

**Model Number:**

OC-1

**Product Description:**

Is a vehicle camera, designed to be powered by vehicle power (12 or 24 V DC). It is designed to be always on and recording video while the vehicle is on. It will upload small video files to Motive back-end servers via LTE on request.

**FCC ID:** 2AQM7-OC1

**IC:** 24516-OC1

**Per:**

CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091),  
FCC KDB 447498 D01 General RF Exposure Guidance v06  
ISED RSS-102 Issue 5

**Report number:** EMC\_KPTRK\_040\_23001\_FCC\_ISED\_RF\_Exposure

**DATE:** 6/28/2023



A2LA Accredited

IC recognized #  
3462B

**CETECOM Inc.**

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: [Contact@cetecom.com](mailto:Contact@cetecom.com) ♦ <http://www.cetecom.com>  
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

**TABLE OF CONTENTS**

1	Assessment.....	3
2	Administrative Data .....	4
2.1	Identification of the Testing Laboratory Issuing the Test Report .....	4
2.2	Identification of the Client / Manufacturer .....	4
2.3	Identification of the Manufacturer .....	4
3	Equipment under Assessment.....	5
4	RF Exposure Limits and FCC and ISED Basic Rules.....	7
4.1	FCC.....	7
4.2	ISED RSS 102 .....	7
5	Evaluations.....	8
5.1	FCC RF Exposure (Standalone) .....	8
5.2	ISED RF Exposure (Standalone).....	8
5.3	Multiple RF sources.....	9
6	Revision History .....	10

## 1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the equipment (as identified in section 3 of this test report) with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1.1307, Part 2 (2.1091) and ISED standard RSS-102 issue 5 under worst case conditions (measured or rated RF output power including tune-up tolerance, antenna gain, the distance towards the human body, multiple transmitter information as presented by the applicant).

In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits stipulated by the above given FCC and ISED rule parts based on available specifications for worst-case conditions at a separation distance greater than 20cm to the body.

Company	Description	Model #
Motive Technologies, Inc.	Is a vehicle camera, designed to be powered by vehicle power (12 or 24 V DC). It is designed to be always on and recording video while the vehicle is on. It will upload small video files to Motive back-end servers via LTE on request.	OC-1

### Responsible for Testing Laboratory:

Stoecker, Arndt			
6/28/2023	Compliance	(Director of Regulatory Services)	
Date	Section	Name	Signature

### Responsible for the Report:

Ghanma, Issa			
6/28/2023	Compliance	(Deputy Lab Manager)	
Date	Section	Name	Signature

## 2 Administrative Data

### 2.1 Identification of the Testing Laboratory Issuing the Test Report

<b>Company Name:</b>	CETECOM Inc.
<b>Department:</b>	Compliance
<b>Street Address:</b>	411 Dixon Landing Road
<b>City/Zip Code</b>	Milpitas, CA 95035
<b>Country</b>	USA
<b>Telephone:</b>	+1 (408) 586 6200
<b>Fax:</b>	+1 (408) 586 6299
<b>EMC Lab Manager:</b>	Stoecker, Arndt
<b>Responsible Project Leader:</b>	Quintal, Phillip

### 2.2 Identification of the Client / Manufacturer

<b>Applicant's Name:</b>	Motive Technologies, Inc.
<b>Street Address:</b>	55 Hawthorne St., Suite 400
<b>City/Zip Code</b>	San Francisco, CA 94105
<b>Country</b>	USA

### 2.3 Identification of the Manufacturer

<b>Manufacturer's Name:</b>	Same as Client /-----
<b>Manufacturers Address:</b>	-----
<b>City/Zip Code</b>	-----
<b>Country</b>	-----

### 3 Equipment under Assessment

<b>Brand:</b>	Motive Technologies, Inc.
<b>Model No:</b>	OC-1
<b>Marketing name:</b>	Omnica
<b>FCC-ID :</b>	2AQM7-OC1
<b>IC:</b>	24516-OC1
<b>HW Version :</b>	1
<b>SW Version :</b>	0.7.2
<b>HVIN:</b>	OC-1
<b>PMN:</b>	Omnica
<b>Product Description:</b>	Is a vehicle camera, designed to be powered by vehicle power (12 or 24 V DC). It is designed to be always on and recording video while the vehicle is on. It will upload small video files to Motive back-end servers via LTE on request.
<b>Frequency Range/number of channels:</b>	<ul style="list-style-type: none"> <li>❖ Cellular:                             <ul style="list-style-type: none"> <li>○ UMTS II, IV, V</li> <li>○ LTE 2, 4, 5, 12, 13</li> </ul> </li> <li>❖ BT LE v5.2                             <ul style="list-style-type: none"> <li>○ Nominal band: 2400 MHz – 2483.5 MHz</li> <li>○ Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 Channels</li> </ul> </li> <li>❖ WLAN 2.4 GHz 802.11b/g/n                             <ul style="list-style-type: none"> <li>○ Nominal band: 2400 MHz – 2483.5 MHz</li> <li>○ Center to center: 2412 MHz (ch 1) – 2462 MHz (ch 11), 11 Channels</li> </ul> </li> <li>❖ WLAN 5.0 GHz 802.11a/n/ac                             <ul style="list-style-type: none"> <li>○ Nominal band: 5725 MHz – 5850 MHz</li> <li>○ 802.11a/n-HT20/ac-VHT20                                     <ul style="list-style-type: none"> <li>▪ Center to center: 5745 MHz (ch 149) – 5825 MHz (ch 165), 5 Channels</li> </ul> </li> <li>○ 802.11n-HT40/ac-VHT40                                     <ul style="list-style-type: none"> <li>▪ Center to center: 5755 MHz (ch 151) – 5795 MHz (ch 159), 2 Channels</li> </ul> </li> <li>○ 802.11ac-VHT80                                     <ul style="list-style-type: none"> <li>▪ Center to center: 5775 MHz (ch 155), 1 Channels</li> </ul> </li> </ul> </li> </ul>
<b>Radio information:</b>	<ul style="list-style-type: none"> <li>❖ Cellular: Sierra Wireless RC7612</li> <li>❖ BT LE/WLAN: Murata LBEE5XV1XZ</li> </ul>

<b>Max. Output Power:</b>	<ul style="list-style-type: none"> <li>❖ Cellular                             <ul style="list-style-type: none"> <li>○ UMTS: 23 dBm ± 1dB Power class 3</li> <li>○ LTE: 23 dBm ± 1dB Power class 3</li> </ul> </li> <li>❖ BT LE (Measured): 4.89 dBm</li> <li>❖ WLAN 0 2.4 GHz (Measured)                             <ul style="list-style-type: none"> <li>○ 802.11b: 17.79 dBm</li> <li>○ 802.11g: 25.06 dBm</li> </ul> </li> <li>❖ WLAN 1 2.4 GHz (Measured)                             <ul style="list-style-type: none"> <li>○ 802.11b: 20.4 dBm</li> <li>○ 802.11g: 25.23 dBm</li> </ul> </li> <li>❖ WLAN MIMO 2.4 GHz (Measured) 802.11n-HT20: 27.59 dBm</li> <li>❖ WLAN 0 U-NII-3 (Measured) 802.11a: 16.03 dBm</li> <li>❖ WLAN 1 U-NII-3 (Measured) 802.11a: 16.02 dBm</li> <li>❖ WLAN MIMO U-NII-3 (Calculated total power)                             <ul style="list-style-type: none"> <li>○ 802.11n-HT20: 18.77 dBm</li> <li>○ 802.11n-HT40: 16.95 dBm</li> <li>○ 802.11ac-VHT20: 18.75 dBm</li> <li>○ 802.11ac-VHT40: 16.76 dBm</li> <li>○ 802.11ac-VHT80: 15.74 dBm</li> </ul> </li> </ul>
<b>Power Supply/ Rated Operating Voltage Range:</b>	12 or 24 V DC
<b>Operating Temperature Range:</b>	T min: -40 °C / T Nom: 20 °C / T max: +60 °C
<b>Antenna Information as declared:</b>	<ul style="list-style-type: none"> <li>❖ LTE Main                             <ul style="list-style-type: none"> <li>○ Type: Monopole Antenna</li> <li>○ Tx/Rx</li> <li>○ Max Gain                                     <ul style="list-style-type: none"> <li>▪ 704 – 894 MHz: 4.6 dBi</li> <li>▪ 1710 – 2155 MHz: 5.3 dBi</li> </ul> </li> </ul> </li> <li>❖ LTE Diversity                             <ul style="list-style-type: none"> <li>○ Type: Inverted-F Antenna</li> <li>○ Rx only</li> <li>○ Max Gain                                     <ul style="list-style-type: none"> <li>▪ 1710 – 2170 MHz: -1.1 dBi</li> </ul> </li> </ul> </li> <li>❖ BLE/WLAN 0                             <ul style="list-style-type: none"> <li>○ Type: Inverted-F Antenna</li> <li>○ Tx/Rx</li> <li>○ Max Gain                                     <ul style="list-style-type: none"> <li>▪ 2.4 -2.48 GHz: 1.7 dBi</li> <li>▪ 5.0 – 6.0 GHz: 4.4 dBi</li> </ul> </li> </ul> </li> <li>❖ BLE/WLAN 1                             <ul style="list-style-type: none"> <li>○ Type: Inverted-F Antenna</li> <li>○ Tx/Rx</li> <li>○ Max Gain                                     <ul style="list-style-type: none"> <li>▪ 2.4 -2.48 GHz: 0.8 dBi</li> <li>▪ 5.0 – 6.0 GHz: 5.6 dBi</li> </ul> </li> </ul> </li> </ul>
<b>Sample Revision:</b>	<input type="checkbox"/> Production Unit; <input checked="" type="checkbox"/> Pre-Production
<b>Product dimensions [mm]:</b>	82mm tall x 82mm wide x 67mm deep
Note: The information of the EUT specifications in the table above is provided by the client except the specified (Measured or calculated) output power.	

## 4 RF Exposure Limits and FCC and ISED Basic Rules

### 4.1 FCC

#### 4.1.1 § 2.1091(c)(1)

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

$$P_{th}(\text{mW}) = ERP_{20\text{ cm}}(\text{mW}) = \begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases}$$

#### 4.1.2 § 2.1091(c)(2)

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

#### 4.1.3 § 1.1307(b)(3)(ii)(B)

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

### 4.2 ISED RSS 102

#### 4.2.1 Clause 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;

## 5 Evaluations

### 5.1 FCC RF Exposure (Standalone)

Radio	Technology / Band	Frequency [GHz]	Power [mW]	Gain [dBi]	ERP [mW]	FCC 2.1091(c)(1) Pth[mW] = ERP <sub>20cm</sub>	ERP<Threshold
Cellular	UMTS II	1852.4	251.2	5.30	518.80	3060.00	Exempt
	UMTS IV	1712.4	251.2	5.30	518.80	3060.00	Exempt
	UMTS V	826.4	251.2	4.60	441.57	1685.86	Exempt
	LTE 2	1855.0	251.2	5.30	518.80	3060.00	Exempt
	LTE 4	1715.0	251.2	5.30	518.80	3060.00	Exempt
	LTE 5	829.0	251.2	4.60	441.57	1691.16	Exempt
	LTE 12	704.0	251.2	4.60	441.57	1436.16	Exempt
	LTE 13	779.5	251.2	4.60	441.57	1590.18	Exempt
BT	LE	2402.0	3.1	1.70	2.78	3060.00	Exempt
WLAN	802.11 b Ant 0	2412.0	60.1	1.70	54.20	3060.00	Exempt
	802.11 b Ant 1	2412.0	109.6	0.80	80.35	3060.00	Exempt
	802.11 g Ant 0	2412.0	320.6	1.70	289.07	3060.00	Exempt
	802.11 g Ant 1	2412.0	333.4	0.80	244.34	3060.00	Exempt
	802.11 n-HT20 MIMO	2412.0	574.1	1.27	468.81	3060.00	Exempt
	802.11 a Ant 0	5745.0	40.1	4.40	67.27	3060.00	Exempt
	802.11 a Ant 1	5745.0	40.0	5.60	88.51	3060.00	Exempt
	802.11 n-HT20 MIMO	5745.0	75.3	5.04	146.55	3060.00	Exempt
	802.11 ac-VHT20 MIMO	5745.0	75.0	5.04	145.88	3060.00	Exempt
	802.11 n-HT40 MIMO	5755.0	49.5	5.04	96.27	3060.00	Exempt
	802.11 ac-VHT20 MIMO	5755.0	47.4	5.04	92.17	3060.00	Exempt
	802.11 ac-VHT80 MIMO	5775.0	37.5	5.04	72.98	3060.00	Exempt

### 5.2 ISED RF Exposure (Standalone)

Radio	Technology / Band	Frequency [GHz]	Power [W]	Gain [dBi]	E.I.R.P [W]	Exemption limit for Routine Evaluation [W]	E.I.R.P <Threshold
Cellular	UMTS II	1852.4	0.251	5.30	0.851	2.2	Exempt
	UMTS IV	1712.4	0.251	5.30	0.851	2.12	Exempt
	UMTS V	826.4	0.251	4.60	0.724	1.29	Exempt
	LTE 2	1855.0	0.251	5.30	0.851	2.24	Exempt
	LTE 4	1715.0	0.251	5.30	0.851	2.13	Exempt
	LTE 5	829.0	0.251	4.60	0.724	1.29	Exempt
	LTE 12	704.0	0.251	4.60	0.724	1.16	Exempt
	LTE 13	779.5	0.251	4.60	0.724	1.24	Exempt
BT	LE	2402.0	0.003	1.70	0.005	2.68	Exempt
WLAN	802.11 b Ant 0	2412.0	0.060	1.70	0.089	2.68	Exempt
	802.11 b Ant 1	2412.0	0.110	0.80	0.132	2.68	Exempt
	802.11 g Ant 0	2412.0	0.321	1.70	0.474	2.68	Exempt
	802.11 g Ant 1	2412.0	0.333	0.80	0.401	2.68	Exempt
	802.11 n-HT20 MIMO	2412.0	0.574	1.27	0.769	2.68	Exempt
	802.11 a Ant 0	5745.0	0.040	4.40	0.110	4.86	Exempt
	802.11 a Ant 1	5745.0	0.040	5.60	0.145	4.86	Exempt
	802.11 n-HT20 MIMO	5745.0	0.075	5.04	0.240	4.86	Exempt
	802.11 ac-VHT20 MIMO	5745.0	0.075	5.04	0.239	4.86	Exempt
	802.11 n-HT40 MIMO	5755.0	0.049	5.04	0.158	4.86	Exempt
	802.11 ac-VHT20 MIMO	5755.0	0.047	5.04	0.151	4.86	Exempt
	802.11 ac-VHT80 MIMO	5775.0	0.038	5.04	0.120	4.87	Exempt



### 5.3 Multiple RF sources

The worst case of simultaneous transmission is LTE 12 + BT LE + WLAN 802.11 n-HT20 MIMO (2.4 GHz):  
 $(251.2/1436.16) + (3.1/3060) + (574.1/3060) = 0.496 \leq 1$

The sum of the fractional contributions to the applicable thresholds is less than or equal to 1, hence the multiple RF sources are exempt

## 6 Revision History

Date	Report Name	Changes to report	Prepared by
6/28/2023	EMC_KPTRK_040_23001_FCC_ISED_RF_Exposure	Initial Version	Ghanma, Issa

<<< The End >>>

---