
图示					
_	裁切线				
_	压线				
-	反匠线				
$\overline{}$	备万线 X/X mm				
$\overline{}$	开槽				
****	粘合区域				

成型尺寸	战型尺寸		±0.5mm	PE袋类	0~200mm ± 2mm 20~500mm ± 3mm	
刀模尺寸	60*40mm	说明书类	±1mm	11.47	> 500mm ± 5mm	
展开尺寸		EPE类	+5nm/-3nm	模具成型类	外尺寸:0~400mm ± 2mm	
公差(天	特殊说明下)	纸箱类	単瓦楞 ± 3mm 双瓦楞 ± 5mm	(EPS/纸塑等)	400~600mm ± 3mm > 600mm ± 4mm 終保分寸: +2 / -0mm	



技术说明:

- 1、 材质: PC (厚度0.075mm) +3M467背胶
- 2、印刷色: PANTONE Cool Gray 5C PANTONE Black C ■
- 3、工艺: 印刷、模切
- 4、 粘性指标: 标签粘贴对应位置无走位、开口、起翘、脱落现象
- 5、 可靠性测试要求: 《SN_B 2055-2020.6 标签、 贴纸测试规范》
- 6、其它特殊说明:

UL要求: 雪浦足UL认证品, PGDQ2要求/ 雪浦足UL认证品 满足对应UL档案号中的要求/供应商需在PGAA名录里(印刷UL认证MARK时需要)

						工艺类别 包材定制-标签贴纸类 等级 质量			FCC标签-P2S1
标记	<u></u> 	更改文		姓名	日期	等级			/
设计	耿琳妍	210624	审核			版本 A	图幅 A4	比例	CE.00.0054.99
校对 标准化	杨隽	210624	批准			投影视角 第 1 页	# 1	章	Segway-Ninebot

Model: T60 Nominal Power: 350 W

Max. Payload: 220.0 lbs (100.0 kg)

Max. Speed: Approx. 15.5 mph (25 km/h) Nominal Capacity: A 551 Wh

B 1004 Wh

DC Input: 42.0 V == 5.0 A





IPX4



This product has been tested and certified to UL2272 Standard



Manufacturer: Ninebot (Changzhou) Tech. Co., Ltd. Address.: 16F-17F, Block A, Building 3, No.18, Changwu Mid Rd, Wujin Dist., Changzhou, Jiangsu, China.

A WARNING

Made in China

To reduce the risk of injury, user must read instruction manual.



