

TEST REPORT

Applicant: Arad Connectivity Co., Ltd.
Address: 5F.-1, No. 63, Sec. 1, Hangzhou S. Rd.,
Zhongzheng Dist., Taipei City 100022 , Taiwan
(R.O.C.)
Equipment Type: MN52M series
Model Name: MN52M
Brand Name: Aradconn
FCC ID: 2BLIDMN52M
ISED Number: 33328-MN52M
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-247 Issue 3
(refer to section 3.1)
Sample Arrival Date: Oct. 11, 2024
Test Date: Oct. 11, 2024 - Oct. 14, 2024
Date of Issue: Dec. 05, 2024

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

Tested by: Hai Su

Checked by: Zhang Yanqing

Approved by: Chen Zidong

(Technical Director)

Hai Su

Zhang Yanqing

Chen Zidong

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Nov. 22, 2024</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Dec. 05, 2024</u>	<u>Modify the ISED Number</u>
		<u>The original report is invalid.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Test Software List	9
4.4	Decision Rule	10
4.5	Measurement Uncertainty	10
4.6	Description of Test Setup	11
4.7	Measurement Results Explanation Example	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.2	Output Power	15
5.3	Occupied Bandwidth	16
5.4	Conducted Spurious Emission	17

5.5	Band Edge (Authorized-band band-edge).....	19
5.6	Conducted Emission	20
5.7	Radiated Spurious Emission	21
5.8	Band Edge (Restricted-band band-edge).....	25
5.9	Power Spectral density (PSD).....	26
ANNEX A	TEST RESULT	27
A.1	Output Power, E.I.R.P, Duty Cycle.....	27
A.2	Occupied Bandwidth	30
A.3	Conducted Spurious Emission	35
A.4	Band Edge (Authorized-band band-edge).....	42
A.5	Conducted Emission	45
A.6	Radiated Spurious Emission	46
A.7	Band Edge (Restricted-band band-edge).....	76
A.8	Power Spectral Density (PSD)	96
ANNEX B	TEST SETUP PHOTOS	98
ANNEX C	EUT EXTERNAL PHOTOS	98
ANNEX D	EUT INTERNAL PHOTOS	98

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1st to 2nd floors, Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1st to 2nd floors, Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 29671.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Arad Connectivity Co., Ltd.
Address	5F.-1, No. 63, Sec. 1, Hangzhou S. Rd., Zhongzheng Dist., Taipei City 100022 , Taiwan (R.O.C.)

2.2 Manufacturer Information

Manufacturer	Arad Connectivity Co., Ltd.
Address	5F.-1, No. 63, Sec. 1, Hangzhou S. Rd., Zhongzheng Dist., Taipei City 100022 , Taiwan (R.O.C.)

2.3 General Description for Equipment under Test (EUT)

EUT Name	MN52M series
Model Name Under Test	MN52M
Series Model Name	N/A
Description of Model name differentiation	N/A
Sample Number	SC-SZ2490816-S06 SC-SZ2490816-S03
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth: BLE 1M&2M
-----------------------------------	----------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	GFSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	1 Mbps, 2 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	40 (at intervals of 2 MHz)
Tested Channel	1 Mbps: 0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz) 2 Mbps: 0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz)
Antenna Type	see Antenna Information
Antenna Gain	3.3 dBi
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

Antenna Information	Antenna type	Manufacturer	Antenna peak gain (dBi)
	Ceramics	Arad Connectivity Co., Ltd.	1.05
	PCB	Arad Connectivity Co., Ltd.	0.8
	Dipole	Pulse Electronics	2
	PCB	Pulse Electronics	3.3
	PCB	Pulse Electronics	2.3

Note: The product MN52M is equipped with above antenna, All Antenna type are tested, Only the worst data are reflected in the report.

All channel was listed on the following table:

BLE 1M&2M:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 3	Digital Transmission Systems (DTSS), Frequency Hopping Systems(FHSs) and Licence-Exemp Local Area Network (LE-LAN) Devices
4	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
5	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	--	Pass ^{Note1}
2	Output Power	15.247(b)	RSS-247, 5.4 (d)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	RSS-GEN, 6.7; RSS-247, 5.2 (a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	RSS-247, 5.5;	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/High	ANNEX A.5	N/A ^{Note3}
7	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (b)	Low/Middle/High	ANNEX A.8	Pass
10	Receiver Spurious Emissions	--	RSS-Gen, 7.4	--	N/A	N/A ^{Note2}

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

Note 3: EUT is powered by DC.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	54% - 58%	
Atmospheric Pressure	101 kPa	
Temperature	NT (Normal Temperature)	+22.6°C to +24.5°C
Working Voltage of the EUT	NV (Normal Voltage)	3.3V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420147	2024.02.22	2025.02.21
Spectrum Analyzer	KEYSIGHT	N9010B	MY60240977	2024.02.22	2025.02.21
Signal Generator	Anritsu	MG3710E	6262063515	2024.02.22	2025.02.21
Wideband Radio Communication Tester	R&S	CMW500	168792	2024.02.22	2025.02.21
EMI Receiver	KEYSIGHT	N9038A	MY55330122	2024.07.09	2025.07.08
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-177	2024.03.11	2027.03.10
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-1203	2024.03.11	2027.03.10
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-2134	2024.03.11	2027.03.10
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400-KF	J211060307	2024.03.11	2027.03.10
Anechoic Chamber	YiHeng	9m*6m*6m	EMC001	2024.04.18	2027.04.17
EMI Receiver	KEYSIGHT	N9038A	MY55330115	2024.02.19	2025.02.18
LISN	SCHWARZBECK	NSLK 8127	8127-940	2024.02.25	2025.02.24
10dB Limiter	SCHWARZBECK	VTSD 9561-F	9561-F N00409	2024.02.19	2025.02.18
Shielded Room	YiHeng	5m*4m*3.2 m	EMC006	2024.02.22	2027.02.21

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable Test Setup
BL410R	BALUN	V2.1.1.496	N/A	The section 4.6.1
BL410E	BALUN	V21.919	N/A	The section 4.6.2&4.6.3&4.6.4&4.6.5

4.4 Decision Rule

☐ No Need

☒ Use General conformity decision rule (Consider uncertainty or not ☒No ☐Yes)

☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐No ☐Yes)

4.5 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.4 %
RF output power, conducted	0.41 dB
Power Spectral Density, conducted	1.73 dB
Unwanted Emissions, conducted	1.73 dB
All emissions, radiated	4.57 dB
Temperature	0.82 °C
Humidity	4.1 %


4.6 Description of Test Setup

4.6.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5 dB used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.6.2 For AC Power Supply Port Test




(Diagram 2)

4.6.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.6.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.6.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.7 Measurement Results Explanation Example

4.7.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.7.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embed ded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW $\geq$ DTS bandwidth.

Set VBW $\geq 3 \times$ RBW.

Set span $\geq 3 \times$ RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW $\geq$ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.2 (a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.6.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.6.3 to 4.6.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.10; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.6.3 to 4.6.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.6.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power, E.I.R.P, Duty Cycle

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low	4.63	2.90	30	1000	Pass
Middle	4.66	2.92			Pass
High	4.41	2.76			Pass

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low	4.53	2.84	30	1000	Pass
Middle	4.60	2.88			Pass
High	4.29	2.69			Pass

E.I.R.P Test Data (For ISSED)

Channel	E.I.R.P		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low	7.93	6.21	36	4000	Pass
Middle	7.96	6.25			Pass
High	7.71	5.90			Pass

Channel	E.I.R.P		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low	7.83	6.07	36	4000	Pass
Middle	7.90	6.17			Pass
High	7.59	5.74			Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL




Duty Cycle Test Data


Band	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)
GFSK (BLE 1Mbps)	0.20	1.54	13.16
GFSK (BLE 2Mbps)	0.10	1.44	6.94

Test Plots

GFSK (BLE 1Mbps)



GFSK (BLE 2Mbps)



A.2 Occupied Bandwidth

Test Data

Test Mode	GFSK (BLE 1Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low	652.600	1021.800	≥500
Middle	682.600	1002.700	≥500
High	674.800	986.930	≥500

Test Mode	GFSK (BLE 2Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low	870.000	2010.400	≥500
Middle	1125.000	2045.400	≥500
High	900.000	1946.700	≥500

Test Plots

6 dB Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



99% Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL




GFSK (BLE 1Mbps) MIDDLE CHANNEL




GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



A.3 Conducted Spurious Emission

Test Data

GFSK (BLE 1Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-51.74	4.63	-15.37	Pass
Middle	-51.76	4.70	-15.30	Pass
High	-51.61	4.33	-15.67	Pass

GFSK (BLE 2Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-51.93	4.52	-15.48	Pass
Middle	-52.05	4.63	-15.37	Pass
High	-50.80	4.33	-15.67	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 1Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



GFSK (BLE 1Mbps) MIDDLE CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 1Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



Keysight Spectrum Analyzer 1 (Sweep SA)

Input Settings: Input RF, Front Panel, Freq. Ref. Internal, 4 dBm, 30 dB, FWD, Hold Wide, (Auto), DC, Avg Type: Log-Power, Avg Hold: 2.51, Freq: 1 Hz, Run, 1.2 3 4 5, 4.63 dBm, 2.439 475 GHz

Frequency Settings: Center Frequency: 2.440000000 GHz, Span: 3.0000000 MHz, Span Span: Zero Span, Full Span, Start Freq: 2.438500000 GHz, Stop Freq: 2.441500000 GHz, AUTO TUNE, CF Stop: 300.000 kHz, Auto, Man, Freq Offset: 0 Hz, X Axis Scale: Log, Lin, Local

Plot Settings: Scale: 10 dB, Log, Ref Level: 15.00 dBm, #Video BW: 300 kHz, Span: 3.000 MHz, Sweep: 1.00 ms (601 pts), 5 Marker: None

Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N		2.439 475 GHz	4.63 dBm			
2							
3							
4							
5							

System Information: Oct 11, 2024, 3:35:35 PM, 11:11

The screenshot displays the Keysight Spectrum Analyzer 1 interface. The main display shows a log scale plot with a peak at 1.1735 GHz and -58.52 dBm. The interface includes various control panels for input, resolution, and markers.

Top Panel:

- Spectrum Analyzer 1** (Sweep SA)
- Input:** Input 2: 50.0, Input Color: Freq Hdg: Internal, Input Att: 30 dB
- Resolution:** Freq Span: 100 MHz, Span: 100 MHz, Freq Res: 100 kHz, Span: 100 kHz
- Marker:** Marker 2

Main Display:

- Scale:** 10 dB
- Ref Level:** 15.00 dBm
- Marker 2:** 1.1735 GHz, -58.52 dBm
- Video BW:** 300 kHz
- Sweep:** 288 ms (1001 pts)

Bottom Panel:

- Marker Table:**
- Marker 1:** 1.1735 GHz, -58.52 dBm
- Marker 2:** 1.1735 GHz, -58.52 dBm

The screenshot displays the Keysight Spectrum Analyzer 1 software interface. The main window shows a spectrum plot with a yellow trace. A peak is labeled 'Mkr2 4.88075 GHz -53.14 dBm'. The plot has a frequency range from 2.00 GHz to 25.00 GHz and a resolution bandwidth of 100 kHz. The Y-axis is labeled 'dBm' and ranges from -70 to 0. The plot is titled 'Spectrum Analyzer 1' and 'SWPWR SA'. The interface includes various controls like 'Sweep', 'Ref Level', 'Marker', and 'Search'.

GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Test Data

GFSK (BLE 1Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-44.16	4.63	-15.37	Pass
High	-29.84	4.33	-15.67	Pass

GFSK (BLE 2Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-48.97	4.52	-15.48	Pass
High	-47.33	4.33	-15.67	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, BAND EDGE



A.5 Conducted Emission

Note: Not applicable.

A.6 Radiated Spurious Emission

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 1M-Mid channel mode is the worst.

Note 5: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots


Antenna type: PCB, Gain: 3.3 dBi

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	120.016	19.42	-28.20	43.5	24.08	Peak	262.00	200	Horizontal	Pass
2	168.031	20.87	-28.44	43.5	22.63	Peak	136.00	100	Horizontal	Pass
3	264.013	28.03	-24.15	46.0	17.97	Peak	237.00	200	Horizontal	Pass
4	312.027	27.25	-23.11	46.0	18.75	Peak	278.00	100	Horizontal	Pass
5	499.480	29.08	-18.11	46.0	16.92	Peak	306.00	200	Horizontal	Pass
6	599.972	28.94	-14.91	46.0	17.06	Peak	241.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	52.456	13.66	-24.72	40.0	26.34	Peak	81.00	100	Vertical	Pass
2	91.450	15.54	-27.61	43.5	27.96	Peak	268.00	100	Vertical	Pass
3	119.967	27.05	-28.19	43.5	16.45	Peak	20.00	100	Vertical	Pass
4	264.013	31.36	-24.15	46.0	14.64	Peak	292.00	200	Vertical	Pass
5	456.024	32.58	-19.37	46.0	13.42	Peak	178.00	100	Vertical	Pass
6	812.887	33.14	-11.45	46.0	12.86	Peak	233.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


Antenna type: PCB, Gain: 3.3 dBi

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1622.500	41.99	-14.84	74.0	32.01	Peak	334.00	150	Horizontal	Pass
1**	1622.500	32.14	-14.84	54.0	21.86	AV	334.00	150	Horizontal	Pass
2	2312.000	48.96	-11.18	74.0	25.04	Peak	93.00	150	Horizontal	Pass
2**	2312.000	44.54	-11.18	54.0	9.46	AV	93.00	150	Horizontal	Pass
3	2440.000	98.83	-11.36	74.0	-24.83	Peak	101.00	150	Horizontal	N/A
3**	2440.000	98.20	-11.36	54.0	-44.20	AV	101.00	150	Horizontal	N/A
4	2568.000	50.85	-10.02	74.0	23.15	Peak	101.00	150	Horizontal	Pass
4**	2568.000	45.95	-10.02	54.0	8.05	AV	101.00	150	Horizontal	Pass
5	7319.500	55.29	2.66	74.0	18.71	Peak	129.00	150	Horizontal	Pass
5**	7319.500	44.93	2.66	54.0	9.07	AV	129.00	150	Horizontal	Pass
6	14597.000	53.55	1.20	74.0	20.45	Peak	360.00	150	Horizontal	Pass
6**	14597.000	42.89	1.20	54.0	11.11	AV	360.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1620.750	48.12	-14.86	74.0	25.88	Peak	212.00	150	Vertical	Pass
1**	1620.750	38.68	-14.86	54.0	15.32	AV	212.00	150	Vertical	Pass
2	2440.000	91.51	-11.36	74.0	-17.51	Peak	221.00	150	Vertical	N/A
2**	2440.000	90.85	-11.36	54.0	-36.85	AV	221.00	150	Vertical	N/A
3	2952.750	48.06	-8.10	74.0	25.94	Peak	348.00	150	Vertical	Pass
3**	2952.750	35.82	-8.10	54.0	18.18	AV	348.00	150	Vertical	Pass
4	4880.000	50.62	-1.33	74.0	23.38	Peak	219.00	150	Vertical	Pass
4**	4880.000	42.76	-1.33	54.0	11.24	AV	219.00	150	Vertical	Pass
5	7320.000	56.51	2.68	74.0	17.49	Peak	90.00	150	Vertical	Pass
5**	7320.000	47.97	2.68	54.0	6.03	AV	90.00	150	Vertical	Pass
6	12463.500	51.54	-0.04	74.0	22.46	Peak	115.00	150	Vertical	Pass
6**	12463.500	40.92	-0.04	54.0	13.08	AV	115.00	150	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1621.250	41.89	-14.84	74.0	32.11	Peak	347.00	150	Horizontal	Pass
1**	1621.250	31.57	-14.84	54.0	22.43	AV	347.00	150	Horizontal	Pass
2	2209.000	44.38	-12.13	74.0	29.62	Peak	360.00	150	Horizontal	Pass
2**	2209.000	32.43	-12.13	54.0	21.57	AV	360.00	150	Horizontal	Pass
3	2439.500	98.40	-11.34	74.0	-24.40	Peak	283.00	150	Horizontal	N/A
3**	2439.500	94.79	-11.34	54.0	-40.79	AV	283.00	150	Horizontal	N/A
4	2936.500	47.88	-7.00	74.0	26.12	Peak	24.00	150	Horizontal	Pass
4**	2936.500	36.78	-7.00	54.0	17.22	AV	24.00	150	Horizontal	Pass
5	4880.500	52.90	-1.33	74.0	21.10	Peak	267.00	150	Horizontal	Pass
5**	4880.500	41.05	-1.33	54.0	12.95	AV	267.00	150	Horizontal	Pass
6	9303.000	51.13	-2.01	74.0	22.87	Peak	26.00	150	Horizontal	Pass
6**	9303.000	40.04	-2.01	54.0	13.96	AV	26.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1623.000	48.33	-14.83	74.0	25.67	Peak	213.00	150	Vertical	Pass
1**	1623.000	39.66	-14.83	54.0	14.34	AV	213.00	150	Vertical	Pass
2	2440.000	90.94	-11.36	74.0	-16.94	Peak	0.00	150	Vertical	N/A
2**	2440.000	89.81	-11.36	54.0	-35.81	AV	0.00	150	Vertical	N/A
3	2999.500	47.74	-7.46	74.0	26.26	Peak	31.00	150	Vertical	Pass
3**	2999.500	36.88	-7.46	54.0	17.12	AV	31.00	150	Vertical	Pass
4	4878.000	51.47	-1.31	74.0	22.53	Peak	233.00	150	Vertical	Pass
4**	4878.000	39.46	-1.31	54.0	14.54	AV	233.00	150	Vertical	Pass
5	7790.500	57.78	3.78	74.0	16.22	Peak	2.00	150	Vertical	Pass
5**	7790.500	45.50	3.78	54.0	8.50	AV	2.00	150	Vertical	Pass
6	15261.000	53.10	2.21	74.0	20.90	Peak	126.00	150	Vertical	Pass
6**	15261.000	42.16	2.21	54.0	11.84	AV	126.00	150	Vertical	Pass

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 1M-Middl channel mode is the worst.

Note 5: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Antenna type: Ceramics, Gain: 1.05 dBi

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	120.016	20.02	-28.20	43.5	23.48	Peak	250.00	200	Horizontal	Pass
2	167.982	21.21	-28.45	43.5	22.29	Peak	163.00	100	Horizontal	Pass
3	209.838	22.83	-26.37	43.5	20.67	Peak	42.00	200	Horizontal	Pass
4	264.013	27.21	-24.15	46.0	18.79	Peak	250.00	200	Horizontal	Pass
5	311.979	26.77	-23.11	46.0	19.23	Peak	274.00	100	Horizontal	Pass
6	498.655	28.89	-18.16	46.0	17.11	Peak	274.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	120.016	27.44	-28.20	43.5	16.06	Peak	53.00	100	Vertical	Pass
2	167.982	24.25	-28.45	43.5	19.25	Peak	89.00	100	Vertical	Pass
3	264.013	26.34	-24.15	46.0	19.66	Peak	187.00	100	Vertical	Pass
4	311.979	27.65	-23.11	46.0	18.35	Peak	193.00	100	Vertical	Pass
5	455.975	32.82	-19.37	46.0	13.18	Peak	181.00	100	Vertical	Pass
6	811.771	33.29	-11.47	46.0	12.71	Peak	223.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


Antenna type: Ceramics, Gain: 1.05 dBi

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1299.750	40.86	-14.65	74.0	33.14	Peak	110.00	150	Horizontal	Pass
1**	1299.750	29.83	-14.65	54.0	24.17	AV	110.00	150	Horizontal	Pass
2	1796.250	41.99	-14.54	74.0	32.01	Peak	0.00	150	Horizontal	Pass
2**	1796.250	30.57	-14.54	54.0	23.43	AV	0.00	150	Horizontal	Pass
3	2439.750	95.37	-11.35	74.0	-21.37	Peak	340.00	150	Horizontal	N/A
3**	2439.750	90.87	-11.35	54.0	-36.87	AV	340.00	150	Horizontal	N/A
4	4880.000	51.88	-1.33	74.0	22.12	Peak	170.00	150	Horizontal	Pass
4**	4880.000	44.16	-1.33	54.0	9.84	AV	170.00	150	Horizontal	Pass
5	7126.000	55.32	2.16	74.0	18.68	Peak	161.00	150	Horizontal	Pass
5**	7126.000	44.05	2.16	54.0	9.95	AV	161.00	150	Horizontal	Pass
6	10642.500	50.88	-1.35	74.0	23.12	Peak	188.00	150	Horizontal	Pass
6**	10642.500	40.10	-1.35	54.0	13.90	AV	188.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1622.000	48.53	-14.84	74.0	25.47	Peak	211.00	150	Vertical	Pass
1**	1622.000	37.48	-14.84	54.0	16.52	AV	211.00	150	Vertical	Pass
2	2184.750	44.52	-11.88	74.0	29.48	Peak	88.00	150	Vertical	Pass
2**	2184.750	33.15	-11.88	54.0	20.85	AV	88.00	150	Vertical	Pass
3	2439.500	94.17	-11.34	74.0	-20.17	Peak	160.00	150	Vertical	N/A
3**	2439.500	91.03	-11.34	54.0	-37.03	AV	160.00	150	Vertical	N/A
4	4879.000	51.44	-1.31	74.0	22.56	Peak	130.00	150	Vertical	Pass
4**	4879.000	43.49	-1.31	54.0	10.51	AV	130.00	150	Vertical	Pass
5	7318.000	55.82	2.63	74.0	18.18	Peak	12.00	150	Vertical	Pass
5**	7318.000	44.97	2.63	54.0	9.03	AV	12.00	150	Vertical	Pass
6	15260.500	52.72	2.23	74.0	21.28	Peak	84.00	150	Vertical	Pass
6**	15260.500	42.58	2.23	54.0	11.42	AV	84.00	150	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1282.750	40.53	-15.03	74.0	33.47	Peak	26.00	150	Horizontal	Pass
1**	1282.750	29.77	-15.03	54.0	24.23	AV	26.00	150	Horizontal	Pass
2	2440.000	94.99	-11.36	74.0	-20.99	Peak	340.00	150	Horizontal	N/A
2**	2440.000	94.39	-11.36	54.0	-40.39	AV	340.00	150	Horizontal	N/A
3	2925.250	47.65	-6.94	74.0	26.35	Peak	18.00	150	Horizontal	Pass
3**	2925.250	36.60	-6.94	54.0	17.40	AV	18.00	150	Horizontal	Pass
4	4880.000	53.26	-1.33	74.0	20.74	Peak	101.00	150	Horizontal	Pass
4**	4880.000	47.20	-1.33	54.0	6.80	AV	101.00	150	Horizontal	Pass
5	7320.000	56.17	2.68	74.0	17.83	Peak	112.00	150	Horizontal	Pass
5**	7320.000	49.38	2.68	54.0	4.62	AV	112.00	150	Horizontal	Pass
6	12909.000	51.93	0.41	74.0	22.07	Peak	360.00	150	Horizontal	Pass
6**	12909.000	41.30	0.41	54.0	12.70	AV	360.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1623.750	48.59	-14.84	74.0	25.41	Peak	223.00	150	Vertical	Pass
1**	1623.750	39.78	-14.84	54.0	14.22	AV	223.00	150	Vertical	Pass
2	2440.000	95.43	-11.36	74.0	-21.43	Peak	163.00	150	Vertical	N/A
2**	2440.000	94.85	-11.36	54.0	-40.85	AV	163.00	150	Vertical	N/A
3	4880.000	50.64	-1.33	74.0	23.36	Peak	230.00	150	Vertical	Pass
3**	4880.000	43.99	-1.33	54.0	10.01	AV	230.00	150	Vertical	Pass
4	7319.500	55.47	2.66	74.0	18.53	Peak	340.00	150	Vertical	Pass
4**	7319.500	45.16	2.66	54.0	8.84	AV	340.00	150	Vertical	Pass
5	10738.000	50.16	-1.38	74.0	23.84	Peak	216.00	150	Vertical	Pass
5**	10738.000	37.71	-1.38	54.0	16.29	AV	216.00	150	Vertical	Pass

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 1M-Middl channel mode is the worst.

Note 5: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Antenna type: PCB, gain: 0.8

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	119.967	16.53	-28.19	43.5	26.97	Peak	286.00	100	Horizontal	Pass
2	167.982	21.45	-28.45	43.5	22.05	Peak	178.00	100	Horizontal	Pass
3	264.013	25.68	-24.15	46.0	20.32	Peak	239.00	100	Horizontal	Pass
4	311.979	26.78	-23.11	46.0	19.22	Peak	268.00	100	Horizontal	Pass
5	499.577	27.84	-18.11	46.0	18.16	Peak	54.00	100	Horizontal	Pass
6	588.380	28.91	-15.51	46.0	17.09	Peak	294.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	44.986	14.36	-24.73	40.0	25.64	Peak	234.00	100	Vertical	Pass
2	120.016	28.40	-28.20	43.5	15.10	Peak	19.00	100	Vertical	Pass
3	167.982	24.28	-28.45	43.5	19.22	Peak	87.00	100	Vertical	Pass
4	264.013	31.04	-24.15	46.0	14.96	Peak	300.00	200	Vertical	Pass
5	455.975	32.03	-19.37	46.0	13.97	Peak	197.00	100	Vertical	Pass
6	811.771	34.37	-11.47	46.0	11.63	Peak	209.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


Antenna type: PCB, gain: 0.8

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1994.750	51.16	-13.35	74.0	22.84	Peak	278.00	150	Horizontal	Pass
1**	1994.750	31.76	-13.35	54.0	22.24	AV	278.00	150	Horizontal	Pass
2	2439.750	97.60	-11.35	74.0	-23.60	Peak	207.00	150	Horizontal	N/A
2**	2439.750	94.76	-11.35	54.0	-40.76	AV	207.00	150	Horizontal	N/A
3	4879.500	51.27	-1.32	74.0	22.73	Peak	119.00	150	Horizontal	Pass
3**	4879.500	42.04	-1.32	54.0	11.96	AV	119.00	150	Horizontal	Pass
4	7311.000	54.60	2.65	74.0	19.40	Peak	360.00	150	Horizontal	Pass
4**	7311.000	43.85	2.65	54.0	10.15	AV	360.00	150	Horizontal	Pass
5	9304.001	48.90	-1.92	74.0	25.10	Peak	12.00	150	Horizontal	Pass
5**	9304.001	39.71	-1.92	54.0	14.29	AV	12.00	150	Horizontal	Pass
6	14596.000	50.13	1.24	74.0	23.87	Peak	99.00	150	Horizontal	Pass
6**	14596.000	40.13	1.24	54.0	13.87	AV	99.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1621.750	46.88	-14.84	74.0	27.12	Peak	228.00	150	Vertical	Pass
1**	1621.750	38.44	-14.84	54.0	15.56	AV	228.00	150	Vertical	Pass
2	2440.250	94.24	-11.37	74.0	-20.24	Peak	260.00	150	Vertical	N/A
2**	2440.250	93.59	-11.37	54.0	-39.59	AV	260.00	150	Vertical	N/A
3	3596.500	46.76	-4.88	74.0	27.24	Peak	20.00	150	Vertical	Pass
3**	3596.500	35.92	-4.88	54.0	18.08	AV	20.00	150	Vertical	Pass
4	4880.000	50.35	-1.33	74.0	23.65	Peak	92.00	150	Vertical	Pass
4**	4880.000	44.10	-1.33	54.0	9.90	AV	92.00	150	Vertical	Pass
5	7319.000	54.86	2.65	74.0	19.14	Peak	302.00	150	Vertical	Pass
5**	7319.000	44.37	2.65	54.0	9.63	AV	302.00	150	Vertical	Pass
6	12717.000	49.81	0.04	74.0	24.19	Peak	1.00	150	Vertical	Pass
6**	12717.000	39.37	0.04	54.0	14.63	AV	1.00	150	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1746.250	40.66	-14.85	74.0	33.34	Peak	7.00	150	Horizontal	Pass
1**	1746.250	29.55	-14.85	54.0	24.45	AV	7.00	150	Horizontal	Pass
2	2440.000	97.02	-11.36	74.0	-23.02	Peak	203.00	150	Horizontal	N/A
2**	2440.000	93.50	-11.36	54.0	-39.50	AV	203.00	150	Horizontal	N/A
3	4879.000	50.89	-1.31	74.0	23.11	Peak	142.00	150	Horizontal	Pass
3**	4879.000	43.10	-1.31	54.0	10.90	AV	142.00	150	Horizontal	Pass
4	7898.500	55.03	3.49	74.0	18.97	Peak	21.00	150	Horizontal	Pass
4**	7898.500	44.04	3.49	54.0	9.96	AV	21.00	150	Horizontal	Pass
5	11997.000	49.40	-1.11	74.0	24.60	Peak	25.00	150	Horizontal	Pass
5**	11997.000	38.43	-1.11	54.0	15.57	AV	25.00	150	Horizontal	Pass
6	16561.000	51.09	2.04	74.0	22.91	Peak	360.00	150	Horizontal	Pass
6**	16561.000	39.48	2.04	54.0	14.52	AV	360.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1619.250	46.63	-14.92	74.0	27.37	Peak	224.00	150	Vertical	Pass
1**	1619.250	33.49	-14.92	54.0	20.51	AV	224.00	150	Vertical	Pass
2	2439.250	94.89	-11.33	74.0	-20.89	Peak	251.00	150	Vertical	N/A
2**	2439.250	90.49	-11.33	54.0	-36.49	AV	251.00	150	Vertical	N/A
3	4880.500	51.78	-1.33	74.0	22.22	Peak	129.00	150	Vertical	Pass
3**	4880.500	40.54	-1.33	54.0	13.46	AV	129.00	150	Vertical	Pass
4	7339.500	54.46	3.19	74.0	19.54	Peak	280.00	150	Vertical	Pass
4**	7339.500	44.20	3.19	54.0	9.80	AV	280.00	150	Vertical	Pass
5	9297.500	49.34	-1.92	74.0	24.66	Peak	160.00	150	Vertical	Pass
5**	9297.500	38.75	-1.92	54.0	15.25	AV	160.00	150	Vertical	Pass
6	16642.500	50.74	1.82	74.0	23.26	Peak	359.00	150	Vertical	Pass
6**	16642.500	39.64	1.82	54.0	14.36	AV	359.00	150	Vertical	Pass

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 1M-Middl channel mode is the worst.

Note 5: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Antenna type: Dipole, Gain: 2 dBi

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	120.016	19.74	-28.20	43.5	23.76	Peak	252.00	200	Horizontal	Pass
2	167.982	21.87	-28.45	43.5	21.63	Peak	163.00	100	Horizontal	Pass
3	264.013	27.96	-24.15	46.0	18.04	Peak	241.00	200	Horizontal	Pass
4	312.027	26.86	-23.11	46.0	19.14	Peak	268.00	100	Horizontal	Pass
5	499.965	29.74	-18.07	46.0	16.26	Peak	343.00	200	Horizontal	Pass
6	862.745	29.87	-9.82	46.0	16.13	Peak	137.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	120.016	27.78	-28.20	43.5	15.72	Peak	38.00	100	Vertical	Pass
2	167.982	24.28	-28.45	43.5	19.22	Peak	62.00	100	Vertical	Pass
3	264.013	31.51	-24.15	46.0	14.49	Peak	301.00	200	Vertical	Pass
4	311.979	27.89	-23.11	46.0	18.11	Peak	325.00	200	Vertical	Pass
5	456.024	33.16	-19.37	46.0	12.84	Peak	184.00	100	Vertical	Pass
6	934.137	32.18	-8.90	46.0	13.82	Peak	138.00	200	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


Antenna type: Dipole, Gain: 2 dBi

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1619.000	41.86	-14.93	74.0	32.14	Peak	255.00	150	Horizontal	Pass
1**	1619.000	31.05	-14.93	54.0	22.95	AV	255.00	150	Horizontal	Pass
2	2213.500	43.97	-12.09	74.0	30.03	Peak	17.00	150	Horizontal	Pass
2**	2213.500	33.04	-12.09	54.0	20.96	AV	17.00	150	Horizontal	Pass
3	2439.500	100.42	-11.34	74.0	-26.42	Peak	211.00	150	Horizontal	N/A
3**	2439.500	97.61	-11.34	54.0	-43.61	AV	211.00	150	Horizontal	N/A
4	2993.500	47.80	-7.67	74.0	26.20	Peak	3.00	150	Horizontal	Pass
4**	2993.500	36.65	-7.67	54.0	17.35	AV	3.00	150	Horizontal	Pass
5	4880.000	53.15	-1.33	74.0	20.85	Peak	131.00	150	Horizontal	Pass
5**	4880.000	47.91	-1.33	54.0	6.09	AV	131.00	150	Horizontal	Pass
6	14900.000	53.22	0.32	74.0	20.78	Peak	0.00	150	Horizontal	Pass
6**	14900.000	40.79	0.32	54.0	13.21	AV	0.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1623.500	48.03	-14.83	74.0	25.97	Peak	210.00	150	Vertical	Pass
1**	1623.500	40.27	-14.83	54.0	13.73	AV	210.00	150	Vertical	Pass
2	2007.750	43.70	-13.01	74.0	30.30	Peak	2.00	150	Vertical	Pass
2**	2007.750	31.98	-13.01	54.0	22.02	AV	2.00	150	Vertical	Pass
3	2439.750	83.79	-11.35	74.0	-9.79	Peak	214.00	150	Vertical	N/A
3**	2439.750	81.57	-11.35	54.0	-27.57	AV	214.00	150	Vertical	N/A
4	2904.750	47.16	-8.36	74.0	26.84	Peak	165.00	150	Vertical	Pass
4**	2904.750	36.03	-8.36	54.0	17.97	AV	165.00	150	Vertical	Pass
5	7738.000	56.96	3.36	74.0	17.04	Peak	0.00	150	Vertical	Pass
5**	7738.000	45.92	3.36	54.0	8.08	AV	0.00	150	Vertical	Pass
6	14596.500	52.35	1.24	74.0	21.65	Peak	233.00	150	Vertical	Pass
6**	14596.500	43.07	1.24	54.0	10.93	AV	233.00	150	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1623.750	41.63	-14.84	74.0	32.37	Peak	32.00	150	Horizontal	Pass
1**	1623.750	32.62	-14.84	54.0	21.38	AV	32.00	150	Horizontal	Pass
2	2440.000	100.94	-11.36	74.0	-26.94	Peak	72.00	150	Horizontal	N/A
2**	2440.000	100.32	-11.36	54.0	-46.32	AV	72.00	150	Horizontal	N/A
3	2978.500	47.67	-7.72	74.0	26.33	Peak	87.00	150	Horizontal	Pass
3**	2978.500	36.43	-7.72	54.0	17.57	AV	87.00	150	Horizontal	Pass
4	4880.000	52.58	-1.33	74.0	21.42	Peak	122.00	150	Horizontal	Pass
4**	4880.000	46.21	-1.33	54.0	7.79	AV	122.00	150	Horizontal	Pass
5	7319.500	57.48	2.66	74.0	16.52	Peak	122.00	150	Horizontal	Pass
5**	7319.500	45.59	2.66	54.0	8.41	AV	122.00	150	Horizontal	Pass
6	15212.500	52.33	1.30	74.0	21.67	Peak	359.00	150	Horizontal	Pass
6**	15212.500	42.55	1.30	54.0	11.45	AV	359.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1621.750	48.58	-14.84	74.0	25.42	Peak	209.00	150	Vertical	Pass
1**	1621.750	38.67	-14.84	54.0	15.33	AV	209.00	150	Vertical	Pass
2	2313.000	45.72	-11.18	74.0	28.28	Peak	360.00	150	Vertical	Pass
2**	2313.000	34.41	-11.18	54.0	19.59	AV	360.00	150	Vertical	Pass
3	2440.000	85.22	-11.36	74.0	-11.22	Peak	300.00	150	Vertical	N/A
3**	2440.000	84.53	-11.36	54.0	-30.53	AV	300.00	150	Vertical	N/A
4	4880.000	52.48	-1.33	74.0	21.52	Peak	259.00	150	Vertical	Pass
4**	4880.000	44.34	-1.33	54.0	9.66	AV	259.00	150	Vertical	Pass
5	7320.000	56.36	2.68	74.0	17.64	Peak	180.00	150	Vertical	Pass
5**	7320.000	48.67	2.68	54.0	5.33	AV	180.00	150	Vertical	Pass
6	14602.500	51.94	0.83	74.0	22.06	Peak	349.00	150	Vertical	Pass
6**	14602.500	42.19	0.83	54.0	11.81	AV	349.00	150	Vertical	Pass

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 1M-Middl channel mode is the worst.

Note 5: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Antenna type: PCB, Gain: 2.3 dBi

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	149.456	17.98	-29.60	43.5	25.52	Peak	233.00	100	Horizontal	Pass
2	167.982	21.76	-28.45	43.5	21.74	Peak	172.00	100	Horizontal	Pass
3	264.013	25.94	-24.15	46.0	20.06	Peak	239.00	100	Horizontal	Pass
4	311.979	25.86	-23.11	46.0	20.14	Peak	274.00	100	Horizontal	Pass
5	455.975	25.92	-19.37	46.0	20.08	Peak	280.00	100	Horizontal	Pass
6	599.972	27.61	-14.91	46.0	18.39	Peak	225.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	120.016	27.03	-28.20	43.5	16.47	Peak	23.00	100	Vertical	Pass
2	168.031	24.30	-28.44	43.5	19.20	Peak	66.00	100	Vertical	Pass
3	264.013	31.19	-24.15	46.0	14.81	Peak	300.00	200	Vertical	Pass
4	311.979	28.80	-23.11	46.0	17.20	Peak	167.00	200	Vertical	Pass
5	455.975	32.92	-19.37	46.0	13.08	Peak	169.00	100	Vertical	Pass
6	906.007	30.67	-9.14	46.0	15.33	Peak	311.00	200	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.


Antenna type: PCB, Gain: 2.3 dBi

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1624.500	41.36	-14.85	74.0	32.64	Peak	215.00	150	Horizontal	Pass
1**	1624.500	32.41	-14.85	54.0	21.59	AV	215.00	150	Horizontal	Pass
2	2440.000	100.63	-11.36	74.0	-26.63	Peak	210.00	150	Horizontal	N/A
2**	2440.000	97.31	-11.36	54.0	-43.31	AV	210.00	150	Horizontal	N/A
3	2930.750	47.80	-6.79	74.0	26.20	Peak	304.00	150	Horizontal	Pass
3**	2930.750	36.97	-6.79	54.0	17.03	AV	304.00	150	Horizontal	Pass
4	4879.000	52.08	-1.31	74.0	21.92	Peak	1.00	150	Horizontal	Pass
4**	4879.000	44.31	-1.31	54.0	9.69	AV	1.00	150	Horizontal	Pass
5	7136.000	56.61	2.10	74.0	17.39	Peak	360.00	150	Horizontal	Pass
5**	7136.000	44.58	2.10	54.0	9.42	AV	360.00	150	Horizontal	Pass
6	13978.000	51.90	0.54	74.0	22.10	Peak	98.00	150	Horizontal	Pass
6**	13978.000	41.24	0.54	54.0	12.76	AV	98.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1621.500	48.32	-14.84	74.0	25.68	Peak	207.00	150	Vertical	Pass
1**	1621.500	38.62	-14.84	54.0	15.38	AV	207.00	150	Vertical	Pass
2	2440.500	89.35	-11.38	74.0	-15.35	Peak	329.00	150	Vertical	N/A
2**	2440.500	86.31	-11.38	54.0	-32.31	AV	329.00	150	Vertical	N/A
3	2871.000	47.40	-8.54	74.0	26.60	Peak	176.00	150	Vertical	Pass
3**	2871.000	36.03	-8.54	54.0	17.97	AV	176.00	150	Vertical	Pass
4	4878.500	51.77	-1.31	74.0	22.23	Peak	228.00	150	Vertical	Pass
4**	4878.500	41.28	-1.31	54.0	12.72	AV	228.00	150	Vertical	Pass
5	7163.500	56.32	2.24	74.0	17.68	Peak	228.00	150	Vertical	Pass
5**	7163.500	44.80	2.24	54.0	9.20	AV	228.00	150	Vertical	Pass
6	14596.000	52.42	1.24	74.0	21.58	Peak	1.00	150	Vertical	Pass
6**	14596.000	43.08	1.24	54.0	10.92	AV	1.00	150	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1621.250	41.66	-14.84	74.0	32.34	Peak	219.00	150	Horizontal	Pass
1**	1621.250	31.41	-14.84	54.0	22.59	AV	219.00	150	Horizontal	Pass
2	2440.000	101.21	-11.36	74.0	-27.21	Peak	6.00	150	Horizontal	N/A
2**	2440.000	100.59	-11.36	54.0	-46.59	AV	6.00	150	Horizontal	N/A
3	2568.000	49.68	-10.02	74.0	24.32	Peak	6.00	150	Horizontal	Pass
3**	2568.000	45.06	-10.02	54.0	8.94	AV	6.00	150	Horizontal	Pass
4	4880.000	53.06	-1.33	74.0	20.94	Peak	130.00	150	Horizontal	Pass
4**	4880.000	47.29	-1.33	54.0	6.71	AV	130.00	150	Horizontal	Pass
5	7320.000	57.00	2.68	74.0	17.00	Peak	89.00	150	Horizontal	Pass
5**	7320.000	50.99	2.68	54.0	3.01	AV	89.00	150	Horizontal	Pass
6	11235.000	50.99	-1.56	74.0	23.01	Peak	360.00	150	Horizontal	Pass
6**	11235.000	40.02	-1.56	54.0	13.98	AV	360.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1622.750	47.77	-14.84	74.0	26.23	Peak	215.00	150	Vertical	Pass
1**	1622.750	39.89	-14.84	54.0	14.11	AV	215.00	150	Vertical	Pass
2	2440.000	87.88	-11.36	74.0	-13.88	Peak	329.00	150	Vertical	N/A
2**	2440.000	87.22	-11.36	54.0	-33.22	AV	329.00	150	Vertical	N/A
3	2925.250	48.14	-6.94	74.0	25.86	Peak	31.00	150	Vertical	Pass
3**	2925.250	36.95	-6.94	54.0	17.05	AV	31.00	150	Vertical	Pass
4	4880.000	52.59	-1.33	74.0	21.41	Peak	269.00	150	Vertical	Pass
4**	4880.000	46.53	-1.33	54.0	7.47	AV	269.00	150	Vertical	Pass
5	7320.000	56.89	2.68	74.0	17.11	Peak	113.00	150	Vertical	Pass
5**	7320.000	50.34	2.68	54.0	3.66	AV	113.00	150	Vertical	Pass
6	12796.500	52.24	-0.20	74.0	21.76	Peak	39.00	150	Vertical	Pass
6**	12796.500	40.78	-0.20	54.0	13.22	AV	39.00	150	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note 1: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note 2: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note 3: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 4: The Level (dBuV/m) has been corrected by factor.

Test Data and Plots


Antenna type: PCB, Gain: 3.3 dBi

GFSK (BLE 1Mbps) LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.100	51.91	-3.73	74.0	22.09	Peak	206.00	150	Vertical	Pass
1**	2390.100	41.48	-3.73	54.0	12.52	AV	206.00	150	Vertical	Pass
2	2379.000	53.88	-3.09	74.0	20.12	Peak	348.00	150	Vertical	Pass
2**	2379.000	41.83	-3.09	54.0	12.17	AV	348.00	150	Vertical	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	60.16	-2.60	74.0	13.84	Peak	111.00	150	Horizontal	Pass
1**	2483.500	43.60	-2.60	54.0	10.40	AV	111.00	150	Horizontal	Pass
2	2483.650	60.73	-2.60	74.0	13.27	Peak	87.00	150	Horizontal	Pass
2**	2483.650	42.72	-2.60	54.0	11.28	AV	87.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.96	-3.74	74.0	22.04	Peak	333.00	150	Horizontal	Pass
1**	2390.000	41.64	-3.74	54.0	12.36	AV	333.00	150	Horizontal	Pass
2	2378.400	53.99	-3.05	74.0	20.01	Peak	328.00	150	Horizontal	Pass
2**	2378.400	41.81	-3.05	54.0	12.19	AV	328.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	59.22	-2.60	74.0	14.78	Peak	93.00	150	Horizontal	Pass
1**	2483.500	44.60	-2.60	54.0	9.40	AV	93.00	150	Horizontal	Pass
2	2483.560	61.38	-2.60	74.0	12.62	Peak	99.00	150	Horizontal	Pass
2**	2483.560	43.67	-2.60	54.0	10.33	AV	99.00	150	Horizontal	Pass


Antenna type: Ceramics, Gain: 1.05 dBi

GFSK (BLE 1Mbps) LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	52.46	-3.73	74.0	21.54	Peak	260.04	150	Vertical	Pass
1**	2390.000	41.68	-3.73	54.0	12.32	AV	260.04	150	Vertical	Pass
2	2324.700	53.56	-3.50	74.0	20.44	Peak	178.00	150	Vertical	Pass
2**	2324.700	41.54	-3.50	54.0	12.46	AV	178.00	150	Vertical	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.79	-2.60	74.0	20.21	Peak	360.00	150	Horizontal	Pass
1**	2483.500	43.26	-2.60	54.0	10.74	AV	360.00	150	Horizontal	Pass
2	2484.730	55.15	-2.62	74.0	18.85	Peak	360.00	150	Horizontal	Pass
2**	2484.730	42.97	-2.62	54.0	11.03	AV	360.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.71	-3.73	74.0	22.29	Peak	98.15	150	Horizontal	Pass
1**	2390.000	41.63	-3.73	54.0	12.37	AV	98.15	150	Horizontal	Pass
2	2372.000	53.74	-2.88	74.0	20.26	Peak	68.00	150	Horizontal	Pass
2**	2372.000	42.09	-2.88	54.0	11.91	AV	68.00	150	Horizontal	Pass


GFSK (BLE 2Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.04	-2.60	74.0	19.96	Peak	338.00	150	Horizontal	Pass
1**	2483.500	42.71	-2.60	54.0	11.29	AV	338.00	150	Horizontal	Pass
2	2483.650	55.30	-2.60	74.0	18.70	Peak	208.00	150	Horizontal	Pass
2**	2483.650	42.36	-2.60	54.0	11.64	AV	208.00	150	Horizontal	Pass


Antenna type: PCB, Gain: 0.8 dBi

GFSK (BLE 1Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.19	-3.73	74.0	22.81	Peak	2.00	150	Horizontal	Pass
1**	2390.000	41.42	-3.73	54.0	12.58	AV	2.00	150	Horizontal	Pass
2	2369.900	54.11	-2.83	74.0	19.89	Peak	105.00	150	Horizontal	Pass
2**	2369.900	41.95	-2.83	54.0	12.05	AV	105.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	52.61	-2.60	74.0	21.39	Peak	236.00	150	Horizontal	Pass
1**	2483.500	42.62	-2.60	54.0	11.38	AV	236.00	150	Horizontal	Pass
2	2485.570	53.78	-2.63	74.0	20.22	Peak	92.00	150	Horizontal	Pass
2**	2485.570	42.18	-2.63	54.0	11.82	AV	92.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.73	-3.73	74.0	22.27	Peak	352.74	150	Horizontal	Pass
1**	2390.000	41.73	-3.73	54.0	12.27	AV	352.74	150	Horizontal	Pass
2	2371.200	53.98	-2.85	74.0	20.02	Peak	188.00	150	Horizontal	Pass
2**	2371.200	42.02	-2.85	54.0	11.98	AV	188.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	57.00	-2.60	74.0	17.00	Peak	219.00	150	Horizontal	Pass
1**	2483.500	43.69	-2.60	54.0	10.31	AV	219.00	150	Horizontal	Pass
2	2483.590	58.06	-2.60	74.0	15.94	Peak	214.00	150	Horizontal	Pass
2**	2483.590	43.06	-2.60	54.0	10.94	AV	214.00	150	Horizontal	Pass


Antenna type: Dipole, Gain: 2 dBi

GFSK (BLE 1Mbps) LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.35	-3.73	74.0	22.65	Peak	96.33	150	Horizontal	Pass
1**	2390.000	41.58	-3.73	54.0	12.42	AV	96.33	150	Horizontal	Pass
2	2335.500	53.75	-3.00	74.0	20.25	Peak	265.00	150	Horizontal	Pass
2**	2335.500	41.89	-3.00	54.0	12.11	AV	265.00	150	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.41	-2.60	74.0	20.59	Peak	239.00	150	Horizontal	Pass
1**	2483.500	43.81	-2.60	54.0	10.19	AV	239.00	150	Horizontal	Pass
2	2486.740	54.94	-2.64	74.0	19.06	Peak	248.00	150	Horizontal	Pass
2**	2486.740	42.46	-2.64	54.0	11.54	AV	248.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	52.12	-3.73	74.0	21.88	Peak	312.70	150	Horizontal	Pass
1**	2390.000	41.85	-3.73	54.0	12.15	AV	312.70	150	Horizontal	Pass
2	2370.100	54.28	-2.81	74.0	19.72	Peak	211.00	150	Horizontal	Pass
2**	2370.100	42.30	-2.81	54.0	11.70	AV	211.00	150	Horizontal	Pass


GFSK (BLE 2Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	60.56	-2.60	74.0	13.44	Peak	211.00	150	Horizontal	Pass
1**	2483.500	44.94	-2.60	54.0	9.06	AV	211.00	150	Horizontal	Pass
2	2483.740	60.69	-2.60	74.0	13.31	Peak	65.00	150	Horizontal	Pass
2**	2483.740	44.18	-2.60	54.0	9.82	AV	65.00	150	Horizontal	Pass


Antenna type: PCB, Gain: 2.3 dBi

GFSK (BLE 1Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.83	-3.73	74.0	22.17	Peak	290.67	150	Vertical	Pass
1**	2390.000	41.68	-3.73	54.0	12.32	AV	290.67	150	Vertical	Pass
2	2372.700	53.91	-2.90	74.0	20.09	Peak	355.00	150	Vertical	Pass
2**	2372.700	42.02	-2.90	54.0	11.98	AV	355.00	150	Vertical	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	55.50	-2.60	74.0	18.50	Peak	216.00	150	Horizontal	Pass
1**	2483.500	45.17	-2.60	54.0	8.83	AV	216.00	150	Horizontal	Pass
2	2483.710	55.95	-2.60	74.0	18.05	Peak	4.00	150	Horizontal	Pass
2**	2483.710	45.22	-2.60	54.0	8.78	AV	4.00	150	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.73	-3.73	74.0	22.27	Peak	254.13	150	Vertical	Pass
1**	2390.000	41.53	-3.73	54.0	12.47	AV	254.13	150	Vertical	Pass
2	2386.500	54.21	-3.54	74.0	19.79	Peak	294.00	150	Vertical	Pass
2**	2386.500	41.82	-3.54	54.0	12.18	AV	294.00	150	Vertical	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	59.19	-2.60	74.0	14.81	Peak	228.00	150	Horizontal	Pass
1**	2483.500	45.08	-2.60	54.0	8.92	AV	228.00	150	Horizontal	Pass
2	2483.800	59.19	-2.61	74.0	14.81	Peak	224.00	150	Horizontal	Pass
2**	2483.800	43.88	-2.61	54.0	10.12	AV	224.00	150	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

GFSK (BLE 1Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-4.10	8	Pass
Middle	-3.44	8	Pass
High	-4.36	8	Pass

GFSK (BLE 2Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-8.53	8	Pass
Middle	-9.40	8	Pass
High	-9.26	8	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SH2490725-AR-1.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SH2490725-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SH2490725-AI.PDF”.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--