



RF EXPOSURE REPORT

Applicant	:	Dongguan Jin wen hua digital technology Co.,LTD.	
Address of Applicant	:	NO.1 Hua Da Road, Long Bei Ling Village, Tangxia Town, Dongguan City, Guangdong, China	
Manufacturer	:	Dongguan Jin wen hua digital technology Co.,LTD.	
Address of Manufacturer	:	NO.1 Hua Da Road, Long Bei Ling Village, Tangxia Town, Dongguan City, Guangdong, China	
Equipment under Test	:	Smart sport glasses	
Model No.	6.	G120PLUS, G120, G120C, G120D, G120E, Tonitrus G120, BG120, RYON130, Airglass 10	
FCC ID	•	2AFSG-G120	
Test Standard(s)		KDB447498 D01 General RF Exposure Guidance v06	
Report No.	••	DDT-RE24112921-1E04	
Issue Date	••	2024/12/26	
Unit 2, Building 1, No. 17, Zongbu 2nd Road,		Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808	



Table of Contents

1.	General Test Information	5
1.1.	Description of EUT	5
1.2.	Accessories of EUT	5
1.3.	Test laboratory	5
2.	RF Exposure evaluation for FCC	6
2.1.	Assessment procedure	6
2.2.	Assess result	6

Test Report Declare

Applicant	:	Dongguan Jin wen hua digital technology Co.,LTD.
Address of Applicant Equipment under Test Model No.		NO.1 Hua Da Road, Long Bei Ling Village, Tangxia Town, Dongguan City, Guangdong, China
		Smart sport glasses
		G120PLUS, G120, G120C, G120D, G120E, Tonitrus G120, BG120, RYON130, Airglass 10
Manufacturer	8	Dongguan Jin wen hua digital technology Co.,LTD.
Address of Manufacturer		NO.1 Hua Da Road, Long Bei Ling Village, Tangxia Town, Dongguan City, Guangdong, China

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24112921-1E04		
Date of Receipt:	2024/12/16	Date of Test:	2024/12/16~2024/12/26

Prepared By:

Approved By:

Tiger Mo

Tiger Mo/Engineer

Approved By:

Damon Hu

Damon Hu

EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

TRF:RT-4-E-006 Page 3 of 6

Revision History

Rev.	Revisions	Issue Date	Revised By
	Initial issue	2024/12/26	8
	XOP XOP	*	1

TRF:RT-4-E-006 Page 4 of

1. General Test Information

1.1. Description of EUT

EUT Name	:	: Smart sport glasses		
Model Number	:	G120PLUS, G120, G120C, G120D, G120E, Tonitrus G120, BG120, RYON130, Airglass 10		
Difference of models		Above models are identical in schematic, appearance and structure only the Model Number and Trade Mark are different for all the models, therefore the test performed on the model G120.		
EUT Function Description	:	Please reference user manual of this device		
Power Supply		DC 5V From Magnetic Charging Cable or DC 3.7VLi-ion polymer battery		
Hardware Version	:	V1		
Software Version	1	12.11		
Antenna Type	:	SMD CERAMIC ANTENNA		
Max Antenna Gain(dBi)	:	2.58		

Note: This EUT support Bluetooth BR/EDR.

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

"⊠" means to be chosen or applicable; "□" means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Magnetic Charging	,	, , ,	,
Cable	/		

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

TRF:RT-4-E-006 Page 5 of 6

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.2. Assess result

Manufacturing Tolerance:

Mode	Antenna	Frequency [MHz]	Target (dBm)	Tolerance ±(dB)
		2402	4.95	2
GFSK (Peak)	Ant1	2441	5.02	2
		2480	4.69	2
		2402	5.61	2
π/4DQPSK (Peak)	Ant1	2441	5.66	2
		2480	5.33	2
5-1	Ant1	2402	5.98	2
8DPSK (Peak)		2441	5.99	2
		2480	5.59	2

Estimtion Result:

Worse case is as below: [2441 MHz, 7.99 dBm, (6.30 mW) output power]

 $(6.30/5) \cdot [\sqrt{2.441} \text{ (GHz)}] = 1.97 < 3.0 \text{ for } 1-\text{g SAR}$

Then SAR evaluation is not required.



TRF:RT-4-E-006 Page 6 of 6