
FCC Test Report

Report No.: AGC03311160604FE03

FCC ID : SXS-BTH3

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : Bluetooth Speaker

BRAND NAME : GSOU

MODEL NAME : H3

CLIENT : GSOU Technology (Shen Zhen) Co., LTD.

DATE OF ISSUE : July 28, 2016

STANDARD(S) : FCC Part 15 Rules

TEST PROCEDURE(S)

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	July 28, 2016	Valid	Original Report

TABLE OF CONTENTS


1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION.....	5
2.2. TABLE OF CARRIER FREQUENCYS.....	5
3. MEASUREMENT UNCERTAINTY.....	7
4. DESCRIPTION OF TEST MODES.....	7
5. SYSTEM TEST CONFIGURATION	9
5.1. CONFIGURATION OF EUT SYSTEM	9
5.2. EQUIPMENT USED IN EUT SYSTEM	9
5.3. SUMMARY OF TEST RESULTS	9
6. TEST FACILITY	10
TEST METHODOLOGY.....	10
7. ALL TEST EQUIPMENT LIST	10
8. RADIATED EMISSION	12
8.1TEST LIMIT.....	12
8.2. MEASUREMENT PROCEDURE	13
8.3. TEST SETUP.....	15
8.4. TEST RESULT	17
9. BAND EDGE EMISSION	46
9.1. MEASUREMENT PROCEDURE	46
9.2 TEST SETUP.....	46
9.3 RADIATED TEST RESULT	47
10. 20DB BANDWIDTH.....	55
10.1. MEASUREMENT PROCEDURE	55
10.2. TEST SET-UP	55
10.3. LIMITS AND MEASUREMENT RESULTS.....	55
11. FCC LINE CONDUCTED EMISSION TEST	64
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST	64
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....	64
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	65
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	65
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....	66
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	70
APPENDIX B: PHOTOGRAPHS OF EUT	73

1. VERIFICATION OF CONFORMITY

Applicant	GSOU Technology (Shen Zhen) Co., LTD.
Applicant Address	14C, Block A, First World Plaza, No.7002 West Hongli Road, Futian District, Shenzhen, Guangdong, China
Manufacturer	GSOU Technology (Shen Zhen) Co., LTD.
Manufacturer Address	14C, Block A, First World Plaza, No.7002 West Hongli Road, Futian District, Shenzhen, Guangdong, China
Product Designation	Bluetooth Speaker
Brand Name	GSOU
Test Model	H3
Date of test	July 04, 2016 to July 05, 2016
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By 
Time Huang(Huang Nanhui) July 28, 2016

Reviewed By 
Forrest Lei(Lei Yonggang) July 28, 2016

Approved By 
Solger Zhang(Zhang Hongyi)
Authorized Officer July 28, 2016

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-0.19dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.0
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK for BR/EDR; GFSK for BLE
Number of channels	79 for BR/EDR, 40 for BLE
Hardware Version	V1.0
Software Version	V1.0
Antenna Designation	PCB Antenna
Antenna Gain	-0.33dBi
Power Supply	DC 3.7V

Note: The USB port only used for charging and can't be used to transfer data with PC.

2.2. TABLE OF CARRIER FREQUENCIES

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

BLE Channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX(GFSK)
2	Middle channel TX (GFSK)
3	High channel TX (GFSK)
4	Low channel TX($\pi/4$ -DQPSK)
5	Middle channel TX ($\pi/4$ -DQPSK)
6	High channel TX ($\pi/4$ -DQPSK)
7	Low channel TX(8DPSK)
8	Middle channel TX 8DPSK)
9	High channel TX 8DPSK)
10	BT Link with charging
11	BT Link

Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The EUT used fully-charged battery when tested.

Software Setting

Bluetooth MP Tool

Mode: **0** Interface: **BT ONLY UART** Port = **1** Baudrate=**115200** **Open** **Close**

Non Link Mode | **Hopping** | **RW** | **LE Test** | ☒ **DL Patch**

Channel: **0** Packet Type: **DH1** Payload Type: **PRBS9** Tx Packet Count: **0** Tx Gain Index: **6** Tx Gain Value: **0xCE**

Pkt-Tx: **Pkt-Tx** **Exec** **Stop** **Clear Report**

Item	Value
Tx bits	686016
Tx Pkt Count	3176

Parameter 1 | Parameter 2 | Parameter 3

TX Report **RX Report**


Message

```
>>Version=0b
>>Is_After_PatchCode=1
>>BT Default Power Index = 4
>>Read Tx dac current value = 0xfl!
>>Enable TRX Thread Mode...!!
>>ActionControlExcute(Pkt-Tx) Success...!!
>>ActionControlExcute(Pkt-Tx) Stop...!!
```


5. SYSTEM TEST CONFIGURATION


5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Note: Owing to the EUT has own battery, Testing will be performed while PC or adapter remove.

Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bluetooth Speaker	GSOU	H3	EUT
2	Battery	BTI	BPI 18650	Accessory
3	PC	DELL	INSPIRON	A.E
4	Control box	DOFLY	LY-USB-TTL v2.2	A.E
5	Adapter	JQH	NSA12UH-050200	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	Bandwidth	Compliant

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013

7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2016	July 3, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2016	July 3, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2016	June 5, 2017
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2016	July 3, 2017
Shielded Room	CHENGYU	843	PTS-002	June 6, 2016	June 5, 2017
Conduction Cable	MXT	SE1	S003	June 6, 2016	June 5, 2017

8. RADIATED EMISSION

8.1 TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark:

- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE


1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak&AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



8.4. TEST RESULT

(Worst modulation:GFSK)


FOR BR/EDR

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth Speaker
M/N: H3
Mode: Low Channel TX
Note:


Polarization: *Horizontal*
Power:
Distance:

Temperature: 24.5
Humidity: 52.6 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		101.1333	21.82	10.22	32.04	43.50	-11.46	peak			
2	!	154.4832	27.58	11.67	39.25	43.50	-4.25	peak			
3	*	199.7500	27.65	11.99	39.64	43.50	-3.86	peak			
4		592.6000	2.01	23.55	25.56	46.00	-20.44	peak			
5		799.5333	2.07	27.31	29.38	46.00	-16.62	peak			
6		953.1167	2.16	29.97	32.13	46.00	-13.87	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: Low Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		104.3667	26.38	-0.93	25.45	43.50	-18.05	peak			
2		136.7000	19.72	13.82	33.54	43.50	-9.96	peak			
3	*	152.8667	23.94	15.28	39.22	43.50	-4.28	peak			
4		199.7500	27.30	9.06	36.36	43.50	-7.14	peak			
5		555.4167	2.98	22.51	25.49	46.00	-20.51	peak			
6		768.8167	1.72	26.89	28.61	46.00	-17.39	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		117.2999	25.52	6.48	32.00	43.50	-11.50	peak			
2		148.0166	23.32	13.25	36.57	43.50	-6.93	peak			
3	*	198.1332	27.84	11.91	39.75	43.50	-3.75	peak			
4		510.1499	1.36	21.40	22.76	46.00	-23.24	peak			
5		791.4500	1.68	27.20	28.88	46.00	-17.12	peak			
6		959.5833	2.26	29.91	32.17	46.00	-13.83	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	152.8667	24.55	15.28	39.83	43.50	-3.67	peak			
2		199.7500	27.39	9.06	36.45	43.50	-7.05	peak			
3		493.9832	9.66	21.06	30.72	46.00	-15.28	peak			
4		545.7165	12.52	22.36	34.88	46.00	-11.12	peak			
5		623.3166	7.90	23.25	31.15	46.00	-14.85	peak			
6		841.5666	1.75	27.31	29.06	46.00	-16.94	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		115.6833	29.09	6.86	35.95	43.50	-7.55	peak			
2	*	148.0166	25.91	13.25	39.16	43.50	-4.34	peak			
3		199.7500	25.37	11.99	37.36	43.50	-6.14	peak			
4		390.5167	13.83	19.01	32.84	46.00	-13.16	peak			
5		468.1166	11.12	20.79	31.91	46.00	-14.09	peak			
6		848.0333	3.23	27.31	30.54	46.00	-15.46	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		139.9333	21.46	15.17	36.63	43.50	-6.87	peak			
2	*	152.8667	24.07	15.28	39.35	43.50	-4.15	peak			
3		199.7500	28.32	9.06	37.38	43.50	-6.12	peak			
4		545.7165	11.38	22.36	33.74	46.00	-12.26	peak			
5		623.3166	11.94	23.25	35.19	46.00	-10.81	peak			
6		941.7999	3.28	29.77	33.05	46.00	-12.95	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.


FOR BLE

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth Speaker
M/N: H3
Mode: Low Channel TX
Note:


Polarization: **Horizontal**
Power:
Distance:

Temperature: 24.5
Humidity: 52.6 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		101.1333	24.32	10.22	34.54	43.50	-8.96	peak			
2	*	144.7832	24.93	14.04	38.97	43.50	-4.53	peak			
3	!	196.5166	27.08	11.84	38.92	43.50	-4.58	peak			
4		592.6000	1.00	23.55	24.55	46.00	-21.45	peak			
5		799.5333	2.07	27.31	29.38	46.00	-16.62	peak			
6		953.1167	1.66	29.97	31.63	46.00	-14.37	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: Low Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		123.7667	27.16	8.43	35.59	43.50	-7.91	peak			
2	*	149.6331	23.38	15.26	38.64	43.50	-4.86	peak			
3	!	199.7500	28.80	9.06	37.86	43.50	-5.64	peak			
4		348.4832	1.49	18.64	20.13	46.00	-25.87	peak			
5		555.4166	1.48	22.51	23.99	46.00	-22.01	peak			
6		768.8166	-0.28	26.89	26.61	46.00	-19.39	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		101.1333	23.75	10.22	33.97	43.50	-9.53	peak			
2	!	146.4000	24.24	13.64	37.88	43.50	-5.62	peak			
3	*	198.1331	26.84	11.91	38.75	43.50	-4.75	peak			
4		401.8333	2.85	19.13	21.98	46.00	-24.02	peak			
5		791.4500	0.18	27.20	27.38	46.00	-18.62	peak			
6		959.5833	0.76	29.91	30.67	46.00	-15.33	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		117.2998	26.38	5.52	31.90	43.50	-11.60	peak			
2	*	151.2500	25.29	15.27	40.56	43.50	-2.94	peak			
3		199.7500	27.39	9.06	36.45	43.50	-7.05	peak			
4		493.9832	9.66	21.06	30.72	46.00	-15.28	peak			
5		545.7164	10.52	22.36	32.88	46.00	-13.12	peak			
6		812.4664	1.49	27.32	28.81	46.00	-17.19	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		115.6833	29.59	6.86	36.45	43.50	-7.05	peak			
2	*	138.3165	23.92	14.41	38.33	43.50	-5.17	peak			
3		199.7500	25.37	11.99	37.36	43.50	-6.14	peak			
4		390.5167	13.83	19.01	32.84	46.00	-13.16	peak			
5		442.2500	11.20	20.35	31.55	46.00	-14.45	peak			
6		848.0333	3.23	27.31	30.54	46.00	-15.46	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 24.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 52.6 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	139.9333	22.96	15.17	38.13	43.50	-5.37	peak			
2	*	154.4833	23.63	15.29	38.92	43.50	-4.58	peak			
3	!	199.7500	29.82	9.06	38.88	43.50	-4.62	peak			
4		493.9832	7.89	21.06	28.95	46.00	-17.05	peak			
5		545.7164	9.88	22.36	32.24	46.00	-13.76	peak			
6		623.3165	10.44	23.25	33.69	46.00	-12.31	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.


2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ

(Worst modulation: GFSK)

FOR BR/EDR

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: Bluetooth Speaker Distance: 3m
M/N: H3
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.24	-9.68	94.56	114.00	-19.44	peak			
2	*	2402.000	90.91	-9.68	81.23	94.00	-12.77	AVG	100	155	
3		3658.333	53.50	-6.91	46.59	74.00	-27.41	peak			
4		5000.000	46.99	-1.80	45.19	74.00	-28.81	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.18	-9.68	94.50	114.00	-19.50	peak			
2	*	2402.000	89.79	-9.68	80.11	94.00	-13.89	AVG	100	192	
3		3416.667	54.67	-7.97	46.70	74.00	-27.30	peak			
4		4216.667	50.37	-4.07	46.30	74.00	-27.70	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth Speaker
M/N: H3
Mode: Middle Channel TX
Note:


Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	103.84	-9.63	94.21	114.00	-19.79	peak			
2	*	2441.000	90.84	-9.63	81.21	94.00	-12.79	AVG	100	163	
3		2941.667	55.07	-8.50	46.57	74.00	-27.43	peak			
4		5075.000	47.62	-1.80	45.82	74.00	-28.18	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	104.21	-9.63	94.58	114.00	-19.42	peak			
2	*	2441.000	91.40	-9.63	81.77	94.00	-12.23	AVG	100	213	
3		3383.333	55.19	-8.00	47.19	74.00	-26.81	peak			
4		4316.667	50.51	-3.73	46.78	74.00	-27.22	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	103.34	-9.59	93.75	114.00	-20.25	peak			
2	*	2480.000	89.75	-9.59	80.16	94.00	-13.84	AVG	100	162	
3		2783.333	56.33	-8.88	47.45	74.00	-26.55	peak			
4		4250.000	51.65	-3.96	47.69	74.00	-26.31	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	102.91	-9.59	93.32	114.00	-20.68	peak			
2	*	2480.000	90.02	-9.59	80.43	94.00	-13.57	AVG	100	235	
3		2733.333	55.95	-9.01	46.94	74.00	-27.06	peak			
4		4516.667	49.61	-3.07	46.54	74.00	-27.46	peak			

RESULT: PASS**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	104.24	-9.68	94.56	114	-19.44	Horizontal
2402	104.18	-9.68	94.50	114	-19.50	Vertical
2441	103.84	-9.63	94.21	114	-19.79	Horizontal
2441	104.21	-9.63	94.58	114	-19.42	Vertical
2480	103.34	-9.59	93.75	114	-20.25	Horizontal
2480	102.91	-9.59	93.32	114	-20.68	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	90.91	-9.68	81.23	94	-12.77	Horizontal
2402	89.79	-9.68	80.11	94	-13.89	Vertical
2441	90.84	-9.63	81.21	94	-12.79	Horizontal
2441	91.40	-9.63	81.77	94	-12.23	Vertical
2480	89.75	-9.59	80.16	94	-13.84	Horizontal
2480	90.02	-9.59	80.43	94	-13.57	Vertical

2Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	103.91	-9.68	94.23	114	-19.77	Horizontal
2402	103.87	-9.68	94.19	114	-19.81	Vertical
2441	103.94	-9.68	94.26	114	-19.74	Horizontal
2441	103.89	-9.68	94.21	114	-19.79	Vertical
2480	103.20	-9.63	93.57	114	-20.43	Horizontal
2480	103.15	-9.63	93.52	114	-20.48	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	90.69	-9.63	81.06	94	-12.94	Horizontal
2402	90.66	-9.63	81.03	94	-12.97	Vertical
2441	90.69	-9.59	81.10	94	-12.90	Horizontal
2441	90.64	-9.59	81.05	94	-12.95	Vertical
2480	89.48	-9.59	79.89	94	-14.11	Horizontal
2480	89.44	-9.59	79.85	94	-14.15	Vertical

3Mbps Result:

Peak value


Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	103.79	-9.68	94.11	114	-19.89	Horizontal
2402	103.73	-9.68	94.05	114	-19.95	Vertical
2441	103.83	-9.68	94.15	114	-19.85	Horizontal
2441	103.76	-9.68	94.08	114	-19.92	Vertical
2480	103.09	-9.63	93.46	114	-20.54	Horizontal
2480	103.02	-9.63	93.39	114	-20.61	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	90.60	-9.63	80.97	94	-13.03	Horizontal
2402	90.56	-9.63	80.93	94	-13.07	Vertical
2441	90.60	-9.59	81.01	94	-12.99	Horizontal
2441	90.56	-9.59	80.97	94	-13.03	Vertical
2480	89.37	-9.59	79.78	94	-14.22	Horizontal
2480	89.31	-9.59	79.72	94	-14.28	Vertical

FOR BLE

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: Bluetooth Speaker Distance: 3m
M/N: H3
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.26	-9.68	94.58	114.00	-19.42	peak			
2	*	2402.000	91.15	-9.68	81.47	94.00	-12.53	AVG	100	142	
3		3650.000	52.86	-6.97	45.89	74.00	-28.11	peak			
4		4850.000	48.18	-2.19	45.99	74.00	-28.01	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	104.69	-9.68	95.01	114.00	-18.99	peak			
2	*	2402.000	91.89	-9.68	82.21	94.00	-11.79	AVG	100	197	
3		2875.000	54.68	-8.66	46.02	74.00	-27.98	peak			
4		5050.000	47.25	-1.80	45.45	74.00	-28.55	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	104.34	-9.64	94.70	114.00	-19.30	peak			
2	*	2440.000	91.61	-9.64	81.97	94.00	-12.03	AVG	100	159	
3		3375.000	54.59	-8.01	46.58	74.00	-27.42	peak			
4		4625.000	48.47	-2.78	45.69	74.00	-28.31	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	104.27	-9.64	94.63	114.00	-19.37	peak			
2	*	2440.000	91.09	-9.64	81.45	94.00	-12.55	AVG	100	178	
3		3500.000	54.24	-7.89	46.35	74.00	-27.65	peak			
4		4525.000	49.12	-3.04	46.08	74.00	-27.92	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	102.90	-9.59	93.31	114.00	-20.69	peak			
2	*	2480.000	90.47	-9.59	80.88	94.00	-13.12	AVG	100	162	
3		3608.333	54.22	-7.22	47.00	74.00	-27.00	peak			
4		5625.000	49.12	-1.75	47.37	74.00	-26.63	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance: 3m

M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	103.32	-9.59	93.73	114.00	-20.27	peak			
2	*	2480.000	89.83	-9.59	80.24	94.00	-13.76	AVG	100	193	
3		3150.000	55.39	-8.22	47.17	74.00	-26.83	peak			
4		3933.333	52.07	-5.22	46.85	74.00	-27.15	peak			

RESULT: PASS**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	104.26	-9.68	94.58	114.00	-19.42	Horizontal
2402	104.69	-9.68	95.01	114.00	-18.99	Vertical
2440	104.34	-9.63	94.70	114.00	-19.30	Horizontal
2440	104.27	-9.63	94.63	114.00	-19.37	Vertical
2480	102.90	-9.59	93.31	114.00	-20.69	Horizontal
2480	103.32	-9.59	93.73	114.00	-20.27	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	91.15	-9.68	81.47	94.00	-12.53	Horizontal
2402	91.89	-9.68	82.21	94.00	-11.79	Vertical
2440	91.61	-9.63	81.97	94.00	-12.03	Horizontal
2440	91.09	-9.63	81.45	94.00	-12.55	Vertical
2480	90.47	-9.59	80.88	94.00	-13.12	Horizontal
2480	89.83	-9.59	80.24	94.00	-13.76	Vertical


9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE

- 1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




9.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:


M/N: H3

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2316.850	33.37	10.23	43.60	74.00	-30.40	peak			
2		2390.000	34.62	10.31	44.93	74.00	-29.07	peak			
3	*	2402.000	84.41	10.32	94.73	74.00	20.73	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:


M/N: H3

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2264.233	33.13	10.17	43.30	74.00	-30.70	peak			
2		2390.000	33.84	10.31	44.15	74.00	-29.85	peak			
3	*	2402.000	84.26	10.32	94.58	74.00	20.58	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:


M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	83.46	10.41	93.87	74.00	19.87	peak			
2		2483.500	32.75	10.41	43.16	74.00	-30.84	peak			
3		2487.497	31.94	10.42	42.36	74.00	-31.64	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26
 Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
 EUT: Bluetooth Speaker Distance:
 M/N: H3
 Mode: High Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	82.85	10.41	93.26	74.00	19.26	peak			
2		2483.500	31.37	10.41	41.78	74.00	-32.22	peak			
3		2492.373	33.06	10.42	43.48	74.00	-30.52	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.


Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

FOR BLE

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:


M/N: H3

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2287.125	32.43	10.20	42.63	74.00	-31.37	peak			
2		2390.000	33.12	10.31	43.43	74.00	-30.57	peak			
3	*	2402.000	83.91	10.32	94.23	74.00	20.23	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:


M/N: H3

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2258.425	31.37	10.16	41.53	74.00	-32.47	peak			
2		2390.000	32.34	10.31	42.65	74.00	-31.35	peak			
3	*	2402.000	83.76	10.32	94.08	74.00	20.08	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:


M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	82.46	10.41	92.87	74.00	18.87	peak			
2		2483.500	31.75	10.41	42.16	74.00	-31.84	peak			
3		2489.403	32.24	10.42	42.66	74.00	-31.34	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: Bluetooth Speaker

Distance:

M/N: H3

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	82.85	10.41	93.26	74.00	19.26	peak			
2		2483.500	32.37	10.41	42.78	74.00	-31.22	peak			
3		2491.787	32.86	10.42	43.28	74.00	-30.72	peak			

RESULT: PASS**Note:** The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

10.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	0.989	1.124	PASS
	Middle Channel	0.988	1.114	PASS
	High Channel	0.988	1.120	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.212	1.377	PASS
	Middle Channel	1.211	1.365	PASS
	High Channel	1.211	1.376	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




C

BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.226	1.383	PASS
	Middle Channel	1.221	1.368	PASS
	High Channel	1.211	1.366	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



FOR BLE


BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.094	1.205	PASS
	Middle Channel	1.092	1.199	PASS
	High Channel	1.089	1.202	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




b

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

By adapter(worst case)

FOR BR/EDR

Line Conducted Emission Test Line 1-L



Site: Conduction

Phase: L1

Temperature: 22.1

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 53.4 %

EUT: Bluetooth Speaker


M/N: H3

Mode: BT Link with charging

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1900	36.72		20.09	10.20	46.92		30.29	64.03	54.03	-17.11	-23.74	P	
2	0.2500	32.74		14.49	10.27	43.01		24.76	61.75	51.75	-18.74	-26.99	P	
3	0.4140	32.49		15.86	10.34	42.83		26.20	57.57	47.57	-14.74	-21.37	P	
4	1.1380	27.91		15.69	10.37	38.28		26.06	56.00	46.00	-17.72	-19.94	P	
5	2.9420	30.22		17.85	10.54	40.76		28.39	56.00	46.00	-15.24	-17.61	P	
6	15.3739	28.13		13.14	10.12	38.25		23.26	60.00	50.00	-21.75	-26.74	P	

Line Conducted Emission Test Line 2-N



Site: Conduction

Phase: **N**

Temperature: 22.1

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 53.4 %

EUT: Bluetooth Speaker

M/N: H3


Mode: BT Link with charging

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4580	31.84		16.72	10.37	42.21		27.09	56.73	46.73	-14.52	-19.64	P	
2	1.5859	29.47		16.41	10.35	39.82		26.76	56.00	46.00	-16.18	-19.24	P	
3	2.2540	27.41		13.08	10.33	37.74		23.41	56.00	46.00	-18.26	-22.59	P	
4	4.0699	25.18		16.57	10.40	35.58		26.97	56.00	46.00	-20.42	-19.03	P	
5	6.9419	19.97		7.60	10.35	30.32		17.95	60.00	50.00	-29.68	-32.05	P	
6	15.7499	25.45		14.31	10.11	35.56		24.42	60.00	50.00	-24.44	-25.58	P	

FOR BLE

Line Conducted Emission Test Line 1-L



Site: Conduction

Phase: L1

Temperature: 22.1

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 53.4 %

EUT: Bluetooth Speaker


M/N: H3

Mode: BT Link with charging

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1940	38.09		20.87	10.21	48.30		31.08	63.86	53.86	-15.56	-22.78	P	
2	0.3980	32.16		16.37	10.33	42.49		26.70	57.89	47.89	-15.40	-21.19	P	
3	0.5180	32.21		7.80	10.38	42.59		18.18	56.00	46.00	-13.41	-27.82	P	
4	1.1260	28.15		14.42	10.37	38.52		24.79	56.00	46.00	-17.48	-21.21	P	
5	2.8820	29.73		16.95	10.52	40.25		27.47	56.00	46.00	-15.75	-18.53	P	
6	15.8539	29.12		13.29	10.11	39.23		23.40	60.00	50.00	-20.77	-26.60	P	

Line Conducted Emission Test Line 2-N



Site: Conduction Phase: **N** Temperature: 22.1
Limit: FCC Class B Conduction(QP) Power: Humidity: 53.4 %
EUT: Bluetooth Speaker
M/N: H3
Mode: BT Link with charging
Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2740	36.81		20.92	10.28	47.09		31.20	60.99	50.99	-13.90	-19.79	P	
2	0.4580	35.17		18.05	10.37	45.54		28.42	56.73	46.73	-11.19	-18.31	P	
3	1.4740	30.69		14.53	10.38	41.07		24.91	56.00	46.00	-14.93	-21.09	P	
4	4.1379	25.52		13.50	10.37	35.89		23.87	56.00	46.00	-20.11	-22.13	P	
5	12.0699	20.67		6.24	10.14	30.81		16.38	60.00	50.00	-29.19	-33.62	P	
6	15.9219	27.03		14.14	10.11	37.14		24.25	60.00	50.00	-22.86	-25.75	P	



APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP









APPENDIX B: PHOTOGRAPHS OF EUT


TOP VIEW OF EUT




BOTTOM VIEW OF EUT




FRONT VIEW OF EUT




BACK VIEW OF EUT



LEFT VIEW OF EUT




RIGHT VIEW OF EUT




VIEW OF EUT (PORT)




OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4




INTERNAL VIEW OF EUT-5




INTERNAL VIEW OF EUT-6



INTERNAL VIEW OF EUT-7



INTERNAL VIEW OF EUT-8



VIEW OF ADAPTER (AE)



THE ADAPTER SUPPLIED BY AGC

----END OF REPORT----