

RF Exposure Report

Report No.: SA141229E04E R1

FCC ID: Q87-WRT1200AC

Test Model: WRT1200AC

Series Model: WRT1200AC V2

Received Date: Mar. 25, 2016

Test Date: Mar. 25 ~ May 11, 2016

Issued Date: Jun. 14, 2016

Applicant: Linksys LLC

Address: 121 Theory Drive Irvine California 92617 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Report Issue History Record	3
Release Control Record	4
1 Certificate of Conformity.....	5
2 RF Exposure.....	6
2.1 Limits for Maximum Permissible Exposure (MPE).....	6
2.2 MPE Calculation Formula	6
2.3 Classification	6
3 Antenna Gain.....	6
4 Calculation Result Of Maximum Conducted Power.....	7

Report Issue History Record

Issue No.	Reason for Change	Date Issued
SA141229E04	Original release.	Mar. 13, 2015
SA141229E04D	1. Upgrade the standard to section 15.407 under new rule for U-NII-3 band. 2. Removed the original adapter "Model : MU30-5120250-A1 and MU30-P120250-A1" 3. Added one Model No.: WRT1200ACV2	May 04, 2016
SA141229E04E	Upgrade the standard to section 15.407 under new rule (16-24) for U-NII-3 band.	May 19, 2016
SA141229E04E R1	Modified the series model from WRT1200ACV2 to WRT1200AC V2.	Jun. 14, 2016

Release Control Record

Issue No.	Description	Date Issued
SA141229E04E	Original release	May 19, 2016
SA141229E04E R1	Modified the series model from WRT1200ACV2 to WRT1200AC V2.	Jun. 14, 2016

1 Certificate of Conformity

Product: 802.11ac Router

Brand: Linksys

Test Model: WRT1200AC

Series Model: WRT1200AC V2

Sample Status: Engineering sample

Applicant: Linksys LLC

Test Date: Mar. 25 ~ May 11, 2016

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 (October 23, 2015)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , Date: Jun. 14, 2016
Polly Chien / Specialist

Approved by :  , Date: Jun. 14, 2016
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 22cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Brand	Gain (dBi)	Cable Loss (dB)	Net Gain (dBi)	Frequency Range (GHz to GHz)	Antenna Type	Connector Type
Chain (0)	LINKSYS	2.5	1	1.5	2.4 ~ 2.4835	DIPOLE	R-SMA
		2.6	1.6	1	5.15 ~ 5.25		
		3.8	1.9	1.9	5.725 ~ 5.85		
Chain (1)	LINKSYS	2.5	1	1.5	2.4 ~ 2.4835	DIPOLE	R-SMA
		2.6	1.5	1.1	5.15 ~ 5.25		
		3.8	2.1	1.7	5.725 ~ 5.85		

4 Calculation Result Of Maximum Conducted Power

For WLAN (2.4GHz) & WLAN (5GHz - U-NII-1) data was copied from the original test report (Report No.: SA141229E04).

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	938.114	4.51	22	0.43571	1
5180-5240	928.803	4.06	22	0.38893	1
5745-5825	961.541	4.81	22	0.47853	1

Note:

2.4GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.51\text{dBi}$

5GHz (5180-5240MHz): Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.06\text{dBi}$

5GHz (5745-5825MHz): Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.81\text{dBi}$

Conclusion:

Both of the WLAN 2.4G & WLAN 5G can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = $0.43571/1 + 0.47853/1 = 0.91424$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---