

FCC Test Report

Applicant : Shenzhen Royal Gold Shield Intelligent Technology Co., Ltd.

Address : No. 301, Building A, Dawo 2nd Road,
Longtian Street, Pingshan District, Shenzhen,
Guangdong, China

Product Name : Smart lock

Report Date : Nov. 27, 2024

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Configuration	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
1.9. Disclaimer	10
2. Summary of Test Results	11
3. Conducted Emission Test	12
3.1. Test Standard and Limit	12
3.2. Test Setup	12
3.3. Test Procedure	12
3.4. Test Data	12
4. Radiation Spurious Emission and Band Edge	15
4.1. Test Standard and Limit	15
4.2. Test Setup	16
4.3. Test Procedure	17
4.4. Test Data	17
5. Frequency Tolerance	23
5.1. Test Requirement	23
5.2. Test Setup	23
5.3. Test Procedure	23
5.4. Test Data	23
6. 20DB Occupy Bandwidth Test	24
6.1. Test Standard and Limit	24
6.2. Test Setup	24
6.3. Test Procedure	24
6.4. Test Data	25
7. Antenna Requirement	26
7.1. Test Standard and Requirement	26
7.2. Antenna Connected Construction	26
APPENDIX I -- TEST SETUP PHOTOGRAPH	27
APPENDIX II -- EXTERNAL PHOTOGRAPH	27
APPENDIX III -- INTERNAL PHOTOGRAPH	27



TEST REPORT

Applicant : Shenzhen Royal Gold Shield Intelligent Technology Co., Ltd.
Manufacturer : Shenzhen Royal Gold Shield Intelligent Technology Co., Ltd.
Product Name : Smart lock
Model No. : G1
Trade Mark : DEVO
Rating(s) : Input: 5V $\overline{\text{--}}$ 2A (with DC 3.7V, 10000mAh battery inside)

Test Standard(s) : 47 CFR Part 15.225

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15.225 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Nov. 06, 2024

Date of Test

Nov. 06, 2024 to Nov. 22, 2024

Prepared By

Cecilia Chen

(Cecilia Chen)

Approved & Authorized Signer

KingKong Jin

(KingKong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Nov. 27, 2024



1. General Information

1.1. Client Information

Applicant	:	Shenzhen Royal Gold Shield Intelligent Technology Co., Ltd.
Address	:	No. 301, Building A, Dawo 2nd Road, Longtian Street, Pingshan District, Shenzhen, Guangdong, China
Manufacturer	:	Shenzhen Royal Gold Shield Intelligent Technology Co., Ltd.
Address	:	No. 301, Building A, Dawo 2nd Road, Longtian Street, Pingshan District, Shenzhen, Guangdong, China
Factory	:	Shenzhen Royal Gold Shield Intelligent Technology Co., Ltd.
Address	:	No. 301, Building A, Dawo 2nd Road, Longtian Street, Pingshan District, Shenzhen, Guangdong, China

1.2. Description of Device (EUT)

Product Name	:	Smart lock
Model No.	:	G1
Trade Mark	:	DEVO
Test Power Supply	:	DC 5V from adapter input AC 120V/60Hz; DC 3.7V Battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Frequency	:	13.56MHz
Number of Channel	:	1 Channel
Modulation Type	:	ASK
Antenna Type	:	FPCB Antenna
Antenna Gain(Peak)	:	0.3dBi
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/



1.4. Description of Test Configuration

The engineering test program was provided and the EUT was programmed to be in transmitting mode.

Channel	Freq.(MHz)
01	13.56



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Jan. 18, 2024	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT00 1	Jan. 17, 2024	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jan. 17, 2024	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Jan. 23, 2024	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Sept. 09, 2024	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-002	Jan. 17, 2024	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Sept. 12, 2024	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Jan. 22, 2024	3 Year
11.	Pre-amplifier	SONOMA	310N	186860	Jan. 17, 2024	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Sept. 09, 2024	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Feb. 04, 2024	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 10, 2024	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Sept. 09, 2024	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 14, 2024	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	May. 06, 2024	1 Year



1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Frequency tolerance	74.60Hz
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.



1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209/15.225	Spurious Emission	PASS
15.215(c)	20dB Occupied Bandwidth	PASS
15.225(e)	Frequency Tolerance	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 13.56MHz
Test Specification: DC 5V from adapter input AC 120V/60Hz
Comment: Live Line
Temp.(°C)/Hum.(%RH): 23.9°C/50%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	35.89	17.82	53.71	65.99	-12.28	QP	
2	0.1660	36.58	17.83	54.41	65.15	-10.74	QP	
3	0.1700	20.58	17.83	38.41	54.96	-16.55	AVG	
4	0.4860	21.39	17.84	39.23	56.24	-17.01	QP	
5	0.4860	12.17	17.84	30.01	46.24	-16.23	AVG	
6	0.6340	23.28	17.86	41.14	56.00	-14.86	QP	
7	0.7780	13.41	17.86	31.27	46.00	-14.73	AVG	
8	1.2140	23.96	17.84	41.80	56.00	-14.20	QP	
9	1.2700	13.30	17.84	31.14	46.00	-14.86	AVG	
10	1.5859	10.22	17.84	28.06	46.00	-17.94	AVG	
11	1.5980	19.65	17.84	37.49	56.00	-18.51	QP	
12	1.9380	8.14	17.83	25.97	46.00	-20.03	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 13.56MHz
Test Specification: DC 5V from adapter input AC 120V/60Hz
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 23.9°C/50%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	35.39	17.83	53.22	65.78	-12.56	QP	
2	0.1660	35.48	17.83	53.31	65.15	-11.84	QP	
3	0.1780	34.06	17.83	51.89	64.57	-12.68	QP	
4	0.1860	17.56	17.83	35.39	54.21	-18.82	AVG	
5	0.4980	21.80	17.85	39.65	56.03	-16.38	QP	
6	0.7780	13.74	17.86	31.60	46.00	-14.40	AVG	
7	1.1260	23.17	17.85	41.02	56.00	-14.98	QP	
8	1.3779	13.23	17.84	31.07	46.00	-14.93	AVG	
9	1.7380	20.58	17.84	38.42	56.00	-17.58	QP	
10	1.7660	9.13	17.84	26.97	46.00	-19.03	AVG	
11	2.0900	7.43	17.83	25.26	46.00	-20.74	AVG	
12	3.1980	2.92	17.84	20.76	46.00	-25.24	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.205, 15.209 and 15.225				
	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
Test Limit	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

Note:

(1) The tighter limit shall apply at the boundary between two frequency range.

(2) Limitation expressed in dBuV/m is calculated by $20\log$ Emission Level (uV/m).

(3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30uV/m * (10)^2 = 100 * 30 uV/m$$



4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz



4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (coplane, coaxial), and found the coplane is the worst case.



Test Results (9KHz~0.15MHz)

Test Mode:

13.56MHz

Power Source:


DC 3.7V Battery inside

Polarization:

Coplane

Temp.(°C)/Hum.(%RH):

25.1°C/51%RH



Test Results (0.15MHz~30MHz)

Test Mode:

13.56MHz

Power Source:

DC 3.7V Battery inside


Polarization:

Coplaner

Temp.(°C)/Hum.(%RH):


25.1°C/51%RH

Fundamental



Test Results (30~1000MHz)

Test Mode: 13.56MHz
Power Source: DC 3.7V Battery inside
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 25.1°C/51%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	443.2943	55.50	-14.59	40.91	46.00	-5.09	QP			
2	303.5437	53.35	-17.13	36.22	46.00	-9.78	QP			
3	151.5972	62.47	-22.61	39.86	43.50	-3.64	QP			
4	49.0145	32.91	-14.96	17.95	40.00	-22.05	QP			
5	210.7860	49.06	-19.60	29.46	43.50	-14.04	QP			
6	364.2595	49.74	-15.91	33.83	46.00	-12.17	QP			



Test Results (30~1000MHz)

Test Mode: 13.56MHz
Power Source: DC 3.7V Battery inside
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 25.1°C/51%RH



Test Results (Inband)

Indicated			Table Angle Degree	Antenna Height (m)	Detector	Correction Factor			Corrected Amplitude (dBuV/m) @3m	FCC part 15.225	
Frequency Range (MHz)	Mark Point (MHz)	Corrected Amplitude (dBuV/m) @3m				Ant. Factor (dB)	Cable Loss (dB)	Pre- Amp. Gain (dB)		Limit (dBuV/m) @3m	Result
13.110~13.410	13.387	40.26	0	1.0	QP	20.8	0.2	30.2	31.06	80.5	PASS
13.410~13.553	13.546	42.07	0	1.0	QP	20.9	0.2	30.2	32.97	90.5	PASS
13.553~13.567	13.557	41.76	0	1.0	QP	20.9	0.2	30.2	32.66	124	PASS
13.567~13.710	13.573	40.17	0	1.0	QP	21.1	0.2	30.2	31.27	90.5	PASS
13.710~14.010	13.891	42.00	0	1.0	QP	21.2	0.2	30.2	33.20	80.5	PASS




5. Frequency Tolerance

5.1. Test Requirement

Test Standard	FCC Part15 C Section 15.225(e)
Test Limit	±0.01% (100ppm)

5.2. Test Setup



5.3. Test Procedure

Let the EUT works on temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.4. Test Data

Temperature:	24.4 ° C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	----------	-----------	------	-----------------------	---------

Voltage (VDC)	Temperature (°C)	Frequency Measured (MHz)	Test data (ppm)	Limit (ppm)	Verdict
3.70	-20	13.560823	60.70	±100	PASS
	-10	13.560749	55.26	±100	PASS
	0	13.560658	48.51	±100	PASS
	+10	13.560693	51.14	±100	PASS
	+20	13.560762	56.17	±100	PASS
	+30	13.560752	55.45	±100	PASS
	+40	13.560714	52.64	±100	PASS
	+50	13.560723	53.29	±100	PASS
3.15	+20	13.560826	60.90	±100	PASS
4.26	+20	13.560784	57.82	±100	PASS




6. 20dB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.215(c)
Test Limit	N/A

6.2. Test Setup



6.3. Test Procedure


The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300Hz RBW and VBW \geq 3*RBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.



6.4. Test Data

Temperature:	24.4 ° C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
--------------	----------	-----------	------	-----------------------	---------

Freq.(MHz)	Bandwidth (kHz)	Results
13.56	0.81	PASS



7. Antenna Requirement

7.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

7.2. Antenna Connected Construction

The antenna is a FPCB Antenna which permanently attached. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

