

EMC TEST REPORT



Report No.: 17071343-FCC-E

Supersede Report No: N/A

Applicant	BLU Products, Inc.	
Product Name	Mobile Phone	
Model No.	STUDIO VIEW MEGA	
Serial No.	N/A	
Test Standard	FCC Part 15 Subpart B Class B:2016, ANSI C63.4: 2014	
Test Date	December 21, 2017 to March 06, 2018	
Issue Date	March 07, 2018	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
<i>Evans He</i>	<i>David Huang</i>	
Evans He Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17071343-FCC-E
Page	3 of 37

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 AC POWER LINE CONDUCTED EMISSIONS.....	9
6.2 RADIATED EMISSIONS.....	15
ANNEX A. TEST INSTRUMENT.....	20
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	21
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	33
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	36
ANNEX E. DECLARATION OF SIMILARITY	37

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17071343-FCC-E	NONE	Original	March 07, 2018

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	STUDIO VIEW MEGA
Serial Model:	N/A
Antenna Gain:	GSM850: -3.8dBi PCS1900: -2.4dBi UMTS-FDD Band V: -3.8dBi UMTS-FDD Band IV: -2.3dBi UMTS-FDD Band II: -2.7dBi WIFI: -3.6dBi Bluetooth/BLE: -3.3dBi GPS: -3.3dBi
Antenna Type:	PIFA antenna
Input Power:	Adapter: Model: TPA-46050200UU Input: AC100-240V~50/60Hz,0.3A Output: DC 5V, 2A Battery Model: C876440350P Voltage: 3.8V, 13.3Wh Battery Capacity: 3500mAh
Equipment Category :	JBP
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
	RX: 1932.4 ~ 1987.6 MHz
RF Operating Frequency (ies):	UMTS-FDD Band IV TX: 1712.4 ~ 1752.6 MHz;
	RX : 2112.4 ~ 2152.6 MHz
	WIFI: 802.11b/g/n(20M): 2412-2462 MHz
	WIFI: 802.11n(40M): 2422-2452 MHz
	Bluetooth& BLE: 2402-2480 MHz
	GPS: 1575.42 MHz
	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band IV: 202CH
	UMTS-FDD Band II: 277CH
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
	GPS:1CH
Port:	USB Port, Earphone Port
Trade Name :	BLU
FCC ID:	YHLBLUSTVIEWMG
Date EUT received:	December 20, 2017
Test Date(s):	December 21, 2017 to March 06, 2018

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2014	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2014	Radiated Emissions	Compliance

Measurement Uncertainty


Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	±3.11dB
Radiated Emission(30MHz~1GHz)	±5.12dB
Radiated Emission(1GHz~6GHz)	±5.34dB


6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	December 28, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.107	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.			
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			

Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	---

Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50Ω /50mH EUT LISN, connected to filtered mains.
-----------	--

	3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode 1:	USB Mode
--------------	----------


Test Mode 2:	MP4 Mode
--------------	----------

Test Mode 3:	Camera Mode
--------------	-------------

Test Mode 4:	FM Mode
--------------	---------

Note: All modes were investigated, the results below show only the worst case(USB mode).

Test Mode 1:	USB Mode
---------------------	-----------------




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1539	35.53	QP	10.03	45.56	65.79	-20.23
2	L1	0.1539	18.06	AVG	10.03	28.09	55.79	-27.70
3	L1	0.4074	32.15	QP	10.03	42.18	57.70	-15.52
4	L1	0.4074	21.59	AVG	10.03	31.62	47.70	-16.08
5	L1	0.7194	30.50	QP	10.03	40.53	56.00	-15.47
6	L1	0.7194	14.07	AVG	10.03	24.10	46.00	-21.90
7	L1	1.7412	30.04	QP	10.04	40.08	56.00	-15.92
8	L1	1.7412	11.48	AVG	10.04	21.52	46.00	-24.48
9	L1	2.6109	33.87	QP	10.05	43.92	56.00	-12.08
10	L1	2.6109	14.62	AVG	10.05	24.67	46.00	-21.33
11	L1	17.2428	30.61	QP	10.26	40.87	60.00	-19.13
12	L1	17.2428	19.79	AVG	10.26	30.05	50.00	-19.95

Test Mode 1: USB Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1929	30.23	QP	10.02	40.25	63.91	-23.66
2	N	0.1929	23.10	AVG	10.02	33.12	53.91	-20.79
3	N	0.3411	34.68	QP	10.02	44.70	59.18	-14.48
4	N	0.3411	24.78	AVG	10.02	34.80	49.18	-14.38
5	N	0.4308	39.03	QP	10.02	49.05	57.24	-8.19
6	N	0.4308	28.13	AVG	10.02	38.15	47.24	-9.09
7	N	0.9339	34.79	QP	10.03	44.82	56.00	-11.18
8	N	0.9339	16.89	AVG	10.03	26.92	46.00	-19.08
9	N	2.5290	31.42	QP	10.05	41.47	56.00	-14.53
10	N	2.5290	18.35	AVG	10.05	28.40	46.00	-17.60
11	N	17.6133	33.23	QP	10.23	43.46	60.00	-16.54
12	N	17.6133	22.69	AVG	10.23	32.92	50.00	-17.08

Test Mode 1:	USB Mode
---------------------	-----------------




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1617	41.78	QP	10.03	51.81	65.38	-13.57
2	L1	0.1617	29.28	AVG	10.03	39.31	55.38	-16.07
3	L1	0.3138	41.73	QP	10.03	51.76	59.87	-8.11
4	L1	0.3138	30.78	AVG	10.03	40.81	49.87	-9.06
5	L1	0.7545	37.85	QP	10.03	47.88	56.00	-8.12
6	L1	0.7545	23.07	AVG	10.03	33.10	46.00	-12.90
7	L1	1.7412	38.82	QP	10.04	48.86	56.00	-7.14
8	L1	1.7412	20.90	AVG	10.04	30.94	46.00	-15.06
9	L1	2.7591	35.62	QP	10.05	45.67	56.00	-10.33
10	L1	2.7591	18.51	AVG	10.05	28.56	46.00	-17.44
11	L1	14.2086	30.37	QP	10.21	40.58	60.00	-19.42
12	L1	14.2086	17.75	AVG	10.21	27.96	50.00	-22.04

Test Mode 1:	USB Mode
---------------------	-----------------



Test Data


Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.2280	35.27	QP	10.02	45.29	62.52	-17.23
2	N	0.2280	24.58	AVG	10.02	34.60	52.52	-17.92
3	N	0.4152	35.96	QP	10.02	45.98	57.54	-11.56
4	N	0.4152	21.12	AVG	10.02	31.14	47.54	-16.40
5	N	0.7389	34.34	QP	10.02	44.36	56.00	-11.64
6	N	0.7389	17.26	AVG	10.02	27.28	46.00	-18.72
7	N	2.1741	30.28	QP	10.04	40.32	56.00	-15.68
8	N	2.1741	15.36	AVG	10.04	25.40	46.00	-20.60
9	N	3.7956	28.84	QP	10.06	38.90	56.00	-17.10
10	N	3.7956	13.80	AVG	10.06	23.86	46.00	-22.14
11	N	15.7023	32.88	QP	10.21	43.09	60.00	-16.91
12	N	15.7023	16.08	AVG	10.21	26.29	50.00	-23.71

6.2 Radiated Emissions

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	December 28, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.109(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges		
		Frequency range (MHz)		Field Strength (µV/m)
		30 – 88		100
		88 – 216		150
		216 - 960		200
		Above 960		500

Test Setup	
------------	--

Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarization (whichever gave the higher emission level
-----------	--

	<p>over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>■ 1 kHz (Duty cycle < 98%) □ 10 Hz (Duty cycle > 98%)</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode 1:	USB Mode
--------------	----------

Test Mode 2:	MP4 Mode
--------------	----------


Test Mode 3:	Camera Mode
--------------	-------------

Test Mode 4:	FM Mode
--------------	---------

Note: All modes were investigated, the results below show only the worst case(USB mode).

Test Mode 1: USB Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/m)	Detector	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	H	64.6594	40.82	peak	7.53	22.40	0.87	26.82	40.00	-13.18	100	360
2	H	99.5281	31.88	peak	10.29	22.32	1.11	20.96	43.50	-22.54	100	19
3	H	166.0680	45.93	peak	12.11	22.26	1.37	37.15	43.50	-6.35	100	330
4	H	238.3102	44.07	peak	11.56	22.31	1.66	34.98	46.00	-11.02	200	151
5	H	318.8170	48.93	QP	14.00	22.24	1.88	42.57	46.00	-3.43	100	207
6	H	480.5276	43.14	QP	17.31	21.85	2.31	40.91	46.00	-5.09	100	294

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	166.0680	43.98	peak	12.11	22.26	1.37	35.20	43.50	-8.30	100	101
2	V	239.9873	49.04	peak	11.54	22.31	1.67	39.94	46.00	-6.06	100	62
3	V	321.0608	44.89	peak	14.04	22.23	1.90	38.60	46.00	-7.40	100	196
4	V	480.5276	39.58	peak	17.31	21.85	2.31	37.35	46.00	-8.65	100	167
5	V	63.7588	44.69	peak	7.49	22.40	0.85	30.63	40.00	-9.37	100	93
6	V	99.8777	32.50	peak	10.37	22.32	1.12	21.67	43.50	-21.83	100	186

Above 1GHz

Frequency (MHz)	Read_level (dBμV/m)	Azimuth	Height (cm)	Polarity (H/V)	Level (dBμV/m)	Factors (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/AV)
1719.5	66.34	77	100	V	-17.67	48.67	74	-25.33	PK
2607.22	59.63	267	100	V	-13.1	46.53	74	-27.47	PK
4393.09	55.23	294	100	V	-7.84	47.39	74	-26.61	PK
1695.2	61.76	101	100	H	-16.6	45.16	74	-28.84	PK
2100.27	62.38	288	100	H	-14.1	48.28	74	-25.72	PK
5311.67	50.8	225	100	H	-3.83	46.97	74	-27.03	PK

*Note1: The highest frequency of the EUT is 2480 MHz, so the testing has been conformed to 5*2480MHz
=12,400MHz.*

Note2: The frequency that above 3GHz is mainly from the environment noise.

Note3: The AV measurement performed, more than 20dB below limit so AV test data was not presented.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Line Impedance Stabilization Network	LI-125A	191106	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Line Impedance Stabilization Network	LI-125A	191107	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna	AH-118	71259	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Label View



EUT - Front View



EUT - Rear View




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View



Mainboard with Shielding – Rear View



Mainboard without Shielding – Rear View



LCD – Front View



LCD – Rear View



A close-up photograph of a black electronic component, possibly a camera module, resting on a blue textured surface. A red circle highlights a small rectangular area on the component's surface, which contains the text "X5923-RW". To the right of the highlighted area is a circular lens. Below the lens is a small circular hole. Further down is a larger rectangular cutout. The component has a matte black finish and some visible wear.


RXD - Antenna View




Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup – Front View



Conducted Emissions Test Setup – Side View



Radiated Emissions Test Setup Below 1GHz




Radiated Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
GOLDWEB	Router	R102	1202032094
Lenovo	AC Adapter	42T4416	21D9JU
HP	Printer	VCVRA-1003	CN36M19JWX
DELL	Mouse	E100	912NMTUT41481
BULL	Socket	GN-403	GN201203
N/A	Earphone	N/A	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	2m	N/A
USB Cable	Un-shielding	No	2m	N/A
RJ45 Cable	Un-shielding	No	2m	N/A
Router Power cable	Un-shielding	No	2m	N/A
Printer Power cable	Un-shielding	No	2m	N/A
Power Cable	Un-shielding	No	0.8m	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A