

## **RF Exposure / SAR Statement**

### **No. : 11014760S-B**

<b>Applicant</b>	<b>:</b>	<b>Sony Corporation</b>
<b>Type of Equipment</b>	<b>:</b>	<b>Wireless Transceiver Module</b>
<b>Model No.</b>	<b>:</b>	<b>BNSY25</b>
<b>FCC ID</b>	<b>:</b>	<b>AK8BNSY25</b>

---

Sony Corporation declares that Model : BNSY25  
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the “BNSY25” as calculated from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

**Where**

<b>P =</b>	<b>4.18 mW (Maximum average output power)</b>	
<b>G =</b>	<b>1.05 Numerical Antenna gain; equal to</b>	<b>0.21 dBi</b>
<b>r =</b>	<b>20.0 cm</b>	

**For: BNSY25**

$$S = 0.00087 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401