



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM180600485002

Page: 1 of 114

FCC TEST REPORT

Application No: SZEM1806004850RG
Applicant: Fibocom Wireless Inc.
Address of Applicant: 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Manufacturer: Fibocom Wireless Inc.
Address of Manufacturer: 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Factory: Shenzhen Eternity Technology Co.,Ltd
Address of Factory: 1F,2F,4F Building A2, Yingzhan Industrial Zone, Longtian Community, Longtian Road, Pingshan District, Shenzhen, Guangdong Province, P.R. China
Product Name: LTE Module
Model No.(EUT): SC806-AM
Trade Mark: Fibocom
FCC ID: ZMOSC806AM
Standards: 47 CFR Part 15, Subpart C
Test Method: KDB 558074 D01 DTS Meas Guidance v04
ANSI C63.10 (2013)
Date of Receipt: 2018-07-08
Date of Test: 2018-07-10 to 2018-07-29
Date of Issue: 2018-08-13

Test Result:	PASS *
---------------------	---------------

. * In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Derek Yang

Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-08-13		Original

Authorized for issue by:				
Tested By		 <hr/> (Mike Hu) /Project Engineer		2018-08-13
				<hr/> Date
Checked By		 <hr/> (David Chen) /Reviewer		2018-08-13
				<hr/> Date



3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS



Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 TEST SUMMARY	3
CONTENTS.....	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 TEST ENVIRONMENT AND MODE	7
4.4 DESCRIPTION OF SUPPORT UNITS	7
4.5 TEST LOCATION	7
4.6 TEST FACILITY	7
4.7 DEVIATION FROM STANDARDS	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
4.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
4.11 EQUIPMENT LIST	9
5 TEST RESULTS AND MEASUREMENT DATA.....	12
5.1 ANTENNA REQUIREMENT	12
5.2 CONDUCTED EMISSIONS	13
5.3 DUTY CYCLE	17
5.3.1 Part I - Test Results.....	17
5.3.2 Part II - Test Plots	17
5.4 CONDUCTED PEAK OUTPUT POWER	20
5.5 6dB EMISSION BANDWIDTH.....	22
5.6 POWER SPECTRAL DENSITY	30
5.7 BAND-EDGE FOR RF CONDUCTED EMISSIONS	38
5.8 RF CONDUCTED SPURIOUS EMISSIONS	43
5.9 RADIATED SPURIOUS EMISSIONS.....	50
5.9.1 Radiated emission below 1GHz.....	53
5.9.2 Transmitter emission above 1GHz	55
5.10 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	80
6 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	114



4 General Information

4.1 Client Information

Applicant:	Fibocom Wireless Inc.
Address of Applicant:	5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Manufacturer:	Fibocom Wireless Inc.
Address of Manufacturer:	5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Factory:	Shenzhen Eternity Technology Co.,Ltd
Address of Factory:	1F,2F,4F Building A2, Yingzhan Industrial Zone, Longtian Community, Longtian Road, Pingshan District, Shenzhen, Guangdong Province, P.R. China

4.2 General Description of EUT

Product Name:	LTE Module
Model No.:	SC806-AM
Trade Mark:	Fibocom
Hardware Version:	V1.0.1
Software Version:	19060.1000.00.12.20.06
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	LTE Module
Antenna Type:	Monopole Antenna
Antenna Gain:	2.5dBi
Power Supply	DC3.85V



Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		
Operation Frequency each of channel (802.11n HT40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency		
3	2422MHz	6	2437MHz	9	2452MHz		
4	2427MHz	7	2442MHz				
5	2432MHz	8	2447MHz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency for 802.11b/g/n (HT20)	Frequency for 802.11n (HT40)
The Lowest channel	2412MHz	2422MHz
The Middle channel	2437MHz	2437MHz
The Highest channel	2462MHz	2452MHz



4.3 Test Environment and Mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	101.30 KPa
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

4.4 Description of Support Units

The EUT has been tested independent unit.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	$\pm 0.75\text{dB}$
2	RF power density, conducted	$\pm 2.84\text{dB}$
3	Spurious emissions, conducted	$\pm 0.75\text{dB}$
4	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (30MHz-1GHz)
		$\pm 4.8\text{dB}$ (1GHz-25GHz)
5	Conduct emission test	$\pm 3.12\text{ dB}$ (9KHz- 30MHz)
6	Temperature test	$\pm 1^{\circ}\text{C}$
7	Humidity test	$\pm 3\%$
8	DC and low frequency voltages	$\pm 0.5\%$



4.11 Equipment List

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Duedate (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2018/3/10	2019/3/9
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2017/10/9	2018/10/9
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2018/2/14	2019/2/13
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2017/9/28	2018/9/28
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2017/9/28	2018/9/28
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2017/9/28	2018/9/28
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018/2/14	2019/2/13
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017/10/9	2018/10/9

RF conducted test						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Duedate (yyyy-mm-dd)
1	Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66311B	W009-09	2018/4/28	2019/4/28
2	Signal Analyzer	Rohde &Schwarz	FSV	W005-02	2018/3/13	2019/3/12
3	Signal Generator	Rohde &Schwarz	SML03	SEM006-02	2018/2/14	2019/2/13
4	Power Meter	Rohde &Schwarz	NRVS	SEM014-02	2017/10/9	2018/10/9
5	Power Sensor	Agilent Technologies	U2021XA	SEM009-01	2017/10/9	2018/10/9



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 10 of 114

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2018/3/10	2019/3/9
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2017/10/9	2018/10/9
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017/11/1	2020/11/1
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015/10/17	2018/10/17
5	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2017/11/24	2020/11/24
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2018/2/14	2019/2/13
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017/10/9	2018/10/9
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2018/3/10	2019/3/9

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2018/3/10	2019/3/9
2	EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2018/2/14	2019/2/13
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016/6/29	2019/6/29
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2018/4/28	2019/4/28
5	.Loop Antenna	ETS-Lindgren	6502	SEM003-08	2018/7/14	2021/7/13



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 11 of 114

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/10	2019/3/9
2	EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2018/6/18	2019/6/17
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2017/11/15	2020/11/15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017/10/9	2018/10/9
5	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-10	2017/10/17	2018/10/17
6	Pre-Amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018/3/14	2019/3/14
7	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/5/14	2020/5/13
8	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2017/11/24	2020/11/24
9	HornAntenna (26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2017/10/17	2020/10/16
10	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017/10/9	2018/10/9
11	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A




5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement:</p> <p>The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
<p>The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.5dBi.</p>	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 		
Test Setup:			



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 14 of 114

Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Charge + Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:




Site : Shielding Room
Condition: Line
Job No. : 04850RG
Test mode: j

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	2.58	0.17	9.53	12.01	21.71	46.00	-24.29	Peak
2	3.74	0.19	9.54	11.40	21.13	46.00	-24.87	Peak
3	7.45	0.18	9.60	10.56	20.34	50.00	-29.66	Peak
4	9.16	0.19	9.62	15.00	24.81	50.00	-25.19	Peak
5	14.21	0.24	9.70	17.31	27.25	50.00	-22.75	Peak
6	23.39	0.27	9.84	10.66	20.77	50.00	-29.23	Peak



Neutral Line:



Site : Shielding Room
Condition: Neutral
Job No. : 04850RG
Test mode: j

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	2.61	0.17	9.64	12.32	22.13	46.00	-23.87	Peak
2	3.94	0.19	9.67	13.78	23.64	46.00	-22.36	Peak
3	9.01	0.19	9.76	14.72	24.67	50.00	-25.33	Peak
4	14.06	0.24	9.91	18.98	29.13	50.00	-20.87	Peak
5	15.23	0.25	9.94	14.87	25.06	50.00	-24.94	Peak
6	23.39	0.27	10.17	13.01	23.45	50.00	-26.55	Peak

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.




5.3 Duty Cycle

5.3.1 Part I - Test Results

Test Mode	TX Freq. [MHz]	Duty cycle [%]
11B	Ant 1: CH1	97
11G	Ant 1: CH1	87
11N_20	Ant 1: CH1	86
11N_40	Ant 1: CH3	72

5.3.2 Part II - Test Plots


5.3.2.1 11B @Ant 1



Date: 16.JUL.2018 05:23:36




5.3.2.2 11G@Ant 1



Date: 16.JUL.2018 05:22:23


5.3.2.3 11N20@Ant 1



Date: 16.JUL.2018 05:21:40




5.3.2.4 11N40@Ant 1



Date: 16 JUL 2018 06:05:36



5.4 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 :2013 Section 11.9.1.3
Test Setup:	 <p>The diagram illustrates the test setup. A rectangular box labeled 'POWER METER' is connected to a smaller rectangular box labeled 'E.U.T.' by a red line. Both boxes are positioned on a horizontal line representing the 'Non-Conducted Table'. This table is supported by two vertical lines. Below the table, a thick horizontal grey bar represents the 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20);13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	30dBm
Test Results:	Pass



Measurement Data

802.11b mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	18.48	30.00	Pass
Middle	18.36	30.00	Pass
Highest	18.81	30.00	Pass
802.11g mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	20.66	30.00	Pass
Middle	20.93	30.00	Pass
Highest	21.16	30.00	Pass
802.11n(HT20)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	20.35	30.00	Pass
Middle	20.14	30.00	Pass
Highest	20.17	30.00	Pass
802.11n(HT40)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	19.49	30.00	Pass
Middle	20.20	30.00	Pass
Highest	19.76	30.00	Pass

5.5 6dB Emission Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013 Section 11.8.1 Option 1
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Instruments Used:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	≥ 500 kHz
Test Results:	Pass




Measurement Data

802.11b mode			
Test channel	6dB Emission Bandwidth (MHz)	Limit (kHz)	Result
Lowest	7.67	≥500	Pass
Middle	7.67	≥500	Pass
Highest	7.70	≥500	Pass
802.11g mode			
Test channel	6dB Emission Bandwidth (MHz)	Limit (kHz)	Result
Lowest	16.54	≥500	Pass
Middle	16.66	≥500	Pass
Highest	16.45	≥500	Pass
802.11n(HT20) mode			
Test channel	6dB Emission Bandwidth (MHz)	Limit (kHz)	Result
Lowest	17.59	≥500	Pass
Middle	17.80	≥500	Pass
Highest	17.68	≥500	Pass
802.11n(HT40) mode			
Test channel	6dB Emission Bandwidth (MHz)	Limit (kHz)	Result
Lowest	35.72	≥500	Pass
Middle	36.14	≥500	Pass
Highest	36.14	≥500	Pass



Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Date: 16 JUL 2018 04:50:57


Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------



Date: 16 JUL 2018 04:46:47




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 16 JUL 2018 04:44:35


Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------



Date: 16 JUL 2018 04:52:52




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Date: 16 JUL 2018 04:48:08


Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Date: 16 JUL 2018 04:43:47




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 04:54:26


Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------



Date: 16 JUL 2018 04:49:09




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 04:42:54


Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 05:53:54




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------




Date: 16.JUL 2018 05:52:40

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16.JUL 2018 05:51:08

5.6 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 :2013 Section 11.10.2
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20);13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	≤8.00dBm/3kHz
Test Results:	Pass




Measurement Data

802.11b mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-5.70	≤8.00	Pass
Middle	-6.39	≤8.00	Pass
Highest	-6.39	≤8.00	Pass
802.11g mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-9.57	≤8.00	Pass
Middle	-10.28	≤8.00	Pass
Highest	-10.96	≤8.00	Pass
802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-11.90	≤8.00	Pass
Middle	-11.57	≤8.00	Pass
Highest	-11.67	≤8.00	Pass
802.11n(HT40) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-15.79	≤8.00	Pass
Middle	-14.12	≤8.00	Pass
Highest	-15.63	≤8.00	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------






Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 16 JUL 2018 05:00:02


Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------



Date: 16 JUL 2018 04:56:05




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Date: 16 JUL 2018 04:57:56


Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Date: 16 JUL 2018 04:59:42




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 04:55:37


Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------



Date: 16 JUL 2018 04:58:24




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 04:58:56


Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 05:54:18




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------




Date: 16 JUL 2018 05:55:19

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 05:56:00


5.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.13
Test Setup:	 <p>The diagram illustrates the test setup for RF conducted emissions. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	V4Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------






Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------






Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 05:04:15


Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 05:08:35




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Date: 16 JUL 2018 06:00:40

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 05:57:01


5.8 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Date: 16 JUL 2018 05:17:31


Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------



Date: 16 JUL 2018 05:14:14




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 16 JUL 2018 05:12:36


Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------



Date: 16 JUL 2018 05:18:53




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Date: 16 JUL 2018 05:15:15


Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Date: 16 JUL 2018 05:11:10




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 05:19:28


Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------



Date: 16 JUL 2018 05:16:21




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 05:09:58


Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 16 JUL 2018 06:02:11




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Date: 16 JUL 2018 06:02:55

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 16 JUL 2018 06:03:35

Remark:



Scan from 9kHz to 25GHz, the disturbance between 9KHz to 30MHz and 18GHz to 25GHz was very low, and the above harmonics were the highest point could be found when testing, The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported

5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 :2013 Section 11.12				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the




	<p>EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge + Transmitting mode.
Final Test Mode:	Pretest the EUT at Charge + Transmitting mode. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40) For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case.Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



5.9.1 Radiated emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Charge + Transmitting	Vertical



Condition: 3m VERTICAL


Job No. : 04850RG

Test mode: e

	Freq	Cable	Ant	Preamp	Read	Limit	Over
	MHz	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1	43.51	0.68	16.26	27.42	29.14	18.66	40.00
2	104.17	1.21	13.80	27.32	27.28	14.97	43.50
3	259.23	1.72	19.09	26.73	23.66	17.74	46.00
4	547.10	2.65	25.59	27.78	27.06	27.52	46.00
5	721.73	2.97	28.04	27.75	26.05	29.31	46.00
6 pp	925.76	3.63	29.93	26.91	25.24	31.89	46.00



Test mode:	Charge + Transmitting	Horizontal
------------	-----------------------	------------



Condition: 3m HORIZONTAL

Job No. : 04850RG


Test mode: e

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.11	0.60	22.44	27.45	25.18	20.77	40.00	-19.23
2	105.27	1.22	13.75	27.32	27.54	15.19	43.50	-28.31
3	313.28	1.94	20.02	26.72	22.85	18.09	46.00	-27.91
4	420.58	2.29	22.89	27.28	24.89	22.79	46.00	-23.21
5	701.76	2.91	27.91	27.78	26.27	29.31	46.00	-16.69
6 pp	851.04	3.41	29.18	27.33	24.20	29.46	46.00	-16.54



5.9.2 Transmitter emission above 1GHz

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 TX RSE

Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	5.28	26.50	38.03	46.09	39.84	74.00	-34.16	peak
2	4109.872	7.11	33.60	38.06	47.67	50.32	74.00	-23.68	peak
3	4824.000	7.91	34.19	38.42	46.71	50.39	74.00	-23.61	peak
4 pp	6954.852	10.25	36.38	37.34	43.56	52.85	74.00	-21.15	peak
5	7236.000	10.07	36.40	37.08	42.86	52.25	74.00	-21.75	peak
6	9648.000	10.77	37.53	35.07	39.06	52.29	74.00	-21.71	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 56 of 114

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 TX RSE

Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	5.25	26.58	38.03	46.30	40.10	74.00	-33.90	peak
2	4133.699	7.14	33.60	38.07	47.69	50.36	74.00	-23.64	peak
3	4824.000	7.91	34.19	38.42	46.15	49.83	74.00	-24.17	peak
4	6995.172	10.14	36.49	37.30	42.43	51.76	74.00	-22.24	peak
5	7236.000	10.07	36.40	37.08	42.51	51.90	74.00	-22.10	peak
6 pp	9648.000	10.77	37.53	35.07	39.37	52.60	74.00	-21.40	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 57 of 114

Test mode:	802.11b	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2437 TX RSE

Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBUV/m	dBUV/m	dB	
1	1682.477	5.25	26.60	38.02	45.15	38.98	74.00	-35.02	peak
2	4495.125	7.55	33.60	38.26	46.73	49.62	74.00	-24.38	peak
3	4874.000	7.96	34.28	38.44	47.63	51.43	74.00	-22.57	peak
4 pp	6974.982	10.20	36.43	37.32	43.31	52.62	74.00	-21.38	peak
5	7311.000	10.05	36.37	37.01	43.04	52.45	74.00	-21.55	peak
6	9748.000	10.82	37.55	35.02	38.91	52.26	74.00	-21.74	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 58 of 114

Test mode:	802.11b	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2437 TX RSE

Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	5.34	26.30	38.03	45.61	39.22	74.00	-34.78	peak
2	4456.315	7.51	33.60	38.24	47.44	50.31	74.00	-23.69	peak
3	4874.000	7.96	34.28	38.44	47.17	50.97	74.00	-23.03	peak
4	6659.763	11.08	35.56	37.62	43.23	52.25	74.00	-21.75	peak
5	pp 7311.000	10.05	36.37	37.01	43.50	52.91	74.00	-21.09	peak
6	9748.000	10.82	37.55	35.02	38.71	52.06	74.00	-21.94	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 59 of 114

Test mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG


Mode : 2462 TX RSE

Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	5.23	26.68	38.02	45.70	39.59	74.00	-34.41	peak
2	4443.453	7.50	33.60	38.24	48.14	51.00	74.00	-23.00	peak
3	4924.000	8.01	34.37	38.47	46.50	50.41	74.00	-23.59	peak
4	6507.536	11.52	35.12	37.77	42.28	51.15	74.00	-22.85	peak
5	7386.000	10.03	36.34	36.94	41.40	50.83	74.00	-23.17	peak
6	9848.000	10.87	37.57	34.97	38.28	51.75	74.00	-22.25	peak



Test mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 TX RSE

Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	5.24	26.64	38.02	45.35	39.21	74.00	-34.79	peak
2	4181.768	7.20	33.60	38.10	47.57	50.27	74.00	-23.73	peak
3	4924.000	8.01	34.37	38.47	46.42	50.33	74.00	-23.67	peak
4	6855.063	10.53	36.10	37.44	42.94	52.13	74.00	-21.87	peak
5	7386.000	10.03	36.34	36.94	42.72	52.15	74.00	-21.85	peak
6 pp	9848.000	10.87	37.57	34.97	38.91	52.38	74.00	-21.62	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 61 of 114

Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG


Mode : 2412 TX RSE

Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1620.431	5.32	26.34	38.03	46.21	39.84	74.00	-34.16	peak
2	4456.315	7.51	33.60	38.24	47.70	50.57	74.00	-23.43	peak
3	4824.000	7.91	34.19	38.42	47.23	50.91	74.00	-23.09	peak
4	6894.806	10.42	36.21	37.40	43.34	52.57	74.00	-21.43	peak
5	7236.000	10.07	36.40	37.08	42.79	52.18	74.00	-21.82	peak
6 pp	9648.000	10.77	37.53	35.07	39.71	52.94	74.00	-21.06	peak



Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 TX RSE

Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	5.25	26.58	38.03	45.81	39.61	74.00	-34.39	peak
2	4027.554	7.01	33.60	38.02	47.97	50.56	74.00	-23.44	peak
3	4824.000	7.91	34.19	38.42	46.97	50.65	74.00	-23.35	peak
4 pp	6874.906	10.47	36.16	37.42	43.51	52.72	74.00	-21.28	peak
5	7236.000	10.07	36.40	37.08	42.72	52.11	74.00	-21.89	peak
6	9648.000	10.77	37.53	35.07	38.97	52.20	74.00	-21.80	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 63 of 114

Test mode:	802.11g	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2437 TX RSE

Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1520.598	5.45	25.89	38.04	46.60	39.90	74.00	-34.10	peak
2	4417.841	7.47	33.60	38.22	48.05	50.90	74.00	-23.10	peak
3	4874.000	7.96	34.28	38.44	46.10	49.90	74.00	-24.10	peak
4 pp	6737.207	10.86	35.78	37.55	43.72	52.81	74.00	-21.19	peak
5	7311.000	10.05	36.37	37.01	42.65	52.06	74.00	-21.94	peak
6	9748.000	10.82	37.55	35.02	38.73	52.08	74.00	-21.92	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 64 of 114

Test mode:	802.11g	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1620.431	5.32	26.34	38.03	46.24	39.87	74.00	-34.13	peak
2	4443.453	7.50	33.60	38.24	47.85	50.71	74.00	-23.29	peak
3	4874.000	7.96	34.28	38.44	46.35	50.15	74.00	-23.85	peak
4 pp	6795.879	10.69	35.94	37.49	43.79	52.93	74.00	-21.07	peak
5	7311.000	10.05	36.37	37.01	42.57	51.98	74.00	-22.02	peak
6	9748.000	10.82	37.55	35.02	38.88	52.23	74.00	-21.77	peak



Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 TX RSE

Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1648.778	5.29	26.46	38.03	45.62	39.34	74.00	-34.66	peak
2	4181.768	7.20	33.60	38.10	47.33	50.03	74.00	-23.97	peak
3	4924.000	8.01	34.37	38.47	46.76	50.67	74.00	-23.33	peak
4	6621.375	11.19	35.45	37.66	43.15	52.13	74.00	-21.87	peak
5	pp 7386.000	10.03	36.34	36.94	43.40	52.83	74.00	-21.17	peak
6	9848.000	10.87	37.57	34.97	38.50	51.97	74.00	-22.03	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 66 of 114

Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 TX RSE

Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1667.951	5.27	26.54	38.03	46.82	40.60	74.00	-33.40	peak
2	4417.841	7.47	33.60	38.22	47.56	50.41	74.00	-23.59	peak
3	4924.000	8.01	34.37	38.47	46.83	50.74	74.00	-23.26	peak
4 pp	6640.542	11.13	35.50	37.64	43.69	52.68	74.00	-21.32	peak
5	7386.000	10.03	36.34	36.94	42.88	52.31	74.00	-21.69	peak
6	9848.000	10.87	37.57	34.97	38.83	52.30	74.00	-21.70	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 67 of 114

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 TX RSE

Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1615.754	5.33	26.32	38.03	45.55	39.17	74.00	-34.83	peak
2	4469.214	7.53	33.60	38.25	47.50	50.38	74.00	-23.62	peak
3	4824.000	7.91	34.19	38.42	46.34	50.02	74.00	-23.98	peak
4 pp	6451.353	11.45	35.06	37.83	43.43	52.11	74.00	-21.89	peak
5	7236.000	10.07	36.40	37.08	42.38	51.77	74.00	-22.23	peak
6	9648.000	10.77	37.53	35.07	38.65	51.88	74.00	-22.12	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 68 of 114

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 TX RSE

Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1583.392	5.37	26.18	38.03	46.22	39.74	74.00	-34.26	peak
2	4169.698	7.18	33.60	38.09	47.65	50.34	74.00	-23.66	peak
3	4824.000	7.91	34.19	38.42	46.25	49.93	74.00	-24.07	peak
4	6679.040	11.02	35.61	37.60	42.30	51.33	74.00	-22.67	peak
5	7236.000	10.07	36.40	37.08	42.33	51.72	74.00	-22.28	peak
6 pp	9648.000	10.77	37.53	35.07	38.66	51.89	74.00	-22.11	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 69 of 114

Test mode:	802.11n(HT20)	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2437 TX RSE

Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	5.25	26.58	38.03	44.86	38.66	74.00	-35.34	peak
2	3946.885	6.93	33.46	38.00	48.30	50.69	74.00	-23.31	peak
3	4874.000	7.96	34.28	38.44	46.42	50.22	74.00	-23.78	peak
4 pp	6855.063	10.53	36.10	37.44	43.54	52.73	74.00	-21.27	peak
5	7311.000	10.05	36.37	37.01	42.46	51.87	74.00	-22.13	peak
6	9748.000	10.82	37.55	35.02	38.02	51.37	74.00	-22.63	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 70 of 114

Test mode:	802.11n(HT20)	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	5.24	26.64	38.02	45.49	39.35	74.00	-34.65	peak
2	4145.664	7.16	33.60	38.08	47.66	50.34	74.00	-23.66	peak
3	4874.000	7.96	34.28	38.44	46.71	50.51	74.00	-23.49	peak
4	6815.551	10.64	36.00	37.47	42.95	52.12	74.00	-21.88	peak
5	7311.000	10.05	36.37	37.01	42.97	52.38	74.00	-21.62	peak
6 pp	9748.000	10.82	37.55	35.02	39.06	52.41	74.00	-21.59	peak



Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 TX RSE

Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	5.25	26.58	38.03	45.20	39.00	74.00	-35.00	peak
2	4169.698	7.18	33.60	38.09	47.88	50.57	74.00	-23.43	peak
3	4924.000	8.01	34.37	38.47	45.73	49.64	74.00	-24.36	peak
4	6874.906	10.47	36.16	37.42	43.25	52.46	74.00	-21.54	peak
5 pp	7386.000	10.03	36.34	36.94	43.05	52.48	74.00	-21.52	peak
6	9848.000	10.87	37.57	34.97	38.88	52.35	74.00	-21.65	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 72 of 114

Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 TX RSE

Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1494.455	5.46	25.78	38.04	46.50	39.70	74.00	-34.30	peak
2	4379.699	7.43	33.60	38.20	47.70	50.53	74.00	-23.47	peak
3	4924.000	8.01	34.37	38.47	45.67	49.58	74.00	-24.42	peak
4	6640.542	11.13	35.50	37.64	43.29	52.28	74.00	-21.72	peak
5	7386.000	10.03	36.34	36.94	41.75	51.18	74.00	-22.82	peak
6 pp	9848.000	10.87	37.57	34.97	38.94	52.41	74.00	-21.59	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 73 of 114

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2422 TX RSE

Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1639.274	5.30	26.42	38.03	46.51	40.20	74.00	-33.80	peak
2	4193.872	7.21	33.60	38.11	48.06	50.76	74.00	-23.24	peak
3	4844.000	7.93	34.23	38.43	45.83	49.56	74.00	-24.44	peak
4	6602.265	11.24	35.39	37.68	43.22	52.17	74.00	-21.83	peak
5 pp	7266.000	10.06	36.39	37.05	42.82	52.22	74.00	-21.78	peak
6	9688.000	10.79	37.54	35.05	38.50	51.78	74.00	-22.22	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 74 of 114

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2422 TX RSE

Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	5.26	26.56	38.03	45.56	39.35	74.00	-34.65	peak
2	4392.376	7.44	33.60	38.21	47.89	50.72	74.00	-23.28	peak
3	4844.000	7.93	34.23	38.43	46.71	50.44	74.00	-23.56	peak
4 pp	6954.852	10.25	36.38	37.34	43.11	52.40	74.00	-21.60	peak
5	7266.000	10.06	36.39	37.05	42.65	52.05	74.00	-21.95	peak
6	9688.000	10.79	37.54	35.05	38.79	52.07	74.00	-21.93	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 75 of 114

Test mode:	802.11n(HT40)	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	5.27	26.52	38.03	45.98	39.74	74.00	-34.26	peak
2	4443.453	7.50	33.60	38.24	47.67	50.53	74.00	-23.47	peak
3	4874.000	7.96	34.28	38.44	46.10	49.90	74.00	-24.10	peak
4	6995.172	10.14	36.49	37.30	43.10	52.43	74.00	-21.57	peak
5	7311.000	10.05	36.37	37.01	42.06	51.47	74.00	-22.53	peak
6	9748.000	10.82	37.55	35.02	39.11	52.46	74.00	-21.54	peak



Test mode:	802.11n(HT40)	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2437 TX RSE

Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	5.27	26.52	38.03	45.49	39.25	74.00	-34.75	peak
2	3935.493	6.92	33.43	37.99	48.56	50.92	74.00	-23.08	peak
3	4874.000	7.96	34.28	38.44	45.34	49.14	74.00	-24.86	peak
4 pp	6564.209	11.35	35.29	37.72	43.83	52.75	74.00	-21.25	peak
5	7311.000	10.05	36.37	37.01	42.50	51.91	74.00	-22.09	peak
6	9748.000	10.82	37.55	35.02	38.68	52.03	74.00	-21.97	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 77 of 114

Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG


Mode : 2452 TX RSE

Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	5.35	26.24	38.03	46.39	39.95	74.00	-34.05	peak
2	4430.628	7.48	33.60	38.23	48.98	51.83	74.00	-22.17	peak
3	4904.000	7.99	34.33	38.46	47.06	50.92	74.00	-23.08	peak
4	pp 6995.172	10.14	36.49	37.30	43.13	52.46	74.00	-21.54	peak
5	7356.000	10.04	36.36	36.97	42.45	51.88	74.00	-22.12	peak
6	9808.000	10.85	37.56	34.99	38.19	51.61	74.00	-22.39	peak



Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2452 TX RSE

Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.804	5.35	26.26	38.03	46.07	39.65	74.00	-34.35	peak
2	4405.090	7.46	33.60	38.22	47.50	50.34	74.00	-23.66	peak
3	4904.000	7.99	34.33	38.46	46.21	50.07	74.00	-23.93	peak
4 pp	6995.172	10.14	36.49	37.30	43.43	52.76	74.00	-21.24	peak
5	7356.000	10.04	36.36	36.97	42.68	52.11	74.00	-21.89	peak
6	9808.000	10.85	37.56	34.99	38.04	51.46	74.00	-22.54	peak



Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance between 9KHz to 30MHz and 18GHz to 25GHz was very low, and the above harmonics were the highest point could be found when testing, The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz




Test Procedure:	<ul style="list-style-type: none">a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channelh. Test the EUT in the lowest channel , the Highest channeli. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge + Transmitting mode.
Final Test Mode:	Pretest the EUT at Charge +Transmitting mode. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



Test plot as follows:

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 Band edge


: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2312.692	5.37	28.39	41.84	59.12	51.04	74.00	-22.96	Peak
2	2390.000	5.47	28.52	41.87	56.72	48.84	74.00	-25.16	Peak
3 pp	2412.000	5.50	28.56	41.88	99.58	91.76	74.00	17.76	Peak



Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 Band edge


: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	5.47	28.52	41.87	66.10	58.22	74.00	-15.78	peak
2	2390.000	5.47	28.52	41.87	64.47	56.59	74.00	-17.41	peak
3 pp	2412.000	5.50	28.56	41.88	109.91	102.09	74.00	28.09	peak



Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	48.26	40.38	54.00	-13.62	Average
2	2390.000	5.47	28.52	41.87	48.26	40.38	54.00	-13.62	Average
3 pp	2412.000	5.50	28.56	41.88	97.46	89.64	54.00	35.64	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 85 of 114

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 Band edge


: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.274	5.47	28.52	41.87	52.78	44.90	54.00	-9.10	Average
2	2390.000	5.47	28.52	41.87	51.62	43.74	54.00	-10.26	Average
3 pp	2412.000	5.50	28.56	41.88	107.89	100.07	54.00	46.07	Average



Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	28.64	41.90	99.00	91.31	74.00	17.31 Peak
2	2483.500	5.60	28.67	41.91	57.68	50.04	74.00	-23.96 Peak
3	2485.999	5.60	28.68	41.91	58.93	51.30	74.00	-22.70 Peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 87 of 114

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBUV/m	dBUV/m	dB	
1 pp	2462.000	5.57	28.64	41.90	108.30	100.61	74.00	26.61	peak
2	2483.500	5.60	28.67	41.91	60.96	53.32	74.00	-20.68	peak
3	2485.245	5.60	28.68	41.91	63.60	55.97	74.00	-18.03	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 88 of 114

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	28.64	41.90	97.10	89.41	54.00	35.41 Average
2	2483.500	5.60	28.67	41.91	47.99	40.35	54.00	-13.65 Average
3	2485.546	5.60	28.68	41.91	48.11	40.48	54.00	-13.52 Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 89 of 114

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 Band edge


: 2.4G WIFI 11B

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	28.64	41.90	106.47	98.78	54.00	44.78	Average
2	2483.500	5.60	28.67	41.91	50.37	42.73	54.00	-11.27	Average
3	2485.446	5.60	28.68	41.91	51.34	43.71	54.00	-10.29	Average



Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2347.860	5.42	28.45	41.85	58.84	50.86	74.00	-23.14	Peak
2	2390.000	5.47	28.52	41.87	56.83	48.95	74.00	-25.05	Peak
3 pp	2412.000	5.50	28.56	41.88	99.55	91.73	74.00	17.73	Peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 91 of 114

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11G

: Powersetting 15

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.726	5.47	28.52	41.87	67.33	59.45	74.00	-14.55	peak
2	2390.000	5.47	28.52	41.87	67.25	59.37	74.00	-14.63	peak
3 pp	2412.000	5.50	28.56	41.88	110.45	102.63	74.00	28.63	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 92 of 114

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	5.47	28.52	41.87	48.37	40.49	54.00	-13.51 Average
2	2390.000	5.47	28.52	41.87	48.37	40.49	54.00	-13.51 Average
3 pp	2412.000	5.50	28.56	41.88	93.57	85.75	54.00	31.75 Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 93 of 114

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	53.96	46.08	54.00	-7.92	Average
2	2390.000	5.47	28.52	41.87	53.96	46.08	54.00	-7.92	Average
3 pp	2412.000	5.50	28.56	41.88	102.84	95.02	54.00	41.02	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 94 of 114

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 Band edge


: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	28.64	41.90	99.12	91.43	74.00	17.43 Peak
2	2483.500	5.60	28.67	41.91	57.84	50.20	74.00	-23.80 Peak
3	2483.790	5.60	28.67	41.91	62.82	55.18	74.00	-18.82 Peak



Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 Band edge


: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	28.64	41.90	109.89	102.20	74.00	28.20	peak
2	2483.500	5.60	28.67	41.91	71.63	63.99	74.00	-10.01	peak
3	2483.940	5.60	28.67	41.91	70.25	62.61	74.00	-11.39	peak



Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	28.64	41.90	92.50	84.81	54.00	30.81 Average
2	2483.500	5.60	28.67	41.91	49.63	41.99	54.00	-12.01 Average
3	2483.840	5.60	28.67	41.91	49.41	41.77	54.00	-12.23 Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 97 of 114

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11G

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	28.64	41.90	101.23	93.54	54.00	39.54	Average
2	2483.500	5.60	28.67	41.91	56.09	48.45	54.00	-5.55	Average
3	2483.790	5.60	28.67	41.91	55.57	47.93	54.00	-6.07	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 98 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 Band edge


: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2311.170	5.37	28.38	41.84	58.78	50.69	74.00	-23.31	Peak
2	2390.000	5.47	28.52	41.87	56.95	49.07	74.00	-24.93	Peak
3 pp	2412.000	5.50	28.56	41.88	98.43	90.61	74.00	16.61	Peak



Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	65.62	57.74	74.00	-16.26	peak
2	2390.000	5.47	28.52	41.87	65.62	57.74	74.00	-16.26	peak
3 pp	2412.000	5.50	28.56	41.88	107.67	99.85	74.00	25.85	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 100 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.484	5.47	28.52	41.87	48.00	40.12	54.00	-13.88	Average
2	2390.000	5.47	28.52	41.87	47.97	40.09	54.00	-13.91	Average
3	pp 2412.000	5.50	28.56	41.88	92.28	84.46	54.00	30.46	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 101 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2412 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.87	52.79	44.91	54.00	-9.09	Average
2	2390.000	5.47	28.52	41.87	52.79	44.91	54.00	-9.09	Average
3 pp	2412.000	5.50	28.56	41.88	100.20	92.38	54.00	38.38	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 102 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	28.64	41.90	98.23	90.54	74.00	16.54 Peak
2	2483.500	5.60	28.67	41.91	59.90	52.26	74.00	-21.74 Peak
3	2484.292	5.60	28.67	41.91	60.92	53.28	74.00	-20.72 Peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 103 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	28.64	41.90	106.99	99.30	74.00	25.30 peak
2	2483.500	5.60	28.67	41.91	67.08	59.44	74.00	-14.56 peak
3	2484.041	5.60	28.67	41.91	71.39	63.75	74.00	-10.25 peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 104 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 2462.000	5.57	28.64	41.90	91.03	83.34	54.00	29.34 Average
2	2483.500	5.60	28.67	41.91	49.17	41.53	54.00	-12.47 Average
3	2483.890	5.60	28.67	41.91	49.14	41.50	54.00	-12.50 Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 105 of 114

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2462 Band edge

: 2.4G WIFI 11N20

: Powersetting 15

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	28.64	41.90	99.39	91.70	54.00	37.70	Average
2	2483.500	5.60	28.67	41.91	54.96	47.32	54.00	-6.68	Average
3	2483.790	5.60	28.67	41.91	54.76	47.12	54.00	-6.88	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 106 of 114

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2422 Band edge


: 2.4G WIFI 11N40

: Powersetting 12

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2384.271	5.47	28.51	41.87	58.33	50.44	74.00	-23.56 Peak
2	2390.000	5.47	28.52	41.87	56.15	48.27	74.00	-25.73 Peak
3 pp	2422.000	5.52	28.57	41.89	92.86	85.06	74.00	11.06 Peak



Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2422 Band edge

: 2.4G WIFI 11N40

: Powersetting 12

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.827	5.47	28.52	41.87	60.12	52.24	74.00	-21.76	peak
2	2390.000	5.47	28.52	41.87	59.17	51.29	74.00	-22.71	peak
3 pp	2422.000	5.52	28.57	41.89	103.42	95.62	74.00	21.62	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 108 of 114

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2422 Band edge

: 2.4G WIFI 11N40

: Powersetting 12

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.226	5.47	28.52	41.87	47.95	40.07	54.00	-13.93 Average
2	2390.000	5.47	28.52	41.87	47.86	39.98	54.00	-14.02 Average
3 pp	2422.000	5.52	28.57	41.89	85.84	78.04	54.00	24.04 Average




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM180600485002

Page: 109 of 114

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2422 Band edge


: 2.4G WIFI 11N40

: Powersetting 12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.827	5.47	28.52	41.87	49.85	41.97	54.00	-12.03	Average
2	2390.000	5.47	28.52	41.87	49.68	41.80	54.00	-12.20	Average
3 pp	2422.000	5.52	28.57	41.89	96.22	88.42	54.00	34.42	Average



Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2452 Band edge


: 2.4G WIFI 11N40

: Powersetting 12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	5.56	28.62	41.90	92.98	85.26	74.00	11.26	Peak
2	2483.500	5.60	28.67	41.91	58.72	51.08	74.00	-22.92	Peak
3	2485.205	5.60	28.68	41.91	59.97	52.34	74.00	-21.66	Peak



Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2452 Band edge


: 2.4G WIFI 11N40

: Powersetting 12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	5.56	28.62	41.90	104.40	96.68	74.00	22.68	peak
2	2483.500	5.60	28.67	41.91	66.41	58.77	74.00	-15.23	peak
3	2485.346	5.60	28.68	41.91	69.67	62.04	74.00	-11.96	peak



Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 4850RG

Mode : 2452 Band edge

: 2.4G WIFI 11N40

: Powersetting 12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	5.56	28.62	41.90	85.94	78.22	54.00	24.22	Average
2	2483.500	5.60	28.67	41.91	49.86	42.22	54.00	-11.78	Average
3	2484.358	5.60	28.67	41.91	50.02	42.38	54.00	-11.62	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180600485002

Page: 113 of 114

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 4850RG

Mode : 2452 Band edge

: 2.4G WIFI 11N40

: Powersetting 12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	5.56	28.62	41.90	96.69	88.97	54.00	34.97	Average
2	2483.500	5.60	28.67	41.91	56.86	49.22	54.00	-4.78	Average
3	2484.923	5.60	28.68	41.91	57.25	49.62	54.00	-4.38	Average



Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

6 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1806004850RG.

The End