

FCC LISTED,
REGISTRATION
NUMBER: 905266IC LISTED,
REGISTRATION
NUMBER: IC 4621

TEST REPORT

Report No.: 21046RET.101**TEST NAME: FCC PART 15.247 TESTING FOR BLUETOOTH RADIO DEVICE**

Product : CARKIT BLUETOOTH
Trade Mark : NOKIA
Model/type Ref. : CK-1W
Manufacturer : NOKIA CORPORATION
Requested by : NOKIA CORPORATION
Other identification of the product : Industry Canada (IC): 661AA-HF2W
 FCC ID: OW3HF-2W
 Prototype
Standard(s) : USA FCC Part 15.247, 15.205, 15.209, 15.109
 CANADA RSS-210

This test report includes 2 annexes and therefore the total number of pages is 63.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, and must not be reproduced except in full without the written approval of Centro de Tecnología de las Comunicaciones, S.A. (CETECOM).

Date: 2004-11-03	Test operator	Revised by:	Approved by:	Page: 1 of 8
	A. Llamas 	Date: 5-Nov-2004 A. Rojas EMC Manager 	Date: Nov 5 th 2004 F. Broissin Division Director 	

INDEX

1. COMPETENCE AND GUARANTEES	3
2. GENERAL CONDITIONS.....	3
3. CHARACTERISTICS OF THE TEST.....	3
3.1 TEST REQUESTED.....	3
3.2 REQUIREMENTS AND METHOD	3
4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT.....	5
4.1 APPLICANT	5
4.2 REPRESENTATIVE	5
4.3 TEST SAMPLES SUPPLIER	5
4.4 IDENTIFICATION OF ITEM/ITEMS TESTED.....	5
5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS .	6
5.1 USAGE OF SAMPLES.....	6
5.2 PERIOD OF TESTING.....	6
5.3 ENVIROMENTAL CONDITIONS.....	6
6. TEST RESULTS.....	8
7. REMARKS AND COMMENTS.....	8
8. SUMMARY	8

ANNEXES

ANNEX A. TEST RESULTS

ANNEX B. PHOTOGRAPHS

Report No.: 21046RET.101		Page: 2 of 8
Date: 2004-11-03		

1. COMPETENCE AND GUARANTEES

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

Centro de Tecnología de las Comunicaciones (CETECOM), S.A. is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621.

In order to assure the traceability to other national and international laboratories, CETECOM has a calibration and maintenance programme for its measuring equipment.

CETECOM guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at CETECOM at the time of execution of the test.

CETECOM is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

2. GENERAL CONDITIONS

1. This report only refers to the item that has undergone the test.
2. This report does not constitute or imply by its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without written approval of CETECOM.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of CETECOM and the Accreditation Bodies.

3. CHARACTERISTICS OF THE TEST

3.1 TEST REQUESTED

Measurements for frequency hopping spread spectrum equipment (Bluetooth) operating in the 2400 MHz -2483.5 MHz band and using, according to FCC Part 15.247.

3.2 REQUIREMENTS AND METHOD

The test has been carried out according to FCC parts 15.33, 15.35, 15.109, 15.205, 15.209, 15.247 and the document DA 00-705:"Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems".

The testing was performed according to the procedure in ANSI C63.4. Radiated testing was performed in Cetecom's semi-anechoic chamber. This site has been fully described in a report submitted to the FCC and was accepted in a letter dated July 25, 2002.

Report No.: 21046RET.101		Page: 3 of 8
Date: 2004-11-03		

The instrumentation used to perform the testing is listed below:

1. Semianechoic Absorber Lined Chamber IR 11. BS.
2. Control Chamber IR 12.BC.
3. Spectrum Analyzer HP 8566 B.
4. RF Preselector HP 85685A.
5. Quasi-peak adaptor HP 85650A.
6. RF linear amplifier HP 8447.F
7. Antenna mast EM 1072 NMT.
8. Rotating table EM 1084-4. ON.
9. Mast controller EM 1053-22.
10. Rotating table controller EM 1064-4023.
11. Process controller HP 98581C.
12. Harddisk HP 9153.
13. Peripheral unit HP 9153 C.
14. Measurement software HP 85879A.
15. 3 dB attenuator HP 8491A.
16. Bilog antenna CHASE CBL6111.
17. Bilog antenna CHASE CBL6111.
18. Antenna tripod EMCO 11968C.
19. Double-ridge Guide Horn antenna 1-18 GHz HP 11966E.
20. Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J.
21. Switch Unit with RF pre-amplifiers R&S TS8930SU.
22. RF pre-amplifier Miteq JS4-12002600-30-5A.
23. EMI Test Receiver R&S ESIB26.

Report No.: 21046RET.101		Page: 4 of 8
Date: 2004-11-03		

4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data in this section has been supplied by the client.

4.1 APPLICANT

Name or Company: NOKIA CORPORATION

V.A.T.: -----

Address: Rensingstrasse, 15

City: Bochum

Postal code: 44807

Country: Germany

Telephone: +49 2349844577

Fax: +49 1719710570

4.2 REPRESENTATIVE

Name: Detlev Aust

4.3 TEST SAMPLES SUPPLIER

Name or Company: Same as indicated in point 4.1.

Samples undergoing test have been selected by: **the client.**

4.4 IDENTIFICATION OF ITEM/ITEMS TESTED

Product: CARKIT BLUETOOTH

Trade mark: NOKIA

Model: CK-1W

Manufacturer: NOKIA CORPORATION

Country of manufacture: ROMANIA

Manufacture site: Data not available

Description: The Bluetooth car handsfree unit is used in a fixed car installation and it offers a handsfree function and a connection to external devices wirelessly.

5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS

5.1 USAGE OF SAMPLES

Sample M/01 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
21046/01	Carkit Bluetooth with integral antenna	CK-1W	Prototype	04/10/04

Sample M/02 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
21046/02	Carkit Bluetooth with antenna connector	CK-1W	Prototype	04/10/04

1. Sample M/01 has undergone following test(s).
Radiated measurements indicated in annex A.
2. Sample M/02 has undergone following test(s).
All tests indicated in annex A, except radiated measurements.

5.2 PERIOD OF TESTING

The performed test started on 2004-10-04 and finished on 2004-10-05.

The tests as detailed in this report have been performed at CETECOM.

5.3 ENVIROMENTAL CONDITIONS

In the control chamber the following limits were not exceeded during the test:

Temperature	Min. = 25 °C Max. = 26 °C
Relative humidity	Min. = 51 % Max. = 52 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 k Ω
Reference resistance to earth	< 0,5 Ω

Report No.: 21046RET.101		Page: 6 of 8
Date: 2004-11-03		

In the semianechoic chamber (21 meters x 11 meters x 8 meters) the following limits were not exceeded during the test.

Temperature	Min. = 26 °C Max. = 26 °C
Relative humidity	Min. = 50 % Max. = 50 %
Air pressure	Min. = 1019 mbar Max. = 1019 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements the following limits were not exceeded during the test:

Temperature	Min. = 19 °C Max. = 20 °C
Relative humidity	Min. = 45 % Max. = 47 %
Air pressure	Min. = 1020 mbar Max. = 1020 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

Report No.: 21046RET.101		Page: 7 of 8
Date: 2004-11-03		

6. TEST RESULTS

Abbreviations used in the VEREDICT column of the following tables are:

- P** Pass
- F** Fail
- NA** not applicable
- NM** not measured

FCC PART 15 PARAGRAPH	VERDICT			
	NA	P	F	NM
15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation		P		
15.247 Subclause (a) (1) (iii). Number of hopping channels		P		
15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)		P		
15.247 Subclause (b). Maximum peak output power and antenna gain		P		
15.247 Subclause (c). Band-edge of conducted emissions (Transmitter)		P		
15.247 Subclause (c). Emission limitations conducted (Transmitter)		P		
15.247 Subclause (c). Emission limitations radiated (Transmitter)		P		
15.109. Receiver spurious radiation		P		

7. REMARKS AND COMMENTS

None.

8. SUMMARY

Based on the results of the performed test, stated in annex A the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 "TEST REQUESTED".

NOTE: The results presented in this Test Report apply only to the particular item under test declared in section 4.4 "IDENTIFICATION OF ITEM/ITEMS TESTED" of this document, as presented for test on the date(s) declared in section 5, "USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS".

Report No.: 21046RET.101		Page: 8 of 8
Date: 2004-11-03		

**ANNEX A
TEST RESULTS**

Report No: 21046RET.101

Report No:
21046RET.101

Date: 2004-11-03
FET45_00.DOC

Page: 1 of 49

Annex A

INDEX

	Page
TEST CONDITIONS.....	3
Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation.....	5
Section 15.247 Subclause (a) (1) (iii). Number of hopping channels	10
Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time).....	12
Section 15.247 Subclause (b). Maximum peak output power and antenna gain	13
Section 15.247 Subclause (c). Band-edge of conducted emissions (Transmitter)	20
Section 15.247 Subclause (c). Emission limitations conducted (Transmitter)	24
Section 15.247 Subclause (c). Emission limitations radiated (Transmitter)	27
Section 15.109. Receiver spurious radiation	40

Report No: 21046RET.101		Page: 2 of 49
Date: 2004-11-03		Annex A

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 12.0 \text{ Vdc}$$

Type of power supply = DC Voltage from lead-acid battery

Type of antenna = Integral antenna

Maximum Declared Gain for antenna= 0 dB

Operating Temperature Range (°C):

$$T_n = -25 \text{ to } +55$$

TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

The test set-up was made in accordance to the general provisions of ANSI C63.4.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyser via the antenna connector (sma type) provided with the test sample. No coaxial low-loss connecting cable was necessary for such connection so no cable attenuation correction was made.

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

Report No: 21046RET.101		Page: 3 of 49
Date: 2004-11-03		Annex A

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Report No: 21046RET.101		Page: 4 of 49
Date: 2004-11-03		Annex A

Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation**SPECIFICATION**

Frequency hopping system shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


RESULTS

20 dB Bandwidth (see next 3 plots).

	Lowest frequency	Middle frequency	Highest frequency
20 dB Spectrum bandwidth (kHz)	2402 MHz 717.43	2441 MHz 721.44	2480 MHz 717.43
Measurement uncertainty (kHz)	±11		

20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.



Date: 4.OCT.2004 15:55:44

Report No: 21046RET.101 Date: 2004-11-03 <small>FET45_00.DOC</small>		Page: 6 of 49 Annex A
---	--	------------------------------

20 dB BANDWIDTH.
Middle Channel: 2441 MHz.



Date: 4.OCT.2004 15:57:49

Report No: 21046RET.101		Page: 7 of 49
Date: 2004-11-03		Annex A


20 dB BANDWIDTH.
 Highest Channel: 2480 MHz.



Date: 4.OCT.2004 15:59:34

Report No: 21046RET.101 Date: 2004-11-03 FET45_00.DOC		Page: 8 of 49 Annex A
--	--	------------------------------

Carrier frequency separation (see next plot).



The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

Report No: 21046RET.101 Date: 2004-11-03 <small>FET45_00.DOC</small>		Page: 9 of 49 Annex A
---	--	------------------------------


Section 15.247 Subclause (a) (1) (iii). Number of hopping channels

SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels.

RESULTS

The number of hopping channels is 79 (see next two plots).




Number of hopping frequencies: 39

Report No: 21046RET.101		Page: 10 of 49
Date: 2004-11-03		Annex A



Marker 1 [T1] RBW 500 kHz RF Att 40 dB
 Ref Lvl 1.58 dBm VBW 500 kHz
 30 dBm 2.44005812 GHz SWT 5 ms Unit dBm



Date: 4.OCT.2004 16:22:36

Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

Report No: 21046RET.101		Page: 11 of 49 Annex A
Date: 2004-11-03 FET45_00.DOC		

Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)

SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed = $0.4 \times 79 = 31.6$ seconds.

RESULTS


The equipment only supports 1 slot packet (DH1).

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of $625\mu s$ with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/2 = 800$ hops per second with 79 channels. So you have each channel $800/79 = 10.13$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $10.13 \times 31.6 = 320.11$ times of appearance .

Each Tx-time per appearance is $450.9 \mu s$ (see next plot).

So we have $320.11 \times 450.9 \mu s = 144.33 \text{ ms}$ per 31.6 seconds.



Date: 4.OCT.2004 16:25:51

Verdict: PASS

Report No: 21046RET.101		Page: 12 of 49
Date: 2004-11-03		Annex A

Section 15.247 Subclause (b). Maximum peak output power and antenna gain

SPECIFICATION

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm).

RESULTS

MAXIMUM PEAK OUTPUT POWER (CONDUCTED). See next plots.

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	2.28	1.40	-0.21
Measurement uncertainty (dB)	±1.5		

The maximum declared antenna gain for this device is 0 dBi, therefore the maximum theoretical peak radiated power (EIRP) in the three measurement channels for this device is 2.28 dBm or 1.69 mW.

The actual peak radiated power (EIRP) was measured for the lowest, middle and highest frequency (see next plots):

MAXIMUM PEAK OUTPUT POWER (RADIATED).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Instrument reading (dBm)	-34.33	-35.55	-36.49
Correction Factor (dB)	34.96	35.10	35.24
Maximum EIRP peak power (dBm)	0.63	-0.45	-1.25
Measurement uncertainty (dB)	+1.98 / -1.75		

Declared peak gain: 0 dBi


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

Report No: 21046RET.101		Page: 13 of 49
Date: 2004-11-03		Annex A

PEAK OUTPUT POWER (CONDUCTED).

Lowest Channel: 2402 MHz.




Date: 4.OCT.2004 16:28:32

Report No: 21046RET.101 Date: 2004-11-03 <small>FET45_00.DOC</small>		Page: 14 of 49 Annex A
---	--	-------------------------------

PEAK OUTPUT POWER (CONDUCTED).

Middle Channel: 2441 MHz.




Date: 4.OCT.2004 16:29:32

Report No: 21046RET.101		Page: 15 of 49 Annex A
Date: 2004-11-03 <small>FET45_00.DOC</small>		

PEAK OUTPUT POWER (CONDUCTED).

Highest Channel: 2480 MHz.



Date: 4.OCT.2004 16:30:26

Report No: 21046RET.101		Page: 16 of 49 Annex A
Date: 2004-11-03 FET45_00.DOC		


Section 15.247 Subclause (c). Band-edge of conducted emissions (Transmitter)

SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

RESULTS:

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Date: 4.OCT.2004 16:45:23

Verdict: PASS

Report No: 21046RET.101		Page: 20 of 49
Date: 2004-11-03 FET45_00.DOC		Annex A

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Date: 4.OCT.2004 16:36:59

Verdict: PASS

Report No: 21046RET.101		Page: 21 of 49
Date: 2004-11-03		Annex A

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.




Date: 4.OCT.2004 16:49:57

Verdict: PASS

Report No: 21046RET.101 Date: 2004-11-03 <small>FET45_00.DOC</small>		Page: 22 of 49 Annex A
---	--	-------------------------------

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Date: 4.OCT.2004 16:42:41

Verdict: PASS

Report No: 21046RET.101 Date: 2004-11-03 FET45_00.DOC		Page: 23 of 49 Annex A
--	--	-------------------------------


Section 15.247 Subclause (c). Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

RESULTS:

1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 21046RET.101		Page: 24 of 49
Date: 2004-11-03 FET45_00.DOC		Annex A

2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).




Date: 4.OCT.2004 16:55:47

Note: The peak above the limit is the carrier frequency.

Verdict: PASS

<p>Report No: 21046RET.101</p> <p>Date: 2004-11-03</p> <p>FET45_00.DOC</p>		<p>Page: 25 of 49</p> <p>Annex A</p>
--	--	--------------------------------------

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Date: 4.OCT.2004 16:58:44

Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 21046RET.101		Page: 26 of 49
Date: 2004-11-03		Annex A

Section 15.247 Subclause (c). Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Report No: 21046RET.101		Page: 27 of 49
Date: 2004-11-03		Annex A

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

Report No: 21046RET.101 Date: 2004-11-03		Page: 28 of 49 Annex A
--	--	-------------------------------

1. CHANNEL: LOWEST (2402 MHz).

Frequency range 30 MHz-1000 MHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Uncertainty (dB)
39.08	V	Quasi-peak	15.1	± 3.8 dB
44.57	V	Quasi-peak	10.7	± 3.8 dB
48.31	V	Quasi-peak	8.9	± 3.8 dB
65.07	V	Quasi-peak	18.3	± 3.8 dB
91.06	H	Quasi-peak	11.3	± 3.8 dB
105.01	V	Quasi-peak	10.8	± 3.8 dB
110.06	V	Quasi-peak	13.9	± 3.8 dB
117.04	V	Quasi-peak	15.7	± 3.8 dB
143.06	H	Quasi-peak	14.9	± 3.8 dB
169.08	H	Quasi-peak	14.3	± 3.8 dB
180.04	H	Quasi-peak	10.9	± 3.8 dB
195.05	H	Quasi-peak	12.9	± 3.8 dB
221.10	V	Quasi-peak	14.1	± 3.8 dB
247.30	H	Quasi-peak	15.4	± 3.8 dB

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz, and at the harmonic frequencies.

Report No: 21046RET.101		Page: 29 of 49
Date: 2004-11-03		Annex A

2. CHANNEL: MIDDLE (2441 MHz).

Frequency range 30 MHz-1000 MHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Uncertainty (dB)
39.05	V	Quasi-peak	16.7	± 3.8 dB
48.31	V	Quasi-peak	9.4	± 3.8 dB
51.78	V	Quasi-peak	7.3	± 3.8 dB
65.07	V	Quasi-peak	19.3	± 3.8 dB
91.06	H	Quasi-peak	12.0	± 3.8 dB
110.06	V	Quasi-peak	11.3	± 3.8 dB
117.04	V	Quasi-peak	15.2	± 3.8 dB
143.02	H	Quasi-peak	14.7	± 3.8 dB
169.08	H	Quasi-peak	14.2	± 3.8 dB
195.05	H	Quasi-peak	12.9	± 3.8 dB
221.10	V	Quasi-peak	13.7	± 3.8 dB
247.30	H	Quasi-peak	15.7	± 3.8 dB
273.40	H	Quasi-peak	16.1	± 3.8 dB

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz, and at the harmonic frequencies.

Report No:
21046RET.101

Date: 2004-11-03

FET45_00.DOC

Page: 30 of 49

Annex A

3. CHANNEL: HIGHEST (2480 MHz).

Frequency range 30 MHz-1000 MHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Uncertainty (dB)
39.05	V	Quasi-peak	14.7	± 3.8 dB
48.31	V	Quasi-peak	10.5	± 3.8 dB
51.82	V	Quasi-peak	6.9	± 3.8 dB
60.05	V	Quasi-peak	5.4	± 3.8 dB
65.07	V	Quasi-peak	18.0	± 3.8 dB
91.10	H	Quasi-peak	12.5	± 3.8 dB
110.02	V	Quasi-peak	13.1	± 3.8 dB
117.04	V	Quasi-peak	16.0	± 3.8 dB
143.02	H	Quasi-peak	15.3	± 3.8 dB
169.08	H	Quasi-peak	14.4	± 3.8 dB
195.05	H	Quasi-peak	12.2	± 3.8 dB
221.10	V	Quasi-peak	14.9	± 3.8 dB
247.30	H	Quasi-peak	16.5	± 3.8 dB
273.40	H	Quasi-peak	16.5	± 3.8 dB

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.


Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz, and at the harmonic frequencies.

Verdict: PASS

Report No: 21046RET.101		Page: 31 of 49
Date: 2004-11-03		Annex A


FREQUENCY RANGE 30 MHz-1000 MHz.

CHANNEL: LOWEST (2402 MHz).



Resolution bandwidth = 100 kHz. Video bandwidth = 100 kHz.


CHANNEL: MIDDLE (2441 MHz).



Resolution bandwidth = 100 kHz. Video bandwidth = 100 kHz.

<p>Report No: 21046RET.101</p> <p>Date: 2004-11-03 FET45_00.DOC</p>		<p>Page: 32 of 49</p> <p>Annex A</p>
---	--	--------------------------------------

CHANNEL: HIGHEST (2480 MHz).




Resolution bandwidth = 100 kHz. Video bandwidth = 100 kHz.

<p>Report No: 21046RET.101</p> <p>Date: 2004-11-03 FET45_00.DOC</p>		<p>Page: 33 of 49</p> <p>Annex A</p>
---	--	--------------------------------------

FREQUENCY RANGE 1 GHz to 2.9 GHz.

CHANNEL: Lowest (2402 MHz).




Date: 4.OCT.2004 12:18:34

Note: The peak above the limit is the carrier frequency.

Report No: 21046RET.101 Date: 2004-11-03 FET45_00.DOC		Page: 34 of 49 Annex A
--	--	-------------------------------

CHANNEL: Middle (2441 MHz).




Date: 4.OCT.2004 12:36:50

Note: The peak above the limit is the carrier frequency.

Report No: 21046RET.101 Date: 2004-11-03 <small>FET45_00.DOC</small>		Page: 35 of 49 Annex A
---	--	-------------------------------

CHANNEL: Highest (2480 MHz).




Date: 4.OCT.2004 12:44:41

Note: The peak above the limit is the carrier frequency.

Report No: 21046RET.101 Date: 2004-11-03 <small>FET45_00.DOC</small>		Page: 36 of 49 Annex A
---	--	-------------------------------

FREQUENCY RANGE 18 GHz to 25 GHz.



Date: 4.OCT.2004 13:29:37

(This plot is valid for all three channels).

Report No: 21046RET.101 Date: 2004-11-03 FET45_00.DOC		Page: 39 of 49 Annex A
--	--	-------------------------------

Section 15.109. Receiver spurious radiation

SPECIFICATION

The field strength shall not exceed the following values:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Report No: 21046RET.101		Page: 40 of 49
Date: 2004-11-03		Annex A

1. CHANNEL: LOWEST (2402 MHz).

Frequency range 30 MHz-1000 MHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Uncertainty (dB)
39.01	V	Quasi-peak	13.9	± 3.8 dB
65.07	V	Quasi-peak	17.9	± 3.8 dB
91.06	H	Quasi-peak	11.5	± 3.8 dB
110.06	V	Quasi-peak	11.3	± 3.8 dB
117.04	V	Quasi-peak	16.5	± 3.8 dB
135.08	V	Quasi-peak	11.9	± 3.8 dB
143.02	H	Quasi-peak	14.9	± 3.8 dB
169.08	H	Quasi-peak	15.9	± 3.8 dB
195.08	H	Quasi-peak	12.2	± 3.8 dB
221.10	V	Quasi-peak	13.7	± 3.8 dB
247.30	H	Quasi-peak	15.6	± 3.8 dB

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Report No: 21046RET.101		Page: 41 of 49
Date: 2004-11-03		Annex A

2. CHANNEL: MIDDLE (2441 MHz).

Frequency range 30 MHz-1000 MHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Uncertainty (dB)
39.05	V	Quasi-peak	15.2	± 3.8 dB
45.05	V	Quasi-peak	11.1	± 3.8 dB
51.86	V	Quasi-peak	9.6	± 3.8 dB
65.07	V	Quasi-peak	20.3	± 3.8 dB
91.10	H	Quasi-peak	11.9	± 3.8 dB
110.06	V	Quasi-peak	13.2	± 3.8 dB
117.04	V	Quasi-peak	15.9	± 3.8 dB
143.06	H	Quasi-peak	15.0	± 3.8 dB
169.08	H	Quasi-peak	15.2	± 3.8 dB
195.05	H	Quasi-peak	11.6	± 3.8 dB
221.10	V	Quasi-peak	14.0	± 3.8 dB
247.30	H	Quasi-peak	15.5	± 3.8 dB
273.40	H	Quasi-peak	15.4	± 3.8 dB

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Report No: 21046RET.101		Page: 42 of 49
Date: 2004-11-03		Annex A

3. CHANNEL: HIGHEST (2480 MHz).

Frequency range 30 MHz-1000 MHz.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Uncertainty (dB)
45.05	V	Quasi-peak	10.1	± 3.8 dB
65.07	V	Quasi-peak	8.4	± 3.8 dB
135.08	V	Quasi-peak	13.2	± 3.8 dB

Frequency range 1 GHz-25 GHz.

No spurious signals were found in all the range.


Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Verdict: PASS.

Report No: 21046RET.101		Page: 43 of 49
Date: 2004-11-03		Annex A


FREQUENCY RANGE 30 MHz-1000 MHz.

CHANNEL: LOWEST (2402 MHz).



Resolution bandwidth = 100 kHz. Video bandwidth = 100 kHz.


CHANNEL: MIDDLE (2441 MHz).



Resolution bandwidth = 100 kHz. Video bandwidth = 100 kHz.

<p>Report No: 21046RET.101</p> <p>Date: 2004-11-03 FET45_00.DOC</p>		<p>Page: 44 of 49</p> <p>Annex A</p>
---	--	--------------------------------------


CHANNEL: HIGHEST (2480 MHz).



Resolution bandwidth = 100 kHz. Video bandwidth = 100 kHz.

<p>Report No: 21046RET.101</p> <p>Date: 2004-11-03 FET45_00.DOC</p>		<p>Page: 45 of 49</p> <p>Annex A</p>
---	--	--------------------------------------


FREQUENCY RANGE 1 GHz-2.9 GHz.



Date: 4.OCT.2004 11:44:45

(This plot is valid for all three channels).

FREQUENCY RANGE 18 GHz-25 GHz.



(This plot is valid for all three channels).

Report No: 21046RET.101		Page: 49 of 49
Date: 2004-11-03 FET45_00.DOC		Annex A

ANNEX B

PHOTOGRAPHS **(Number of photographs: 6)**

Report No.: 21046RET.101

Report No.:
21046RET.101

Date: 2004-11-03

Page: 1 of 7

Annex B

1. Equipment (external view)



Report No.:
21046RET.101


Date: 2004-11-03

FET18_00.DOC

Page: 2 of 7

Annex B

2. Equipment for conducted measurements.




Report No.:
21046RET.101

Date: 2004-11-03

Page: 3 of 7

Annex B

3. General test set-up for radiated measurements.



Report No.:
21046RET.101


Date: 2004-11-03

FET18_00.DOC

Page: 4 of 7

Annex B

4. Test set-up for radiated measurements below 1 GHz.



Report No.:
21046RET.101

Date: 2004-11-03

FET18_00.DOC

Page: 5 of 7

Annex B

5. Test set-up for radiated measurements above 1 GHz.



Report No.:
21046RET.101


Date: 2004-11-03

FET18_00.DOC

Page: 6 of 7

Annex B

6. Test set-up for RF conducted measurements.



Report No.:
21046RET.101

Date: 2004-11-03

FET18_00.DOC

Page: 7 of 7

Annex B