

RF Exposure information

The Allegro Cellular is classified as mobile.

The Allegro Cellular includes BLE , LoRa transmitters operating according to FCC part 15 subpart C section 15.247 (DTS) and approved LTE CAT-M module that approved under FCC ID: P27-TPM540.

The RF technologies: LoRaWAN, BLE and LTE CAT-M (Bands 2,4 and 12) is not transmitting simultaneously.

The FCC power density limit for general population/uncontrolled exposure is 1 mW/cm² for 2.4 GHz for BLE transmitter.

Limit for power density for general population/uncontrolled exposure is 1 mW/cm² for 1500 -100000 MHz frequency range.

The FCC power density limit for general population/uncontrolled exposure is 0.609 mW/cm² for 914.9 MHz for LoRa transmitter.

Limit for power density for general population/uncontrolled exposure is f/1500 mW/cm² for 300-1500 MHz frequency range.

The power density **P (mW/cm²) = $P_T / 4\pi r^2$**

BLE transmitter

P_T is the transmitted power, which is equal to the peak transmitter output power 4.92 dBm plus maximum antenna gain 2.5 dBi, the maximum equivalent isotopically radiated power EIRP is

$$P_T = 4.92 \text{ dBm} + 2.5 \text{ dBi} = 7.42 \text{ dBm} = 5.52 \text{ mW}.$$

The power density at 20 cm (minimum safe distance, required for mobile devices), calculated as follows:

$$5.52 \text{ mW} / 4\pi (20 \text{ cm})^2 = 0.001 \text{ mW/cm}^2 \ll 1 \text{ mW/cm}^2$$

General public cannot be exposed to dangerous RF level.

LoRa transmitter

P_T is the transmitted power, which is equal to the peak transmitter output power 27.94 dBm plus maximum antenna gain 0 dBi, the maximum equivalent isotopically radiated power EIRP is

$$P_T = 27.94 \text{ dBm} + 0 \text{ dBi} = 27.94 \text{ dBm} = 622.3 \text{ mW}.$$

The power density at 20 cm (minimum safe distance, required for mobile devices), calculated as follows:

$$622.3 \text{ mW} / 4\pi (20 \text{ cm})^2 = 0.123 \text{ mW/cm}^2 \ll 0.609 \text{ mW/cm}^2$$

General public cannot be exposed to dangerous RF level.