

Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transmitter (Car Unit) for a RC Car. The sample supplied operated on 40 channels of BT 4.2 BLE only, normally at 2402 - 2480 MHz. The channels are separated with 2 MHz spacing.

The EUT is powered by 6.4V rechargeable battery or 6.0V (4 x 1.5V "AA" batteries). After switch on the EUT, the car will be moved forward or backward and turned left and right based on the switches pressed in the phone application controller.

Antenna Type: Internal, Integral antenna

Antenna Gain: 0dBi

Nominal rated field strength is 97.8 dBμV/m at 3m

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 100.8dBμV/m at 3m in frequency 2.402GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 * 5 / \sqrt{2.483.5} \text{ mW}$

= 9.52 mW

According to the KDB 412172 D01:

$\text{EIRP} = [(\text{FS} * \text{D})^2 * 1000 / 30]$

Calculated Field Strength for 9.52mW is 105dBuV/m @3m

Since maximum field strength plus production tolerance < = 105dBuV/m @3m and antenna gain is > = 0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.