

# FCC RF Test Report

APPLICANT : VERTU Corporation Limited  
EQUIPMENT : Cellular Telephone  
BRAND NAME : VERTU  
MODEL NAME : SIGNATURE TOUCH  
TYPE NAME : VM-03  
FCC ID : P7QVM-03  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DTS) Digital Transmission System


The product was received on Jul. 02, 2015 and testing was completed on Aug. 16, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.**

---

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : P7QVM-03

Page Number : 1 of 42

Report Issued Date : Sep. 07, 2015

Report Version : Rev. 02

Report Template No.: BU5-FR15CBT4.0 Version 1.0



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard .....	6
1.5 Modification of EUT .....	7
1.6 Testing Location .....	7
1.7 Applicable Standards.....	8
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>9</b>
2.1 Descriptions of Test Mode .....	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system .....	13
2.5 EUT Operation Test Setup .....	13
2.6 Measurement Results Explanation Example.....	13
<b>3 TEST RESULT .....</b>	<b>14</b>
3.1 6dB and 99% Bandwidth Measurement .....	14
3.2 Peak Output Power Measurement .....	19
3.3 Power Spectral Density Measurement .....	20
3.4 Conducted Band Edges and Spurious Emission Measurement .....	25
3.5 Radiated Band Edges and Spurious Emission Measurement .....	30
3.6 AC Conducted Emission Measurement.....	34
3.7 Antenna Requirements.....	40
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>41</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>42</b>
<b>APPENDIX A. CONDUCTED TEST RESULTS</b>	
<b>APPENDIX B. RADIATED TEST RESULTS</b>	
<b>APPENDIX C. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR570205B	Rev. 01	Initial issue of report	Aug. 28, 2015
FR570205B	Rev. 02	Updating the Bluetooth version 4.0 to 4.1.	Sep. 07, 2015

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(1)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.54 dB at 41.070 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.90 dB at 13.558 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**VERTU Corporation Limited**

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom

## 1.2 Manufacturer

**VERTU Corporation Limited**

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Cellular Telephone
Brand Name	VERTU
Model Name	SIGNATURE TOUCH
Type Name	VM-03
FCC ID	P7QVM-03
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v4.1 EDR/LE
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessory		
AC Adapter	Brand Name	VERTU
	Model Name	AC-32V
Car Charger	Brand Name	VERTU
	Model Name	DC-30V
Battery	Brand Name	VERTU
	Model Name	VBL-02
Portable Power Charger	Brand Name	VERTU
	Model Name	DC-15V
Earphone 1	Brand Name	VERTU
	Model Name	WH-4V
Earphone 2	Brand Name	VERTU
	Model Name	WH-5V
Earphone 3	Brand Name	VERTU
	Model Name	HP-1V
USB Cable	Brand Name	VERTU
	Model Name	CA-225DV
Wireless Charger	Brand Name	VERTU
	Model Name	AC-35V
Wireless Speaker	Brand Name	VERTU
	Model Name	SP-1V

#### 1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	2.36 dBm (0.0017 W)
99% Occupied Bandwidth	1.058MHz
Antenna Type	PIFA Antenna type with gain -2.20 dBi
Type of Modulation	Bluetooth LE : GFSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2009 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH11-HY	

**Note:** The test site complies with ANSI C63.4 2009 requirement.



## **1.7 Applicable Standards**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ♦ ANSI C63.10-2009

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth 4.1 – LE RF Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	1.100 dBm
Ch19	2440MHz	<b>2.360 dBm</b>
Ch39	2480MHz	1.960 dBm

- The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (X plane as worst plane) from all possible combinations.
- AC power line Conducted Emission was tested under maximum output power.


## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 4.1 – LE / GFSK
<b>Conducted TCs</b>	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
<b>Radiated TCs</b>	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_1Mbps with WPC Mode
<b>AC Conducted Emission</b>	Mode 1: LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC On + Earphone 2 + Battery + USB Cable (Charging from Adapter)


## 2.3 Connection Diagram of Test System

### <Bluetooth 4.1 – LE Tx Mode>



### <EUT with Wireless Charger Mode>



**<AC Conducted Emissions>**

## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, "QRCT" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth


Test data refer to Appendix A.

6 dB Bandwidth Plot on Channel 00




Date: 6.AUG.2015 01:26:52

### 6 dB Bandwidth Plot on Channel 19



Date: 6.AUG.2015 01:30:02

### 6 dB Bandwidth Plot on Channel 39




Date: 6.AUG.2015 01:32:49



### 3.1.6 Test Result of 99% Occupied Bandwidth

Test data refer to Appendix A.


### 99% Bandwidth Plot on Channel 00



Date: 6.AUG.2015 01:28:51




99% Occupied Bandwidth Plot on Channel 19



Date: 6.AUG.2015 01:31:35

99% Occupied Bandwidth Plot on Channel 39



Date: 6.AUG.2015 01:35:16

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Test data refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup






### 3.3.5 Test Result of Power Spectral Density

Test data refer to Appendix A.

### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


PSD 100kHz Plot on Channel 00



Date: 6.AUG.2015 01:27:34




PSD 100kHz Plot on Channel 19



Date: 6.AUG.2015 01:30:44

PSD 100kHz Plot on Channel 39




Date: 6.AUG.2015 01:33:32



### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)


PSD 3kHz Plot on Channel 00



Date: 6.AUG.2015 01:27:13




### PSD 3kHz Plot on Channel 19



Date: 6.AUG.2015 01:30:24

### PSD 3kHz Plot on Channel 39



Date: 6.AUG.2015 01:33:10



### 3.4 Conducted Band Edges and Spurious Emission Measurement

#### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


#### 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


#### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges

#### Low Band Edge Plot on Channel 00



Date: 6.AUG.2015 01:28:00

#### High Band Edge Plot on Channel 39




Date: 6.AUG.2015 01:34:05



### 3.4.6 Test Result of Conducted Spurious Emission

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


##### GFSK Channel 00



Date: 6.AUG.2015 01:28:21

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


##### GFSK Channel 00



Date: 6.AUG.2015 01:28:39




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 6.AUG.2015 01:31:05


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19



Date: 6.AUG.2015 01:31:23




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 6.AUG.2015 01:34:44

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39



Date: 6.AUG.2015 01:35:02



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
  2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
  3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
  4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
  5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
  6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  7. Use the following spectrum analyzer settings:
    - (1) Span shall wide enough to fully capture the emission being measured;
    - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
    - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.
- For average measurement:
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
  - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T( $\mu$ s)	1/T(kHz)	VBW Setting
Bluetooth 4.1 - LE	64.97	408	2.45	3kHz

### 3.5.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz





For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

### 3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix B.

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.


#### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

#### <Original Test Result>

Test Mode :	Mode 1	Temperature :	23~25℃
Test Engineer :	Eric Jeng and Kai-Chun Chu	Relative Humidity :	48~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC On + Earphone 2 + Battery + USB Cable (Charging from Adapter)		




#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.430000	33.4	Off	L1	19.5	23.9	57.3
0.502000	34.6	Off	L1	19.4	21.4	56.0
0.654000	34.6	Off	L1	19.5	21.4	56.0
0.862000	31.8	Off	L1	19.5	24.2	56.0
1.110000	33.9	Off	L1	19.5	22.1	56.0
13.558000	58.8	Off	L1	19.9	1.2	60.0
18.854000	36.1	Off	L1	20.0	23.9	60.0

#### Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.430000	25.1	Off	L1	19.5	22.2	47.3
0.502000	27.3	Off	L1	19.4	18.7	46.0
0.654000	24.5	Off	L1	19.5	21.5	46.0
0.862000	20.6	Off	L1	19.5	25.4	46.0
1.110000	21.0	Off	L1	19.5	25.0	46.0
13.558000	55.4	Off	L1	19.9	-5.4	50.0
18.854000	21.6	Off	L1	20.0	28.4	50.0

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	23~25℃
<b>Test Engineer :</b>	Eric Jeng and Kai-Chun Chu	<b>Relative Humidity :</b>	48~52%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC On + Earphone 2 + Battery + USB Cable (Charging from Adapter)		


**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.438000	30.9	Off	L1	19.5	26.2	57.1
0.582000	32.0	Off	L1	19.4	24.0	56.0
1.070000	31.8	Off	L1	19.6	24.2	56.0
1.670000	28.7	Off	L1	19.6	27.3	56.0
13.558000	59.9	Off	L1	19.9	0.1	60.0
16.574000	30.5	Off	L1	20.0	29.5	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.438000	19.8	Off	L1	19.5	27.3	47.1
0.582000	29.4	Off	L1	19.4	16.6	46.0
1.070000	20.2	Off	L1	19.6	25.8	46.0
1.670000	16.7	Off	L1	19.6	29.3	46.0
13.558000	56.7	Off	L1	19.9	-6.7	50.0
16.574000	17.9	Off	L1	20.0	32.1	50.0

**<Terminal Test Result>**

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	23~25°C
<b>Test Engineer :</b>	Eric Jeng and Kai-Chun Chu	<b>Relative Humidity :</b>	48~52%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC On + Earphone 2 + Battery + USB Cable (Charging from Adapter)		


**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	50.4	Off	L1	19.9	9.6	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	41.1	Off	L1	19.9	8.9	50.0



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	23~25℃
<b>Test Engineer :</b>	Eric Jeng and Kai-Chun Chu	<b>Relative Humidity :</b>	48~52%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	LTE Band 7 Idle + WLAN Link + Bluetooth Link + NFC On + Earphone 2 + Battery + USB Cable (Charging from Adapter)		

**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	42.3	Off	N	20.0	17.7	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	37.0	Off	N	20.0	13.0	50.0



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.





## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 14, 2015	Jul. 31, 2015~ Aug. 06, 2015	Jan. 13, 2016	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 14, 2015	Jul. 31, 2015~ Aug. 06, 2015	Jan. 13, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jun. 18, 2015	Jul. 31, 2015~ Aug. 06, 2015	Jun. 17, 2016	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890089	1V~20V 0.5A~5A	Jan. 14, 2015	Jul. 31, 2015~ Aug. 06, 2015	Jan. 13, 2016	Conducted (TH05-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 03, 2014	Aug. 06, 2015~ Aug. 16, 2015	Nov. 02, 2015	Radiation (03CH11-HY)
Loop Antenna	TESEQ	HLA 6120	31244	9kHz~30MHz	Feb. 02, 2015	Aug. 06, 2015~ Aug. 16, 2015	Feb. 01, 2016	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 24, 2014	Aug. 06, 2015~ Aug. 16, 2015	Nov. 23, 2015	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D	35414	30MHz~1GHz	Oct. 24, 2014	Aug. 06, 2015~ Aug. 16, 2015	Oct. 23, 2015	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 03, 2014	Aug. 06, 2015~ Aug. 16, 2015	Oct. 02, 2015	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 19, 2014	Aug. 06, 2015~ Aug. 16, 2015	Nov. 18, 2015	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 20, 2014	Aug. 06, 2015~ Aug. 16, 2015	Nov. 19, 2015	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1902247	1GHz~18GHz	Jul. 01, 2015	Aug. 06, 2015~ Aug. 16, 2015	Jun. 30, 2016	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHZ	Sep. 24, 2014	Aug. 06, 2015~ Aug. 16, 2015	Sep. 23, 2015	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 06, 2015~ Aug. 16, 2015	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1~4m	N/A	Aug. 06, 2015~ Aug. 16, 2015	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0-360 degree	N/A	Aug. 06, 2015~ Aug. 16, 2015	N/A	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A	MY53290053	20Hz to 26.5GHz	Feb. 02, 2015	Aug. 06, 2015~ Aug. 16, 2015	Feb. 01, 2016	Radiation (03CH11-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Aug. 06, 2015~ Aug. 16, 2015	Jun. 01, 2016	Radiation (03CH11-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz – 2.75GHz	Dec. 01, 2014	Aug. 07, 2015~ Aug. 11, 2015	Nov. 30, 2015	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2014	Aug. 07, 2015~ Aug. 11, 2015	Dec. 01, 2015	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 07, 2015~ Aug. 11, 2015	N/A	Conduction (CO05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
--	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.90
--	------



## **Appendix A. Conducted Test Results**

**Bluetooth Low Energy**

Test Engineer:	Bill Kuo	Temperature:	21~25	°C
Test Date:	2015/8/5	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.06	0.68	0.50	Pass
BLE	1Mbps	1	19	2440	1.06	0.67	0.50	Pass
BLE	1Mbps	1	39	2480	1.06	0.67	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	1.10	30.00	-2.20	-1.10	36.00	Pass
BLE	1Mbps	1	19	2440	2.36	30.00	-2.20	0.16	36.00	Pass
BLE	1Mbps	1	39	2480	1.96	30.00	-2.20	-0.24	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
**(Reporting Only)**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	1.87	-0.65
BLE	1Mbps	1	19	2440	1.87	1.01
BLE	1Mbps	1	39	2480	1.87	0.54

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-1.84	-16.82	-2.20	8.00	Pass
BLE	1Mbps	1	19	2440	-0.10	-14.95	-2.20	8.00	Pass
BLE	1Mbps	1	39	2480	-0.77	-15.65	-2.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



## Appendix B. Radiated Spurious Emission

Test Engineer :	Nick Yu and James Chiu	Temperature :	21~23°C
		Relative Humidity :	56~59%

### <ETU with Adapter Mode>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
BLE CH 00 2402MHz		2363.82	50.46	-23.54	74	51.36	27.14	6.01	34.05	100	111	P	H
		2349.87	41.31	-12.69	54	42.31	27.1	5.95	34.05	100	111	A	H
	*	2402.338	90.74	-	-	91.54	27.23	6.01	34.04	100	111	P	H
	*	2402.087	90.13	-	-	90.93	27.23	6.01	34.04	100	111	A	H
													H
													H
		2363.46	50.73	-23.27	74	51.69	27.14	5.95	34.05	100	296	P	V
		2380.38	42.44	-11.56	54	43.28	27.19	6.01	34.04	100	296	A	V
	*	2402.254	88.38	-	-	89.18	27.23	6.01	34.04	100	296	P	V
	*	2402.004	87.69	-	-	88.49	27.23	6.01	34.04	100	296	A	V
													V
													V
BLE CH 19 2440MHz		2387.67	50.68	-23.32	74	51.48	27.23	6.01	34.04	125	110	P	H
		2381.19	41.42	-12.58	54	42.26	27.19	6.01	34.04	125	110	A	H
	*	2440.247	92.95	-	-	93.57	27.37	6.04	34.03	125	110	P	H
	*	2440.08	92.31	-	-	92.93	27.37	6.04	34.03	125	110	A	H
		2486.4	50.93	-23.07	74	51.39	27.46	6.09	34.01	125	110	P	H
		2489.36	41.87	-12.13	54	42.29	27.5	6.09	34.01	125	110	A	H
		2311.62	50.59	-23.41	74	51.76	27.01	5.89	34.07	100	296	P	V
		2361.93	41.6	-12.4	54	42.56	27.14	5.95	34.05	100	296	A	V
	*	2439.746	89.84	-	-	90.46	27.37	6.04	34.03	100	296	P	V
	*	2440.08	89.17	-	-	89.79	27.37	6.04	34.03	100	296	A	V
		2494.8	51.05	-22.95	74	51.46	27.5	6.09	34	100	296	P	V
		2488.8	41.82	-12.18	54	42.24	27.5	6.09	34.01	100	296	A	V



<b>BLE CH 39 2480MHz</b>	*	2479.826	92.46	-	-	92.94	27.46	6.07	34.01	100	110	P	H
	*	2480.076	91.82	-	-	92.3	27.46	6.07	34.01	100	110	P	H
		2489.04	51.33	-22.67	74	51.75	27.5	6.09	34.01	100	110	P	H
		2494.6	41.97	-12.03	54	42.38	27.5	6.09	34	100	110	A	H
													H
													H
	*	2479.826	89.48	-	-	89.96	27.46	6.07	34.01	100	296	P	V
	*	2480.076	88.8	-	-	89.28	27.46	6.07	34.01	100	296	A	V
		2496.08	50.87	-23.13	74	51.28	27.5	6.09	34	100	296	P	V
		2493.36	41.95	-12.05	54	42.36	27.5	6.09	34	100	296	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
BLE CH 00 2402MHz		4806	36.97	-37.03	74	62.11	31.3	8.65	65.09	100	0	P	H
													H
													H
													H
		4806	36.56	-37.44	74	61.7	31.3	8.65	65.09	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4878	37.18	-36.82	74	62.1	31.41	8.69	65.02	100	0	P	H
		7320	41.57	-32.43	74	59.93	36.32	10.39	65.07	100	0	P	H
													H
													H
		4878	36.78	-37.22	74	61.7	31.41	8.69	65.02	100	0	P	V
		7320	41.47	-32.53	74	59.83	36.32	10.39	65.07	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4962	37.79	-36.21	74	62.35	31.54	8.83	64.93	100	0	P	H
		7440	41.2	-32.8	74	59.18	36.59	10.52	65.09	100	0	P	H
													H
													H
		4962	37.74	-36.26	74	62.3	31.54	8.83	64.93	100	0	P	V
		7440	40.83	-33.17	74	58.81	36.59	10.52	65.09	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

## Emission below 1GHz

## 2.4GHz BLE (LF)

[illegible]





**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## &lt;ETU with WPC Mode&gt;

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2350.77	50.71	-23.29	74	51.71	27.1	5.95	34.05	100	223	P	H
		2330.34	40.72	-13.28	54	41.78	27.05	5.95	34.06	100	223	A	H
	*	2402.254	93.44	-	-	94.24	27.23	6.01	34.04	100	223	P	H
	*	2402.004	92.49	-	-	93.29	27.23	6.01	34.04	100	223	A	H
													H
													H
		2388.84	51.19	-22.81	74	51.99	27.23	6.01	34.04	110	145	P	V
		2387.58	40.71	-13.29	54	41.51	27.23	6.01	34.04	110	145	A	V
	*	2401.837	91.61	-	-	92.41	27.23	6.01	34.04	110	145	P	V
	*	2402.004	90.61	-	-	91.41	27.23	6.01	34.04	110	145	A	V
													V
													V
<b>Remark</b> <ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against Peak and Average limit line.</li> </ol>													

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		4806	36.48	-37.52	74	61.62	31.3	8.65	65.09	100	0	P	H
													H
													H
													H
		4806	35.83	-38.17	74	60.97	31.3	8.65	65.09	100	0	P	V
													V
													V
													V
<b>Remark</b> <ol style="list-style-type: none"> <li>No other spurious found.</li> <li>All results are PASS against Peak and Average limit line.</li> </ol>													

## Emission below 1GHz

## 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz  BLE  LF		87.51	27.44	-12.56	40	49.85	8.1	1.28	31.79			P	H
		122.61	30.65	-12.85	43.5	49.7	11.45	1.28	31.78			P	H
		189.03	32.24	-11.26	43.5	54.2	8.18	1.64	31.78	112	214	P	H
		314	23.35	-22.65	46	39.57	13.44	2.11	31.77			P	H
		729.8	22.48	-23.52	46	31.44	19.79	3.25	32			P	H
		954.5	23.34	-22.66	46	30.15	20.51	3.68	31			P	H
													H
													H
													H
													H
													H
													H
		81.03	27.17	-12.83	40	51.11	6.81	1.04	31.79	100	231	P	V
		122.07	29.97	-13.53	43.5	49.03	11.44	1.28	31.78			P	V
		243.3	24.35	-21.65	46	43.17	11.16	1.79	31.77			P	V
		394.5	24.53	-21.47	46	38.58	15.43	2.32	31.8			P	V
		741.7	22.54	-23.46	46	31.48	19.8	3.25	31.99			P	V
		911.1	27.81	-18.19	46	35.49	20.11	3.55	31.34			P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

3. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

4. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

3. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

4. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

3. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

4. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**