

5473A Clouds Rest Road: Mariposa, CA 95338: Phone 209-966-5420: Fax 209-742-6133

Maximum Permissible Exposure Calculations

Date of Report: January 9, 2002

Calculations prepared for: Calculations prepared by:

Dustin Oaks

IP Mobile NetCKC Laboratories, Inc.11909 East Telegraph Road5473A Clouds Rest RoadSanta Fe Springs, CA 90670Mariposa, CA 95338

Model Number: IP1

FCC Identification: MI7-IPMNIP1

Fundamental Operating Frequency: 150MHz - 156MHz

Maximum Rated Output Power: 60.00 Watts Measured Output Power: 60.25 Watts

Power Output and Operating Frequency Information used for these calculations were from: CKC Laboratories, Test Report # FC01-064A

In accordance with 47CFR2.1093(d)(2), source based time averaging is allowed for this type of device:

Source Based Time Averaging = 20LOG(ON time/TOTAL time)= 20LOG(389 mS/(389+310=699 mS))= -5.09 dB

- -3.09uD

Therefore the Power Output = 47.8 dBm (60.25W) - 5.09 dB = 42.71 dBm (18.66W)

MPE Limit in accordance with 1.1310(b): Limits for general population/uncontrolled exposure

MPE Limit = 0.2mW/cm² or 27.5V/M

Power Output (Watts)	Distance (Meters)	Power Density (mW/cm ²)	Result
18.66	1.0	0.1485	PASS
18.66	0.87	0.1962	PASS

Power Density $(W/M^2) = (30 * P_t * G) / (d^2 * Z_0)$

 P_t = Power Delivered to the Antenna G =

d = Distance in meters Zo = Impedance of Free Space

The typical vehicle used by police was measured, and a separation distance of 1 meter was found to be an appropriate distance. Under normal operating conditions, the antenna will maintain a separation of 1 meter from all persons. As can be seen from the MPE results, this device passes the limits specified in 1.1310 at a distance of 0.87 Meters (34.25 Inches).