


# FCC RF Exposure Report

**FCC ID** : I8803935  
**Equipment** : 802.11be (WiFi 7) Triple-Radio Unified Pro  
Access Point  
**Model No.** : WBE660S  
**Brand Name** : ZYXEL  
**Applicant** : Zyxel Communications Corporation  
**Address** : No.2 Industry East RD. IX, Hsinchu Science  
Park, Hsinchu 30075, Taiwan, R.O.C  
**Standard** : 47 CFR FCC Part 2.1091  
**Received Date** : Jul. 17, 2023  
**Tested Date** : Aug. 08 ~ Aug. 31, 2023

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:

  
Along Chen / Assistant Manager

  
Gary Chang / Manager

## Table of Contents

<b>1</b>	<b>MPE EVALUATION OF MOBILE DEVICES .....</b>	<b>4</b>
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	4
1.2	MPE EVALUATION FORMULA .....	4
1.3	REFERENCE GUIDANCE .....	4
1.4	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE .....	4
1.5	MEASUREMENT UNCERTAINTY .....	4
1.6	MPE EVALUATION RESULTS .....	5
1.7	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.....	7
<b>2</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>8</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FA371702	Rev. 01	Initial issue	Sep. 22, 2023

# 1 MPE EVALUATION OF MOBILE DEVICES

## 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm <sup>2</sup> )	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

## 1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

## 1.3 REFERENCE GUIDANCE

447498 D01 General RF Exposure Guidance v06

## 1.4 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

## 1.5 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

## 1.6 MPE EVALUATION RESULTS

### *Non-beamforming mode*

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	*Ratio	Pass / Fail
2412-2462	29.81	30.0	4.34	25	0.346	1	0.346	Pass
5180-5240	28.06	28.5	7.28	25	0.482	1	0.482	Pass
5260-5320	21.94	22.0	7.56	25	0.115	1	0.115	Pass
5500-5720	22.14	22.5	7.37	25	0.124	1	0.124	Pass
5745-5825	27.83	28.0	7.64	25	0.467	1	0.467	Pass

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Ratio*	Pass / Fail
2402-2480	5.72	6.0	0.97	25	0.001	1	0.001	Pass

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	*Ratio	Pass / Fail
5925-6425	21.54	22	7.41	25	0.111	1	0.111	Pass
6425-6525	21.87	22	7.01	25	0.101	1	0.101	Pass
6525-6875	19.44	20	7.01	25	0.064	1	0.064	Pass
6875-7125	21.97	22	6.79	25	0.096	1	0.096	Pass

\*Ratio = Power density / Limit.

### Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Ratio*	Pass / Fail
2412-2462	23.79	24.0	8.46	25	0.224	1	0.224	Pass
5180-5240	22.04	22.5	7.28	25	0.121	1	0.121	Pass
5260-5320	15.92	16.0	7.56	25	0.029	1	0.029	Pass
5500-5720	16.12	16.5	7.37	25	0.031	1	0.031	Pass
5745-5825	21.81	22.0	7.64	25	0.117	1	0.117	Pass

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	*Ratio	Pass / Fail
5925-6425	15.52	16	7.41	25	0.028	1	0.028	Pass
6425-6525	15.85	16	7.01	25	0.025	1	0.025	Pass
6525-6875	13.42	13.5	7.01	25	0.014	1	0.014	Pass
6875-7125	15.95	16	6.79	25	0.024	1	0.024	Pass

Ratio\* = Power density / Limit.

## 1.7 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

### *Non-beamforming mode*

Mode	Max Ratio of Each Mode
WLAN 2.4GHz	0.346
WLAN 5GHz	0.482
WLAN 6GHz	0.111
Sum	0.939
Limit	1
Pass / Fail	Pass

### *Beamforming mode*

Mode	Max Ratio of Each Mode
WLAN 2.4GHz	0.224
WLAN 5GHz	0.121
WLAN 6GHz	0.028
Sum	0.373
Limit	1
Pass / Fail	Pass

## 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan  
(R.O.C.)

### **Kwei Shan**

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)  
No.2-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC\_Service@icertifi.com.tw

==END==