140

GETTING STARTED

140

Insert the micro USB adapter

Lift up the micro USB cover on the back of your camera. Then plug your cable into the camera. (Press firmly)

2

Mount your camera on the wall

Secure your camera on the wall following our mounting instructions.

Secure the cable

3

Snap the included strain-relief clip to your cable near the top. Then screw it into the wall near your camera (approx. 6 in. away)

ART-10273-00 USA

Below Notes Pertain only to Pulp Trays									
NOTES:									
1. ALL RADII ARE TO BE 3.0mm.									
2. DRAFT ANGLE TO BE 3 DEGREES.					-	-			-
WEIGHT TOLERANCE TO BE 10%.					PROJECT #: SLSI2	20003A CUSTOMER: Sim	pliSafe		SUBSTRAT
 PART NUMBER; REVISION; PART DESCRIPTION AND RECYCLE LOGO TO BE CLEARLY EMBOSSED ON PULP. FOR ALL UNSPECIFIED DIMENSIONS, REFER TO 3D DATA. 					CRM #: NA	BRAND: NA			PROCESS:
5. FUR ALL UNSPECIFIED DIMENSIONS, REFER TO 3D DATA.			6	gpa GLOBAL	COMPONENT #: NA	A STYLE: NA			
METRIC MIN BOX COMPRESSION (kg) 127	CORRUGATION / GRAIN DIRECTION				ARTWORK #: NA	CUTTER / CAD #:	NA		CHEK L
BLANK SIZE (MM): 140 x140 AREA (Sq M DIMENSION (REF ONLY)[LENGTH (MM)] WIDTH (MM) [HE	· /		0	10 20 30 40 50 60	70 80 BARCODE #: NA	DESIGNER: Zoe	DATE: 28-03-202	ISSUE: 5	VARNISH / LA
				IMPORTANT NOTES: Please check this artwork proof thoroughly, including all copy, colours, cutt prior to approval. If you have any questions relating to this or if you require any guidance on che					
OUTSIDE 140 140 Image: ToleRance +/-2 +/-2	0.3			approval. If you have any questions relating to this or if you requir happily advise. Please notify us immediately if you have any conce		e let us know and			GLOSS VARNSH
	2		2	4		5		4	

	2				10			
REVISIONS								
ULE LEGEND:		REV	ECN		DESCRIPTION	BY	DATE	
Cut		A		PRELIMINA	ARY RELEASE	V.Pavao	06/28/2021	
Crease Generic perf		В						
		C						
artial cut		D						
Generic perf in c	hannel	E						
SPECIAL RULE	:	F						

140

140

4

R29.3

Plug the cable into an outlet

Plug into an outlet inside your home or use an outdoor outlet with a waterproof cover.



5

OPTIONAL

Tether the rest of your cable

Peel and stick your cable management clips to the wall, holding in place 15 seconds each time. Or screw them in using the hole in the middle. Then just press your cable into the clips to keep it in place.

Want to make sure your camera is plugged in and charging? Check the battery level anytime in the SimpliSafe App.

STR-10561-00 ART-10273-00 US

4



Notice: This drawing,and the subject matter disclosed therein,embody proprietary information which is the confidential property of Simplisafe. Such information shall not be copied,reproduced,disclosed to others. published,or used,in whole or in part for any purpose,without the advance permission of a duly authorized Simplisafe representaive.All drawings and related material included herein are subject to return upon Simplisafe's request at any time.

ALL DIM	ENSIONS ARE IN MILL	IMETERS	
UNLES	S OTHERWISE SPECI	FIED	SimpliSafe [®]
DIMENSION	MOLDED	PRESSED	
00.0 - 49.9	±2.0mm	±1.0mm	MATERIAL FINISH & COLOR THICKNESS
50.0 - 99.9	±2.5mm	±1.5mm	MATERIAL FINISH & COLOR THICKNESS
100.0 - 199.9	±3.0mm	±1.5mm	300G C2S
200.0 - 299.9	±3.5mm	±1.5mm	VENDOR PART NUMBER
300.0 - 399.9	±4.0mm	±1.5mm	DESIGNED BY V.PAVAO DATE 06/28/2021
400.0 or MORE	1%	0.5%	TITLE
WARPAGE	5%	3%	QSG
PACK	AGING DRAWING FC	RMAT	SIZE SCALE SHEET PART NUMBER STR-10561-00
4	9		10