COMPRESSOR **DEHUMIDIFIER** INSTRUCTION MANUAL <u>4</u> Thank you very much for using our products.
Please read the user manual carefully before use, and keep it for future reference. — Model:Libra — <u>6</u>



- Model: Libra -

DEHUMIDIFIER

01/SAFETY PRECAUTIONS

This page records the main topics of safety precautions to prevent personal liquity or property loss of users and others. Please read them carefully and observe the precautions recorded here.

- Please reset them. certally, and observe the precundant

 1. Do not opposed the nucleus with we state, of that the
 otherwised resets with water or prize
 the nucleus resets which was the state of the reset of the
 nucleus resets which was the control of the reset of the
 nucleus resets which was the reset of the reset of the
 nucleus resets which was the reset of the reset of the
 nucleus resets which was the reset of the
 1. Do not the reset of the reset of the reset of the
 1. Do not the reset of the reset of the reset of the
 1. Do not the
 1. Do not the reset of the
 1. Do not the reset of the
 1. Do not the
 1. 1. It is followed by the control of the control of

- 16. Never insert your fingers, root into the air codist. Take 16. Never the unit spowed while transport and drouge for the compressor locates properly.

 17. If the special properly is to ensure that they do not a final part of the properly of the special part of the properly of the special part of the spe



26. Any person who is involved with working on or breaking into a infriguent critar should hold a current valid critificate from a hold with control and control and the criticate from the control and the control and the control and with an industry recognised assessment specification. Yet servicing value lay be performed as recommended by the control and the control and the control and the assistance of other validate operanced shall be carried and the control and which is the control of the person conference in the cut of 2.8 the net specime or his other with the control and power plays. It may carried effort: finds or find us to be promote plays. It may carried effort: finds or find us to yet all the proper plays and the control and yet all the proper plays and the proper plays are plays yet all the proper plays are plays and the control and yet all the proper plays are plays and yet all the proper plays are plays and yet all the proper plays are plays and yet all the plays are plays and yet all the plays are plays and yet all the plays are plays and yet all yet and yet all yet all yet and yet all yet all

S. Dish appliance is not intended for use by persons (including childen) with reduced physical, sensory or mental capabilities, or task of experience and incondegar unless then have been given is appreciated in intended in concerning use of the appliance. In children children is experienced in the content of the appliance. In Children children is experienced to ensure that they do not play with the appliance. It is a suppliance of the proper content of the properties of the of





Notes:

If any parts damage, please contact the dealer or a designated report in hop.

If any parts damage, please are not the air switch, deconnect the power supply, and contact the dealer or a designated report in the provided provided in the dealer or a designated report in the provided provided in the dealer of a designated report in the provided provided provided in the dealer of the air switch and disconnect the power supply file must be replaced from the dealer or a designated repair. If must be replaced from the dealer or a designated repair.

All required signs are to be maintained and employers should ensure that employees receive suitable and sufficient instruction and training on the meaning of appropriate safety signs and the actions that need to be taken in connection with these closers.

Risk of Fire or Englaster. This and contains Remnable netrigenests delitional sating precautions must be full losed.

The continues of the co

the actions that need to be taken in connection with these configurations of the properties of the pro

02/POINTS FOR ATTENTION

- Please keep the machine on a flat and firm ground.
 Do not immerse the machine in water or put it near the water.
- Transportation, marking and storage for units that employ filammable refrigerants.

 Transport of explorem containing filammable refrigerants.

 Attention is drawn to the fact that additional transportation regulations may exist with respect.

 The state of the state 2. Do not immers the machine in water or put in creat the water. Parked and or operation of the machine if the power code of or other connections are found to the damander of the machine in the power after being point against any operation of the machine in the first ender power of the machine in the machine is being moved, cleaned, maintained, and it is visue, be set on trulings and and or off the maline power for it visue, the set on trulings and and or off the maline power in visue, the set of the maline power for its visue, the set of the maline power and visue is visue to the power of the maline power and visue in visue to the power of the visue of of the

- Reaso use this product under the specified power supply and voltage.
 He will be machine in case the compressor is referred to the machine in case the compressor is referred.
 Reaso do not invest anything the first machine in the referred to the result of the machine of the referred to the result of the referred to the re

- This device complies with Part 15 of the PCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, includ-ing interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a class is digital device, pursuant to part 1 of the FCE fulls. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can relate installation this equipment generates uses and can relate action frequency energy and, finct installation and in accordance with the instructions, may cause burnful interference to dence with the instructions, may cause burnful interference.

radio communications. However, there is no quarantee that interference will not occur in a particular installation. If this interference will not occur in a particular installation. This is not receiption, which make the properties of an articular interference of an an in the user's excousaged to try to correct the electricity of stocks for exclusive states. However, the exclusive of reduce the exclusive actions. He exclusive actions considered the exclusive actions. He exclusive actions considered into an order on a cortical different connect the explained into an order on a cortical different considered in the dealer or an apparenced radio TV technican for holp.

This equipment compiles with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator k your body.




04/MODEL AND SPECIFICATION

Region		China		110000	Sout	h Korea	USA	
Model		0000000	OF CHICA	ACC100	1800	ACCES.	DESCRIPTION OF THE PERSON OF T	
Voltage		20/500			231.905			
Power		238				XX		
Working capacity		26.0						
		EM 74			10.06		IDW/Dk	
Owly defruendfission Capacity		SERVICE SHIP SECURITY						
Effective Area		1907						
Celsonidification (Rode		Continues debasial/Contine, banking debasial/Contine, content debasial/Contine						
Water Tank Capacity		4.00						
Water Tank More Hode		Parietti I						
Noise Decibel		<68						
Timing		Section #28						
Wind Oosr		Righ Wellian Con						
Product Weight		The 13.50				lu .		
Product Dimension		HOOMON						
Punction	Chi	ld Lock	Standard	Stand	ord	Standard	Standard	
	Full Water Tank Mann		Standard	Sandard		Standard	Standard	
	Fan Speed		Standard	d Standard		Standard	Standard	
	WER		Optional	mal Option		Optional	Optional	
	Castern		Standard	Stand	-	Standard	Standard	

05/MODEL AND SPECIFICATION

Control Panel



(*) Power key

O Power key
It is used for Power ON or Power OFF. Press it once and the machine will switch between these two states. When the machine is started, it remains the working state of the last time, and the power indicator would light up.

Comfort Mode key In the startup status, press the Comfort key, its indicator light will be on, and the machine will enter the status of comfor-able deluminification (releminification humbally will be controlled automatically between 45% and 55%). Press this key again, its indicator light will be off, and every time it is pressed, the buzzer will sound enter.

★ E Left and Right Adjustment keys

4 b Left and Bight Adjustment keys This keys only affective when either the Custom Dehumidifi-cation keys or the Timer key is solid; When this key takes feeter. She Left and high Adjustments keys fash their keys feeter, the Left and high Adjustment keys fash their keys whole process takes about 3 seconds). At this time, corresponding settings can be made. For detailed setting methods, picase refet to the corresponding key descriptions in points (3) and (4) above. Naciatur high Description.

Child Lock Button

Child lock setting button /keep pressing the button for three seconds. Child lock function will be opened or closed . And it's indication light will be on or off.

Recording the Record of the Re

1.The states of the current measured ambient relative

humidity are displayed as follows.

In the startup state, the humidity can be displayed directly.

In the startup state, the humidity can be displayed directly.

The hormal range of ambient humidity is 40-80; LO is shown when it is below 40, and HI is shown when it is below 40, and HI is shown when it is

2.5et humölty display. You can start after pressing the humölista key" and "left and right adjustment keys. See "Description of humölista key" for elsen het "humölista key" 2. Fault display; when the "limit" key and the "humölista key temperature valve with the display and the humbolista key the temperature valve with the display and is from that in the displat labe. The normal display can be resumed after the same operation. Note:

he 'tox'. If the negative value of the coil temperature exceeds the display range of 'fai', -f will be displayed in shorn flash. If the coil temperature resoror false, If the coil temperature resoror false, If thulb deliphoped in show flash. Remarks: The priority of the display flushed splay modes is as follows: Falst cools if 12 coil temperature value set humidity value member humidity value which is also displayed, the humidity cannot be set, at the value cannot be obligated.

→ WIFI indicator light

WHI Indicator light Sow flash—Oungable networking mode to wait for networking. Out of Nash—Waiting for networking Normally on—The network has been connected Normally on—The machine is in standary state, or the network is not connected, or WFI module signal is not detected. Note: In standby mode, the default WIFI indicator light is off.

Full Tank Light Full. Tank Light, and the Environmental Display Light is turned on at the same time; Rules for defining a full tank:

If the Full Tank signal is detected to be valid for 3 consecu-tive seconds when the tank is fulf, then it indicates that the tank has been ful.

If the Full Tank signal is detected to be valid for 1 consecu-tive seconds when the tank is full, then it indicates that the tank has been full.

If the Full Tank signal is detected to be invalid for 1 second when the tank is full, then it indicates that the tank is not full and returns to normal.

when the lanks four, and it includes such the calls to include full and returns to normal. When the Full Tark signal is valid, whether the switch is closed or open depends on the specific Machine. Action after the tank is full:

Action after the tank is fulf:

When the mochine to spow working, the buzzer will not sound, instead the fulf than kindicator lightest the normally confused than the fulf than kindicator lightest the normally confused than the fulf than the normal confused that the fulf than the present than of the machine instead of just the fulf trank symbol or is indicated fulf, after hustdown, if the machine is not turned off, after the action will adultionally the machines is not turned off, after the action of the machine is not turned off, after the action of the machine is not turned off, after the action of the machine is not turned off, after the company of the machine is not turned off, after the company of the machine is not turned off, after the company of the machine is not turned off, after the company of the machine is not turned off, after the company of the machine is not turned off, after the company of the machine is not turned off. The state of the state of the company of the c

Wind Speed key

Fan Speed Key: It is used to select wind gears, which would circulate among "High- MediumLow" after the correspond-ing status is selected. High Mode: Three indicator lights are

on. Medium Mode: Two lights are on; Low Mode: One light is on; after selection, the machine will be operated in the selected status first in any dehumidification mode (default continuous dehumidification, healthy dehumidification and ordinary dehumidification).

(9) Timer key when the machine is on, overy time this key is pressed, the buzzer would sound coord. The destred timing can be realized by pressing the Timer key and then pressing the Left and Right Adjustment key. The Inting falls since the range of G-2Ms, when the set time is up, the machine would be shut down and enter the standay state.
Nate:

Note:

If you press the On/Off Rey to turn off the machine before the timing is done, then the timing sating, will be cancelled, original setting in the machine plant in the process, the original setting will be markation.

3. When the embleret temperature is OYL-OYC, the eming accuracy is EAV, which is normal, which is normal.

There is a press the time of the ti

Imme sey again to sest me omnor.

This key can be also used as a Well key
After the machine is sumed on, press this key for about 5
seconds, then the vell indicator light will display the current wiff!
be considered to the property of the current wiff!
be considered to the control of the current wiff.
be considered to the control of the current wiff.
be considered to the current wiff to the control of the current wiff to the control of the current wife.

The control of the current wife wife the current wife to the curren

get Annon key

Negative ion key (with negative ion function, this button); used to turn on and off the negative ion function, corresponding indicator light on or off. This button is also the child lock key, long perss: 3s to open-closes the child lock, the corresponding indicator light on or off. Se Anion key

Drainage instructions: (including water tank drainage and continuous drainage)

Water Tank Drainage







Continuous drainage

Open the soft water plug at the rear shell, take out the PVC water pipe and insert one end of it into the continuous drainage hole of the machine with the other end in the drainage carea.



06 / CLEANING AND MAINTENANCE

Before (claiming or maintaining the machine in any mode, the machine must be shut down, the power plug must be machine must be shut down, the power plug must be unpluguged, and water cannot be perinded on the machine; Clean the casing with a soft wet cloth, and chemical solvents such as be praises, alsohold and spaciniae are not allowed to use, otherwise, the machine casing will be damaged or even detormed.

Cleaning of the filter



07 / TROUBLESHOOTING

The following list contains the common problems, but none of them are faults caused by imperfect manufacturing process or material defects.

Before cleaning or maintaining the machine in any mode, the machine must be shut down, the power plug must be unplugged, and water cannot be sprinkled on the machine; Clean the casing with a soft wet cloth, and chemical solvents such as benzere, alcohol and gasoline are not allowed to otherwise, the machine calony will be damaged or ever otherwise, the machine calony will be damaged or ever the control of the contro

such as enterior, action data by aparties in this authority of the designed or research deformed.

Conditions for the machine contriguist his designed or research deformed.

Conditions for the machine compressor to start and stop

Linkthen the ambients temperature is 15 or 35 °C, or when the temperature serior fails, the compressor does not work.

Lournal contribution of a regular interval propersion makes

Journal deforming a regular interval.

Journal deforming a regular interval.

In case of the following conditions, pulse confirm which in case of the following conditions, pulse confirm which before consulting outstomers service: Hong Keng, Macoo and Talwan),

2. Within the following period from the date of purchase; the
warranty is valid in case of any damage caused by Chinese
munification; processes or composers and parts underwithout muchine (except the filter screen and cosmodals)

which muchine (except the filter screen and cosmonable
parts; 13 years, compressor 5 years, committee) parts can be
reasized as a cost (they are not covered by warranty).

1. In case of any one of the following circumstances, free
warranty cannot be provided even if the muchine is under
warranty, but plicepairs are still audited.

perore ci	ansuiting custome	r service:			
d description	Fall disposes	54.00			
Code/E1	Faily of Impostors sensor or executed simula	Prose on again			
Circlordon	The parted of arritises temperature APCG is width	Person again			
Cindodon	The period of prolited temperature NS City (400)	Personagen			
Cota PG	Ever refrestry note	Industrial the matrices debuting above of adventions above to come display after finding the present			

Note: If there are other faults, please contact the manufacturer or the point of purchase for inspection and repair. Do not disassemble the machine by yourself.

The product is beyond the scope of warranty.
The product is not used as required in the Operation Manual.
This warranty card and valid purchase invoice cannot be presented.
The product bar code or model on the warranty card is

4.These clauses for free warranty are only applicable to the occasions where consumers purchase the product for living needs, instead of for operational purposes (such as for industrial and commercial purposes).

industrial and commercial purposes). Special information in a single program of the pignismate rights and interests of customers, our company implaments the "Three Guarantees" policy based on national regulations, eccording to which consumers can return, replace or have the marchine repaired which will be the program of the program of the Forth machine whose warranty period has expired, the customer can contact our After-riade Department to order the required spape part by mell.

08 / AFTER-SALES SERVICE

The warranty (repair for free) of the commodity under warranty shall take effect from the date of purchase. If the quality disappoints you in any way, the commodity under warranty can be returned to our company for handling. The following issues should be paid particular attention to:
 This warranty card will not be reisoued if foot, so please keep in

well.

This warranty card is only valid in the People's Republic of China (Temporarily not available in Hong Kong, Macoo and Taiwan).