

NOKIA MOBILE PHONES

Nokia GmbH
Lise Meitner Strasse 10
89081 Ulm / Germany
+49 731 1754 0
+49 731 6800

8 May 2006

Certification and Engineering Bureau
Industry Canada
3701 Carling Avenue Bldg. 94
Ottawa, Ontario
Canada K2H 8S2

IMEI PROTECTION OF NOKIA RM-166


The International Mobile Equipment Identifier (IMEI) for each transceiver is unique.

The IMEI host component is permanently attached to a main circuit board of the alterable.
The IMEI is isolated from fraudulent contact and tampering.

- ☐ The host component does not contain other information, it is not removable and its electrical connections are not accessible.
- ☒ The host component does contain other information, and the IMEI information is encoded using:
 - ☐ (1) Multiplication or division by a polynomial.
 - ☒ (2) Cyclic coding.
 - ☒ (3) The spreading of IMEI bits over various non-sequential memory locations.

The IMEI is factory set and is not alterable, transferable, removable, or otherwise able to be manipulated. Cellular mobile equipment is designed such that any attempt to remove, tamper with, or change the IMEI chip, its logic system, or firmware originally programmed by the manufacturer will render the mobile transmitter inoperative.

NOKIA MOBILE PHONES



Jürgen Sitzmann
Product Program Manager, Ulm