TEST REPORT

Report No.:	TW2305189E
Applicant:	Shenzhen Star Sources Electronic Technology Co., Ltd.
Product:	Portable Wireless Keyboard
Model No.:	TWKB1, TWKB1BLK, TWKB1PNK, TWKB1WHT, ST-BK68, ST-BK05，ST-BK06, ST-BK10, ST-BK11, ST-BK13, ST-BK14, ST-BK15, ST-BK16, ST-BK17, ST-BK18, ST-BK31, ST-BK32, ST-BK33, ST-BK37, ST-BK38, ST-BKxy (x=0-9; y=0-9;)
Trademark:	N/A
Test Standards:	FCC Part 15.249
Test result:	It is herewith confirmed and found to comply with the requirements set up by ANSI C63.10 &FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of electromagnetic compatibility

Approved by:

Terry Tang

Manager

Dated: June 25, 2023

Results appearing herein relate only to the sample tested
The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) —Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Test Report Conclusion

Content

1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688

Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189

For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Shenzhen Star Sources Electronic Technology Co., Ltd.

Address: Room 2102, Block 1st, Yi Luan Building, Xixiang Road 230, BaoAn District, Shenzhen, China

Telephone: --

Fax: --

1.3 Description of EUT

Product:	Portable Wireless Keyboard
Manufacturer:	Shenzhen Star Sources Electronic Technology Co., Ltd.
Address:	Room 2102, Block 1st, Yi Luan Building, Xixiang Road 230, BaoAn District, Shenzhen, China
Trademark:	N/A
Additional Trademark:	N/A
Model Number:	TWKB1
Additional Model Name	TWKB1BLK, TWKB1PNK, TWKB1WHT, ST-BK68, ST-BK05， ST-BK06, ST-BK10, ST-BK11, ST-BK13, ST-BK14, ST-BK15, ST-BK16, ST-BK17, ST-BK18, ST-BK31, ST-BK32, ST-BK33, ST-BK37, ST-BK38, ST-BKxy (x=0-9; y=0-9;)
Rating:	DC5V, 1A, 5W
Battery:	DC3.7V, 150mAh Li-ion battery
Modulation Type:	GFSK (Bluetooth Low Energy)
Operation Frequency:	2402-2480MHz
Channel Separate:	2MHz
Channel Number:	40
Hardware Version:	V1.1
Software Version:	V1.1

Serial No.:	TWKB10001-TWKB17500
Antenna Designation	PCB antenna with gain 1.5dBi Max (Get from the antenna specification)

1.4 Submitted Sample: 1 Sample

1.5 Test Duration

2023-05-17 to 2023-06-25

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty =5%

Conducted Emissions Uncertainty =3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by _____

Print Name: Andy Xing

2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2022-07-15	2023-07-14
LISN	R&S	EZH3-Z5	100294	2022-07-18	2023-07-17
LISN	R&S	EZH3-Z5	100253	2022-07-18	2023-07-17
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2022-07-18	2023-07-17
Loop Antenna	EMCO	6507	00078608	2022-07-18	2025-07-17
Spectrum	R&S	FSIQ26	100292	2022-07-15	2023-07-14
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2022-07-18	2025-07-17
Horn Antenna	R&S	BBHA 9120D	9120D-631	2022-07-18	2024-07-17
Power meter	Anritsu	ML2487A	6K00003613	2022-07-18	2023-07-17
Power sensor	Anritsu	MA2491A	32263	2022-07-18	2023-07-17
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2022-07-18	2025-07-17
9*6*6 Anechoic	--	--	N/A	2022-07-26	2025-07-25
EMI Test Receiver	RS	ESVB	826156/011	2022-07-15	2023-07-14
EMI Test Receiver	RS	ESCS 30	834115/006	2022-07-15	2023-07-14
Spectrum	HP/Agilent	E4407B	MY50441392	2022-07-15	2023-07-14
Spectrum	RS	FSP	1164.4391.38	2022-07-15	2023-07-14
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA	--	2022-07-15	2023-07-14
RF Cable	Zhengdi	7m	--	2022-07-15	2023-07-14
Pre-Amplifier	Schwarebeck	BBV9743	#218	2022-07-15	2023-07-14
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2022-07-15	2023-07-14
LISN	SCHAFFNER	NNB42	00012	2022-08-18	2023-07-17
ESPI Test Receiver	R&S	ESPI 3	100379	2022-07-15	2023-07-14
LISN	R&S	EZH3-Z5	100294	2022-07-18	2023-07-17

2.1 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna Requirement	Pass	Complies
FCC Part 15, Paragraph 15.207	Conducted Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	Pass	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	Pass	Complies

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249 , ANSI C63.4 :2014 and ANSI C63.10 :2013

4.0 EUT Modification

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES

5. Power Line Conducted Emission Test

5.1 Schematics of the test



EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013.The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~~, 60Hz

Block diagram of Test setup



5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

40 channels are provided to the EUT

A. EUT

Device	Manufacturer	Model	FCC ID
Portable Wireless Keyboard	Shenzhen Star Sources Electronic Technology Co., Ltd.	TWKB1, TWKB1BLK, TWKB1PNK, TWKB1WHT, ST-BK68, ST-BK05，ST-BK06, ST-BK10, ST-BK11, ST-BK13, ST-BK14, ST-BK15, ST-BK16, ST-BK17, ST-BK18, ST-BK31, ST-BK32, ST-BK33, ST-BK37, ST-BK38, ST-BKxy (x=0-9; y=0-9;)	ZJEST-BK68

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A; Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

A Setup the EUT and simulators as shown on follow

B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency (MHz)	Limits (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ～ 0.50	66.0～56.0*	56.0～46.0*
0.50 ～ 5.00	56.0	46.0
5.00 ～ 30.00	60.0	50.0

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

5.6 Test Results:

Pass

A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25℃ Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Charging + Communication by BT

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1655	46.39	9.77	56.16	65.18	-9.02	QP	P
2	0.1655	33.14	9.77	42.91	55.18	-12.27	AVG	P
3	0.2397	41.57	9.75	51.32	62.11	-10.79	QP	P
4	0.2397	25.31	9.75	35.06	52.11	-17.05	AVG	P
5	0.2943	34.34	9.76	44.10	60.40	-16.30	QP	P
6	0.2943	18.32	9.76	28.08	50.40	-22.32	AVG	P
7	0.6531	32.26	9.78	42.04	56.00	-13.96	QP	P
8	0.6531	23.09	9.78	32.87	46.00	-13.13	AVG	P
9	4.3845	23.11	9.90	33.01	56.00	-22.99	QP	P
10	4.3845	11.67	9.90	21.57	46.00	-24.43	AVG	P
11	17.0634	25.15	10.50	35.65	60.00	-24.35	QP	P
12	17.0634	17.69	10.50	28.19	50.00	-21.81	AVG	P

B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25℃ Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Charging + Communication by BT

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1734	48.33	9.77	58.10	64.80	-6.70	QP	P
2	0.1734	26.90	9.77	36.67	54.80	-18.13	AVG	P
3	0.2085	43.39	9.75	53.14	63.26	-10.12	QP	P
4	0.2085	25.27	9.75	35.02	53.26	-18.24	AVG	P
5	0.2436	40.17	9.75	49.92	61.97	-12.05	QP	P
6	0.2436	24.21	9.75	33.96	51.97	-18.01	AVG	P
7	0.6882	33.82	9.78	43.60	56.00	-12.40	QP	P
8	0.6882	24.45	9.78	34.23	46.00	-11.77	AVG	P
9	1.4175	29.16	9.79	38.95	56.00	-17.05	QP	P
10	1.4175	21.12	9.79	30.91	46.00	-15.09	AVG	P
11	17.7459	24.59	10.54	35.13	60.00	-24.87	QP	P
12	17.7459	17.30	10.54	27.84	50.00	-22.16	AVG	P

6 Radiated Emission Test

6.1 Test Method and test Procedure:

(1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189

(2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.

(3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz (Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.

(4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.

(5) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



6.2 Configuration of The EUT

Same as section 5.3 of this report

6.3 EUT Operating Condition

Same as section 5.4 of this report.

6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency (MHz)	Field Strength of Fundamental (3m)			Field Strength of Harmonics (3m)		
	mV/m	**dBuV/m**		**uV/m**	**dBuV/m**	
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note: 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)

2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/)
0.009-0.490	3	20log(2400/F(kHz)) +40log (300/3)
0.490-1.705	3	20log(24000/F(kHz)) +40log (30/3)
1.705-30	3	69.5
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note: 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)

2. In the Above Table, the tighter limit applies at the band edges.

3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

4. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.

5. For radiated emissions from 9kHz to 30MHz，the emission level is much less than the limit for more than 20dB. No necessary to take down the record.

6. Battery was fully charged during the test.

6.5 Test result

A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2402	89.51	-3.57	114.0	-24.49	Peak	54.00	100	Horizontal	Pass
2	4802.799	48.04	3.12	74.0	-25.96	Peak	264.00	100	Horizontal	Pass

Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2402	82.64	-3.57	114.0	-31.36	Peak	0.00	100	Vertical	Pass

Please refer to the following test plots for details: Middle Channel-2440MHz

Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2440	88.21	-3.57	114.0	-25.79	Peak	87.00	100	Horizontal	Pass
2	4879.280	47.18	3.20	74.0	-26.82	Peak	87.00	100	Horizontal	Pass

Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2440	82.97	-3.57	114.0	-31.03	Peak	357.00	100	Vertical	Pass

Please refer to the following test plots for details: High Channel-2480MHz

Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480	88.07	-3.57	114.0	-25.93	Peak	303.00	100	Horizontal	Pass
2	4960.010	52.51	3.36	74.0	-21.49	Peak	76.00	100	Horizontal	Pass

Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480	82.79	-3.57	114.0	-31.21	Peak	349.00	100	Vertical	Pass

Note: (2) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

(3) Margin=Emission-Limits

(4) According to section 15.35(b), the peak limit is 20dB higher than the average limit

(5) For test purpose, keep EUT continuous transmitting

(5) For emission above 18GHz and Below 30MHz, It is only the floor noise. No necessary to take down.

(6) the measured PK value less than the AV limit.

B. General Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	49.153	20.93	-11.24	40.0	-19.07	Peak	81.00	200	Horizontal	Pass
2	119.945	19.50	-15.32	43.5	-24.00	Peak	159.00	200	Horizontal	Pass
3	174.979	19.17	-15.68	43.5	-24.33	Peak	0.00	200	Horizontal	Pass
4	373.052	25.05	-9.46	46.0	-20.95	Peak	156.00	200	Horizontal	Pass
5	545.184	26.71	-6.35	46.0	-19.29	Peak	161.00	100	Horizontal	Pass
6	823.989	31.32	-2.88	46.0	-14.68	Peak	26.00	200	Horizontal	Pass

Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	37.273	28.49	-13.06	40.0	-11.51	Peak	324.00	100	Vertical	Pass
2	119.945	22.16	-15.32	43.5	-21.34	Peak	130.00	100	Vertical	Pass
3	181.282	19.54	-15.11	43.5	-23.96	Peak	223.00	100	Vertical	Pass
4	240.195	19.50	-12.33	46.0	-26.50	Peak	90.00	100	Vertical	Pass
5	469.300	25.67	-7.54	46.0	-20.33	Peak	332.00	100	Vertical	Pass
6	587.611	27.52	-5.50	46.0	-18.48	Peak	16.00	100	Vertical	Pass

7. Band Edge

7.1 Test Method and test Procedure:

(1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189

(2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.

(3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.

(4) The antenna polarization: Vertical polarization and Horizontal polarization.

7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

7.3 Configuration of The EUT

Same as section 5.3 of this report

7.4 EUT Operating Condition

Same as section 5.4 of this report.

7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

7.6 Test Result

Product:	Portable Wireless Keyboard	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	--	--



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2402.082	89.23	-3.57	74.0	15.23	Peak	72.00	100	Horizontal	N/A
2	2400.000	67.05	-3.57	74.0	-6.95	Peak	57.00	100	Horizontal	Pass
2**	2400.000	51.76	-3.57	54.0	-2.24	AV	57.00	100	Horizontal	Pass
3	2390.000	40.03	-3.53	74.0	-33.97	Peak	95.33	100	Horizontal	Pass
4	2390.865	45.34	-3.53	74.0	-28.66	Peak	0.00	100	Horizontal	Pass
5	2393.939	45.06	-3.55	74.0	-28.94	Peak	350.00	100	Horizontal	Pass

Product:	Portable Wireless Keyboard	Detector	Vertical
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	--	--



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2401.767	82.50	-3.57	74.0	8.50	Peak	358.00	100	Vertical	N/A
2	2400.000	60.95	-3.57	74.0	-13.05	Peak	306.86	100	Vertical	Pass
2**	2400.000	45.91	-3.57	54.0	-8.09	AV	306.86	100	Vertical	Pass
3	2390.000	41.85	-3.53	74.0	-32.15	Peak	276.00	100	Vertical	Pass
4	2392.589	50.53	-3.54	74.0	-23.47	Peak	278.00	100	Vertical	Pass
5	2396.338	50.26	-3.55	74.0	-23.74	Peak	308.00	100	Vertical	Pass

Product:	Portable Wireless Keyboard	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	--	--



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2479.995	88.55	-3.57	74.0	14.55	Peak	73.00	100	Horizontal	N/A
2	2483.500	56.74	-3.57	74.0	-17.26	Peak	100.00	100	Horizontal	Pass
2**	2483.500	41.73	-3.57	54.0	-12.27	AV	100.00	100	Horizontal	Pass

Product:	Portable Wireless Keyboard	Detector	Vertical
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	--	--



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480.040	82.55	-3.57	74.0	8.55	Peak	175.00	100	Vertical	N/A
2	2483.500	47.13	-3.57	74.0	-26.87	Peak	77.57	100	Vertical	Pass

Note: The PK emission level less than the AV limit. No necessary to record the AV emission level.

8.0 Antenna Requirement

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has an PCB antenna. The antenna gain is 1.5dBi Max. It fulfills the requirement of this section.

Test Result: Pass

9.0 20dB Bandwidth Measurement			
Product:	Portable Wireless Keyboard	Test Mode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	1.311MHz	--	--



Product:	Portable Wireless Keyboard	Test Mode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	1.311MHz	--	--



Product:	Portable Wireless Keyboard	Test Mode:	Keep transmitting
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK
20dB Bandwidth	1.293MHz	--	--



10.0 FCC ID Label

FCC ID: ZJEST-BK68

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



11.0 Photo of testing

11.1 Conducted test View--



Radiated emission test view

11.2 Photographs – EUT



Photographs – EUT



Photographs – EUT





Photographs – EUT





Photographs – EUT





-End of the Report--