



# **RF TEST REPORT**

Applicant	Asiatelco Technologies Co.
FCC ID	XYO-J912
Product	LTE CPE
Brand	ATEL
Model	AOL-J912
Report No.	R2111A0991-R5V1
Issue Date	December 15, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 / FCC CFR 47 Part 90R**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Peng Tao

Prepared by: Peng Tao

KaiXu

Approved by: Kai Xu

# TA Technology (Shanghai) Co., Ltd. No. 145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China TEL: +86-021-50791141/2/3 FAX: +86-021-50791141/2/3-8000



# **TABLE OF CONTENT**

1.	Test	Laboratory	5
1	.1.	Notes of the Test Report	5
1	.2.	Test facility	5
1	.3.	Testing Location	5
2.	Gen	eral Description of Equipment under Test	6
2	2.3.	Applicant and Manufacturer Information	6
2	2.4.	General Information	6
3.	Арр	lied Standards	7
4.	Test	Configuration	8
5.	Test	Case Results	9
5	5.1.	RF Power Output and Effective Radiated Power	9
5	5.2. Ra	adiates Spurious Emission1	3
6.	Mair	1 Test Instruments1	7
AN	NEX /	A: The EUT Appearance1	8
AN	NEX E	3: Test Setup Photos1	9



Version	Revision description	Issue Date					
Rev.0	Initial issue of report.	December 3, 2021					
Rev.1	Update description in Page 4.	December 15, 2021					
Note: This	Note: This revised report (Report No. R2111A0991-R5V1) supersedes and replaces the						
previously issued report (Report No. R2111A0991-R5). Please discard or destroy the previously							
issued rep	ort and dispose of it accordingly.						



# Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict				
1	RF power output and Effective Radiated Power	2.1046/90.635 (b)/ 90.542	PASS				
2	Radiates Spurious Emission	90.543 (e)	PASS				
Date of Te	Date of Testing: November 12, 2021 ~ November 29, 2021						
Date of Sa	ample Received: November 9, 2021						
Note: PAS	S: The EUT complies with the essential require	ements in the standard.					
FAIL: The EUT does not comply with the essential requirements in the standard.							
All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd.							
based on i	nterpretations and/or observations of test result	ts. Measurement Uncertainties we	re not taken				
into accou	nt and are published for informational purposes	s only.					

Only RF Power Output and Effective Radiated Power and Radiates Spurious Emission are tested for LTE CPE in this report. Other test items refer to the Module report (Report No.: FG8N2911D; FCC ID: XMR201901EM12G).



# 1. Test Laboratory

#### 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology** (shanghai) co., Ltd. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

#### 1.2. Test facility

#### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

#### 1.3. Testing Location

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	xukai@ta-shanghai.com



# 2. General Description of Equipment under Test

Applicant	Asiatelco Technologies Co.		
Applicant address	#68 HuaTuo Road, Building-8, Zhangjiang Hi-Tech Park,		
Applicant address	Pudong, Shanghai 201204, China		
Manufacturer	Asiatelco Technologies Co.		
Manufacturer address	#68 HuaTuo Road, Building-8, Zhangjiang Hi-Tech Park,		
Manufacturer address	Pudong, Shanghai 201204, China		

# 2.3. Applicant and Manufacturer Information

#### 2.4. General Information

EUT Description							
Model	AOL-J912						
IMEI	8697100300519	185					
Hardware Version	J91-P1						
Software Version	CPE3_WT_J91_	_00_v1.0.3					
Power Supply	POE						
Antenna Type	Internal Antenna	à					
Antenna Gain	2 dBi	2 dBi					
Test Mode(s)	LTE Band 14;						
Test Modulation	QPSK, 16QAM, 64QAM;						
LTE Category	12						
Maximum E.R.P.	21.79 dBm						
Rated Power Supply Voltage	50 V						
Operating Voltage	Minimum: 48 V	Maximum: 55 V					
Operating Temperature	Lowest: -30°C	Highest: +60°C					
Operating Fraguancy Pango(s)	Band	Tx (MHz)	Rx (MHz)				
Operating Frequency Range(s)	LTE Band 14	788 ~ 798	758 ~ 768				
	EUT Acce	ssory					
	Manufacturer: K	eTujia					
	Model: PSE3020	Э					
Note: 1. The EUT is sent from th	e applicant to TA	and the information of the	he EUT is declared by				
the applicant.							



# 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards: FCC CFR 47 Part 90R (2020) ANSI C63.26 (2015)

Reference standard: FCC 47 CFR Part 2 (2020) KDB 971168 D01 Power Meas License Digital Systems v03r01



# 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, Vertical polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. The following testing in LTE is set based on the maximum RF Output Power.

Tost itoms	Bandwidth (MHz)		Modulation		RB			Test Channel		
rest items	5	10	QPSK	16QAM/ 64QAM	1	50%	100%	L	М	Н
RF Power Output and Effective Radiated Power	0	0	0	О	0	0	0	0	0	0
Radiates Spurious Emission	0	0	0	-	0	-	-	-	0	-
Note	<ol> <li>The mark "O" means that this configuration is chosen for testing.</li> <li>The mark "-" means that this configuration is not testing.</li> </ol>									

Test modes are chosen as the worst case configuration below for LTE Band 14





**RF Test Report** 

### 5.1. RF Power Output and Effective Radiated Power

#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### **Methods of Measurement**

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.

ERP can then be calculated as follows:

EIRP (dBm) = Output Power (dBm) - Losses (dB) + Antenna Gain (dBi) where:dBd refers to gain relative to an ideal dipole.

EIRP (dBm) = ERP (dBm) + 2.15 (dB.)

#### Test Setup



#### Limits

Part 90.635 (b) the maximum output power of the transmitter for mobile stations is 100 watts.

90.542(7) Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

#### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB for RF power output, k = 2, U = 1.19 dB for ERP.



#### **Test Results**

Band	Bandwidth (MHz)	UL Channel	RB Size	RB Position	Modulation	Maximum Output Power	ERP (dBm)
	(	Critarino	0.20			(dBm)	()
LTE Band14	5	23305	1	#0	QPSK	21.94	21.79
LTE Band14	5	23305	1	#Mid	QPSK	21.92	21.77
LTE Band14	5	23305	1	#Max	QPSK	21.87	21.72
LTE Band14	5	23305	12	#0	QPSK	20.94	20.79
LTE Band14	5	23305	12	#Mid	QPSK	20.98	20.83
LTE Band14	5	23305	12	#Max	QPSK	20.92	20.77
LTE Band14	5	23305	25	#0	QPSK	20.89	20.74
LTE Band14	5	23305	1	#0	QAM16	21.18	21.03
LTE Band14	5	23305	1	#Mid	QAM16	21.19	21.04
LTE Band14	5	23305	1	#Max	QAM16	21.12	20.97
LTE Band14	5	23305	12	#0	QAM16	19.99	19.84
LTE Band14	5	23305	12	#Mid	QAM16	19.99	19.84
LTE Band14	5	23305	12	#Max	QAM16	19.94	19.79
LTE Band14	5	23305	25	#0	QAM16	19.97	19.82
LTE Band14	5	23330	1	#0	QPSK	21.79	21.64
LTE Band14	5	23330	1	#Mid	QPSK	21.79	21.64
LTE Band14	5	23330	1	#Max	QPSK	21.67	21.52
LTE Band14	5	23330	12	#0	QPSK	20.88	20.73
LTE Band14	5	23330	12	#Mid	QPSK	20.83	20.68
LTE Band14	5	23330	12	#Max	QPSK	20.84	20.69
LTE Band14	5	23330	25	#0	QPSK	20.83	20.68
LTE Band14	5	23330	1	#0	QAM16	21.13	20.98
LTE Band14	5	23330	1	#Mid	QAM16	21.16	21.01
LTE Band14	5	23330	1	#Max	QAM16	21.07	20.92
LTE Band14	5	23330	12	#0	QAM16	20.01	19.86
LTE Band14	5	23330	12	#Mid	QAM16	19.97	19.82
LTE Band14	5	23330	12	#Max	QAM16	19.94	19.79
LTE Band14	5	23330	25	#0	QAM16	19.96	19.81
LTE Band14	5	23355	1	#0	QPSK	21.80	21.65
LTE Band14	5	23355	1	#Mid	QPSK	21.80	21.65
LTE Band14	5	23355	1	#Max	QPSK	21.69	21.54
LTE Band14	5	23355	12	#0	QPSK	20.85	20.70
LTE Band14	5	23355	12	#Mid	QPSK	20.83	20.68
LTE Band14	5	23355	12	#Max	QPSK	20.80	20.65
LTE Band14	5	23355	25	#0	QPSK	20.82	20.67
LTE Band14	5	23355	1	#0	QAM16	21.17	21.02
LTE Band14	5	23355	1	#Mid	QAM16	21.13	20.98
LTE Band14	5	23355	1	#Max	QAM16	21.11	20.96

A	RF Test R	Report				Repo	ort No.: R2111A099	1-R5V1
LTE E	Band14	5	23355	12	#0	QAM16	19.88	19.73
LTE E	Band14	5	23355	12	#Mid	QAM16	19.88	19.73
LTE E	Band14	5	23355	12	#Max	QAM16	19.85	19.70
LTE E	Band14	5	23355	25	#0	QAM16	19.95	19.80
LTE E	Band14	10	23330	1	#0	QPSK	21.84	21.69
LTE E	Band14	10	23330	1	#Mid	QPSK	21.75	21.60
LTE E	Band14	10	23330	1	#Max	QPSK	21.63	21.48
LTE E	Band14	10	23330	25	#0	QPSK	20.90	20.75
LTE E	Band14	10	23330	25	#Mid	QPSK	20.89	20.74
LTE E	Band14	10	23330	25	#Max	QPSK	20.81	20.66
LTE E	Band14	10	23330	50	#0	QPSK	20.86	20.71
LTE E	Band14	10	23330	1	#0	QAM16	21.24	21.09
LTE E	Band14	10	23330	1	#Mid	QAM16	21.11	20.96
LTE E	Band14	10	23330	1	#Max	QAM16	21.03	20.88
LTE E	Band14	10	23330	25	#0	QAM16	20.07	19.92
LTE E	Band14	10	23330	25	#Mid	QAM16	20.04	19.89
LTE E	Band14	10	23330	25	#Max	QAM16	19.96	19.81
LTE E	Band14	10	23330	50	#0	QAM16	19.97	19.82
LTE E	Band14	5	23305	1	#0	QAM64	20.60	20.45
LTE E	Band14	5	23305	1	#Mid	QAM64	20.55	20.40
LTE E	Band14	5	23305	1	#Max	QAM64	20.48	20.33
LTE E	Band14	5	23305	12	#0	QAM64	19.41	19.26
LTE E	Band14	5	23305	12	#Mid	QAM64	19.39	19.24
LTE E	Band14	5	23305	12	#Max	QAM64	19.31	19.16
LTE E	Band14	5	23305	25	#0	QAM64	19.37	19.22
LTE E	Band14	5	23330	1	#0	QAM64	20.57	20.42
LTE E	Band14	5	23330	1	#Mid	QAM64	20.54	20.39
LTE E	Band14	5	23330	1	#Max	QAM64	20.45	20.30
LTE E	Band14	5	23330	12	#0	QAM64	19.41	19.26
LTE E	Band14	5	23330	12	#Mid	QAM64	19.40	19.25
LTE E	Band14	5	23330	12	#Max	QAM64	19.33	19.18
LTE E	Band14	5	23330	25	#0	QAM64	19.37	19.22
LTE E	Band14	5	23355	1	#0	QAM64	20.57	20.42
LTE E	Band14	5	23355	1	#Mid	QAM64	20.55	20.40
LTE E	Band14	5	23355	1	#Max	QAM64	20.47	20.32
LTE E	Band14	5	23355	12	#0	QAM64	19.33	19.18
LTE E	Band14	5	23355	12	#Mid	QAM64	19.33	19.18
LTE E	Band14	5	23355	12	#Max	QAM64	19.24	19.09
LTE E	Band14	5	23355	25	#0	QAM64	19.34	19.19
LTE E	Band14	10	23330	1	#0	QAM64	20.65	20.50
LTE E	Band14	10	23330	1	#Mid	QAM64	20.52	20.37
LTE E	Band14	10	23330	1	#Max	QAM64	20.42	20.27
LTE E	Band14	10	23330	25	#0	QAM64	19.45	19.30

TA Technology (Shanghai) Co., Ltd.TA-MB-01-040RPage 11 of 19This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

RF Test Report

Report No.: R2111A0991-R5V1

LTE Band14	10	23330	25	#Mid	QAM64	19.43	19.28
LTE Band14	10	23330	25	#Max	QAM64	19.36	19.21
LTE Band14	10	23330	50	#0	QAM64	19.37	19.22





#### 5.2. Radiates Spurious Emission

#### Ambient condition

Temperature	Relative humidity	Pressure		
23°C ~25°C	45%~50%	101.5kPa		

#### **Method of Measurement**

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI C63.26 (2015).

2. Above 30MHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC' s permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100KHz, VBW=300KHz for all frequency, and the maximum value of the receiver should be recorded as (Pr).

5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization. 6. A amplifier should be connected to the Signal Source output port. And the cable should be connect

between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.

7. The measurement results are obtained as described below:

Power(EIRP)=PMea- PAg - Pcl + Ga

The measurement results are amend as described below:

Power(EIRP)=PMea- Pcl + Ga

8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP



#### = EIRP-2.15dBi.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

#### Test setup

9KHz ~ 30MHz











Note: Area side:2.4mX3.6m



90.543 Emission limitations (e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

(4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

#### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U= 3.55 dB.



#### **Test Result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1581.0	-62.44	1.70	8.70	Vertical	-57.59	-40.00	17.59	45
3	2371.5	-63.57	2.30	12.00	Vertical	-56.02	-13.00	43.02	90
4	3162.0	-63.43	2.30	13.10	Vertical	-54.78	-13.00	41.78	225
5	3952.5	-62.05	2.90	12.50	Vertical	-54.60	-13.00	41.60	45
6	4743.0	-59.16	3.10	12.50	Vertical	-51.91	-13.00	38.91	135
7	5533.5	-57.69	3.30	12.50	Vertical	-50.64	-13.00	37.64	90
8	6324.0	-56.33	3.80	11.50	Vertical	-50.78	-13.00	37.78	225
9	7114.5	-54.68	4.20	11.80	Vertical	-49.23	-13.00	36.23	0
10	7950.0	-52.58	4.40	12.30	Vertical	-46.83	-13.00	33.83	135
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.									
2. The worst emission was found in the antenna is Vertical position.									

LTE Band 14 QPSK 5MHz CH- Middle, RB 1

#### LTE Band 14 QPSK 10MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1576.0	-64.42	1.70	8.70	Vertical	-59.57	-40.00	19.57	225
3	2364.0	-63.47	2.30	12.00	Vertical	-55.92	-13.00	42.92	40
4	3152.0	-63.43	2.30	13.10	Vertical	-54.78	-13.00	41.78	135
5	3940.0	-62.45	2.90	12.50	Vertical	-55.00	-13.00	42.00	225
6	4728.0	-59.49	3.10	12.50	Vertical	-52.24	-13.00	39.24	0
7	5516.0	-57.60	3.30	12.50	Vertical	-50.55	-13.00	37.55	45
8	6304.0	-56.04	3.80	11.50	Vertical	-50.49	-13.00	37.49	90
9	7092.0	-55.47	4.20	11.80	Vertical	-50.02	-13.00	37.02	45
10	7880.0	-53.64	4.40	12.30	Vertical	-47.89	-13.00	34.89	225
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Vertical position.									



# 6. Main Test Instruments

Name	Manufacturer	Туре	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	150415	2021-05-15	2022-05-14
Universal Radio Communication Tester	Key sight	E5515C	GB44400275	2021-05-15	2022-05-14
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	391	2019-12-16	2021-12-15
Horn Antenna	R&S	HF907	102723	2020-08-11	2023-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
RF Cable	Agilent	SMA 15cm	0001	2021-06-09	2021-12-08
Software	R&S	EMC32	10.35.10	/	/

\*\*\*\*\*\*END OF REPORT \*\*\*\*\*\*



# **ANNEX A: The EUT Appearance**

The EUT Appearance are submitted separately.



# **ANNEX B: Test Setup Photos**

The Test Setup Photos are submitted separately.