

FCC RF EXPOSURE REPORT

FCC ID:TE7KC115

Project No. : 1910C002

Equipment: Kasa Spot Pan Tilt, 24/7 Recording

Brand Name : tp-link
Test Model : KC115
Series Model : N/A

Applicant: TP-Link Technologies Co., Ltd.

Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and

Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Manufacturer : TP-Link Technologies Co., Ltd.

Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and

Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Date of Receipt : Oct. 11, 2019

Date of Test : Oct. 17, 2019 ~ Nov. 05, 2019

Issued Date : Nov. 15, 2019

Report Version : R00

Test Sample: Engineering Sample No.: DG2019093074 for conducted,

DG2019093070 for radiated.

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part

2.1091

FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Rose . Liw Prepared by : Rose Liu

Approved by: Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000 Web: www.newbtl.com



REPORT ISSUED HISTORY

Report Version	Description	Issued Date	
R00	Original Issue	Nov. 15, 2019	





1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	TP-LINK	N/A	PIFA	N/A	2.97

2. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.97	1.9815	20.18	104.2317	0.04111	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

End of Test Report