

## Product Specification



Specification	weight	≈275g
	Conversion efficiency (full load)	≥75%
	input	5V3A, 9V2A, 15V2A (PD30W and above)
	Output	5W/7.5W/15W (MFM output) 5W (Qi wireless) (Side USB-C receptacle ) 5W
	input port	Rear USB-C receptacle
	output port	side USB-C receptacle (USB C port unique appearance design, not for Apple devices) + MFM + Qi wireless
	Ripple noise	≤200mVpp
	Working temperature	0~40℃
	Relative humidity	10%~80%
	Average working time without failure	Working for 10,000 hours, the average failure rate is less than 0.5% at 25℃
	Aging test	Normal temperature, full load aging time 4H
	No-load test	Input end power supply, output end no load, standby time 4H, electrical normal, no abnormal structure
	The response time	After power-on initialization, the normal recognition charging time of mobile phone is less than 3 seconds
LED	Power on	The indicator is steady blue
	Standby	The indicator is steady blue
	Charge	The indicator is steady blue
Usage	Connect the product to the PD2.0/3.0 charger through USB C to USB C data cable, and wait for the blue light on the product to be steady on. After about 8 seconds of initialization, it can enter the normal use state	
FCC Warning Statement:	<p>Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:</p> <ul style="list-style-type: none"> <li>- Reorient or relocate the receiving antenna.</li> <li>- Increase the separation between the equipment and receiver.</li> <li>- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.</li> <li>- Consult the dealer or an experienced radio/TV technician for help.</li> </ul> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. FCC Radiation Exposure Statement The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located for operating in conjunction with any other antenna or transmitter.</p>	