




## Notes:

- Material: 詳細材質+表面處理+背膠型式(可移膠 or 永久膠)  
(含膠厚度  $t = **\text{mm} \pm 15\%$ )
- Background:
- Printing color:
- Tolerance  $\pm 0.2\text{mm}$  unless otherwise specified.
- Label gap throughout the entire roll of 3mm.
- 特殊需求(需符合UL、.....等)
- 測試規範(依C201文件規範隨鍵盤環測 or 客戶規範、.....等)
- 判定標準(不可產生起泡、皺褶、翹起、脫膠、溢膠等情形, 如為可移膠需加入"撕下後產品上不可以有殘膠"字樣)
- 入料方式: 卷裝

| 003 | 修改安規                         | Vicky | 10/25<br>2021 |
|-----|------------------------------|-------|---------------|
| 002 | ADD WEEE LOGO<br>ADD UL LOGO | Vicky | 05/03<br>2021 |
| 001 | RELEASE DRAWING              | Vicky | 04/26<br>2021 |
| REV | DESCRIPTION                  | SIGN  | DATE          |

|                               |      |                            |       |     |       |                               |        |              |                                                                                       |           |
|-------------------------------|------|----------------------------|-------|-----|-------|-------------------------------|--------|--------------|---------------------------------------------------------------------------------------|-----------|
| UNITS OR<br>ASSEMBLY          | T16U | NAME                       |       |     |       | SCALE                         | DIM IN | M.M          |  |           |
|                               |      | LABEL SPEC FOR EU &UK T16U |       |     |       | LIMITS UNLESS OTHERWISE NOTED |        |              |                                                                                       |           |
| DRN                           |      | MATERIAL                   |       |     |       | 1-6                           | ±0.1   | 300-1000     | ±0.8                                                                                  | STOCK NO. |
| DSN                           |      | FINISH                     | _____ | QTY | 1 / 1 | 6-30                          | ±0.2   | 1000-2000    | ±1.2                                                                                  | SHEET     |
| CKD                           |      |                            |       |     |       | 30-100                        | ±0.3   | 2000-        | ±2.0                                                                                  |           |
| APPD                          |      |                            |       |     |       | 100-300                       | ±0.5   | ANG          | ±1/2*                                                                                 |           |
| 達方電子 Darfon Electronics Corp. |      |                            |       |     |       | ASSEMBLY DR.NO.               |        |              |                                                                                       |           |
|                               |      |                            |       |     |       | DRAWING NO.                   |        | 4E+20001.AKU |                                                                                       |           |