

# **FCC Test Report**

Report No.: AGC13779220901FE03

FCC ID : Z63-W2E9PRO

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: Wireless Headset

**BRAND NAME** : Mixcder, AUSDOM

**MODEL NAME** : E9, E9 PRO

**APPLICANT**: SHENZHEN AONI ELECTRONIC CO., LTD

**DATE OF ISSUE** : Sep. 19, 2022

**STANDARD(S)** : FCC Part 15.247

**REPORT VERSION** : V1.0

Attestation of Global Companie (Shenzhen) Co., Ltd



Report No.: AGC13779220901FE03

Page 2 of 69

#### REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 19, 2022	Valid	Initial Release




# **TABLE OF CONTENTS**

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RECEIVER INPUT BANDWIDTH	7
2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	7
2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR	7
2.6. RELATED SUBMITTAL(S) / GRANT (S)	8
2.7. TEST METHODOLOGY	8
2.8. SPECIAL ACCESSORIES	8
2.9. EQUIPMENT MODIFICATIONS	8
2.10. ANTENNA REQUIREMENT	8
3. MEASUREMENT UNCERTAINTY	9
4. DESCRIPTION OF TEST MODES	10
5. SYSTEM TEST CONFIGURATION	11
5.1. CONFIGURATION OF EUT SYSTEM	11
5.2. EQUIPMENT USED IN TESTED SYSTEM	11
5.3. SUMMARY OF TEST RESULTS	11
6. TEST FACILITY	12
7. PEAK OUTPUT POWER	13
7.1. MEASUREMENT PROCEDURE	13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
7.3. LIMITS AND MEASUREMENT RESULT	14
8. 20DB BANDWIDTH	19
8.1. MEASUREMENT PROCEDURE	19
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
8.3. LIMITS AND MEASUREMENT RESULTS	20
9. CONDUCTED SPURIOUS EMISSION	25
9.1. MEASUREMENT PROCEDURE  Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stampe Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the v presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within	ed by the "Dedicated Testing/Inspection written authorization of AGC. The test results

Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



9.3. MEASUREMENT EQUIPMENT USED 9.4. LIMITS AND MEASUREMENT RESULT	9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	25
10. RADIATED EMISSION  10.1. MEASUREMENT PROCEDURE  10.2. TEST SETUP  10.3. LIMITS AND MEASUREMENT RESULT  10.4. TEST RESULT  11. NUMBER OF HOPPING FREQUENCY  11.1. MEASUREMENT PROCEDURE  11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  11.3. MEASUREMENT EQUIPMENT USED  11.4. LIMITS AND MEASUREMENT RESULT  12.1. MEASUREMENT PROCEDURE  12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  12.3. MEASUREMENT PROCEDURE  12.4. LIMITS AND MEASUREMENT RESULT  13. FREQUENCY SEPARATION  13.1. MEASUREMENT PROCEDURE  13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  13.3. MEASUREMENT PROCEDURE  13.4. LIMITS AND MEASUREMENT RESULT  14.1. LIMITS AND MEASUREMENT RESULT  14.1. LIMITS OF LINE CONDUCTED EMISSION TEST  14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST  14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	9.3. MEASUREMENT EQUIPMENT USED	25
10.1. MEASUREMENT PROCEDURE  10.2. TEST SETUP  10.3. LIMITS AND MEASUREMENT RESULT  10.4. TEST RESULT  11. NUMBER OF HOPPING FREQUENCY  11.1. MEASUREMENT PROCEDURE  11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  11.3. MEASUREMENT EQUIPMENT USED  11.4. LIMITS AND MEASUREMENT RESULT  12. TIME OF OCCUPANCY (DWELL TIME)  12.1. MEASUREMENT PROCEDURE  12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  12.3. MEASUREMENT PROCEDURE  12.4. LIMITS AND MEASUREMENT RESULT  13. FREQUENCY SEPARATION  13.1. MEASUREMENT PROCEDURE  13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  13.3. MEASUREMENT PROCEDURE  13.4. LIMITS AND MEASUREMENT RESULT  14.1. LIMITS AND MEASUREMENT USED  14.4. LIMITS AND MEASUREMENT RESULT  14.4. LIMITS OF LINE CONDUCTED EMISSION TEST  14.5. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST  14.6. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	9.4. LIMITS AND MEASUREMENT RESULT	25
10.2. TEST SETUP  10.3. LIMITS AND MEASUREMENT RESULT  10.4. TEST RESULT	10. RADIATED EMISSION	46
10.2. TEST SETUP  10.3. LIMITS AND MEASUREMENT RESULT  10.4. TEST RESULT	10.1. MEASUREMENT PROCEDURE	46
10.4. TEST RESULT  11. NUMBER OF HOPPING FREQUENCY  11.1. MEASUREMENT PROCEDURE  11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  11.3. MEASUREMENT EQUIPMENT USED  11.4. LIMITS AND MEASUREMENT RESULT  12. TIME OF OCCUPANCY (DWELL TIME)  12.1. MEASUREMENT PROCEDURE  12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  12.3. MEASUREMENT EQUIPMENT USED  12.4. LIMITS AND MEASUREMENT RESULT  13. FREQUENCY SEPARATION  13.1. MEASUREMENT PROCEDURE  13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  13.3. MEASUREMENT PROCEDURE  13.4. LIMITS AND MEASUREMENT USED  14.4. LIMITS AND MEASUREMENT RESULT  14.4. LIMITS OF LINE CONDUCTED EMISSION TEST  14.5. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST  14.6. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	10.2. TEST SETUP	48
11. NUMBER OF HOPPING FREQUENCY	10.3. LIMITS AND MEASUREMENT RESULT	49
11.1. MEASUREMENT PROCEDURE	10.4. TEST RESULT	49
11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  11.3. MEASUREMENT EQUIPMENT USED  11.4. LIMITS AND MEASUREMENT RESULT  12. TIME OF OCCUPANCY (DWELL TIME)  12.1. MEASUREMENT PROCEDURE  12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  12.3. MEASUREMENT EQUIPMENT USED  12.4. LIMITS AND MEASUREMENT RESULT  13. FREQUENCY SEPARATION  13.1. MEASUREMENT PROCEDURE  13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  13.3. MEASUREMENT PROCEDURE  13.4. LIMITS AND MEASUREMENT USED  13.4. LIMITS AND MEASUREMENT RESULT  14.1. LIMITS OF LINE CONDUCTED EMISSION TEST  14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST  14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	11. NUMBER OF HOPPING FREQUENCY	59
11.3. MEASUREMENT EQUIPMENT USED  11.4. LIMITS AND MEASUREMENT RESULT  12. TIME OF OCCUPANCY (DWELL TIME)  12.1. MEASUREMENT PROCEDURE  12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  12.3. MEASUREMENT EQUIPMENT USED  12.4. LIMITS AND MEASUREMENT RESULT  13. FREQUENCY SEPARATION  13.1. MEASUREMENT PROCEDURE  13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  13.3. MEASUREMENT PROCEDURE  13.4. LIMITS AND MEASUREMENT USED  13.4. LIMITS AND MEASUREMENT RESULT  14.1. LIMITS OF LINE CONDUCTED EMISSION TEST  14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST  14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	11.1. MEASUREMENT PROCEDURE	59
11.4. LIMITS AND MEASUREMENT RESULT	11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	59
12. TIME OF OCCUPANCY (DWELL TIME)	11.3. MEASUREMENT EQUIPMENT USED	59
12.1. MEASUREMENT PROCEDURE	11.4. LIMITS AND MEASUREMENT RESULT	59
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	12. TIME OF OCCUPANCY (DWELL TIME)	60
12.3. MEASUREMENT EQUIPMENT USED	12.1. MEASUREMENT PROCEDURE	60
12.4. LIMITS AND MEASUREMENT RESULT	12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	60
13.1 MEASUREMENT PROCEDURE	12.3. MEASUREMENT EQUIPMENT USED	60
13.1. MEASUREMENT PROCEDURE	12.4. LIMITS AND MEASUREMENT RESULT	60
13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)  13.3. MEASUREMENT EQUIPMENT USED  13.4. LIMITS AND MEASUREMENT RESULT  14.1. LIMITS OF LINE CONDUCTED EMISSION TEST  14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST  14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST  14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	13. FREQUENCY SEPARATION	64
13.3. MEASUREMENT EQUIPMENT USED	13.1. MEASUREMENT PROCEDURE	64
13.4. LIMITS AND MEASUREMENT RESULT	13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	64
14. LINE CONDUCTED EMISSION TEST       0         14.1. LIMITS OF LINE CONDUCTED EMISSION TEST       0         14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST       0         14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST       0         14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST       0	13.3. MEASUREMENT EQUIPMENT USED	64
14.1. LIMITS OF LINE CONDUCTED EMISSION TEST	13.4. LIMITS AND MEASUREMENT RESULT	64
14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	14. LINE CONDUCTED EMISSION TEST	65
14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	14.1. LIMITS OF LINE CONDUCTED EMISSION TEST	65
14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	65
	14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	66
14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST		
	14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	67
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	APPENDIX A: PHOTOGRAPHS OF TEST SETUP	69
APPENDIX B: PHOTOGRAPHS OF EUT	APPENDIX B: PHOTOGRAPHS OF EUT	69





#### 1. VERIFICATION OF CONFORMITY

Applicant	SHENZHEN AONI ELECTRONIC CO., LTD
Address	No.5, Bldg., Honghui Industrial Park, 2nd Liuxian Road, Xin'An streets, Baoan District, Shenzhen, China
Manufacturer	SHENZHEN AONI ELECTRONIC CO., LTD
Address	No.5, Bldg., Honghui Industrial Park, 2nd Liuxian Road, Xin'An streets, Baoan District, Shenzhen, China
Factory	SHENZHEN AONI ELECTRONIC CO., LTD
Address	No.5, Bldg., Honghui Industrial Park, 2nd Liuxian Road, Xin'An streets, Baoan District, Shenzhen, China
Product Designation	Wireless Headset
Brand Name	Mixcder,AUSDOM
Test Model	E9
Series Model	E9 PRO
Declaration of Difference	All the series models are the same as the test model except for the model names.
Date of test	Sep. 09, 2022 to Sep. 19, 2022
Deviation	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BR/RF

## We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

Prepared By	Alan Duan	
	Alan Duan (Project Engineer)	Sep. 19, 2022
Reviewed By	Calvin Lin	
	Calvin Liu (Reviewer)	Sep. 19, 2022
Approved By	Max Zhang	
	Max Zhang (Authorized Officer)	Sep. 19, 2022



Report No.: AGC13779220901FE03

Page 6 of 69

## 2. GENERAL INFORMATION

#### 2.1. PRODUCT DESCRIPTION


The EUT is designed as "Wireless Headset". It is designed by way of utilizing the GFSK, Pi/4 DQPSK and 8DPSK technology to achieve the system operation.

A major technical description of EUT is described as following

A major technical description of Learnis described as following		
Operation Frequency	2.402 GHz to 2.480 GHz	
RF Output Power	11.091dBm (Max)	
Bluetooth Version	V5.0	
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK 1Mbps □GFSK 2Mbps	
Number of channels	79	
Hardware Version	V10	
Software Version	V03	
Antenna Designation	FPC Antenna (Comply with requirements of the FCC part 15.203)	
Antenna Gain	1.41dBi	
Power Supply	DC 3.7V by battery or DC 5V by adapter	

## 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402 MHz
	1	2403 MHz
	:	:
	38	2440 MHz
2402~2480MHz	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz





#### 2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a hopping sequence in data mode:

40, 21, 44, 23, 04, 15, 66, 56, 19, 78, 07, 28, 69, 55,

36, 45, 05, 13, 43, 74, 57, 35, 67, 76, 02, 34, 54, 63,

42, 11, 30, 06, 64, 25, 75, 48, 17, 33, 58, 01, 29, 14,

51, 72, 03, 31, 50, 61, 77, 18, 10, 47, 12, 68, 08, 49,

20, 00, 73, 09, 16, 60, 71, 41, 24, 53, 38, 26, 46, 37,

65, 32, 70, 52, 27, 59, 22, 62, 39

#### 2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:


- 1. LAP/UAP of the master of the connection.
- 2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.





The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.

## 2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID**: **Z63-W2E9PRO** filing to comply with the FCC PART 15.247 requirements.

#### 2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### 2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

#### 2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.10. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



Report No.: AGC13779220901FE03

Page 9 of 69

## 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$




## 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION	
1	Low channel GFSK	
2	Middle channel GFSK	
3	High channel GFSK	
4	Low channel π/4-DQPSK	
5	Middle channel π/4-DQPSK	
6	High channel π/4-DQPSK	
7	Low channel 8DPSK	
8	Middle channel 8DPSK	
9	High channel 8DPSK	
10	Hopping mode GFSK	
11	Hopping mode π/4-DQPSK	
12	Hopping mode 8DPSK	

#### Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

#### Software Setting





Report No.: AGC13779220901FE03

Page 11 of 69


## 5. SYSTEM TEST CONFIGURATION

## **5.1. CONFIGURATION OF EUT SYSTEM**

Radiated Emission Configure:



Conducted Emission Configure:



#### **5.2. EQUIPMENT USED IN TESTED SYSTEM**

It	em	Equipment	Model No.	ID or Specification	Remark
	1	Wireless Headset	E9	Z63-W2E9PRO	EUT
	2	Adapter	HW-050200C01	N/A	AE

## **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(1)	Peak Output Power	Compliant
15.247 (a)(1)	20 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.209	Radiated Emission	Compliant
15.247 (a)(1)(iii)	Number of Hopping Frequency	Compliant
15.247 (a)(1)(iii)	Time of Occupancy	Compliant
15.247 (a)(1)	Frequency Separation	Compliant
15.207	Conducted Emission	Compliant



Report No.: AGC13779220901FE03

Page 12 of 69

## 6. TEST FACILITY


Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

# TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Mar.28, 2022	Mar.27, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 09, 2022	Jun. 08, 2023
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A

#### TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 23, 2022	Mar. 22, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 03, 2022	Aug. 02, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Aug. 03, 2022	Aug. 02, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A





## 7. PEAK OUTPUT POWER

#### 7.1. MEASUREMENT PROCEDURE


For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW ≥RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

## 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

#### **PEAK POWER TEST SETUP**






#### 7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power					
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail	
	2402	8.032	<b></b> 21	Pass	
GFSK	2441	8.032	<b></b> \$21	Pass	
	2480	8.138	<b></b> 21	Pass	
π /4-DQPSK	2402	10.200	<b></b> \$21	Pass	
	2441	10.314	<b></b> \$21	Pass	
	2480	10.237	<b></b> 21	Pass	
8DPSK	2402	10.765	<b></b> \$21	Pass	
	2441	10.956	<b></b> \$21	Pass	
	2480	11.091	<b></b> \$21	Pass	

# **Test Graphs of Conducted Output Power**








Test\_Graph\_BR\_ANT1\_2480\_1Mbps\_Peak Power

#VBW 5.0 MHz

Span 5.000 MHz Sweep 1.066 ms (1000 pts)

Center 2.480000 GHz #Res BW 1.5 MHz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_EDR\_ANT1\_2441\_2Mbps\_Peak Power

#VBW 5.0 MHz

Span 5.000 MHz Sweep 1.066 ms (1000 pts)

Center 2.441000 GHz #Res BW 1.5 MHz






Test\_Graph\_EDR\_ANT1\_2402\_3Mbps\_Peak Power

#VBW 5.0 MHz

Span 5.000 MHz Sweep 1.066 ms (1000 pts)

Center 2.402000 GHz #Res BW 1.5 MHz





Test\_Graph\_EDR\_ANT1\_2480\_3Mbps\_Peak Power

#VBW 5.0 MHz

Span 5.000 MHz Sweep 1.066 ms (1000 pts)

Center 2.480000 GHz #Res BW 1.5 MHz




## 8. 20DB BANDWIDTH

## **8.1. MEASUREMENT PROCEDURE**

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
  The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
  bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

## 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






#### 8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and -20dB Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail
	2402	0.875	0.958	N/A	Pass
GFSK	2441	0.868	0.958	N/A	Pass
	2480	0.866	0.957	N/A	Pass
π /4-DQPSK	2402	1.187	1.330	N/A	Pass
	2441	1.190	1.331	N/A	Pass
	2480	1.190	1.333	N/A	Pass
8DPSK	2402	1.187	1.304	N/A	Pass
	2441	1.188	1.302	N/A	Pass
	2480	1.189	1.301	N/A	Pass

# Test Graphs of Occupied Bandwidth and -20 Bandwidth





















Report No.: AGC13779220901FE03

Page 25 of 69

#### 9. CONDUCTED SPURIOUS EMISSION

# 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- 3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
  - RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
- 4. Set SPA Trace 1 Max hold, then View.

## 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2

#### 9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6

# 9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT				
Amuliachia Limita	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 kHz Bandwidth Outside the	At least -20dBc than the limit			
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS		
intentional radiator is operating, the radio frequency	Channel			
power that is produce by the intentional radiator shall				
be at least 20 dB below that in 100KHz bandwidth				
within the band that contains the highest level of the				
desired power.	At least -20dBc than the limit	PASS		
In addition, radiation emissions which fall in the	Specified on the TOP Channel	PASS		
restricted bands, as defined in §15.205(a), must also				
comply with the radiated emission limits specified				
in§15.209(a))				



## Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands







Test\_Graph\_BR\_ANT1\_2441\_1Mbps\_Reference Level

#VBW 300 kHz

Span 3.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.441000 GHz #Res BW 100 kHz

Man

Freq Offset

Stop 25.00 GHz Sweep 2.152 s (30000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_BR\_ANT1\_2441\_1Mbps\_Higher Band Emissions

#VBW 300 kHz

Start 2.48 GHz #Res BW 100 kHz






Test\_Graph\_BR\_ANT1\_2480\_1Mbps\_Lower Band Emissions


#VBW 300 kHz





Test\_Graph\_EDR\_ANT1\_2402\_2Mbps\_Reference Level





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_EDR\_ANT1\_2402\_2Mbps\_Higher Band Emissions

#VBW 300 kHz

Stop 25.00 GHz Sweep 2.152 s (30000 pts)

Start 2.48 GHz #Res BW 100 kHz






Test\_Graph\_EDR\_ANT1\_2441\_2Mbps\_Lower Band Emissions

#VBW 300 kHz

Stop 2.400 GHz Sweep 228.0 ms (30000 pts)


Start 30 MHz #Res BW 100 kHz





Test\_Graph\_EDR\_ANT1\_2480\_2Mbps\_Reference Level





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_EDR\_ANT1\_2480\_2Mbps\_Higher Band Emissions

#VBW 300 kHz

Stop 25.00 GHz Sweep 2.152 s (30000 pts)

Start 2.50 GHz #Res BW 100 kHz






Test\_Graph\_EDR\_ANT1\_2402\_3Mbps\_Lower Band Emissions

#VBW 300 kHz

Stop 2.390 GHz Sweep 226.0 ms (30000 pts)

Start 30 MHz #Res BW 100 kHz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_EDR\_ANT1\_2441\_3Mbps\_Reference Level

#VBW 300 kHz

Span 3.000 MHz Sweep 2.000 ms (30000 pts)

Center 2.441000 GHz #Res BW 100 kHz





Test\_Graph\_EDR\_ANT1\_2441\_3Mbps\_Higher Band Emissions

#VBW 300 kHz

Stop 25.00 GHz Sweep 2.152 s (30000 pts)

Start 2.48 GHz #Res BW 100 kHz






Test\_Graph\_EDR\_ANT1\_2480\_3Mbps\_Lower Band Emissions


#VBW 300 kHz








### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_BR\_ANT1\_2480\_1Mbps\_Higher Band Edge Emissions
















Test\_Graph\_EDR\_HOP\_ANT1\_NA\_2Mbps\_Higher Band Edge Emissions









Test\_Graph\_EDR\_HOP\_ANT1\_NA\_3Mbps\_Higher Band Edge Emissions



Report No.: AGC13779220901FE03 Page 46 of 69

#### 10. RADIATED EMISSION

#### 10.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Report No.: AGC13779220901FE03

Page 47 of 69

# The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting	
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP	
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP	
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP	
Start ~Stop Frequency	1GHz~26.5GHz	
Start ~Stop i requerity	1MHz/3MHz for Peak, 1MHz/3MHz for Average	

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




#### 10.2. TEST SETUP


## Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Report No.: AGC13779220901FE03

Page 49 of 69

#### 10.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

### 10.4. TEST RESULT


#### Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



#### Radiated emission from 30MHz to 1000MHz

EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Horizontal




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		60.0691	4.53	16.44	20.97	40.00	-19.03	peak
2		138.8735	5.22	19.38	24.60	43.50	-18.90	peak
3		199.9856	4.20	20.06	24.26	43.50	-19.24	peak
4		279.0436	4.00	21.77	25.77	46.00	-20.23	peak
5		383.9318	7.29	22.68	29.97	46.00	-16.03	peak
6	*	900.1474	5.35	31.86	37.21	46.00	-8.79	peak

### **RESULT: PASS**




EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical



No	). N	۸k.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	I		40.4172	4.94	16.02	20.96	40.00	-19.04	peak
2	2		66.2662	5.96	18.02	23.98	40.00	-16.02	peak
3	3	1	20.2766	4.57	18.95	23.52	43.50	-19.98	peak
	1	2	90.0172	4.85	20.70	25.55	46.00	-20.45	peak
	5	6	42.8613	6.17	25.46	31.63	46.00	-14.37	peak
- 6	*	9	16.0687	6.16	34.15	40.31	46.00	-5.69	peak

**Note:** 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

2. All test modes had been pre-tested. The mode 9 is the worst case and recorded in the report.






Radiated emission above 1GHz

EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4804.000	44.28	0.08	44.36	74	-29.64	peak	
4804.000	37.15	0.08	37.23	54	-16.77	AVG	
7206.000	40.59	2.21	42.8	74	-31.2	peak	
7206.000	32.82	2.21	35.03	54	-18.97	AVG	
Remark:							
actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier.				

EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	43.95	0.08	44.03	74	-29.97	peak
4804.000	36.46	0.08	36.54	54	-17.46	AVG
7206.000	40.07	2.21	42.28	74	-31.72	peak
7206.000	31.52	2.21	33.73	54	-20.27	AVG
demark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			





EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 8	Antenna	Horizontal


Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
45.79	0.14	45.93	74	-28.07	peak
38.18	0.14	38.32	54	-15.68	AVG
41.62	2.36	43.98	74	-30.02	peak
34.26	2.36	36.62	54	-17.38	AVG
	(dBµV) 45.79 38.18 41.62	(dBμV) (dB) 45.79 0.14 38.18 0.14 41.62 2.36	(dBμV)     (dB)     (dBμV/m)       45.79     0.14     45.93       38.18     0.14     38.32       41.62     2.36     43.98	(dBμV)     (dB)     (dBμV/m)     (dBμV/m)       45.79     0.14     45.93     74       38.18     0.14     38.32     54       41.62     2.36     43.98     74	(dBμV)     (dB)     (dBμV/m)     (dBμV/m)     (dBμV/m)       45.79     0.14     45.93     74     -28.07       38.18     0.14     38.32     54     -15.68       41.62     2.36     43.98     74     -30.02

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 8	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4882.000	45.28	0.14	45.42	74	-28.58	peak
4882.000	37.64	0.14	37.78	54	-16.22	AVG
7323.000	40.96	2.36	43.32	74	-30.68	peak
7323.000	33.77	2.36	36.13	54	-17.87	AVG
emark:	•		•			•

Factor = Antenna Factor + Cable Loss - Pre-amplifier.





EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	46.59	0.22	46.81	74	-27.19	peak
4960.000	38.43	0.22	38.65	54	-15.35	AVG
7440.000	41.27	2.64	43.91	74	-30.09	peak
7440.000	32.88	2.64	35.52	54	-18.48	AVG
Remark:						
actor = Anter	na Factor + Cabl	e Loss – Pre-a	mplifier.		·	

Factor = A	Antenna ⊦ac	tor + Cable	Loss – Pre	e-amplitier.

EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
46.13	0.22	46.35	74	-27.65	peak
38.55	0.22	38.77	54	-15.23	AVG
40.77	2.64	43.41	74	-30.59	peak
31.95	2.64	34.59	54	-19.41	AVG
	(dBµV) 46.13 38.55 40.77	(dBµV) (dB) 46.13 0.22 38.55 0.22 40.77 2.64	(dBμV)     (dB)     (dBμV/m)       46.13     0.22     46.35       38.55     0.22     38.77       40.77     2.64     43.41	(dBμV)     (dB)     (dBμV/m)     (dBμV/m)       46.13     0.22     46.35     74       38.55     0.22     38.77     54       40.77     2.64     43.41     74	(dBμV)     (dB)     (dBμV/m)     (dBμV/m)     (dBμV/m)       46.13     0.22     46.35     74     -27.65       38.55     0.22     38.77     54     -15.23       40.77     2.64     43.41     74     -30.59

### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been tested. The 8DPSK modulation is the worst case and recorded in the report.




### Test result for band edge emission at restricted bands

EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Horizontal

#### Test Graph for Peak Measurement



Test Graph for Average Measurement



**RESULT: PASS** 




EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Vertical

Test Graph for Peak Measurement




Test Graph for Average Measurement






EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Horizontal

Test Graph for Peak Measurement




Test Graph for Average Measurement






EUT	Wireless Headset	Model Name	E9
Temperature	22°C	Relative Humidity	55%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. The 8DPSK modulation is the worst case and recorded in the report.



### 11. NUMBER OF HOPPING FREQUENCY

#### 11.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 3. VBW > RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.
- 4. Allow the trace to stabilize.

# 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

#### 11.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

#### 11.4. LIMITS AND MEASUREMENT RESULT

Test Data of Number of Hopping Frequency					
Test Mode	Number of Hopping Frequency	Limits	Pass or Fail		
GFSK Hopping	79	>=15	Pass		

### **Test Graphs of Number of Hopping Frequency**



Note: The GFSK modulation is the worst case and recorded in the report.



Report No.: AGC13779220901FE03

Page 60 of 69

# 12. TIME OF OCCUPANCY (DWELL TIME)

#### 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: Zero span, centered on a hopping channel.
- 2. RBW shall be ≤channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- 4. Detector function: Peak. Trace: Max hold.
- 5. Use the marker-delta function to determine the transmit time per hop.
- 6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer)  $\times$  (period specified in the requirements / analyzer sweep time)

7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

### 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

### 12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6


#### 12.4. LIMITS AND MEASUREMENT RESULT

Test Data of Dwell Time							
Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)	Pass or Fail		
2402	2.881	27.0*4	311.148	400	Pass		
2441	2.881	27.0*4	311.148	400	Pass		
2480	2.881	27.0*4	311.148	400	Pass		

Note: The 8DPSK modulation is the worst case and recorded in the report.



## **Test Graphs of Dwell Time**



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_BR\_HOP\_ANT1\_NA\_1Mbps\_2402\_Time per Burst

**#VBW** 3.0 MHz

Sweep 8.000 ms (30000 pts)

Web: http://www.agccert.com/






08:15:07 PM Sep 15, 2022 Frequency Trig Delay-2.000 ms Trig: Video #Atten: 40 dB Center Freq 2.441000000 GHz Avg Type: Log-Pwr PNO: Fast ↔ IFGain:Low **Auto Tune** ΔMkr1 2.881 ms 1.82 dB Ref 30.00 dBm Center Frea 2.441000000 GHz 1Δ2  $X_2$ Start Freq 2 441000000 GHz Stop Frea 2.441000000 GHz 1.000000 MHz Auto Man Freq Offset Center 2.441000000 GHz Res BW 1.0 MHz Span 0 Hz Sweep 8.000 ms (30000 pts) **#VBW 3.0 MHz** 

Test\_Graph\_BR\_HOP\_ANT1\_NA\_1Mbps\_2441\_Time per Burst

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





08:15:30 PM Sep 15, 2022 Frequency Trig Delay-2.000 ms Trig: Video #Atten: 40 dB Center Freq 2.480000000 GHz Avg Type: Log-Pwr PNO: Fast ↔ IFGain:Low **Auto Tune** ΔMkr1 2.881 ms 1.83 dB Ref 30.00 dBm Center Frea 2.480000000 GHz **1**∆2  $X_2$ Start Freq 2 480000000 GHz Stop Frea 2.480000000 GHz 1.000000 MHz Auto Man Freq Offset Center 2.480000000 GHz Res BW 1.0 MHz Span 0 Hz Sweep 8.000 ms (30000 pts) #VBW 3.0 MHz Test\_Graph\_BR\_HOP\_ANT1\_NA\_1Mbps\_2480\_Time per Burst



#### 13. FREQUENCY SEPARATION

#### 13.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: Wide enough to capture the peaks of two adjacent channels.
- 2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3. Video (or average) bandwidth (VBW) ≥ RBW.
- 4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2


#### 13.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

#### 13.4. LIMITS AND MEASUREMENT RESULT

Test Data of Frequency Separation					
Test Mode	Channel Separation (MHz)	Limits	Pass or Fail		
GFSK Hopping	1.003	>= 2/3 -20dB BW	Pass		

### **Test Graphs of Number of Hopping Frequency**



Note: The GFSK modulation is the worst case and recorded in the report.



### 14. LINE CONDUCTED EMISSION TEST


### 14.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Fraguanay	Maximum RF	Line Voltage
Frequency	Q.P. (dBμV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Report No.: AGC13779220901FE03 Page 66 of 69

### 14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


#### 14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



### 14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

#### Line Conducted Emission Test Line 1-L



# MEASUREMENT RESULT: "agc\_fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.162000	51.40	6.8	65	14.0	QP	L1
0.426000	31.50	5.6	57	25.8		L1
0.446000	33.80	5.5	57	23.1		L1
0.470000	32.80	5.5	57	23.7	_	L1
0.490000	32.30	5.4	56	23.9		L1
0.538000	36.10	5.4	56	19.9		L1

# MEASUREMENT RESULT: "agc\_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.186000 0.538000	35.50 33.50	6.6 5.4	54 46	18.7 12.5		L1 L1
0.558000	30.90	5.4	46	15.1		L1
0.582000	30.90 31.10	5.4 5.4	46 46	15.1 14.9	AV AV	L1 L1
0.630000	28.50	5.4	46	17.5	AV	L1



### Line Conducted Emission Test Line 2-N



# MEASUREMENT RESULT: "agc\_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.162000	48.30	6.8	65	17.1	QP	N
0.186000	46.50	6.6	64	17.7	QP	N
0.210000	43.80	6.5	63	19.4	QP	N
0.534000	38.20	5.4	56	17.8	QP	N
0.582000	34.20	5.4	56	21.8	QP	N
0.602000	34.10	5.4	56	21.9	QP	N

### MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	38.50	6.9	56	17.5	AV	N
0.538000	30.40	5.4	46	15.6	AV	N
0.558000	29.40	5.4	46	16.6	AV	N
0.582000	28.30	5.4	46	17.7	AV	N
0.606000	28.90	5.4	46	17.1	AV	N
0.630000	26.30	5.4	46	19.7	AV	N

#### **RESULT: PASS**

Note: All the test modes had been tested, the mode 9 was the worst case. Only the data of the worst case would be record in this test report.



### **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC13779220901AP02

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC13779220901AP03

----END OF REPORT----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.