

CUSTOMER

KFT-107

ROHS

SPECIFICATION FOR APPROVAL

MODEL NO. : RC 25X2.5-10MM-8.1uH-01

KEFEITE NO. : 79-P1(R25X2.5)-0.08X24PX14TS-10MM-8.1uH

CUSTOMER P/N: T1

DATE : 2022/08/15

REV : A1

※Product complies with: ☒RoHS ☐PAHS ☐6P ☐REACH

PLEASE RETURN TO US COPY OF "SPECIFICATION FOR APPROVAL" WITH YOUR APPROVED SIGNATURES.

	"√"	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITIONAL APPROVED			
REJECTED			

SHENZHEN KEFEITE ELELECTRONICS CO., LTD

FactoryAddress:2/F,New era industrial area C Building
Guantiancommunity, Shenzhen.

TEL:86-755-27352660

FAX:86-755-27352742

HTTP:WWW.Kefeite.net



SHENZHEN KEFEITE ELECTRONICS CO., LTD

[illegible]


NOTES :



SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-79	VERSION:	A1
CUSTOMER NO:	T1 watch coil	PAGE:	3/4
KFT P/N:	79-P1 (R25X2.5)-0.08X24PX14TS--10MM-8.1uH	Date:	2022/08/15

1. CONFIGURATION&DIMENSIONS:



A	$20.9 \pm 1.0\text{mm}$
B	$14.9 \pm 0.5\text{mm}$
C	$1.1 \pm 0.2\text{mm}$
D	$10.0 \pm 1.5\text{mm}$
E	3.0ref
F	2~4mm
G	$24.5 \pm 1.0\text{mm}$
H	2.8MAX (不含离型纸)

2. ELECTRICAL CHARACTER:

atm	Specifications	Test conditions	Test instrument
Inductance	$4.8\mu\text{H} \pm 5\%$	100KHZ/1.0V	CH1062
Inductance	$8.1\mu\text{H} \pm 5\%$	100KHZ/1.0V	CH1062
(RDC)	$163\text{m}\Omega$ MAX	25°C	HG2512

3. SCHEMATIC



4. PART NUMBERING:PRODUCT IDENTIFICATION

79	T1(RC25X2.5)	0.08X24PX14TS	10MM	8.1uH	
					Inductance
					Line Length
					Wire Diameter
					Magnetic Sheet Specification
					Customer number

DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
Hu Guoqiang	Zhou Miao		Wan Jianjun



SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-79	VERSION:	A1
CUSTOMER NO:	T1 watch coil	PAGE:	4/4
KFT P/N:	79-P1(R25X2.5)-0.08X24PX14TS--10MM-8.1uH	Date:	2022/08/15

5. MATERIAL LIST:

NO	ITEM	DESCRIPTION	RATING	SUPPLIERS	UL NO.	REMARK
1	WIRE	热风线	155℃	SHANTOU SHENGANG ELECTRICAL INDUSTRIAL CO., LTD	E239508	
2	SOLDER	99.3/0.7		SHENZHEN Hong Xing Wei solder Limited		
3	CORE	25/7.7/2.5		Changxing BO Cheng Electronics CO., LTD		
4	EPOXY	1603HFR-HS		DONGBU FINE CHEMICAL CO LTD		
5	Strong Magnet	7.8X2.5>3500GS		DONGBU FINE CHEMICAL CO LTD		

6. GENERAL SPECIFICATION:

1 Tested at 1.0KHZ/0.25Vrms, 0 Adc.

Average current for 40℃ temperature rise from 25℃.

2 Saturation current(Isat):

Inductance drop:10% typ at Isat.

3 Heat rating current(Irms):

$L@I_{rms} = \Delta T \leq 40^{\circ}\text{C}$.

4 Electrical specifications at 25℃

5 Storage Temp:-40℃....+85℃

6 Operating Temp:-40℃....+85℃

DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
Hu Guoqiang	Zhou Miao		Wan Jianjun