



ATW-T1406, T1407 Antenna Report

Specification	
Model	ATW-T1406, T1407 *Both models have same PCB and Antenna
Antenna Type	PIFA Antenna
Impedance	50Ω
Frequency Range	2402 – 2480MHz
Gain	0.12dBi (Peak)
Manufacturer	Audio-Technica

PIFA Antenna



Antenna Radiation Pattern



Test Configuration

Test Facility

Test Site	Audio-Technica Fukui Inc.
Test Software	TY2100AM (TOYO Corporation)
Date	8/3/2023
Measurer	Hiroki Takeichi


Test Equipment

Equipment	Manufacturer	Model	Cal. Date	Cal. Due
Signal Generator	ROHDE&SCHWARZ	SMB 100A	25/4/2022	25/4/2025
Test Receiver	ROHDE&SCHWARZ	ESU	27/4/2022	27/4/2023
Antenna	SCHWARZBECK	BBHA9120E	N/A	N/A
Reference Antenna	SCHWARZBECK	BBHA9120B	3/5/2022	3/5/2023

Test Procedure

1. The reference antenna with known antenna gain was placed on the top of the turntable 1.5 meter above ground and connected to the Signal Generator.
2. The receiving antenna was placed 3 meters far away from the center of the turntable and connected to the Spectrum analyzer.
3. Turn on the Signal analyzer output. The turntable was rotated by 360 degrees and the spectrum analyzer record the input level for each degree.
4. The maximum reading is the antenna gain of the reference antenna.
5. Replace the reference antenna with EUT.
6. Turn on the Signal analyzer output. The turntable was rotated by 360 degrees and the spectrum analyzer record the input level for each degree.
7. Subtract the maximum reading of the reference antenna and the measured reading of the EUT to obtain the radiation pattern of the antenna.
8. The peak reading is the antenna gain of EUT.

Test Set-up (Block Diagram of Antenna Radiation Test)



Test Set-up Photo

