



**FCC 47 CFR PART 15 SUBPART C  
ISED RSS-210 ISSUE 11**

**CERTIFICATION TEST REPORT**

*For*

**5000 Series**

**MODEL NUMBER: HX369LB, HX369W4**

**FCC ID: 2ADZNHX36**

**IC: 20109-HX36**

**REPORT NUMBER: 4791566766-1**

**ISSUE DATE: November 20, 2024**

*Prepared for*

**Philips Oral Healthcare, Inc. (FCC)  
22100 Bothell-Everett Highway Bothell Washington 98021 United States  
Philips Oral Healthcare (ISED)  
22100 Bothell-Everett Highway Bothell US 98021 United States Of America  
(Excluding The States Of Alaska)**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	November 20, 2024	Initial Issue	

Note: This report is based on 4790458026-1 which is issued by UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch. The EUT had already applied for the FCC ID, the customer added the new EUT name and model name. The new model HX369LB and HX369W4 have the same RF technical construction including circuit diagram, PCB Layout, component layout and performance with HX369SR. The difference is minor non-RF boards and circuitry, minor RF antenna matching circuit, model number and product description. Therefore, the new model will be reconsidered testing in the EMC part and spot check in RF part from 9kHz-1GHz. For the RF data, please refer to the original report.

Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	Transmitter 99% Emission Bandwidth / 20dB Bandwidth	RSS-Gen 6.7/ Part 15.215 (c)	Note 3
2	Transmitter Frequency Stability (Temperature & Voltage Variation)	CFR 47 FCC §15.225(e) ISED RSS-Gen Clause 6.11 ISED RSS-210 Annex B.6	Note 3
3	Fundamental Field Strength	CFR 47 FCC §15.225(a)(b)(c)(d) ISED RSS-Gen Clause 6.12 ISED RSS-210 Annex B.6	PASS
4	Radiated Emissions	CFR 47 FCC§15.209(a) CFR 47 FCC§15.225(d) ISED RSS-Gen Clause 6.13 ISED RSS-210 Annex B.6	PASS
5	Band Edge Radiated Emissions	CFR 47 FCC §15.209(a) CFR 47 FCC §15.225(c)(d) ISED RSS-Gen Clause 6.13 ISED RSS-210 Annex B.6	PASS
6	Antenna Requirement	CFR 47 FCC §15.203 ISED RSS-Gen Clause 6.8	PASS
<p>Note 1: This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>Note 2: The measurement result for the sample received is &lt;Pass&gt; according to &lt; CFR 47 FCC PART 15 SUBPART C, ISED RSS-210 Issue 11 and ISED RSS-GEN Issue 5 &gt; when &lt;Simple Acceptance&gt; decision rule is applied.</p> <p>Note 3: Please refer to original test report 4790458026-1.</p>			

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b>	<b>5</b>
<b>2. TEST METHODOLOGY</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY</b>	<b>8</b>
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
<b>5. EQUIPMENT UNDER TEST</b>	<b>9</b>
5.1. DESCRIPTION OF EUT	9
5.2. MAXIMUM FIELD STRENGTH	9
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.4. TEST ENVIRONMENT	10
5.5. DESCRIPTION OF TEST SETUP	11
5.6. MEASURING INSTRUMENT AND SOFTWARE USED	12
<b>6. ANTENNA PORT TEST RESULTS</b>	<b>13</b>
6.1. 99% & 20dB BANDWIDTH	13
6.2. TRANSMITTER FREQUENCY STABILITY	14
<b>7. RADIATED EMISSION TEST RESULTS</b>	<b>15</b>
7.1. FIELD STRENGTH OF INTENTIONAL EMISSIONS	22
7.2. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz	23
7.3. SPURIOUS EMISSIONS BELOW 30MHz	25
<b>8. ANTENNA REQUIREMENTS</b>	<b>28</b>

## 1. ATTESTATION OF TEST RESULTS

### FCC

#### Applicant Information

Company Name: Philips Oral Healthcare, Inc.  
Address: 22100 Bothell-Everett Highway Bothell Washington 98021 United States

### ISED

#### Applicant Information

Company Name: Philips Oral Healthcare  
Address: 22100 Bothell-Everett Highway Bothell US 98021 United States Of America (Excluding The States Of Alaska)

### FCC

#### Manufacturer Information

Company Name: Philips Oral Healthcare, Inc.  
Address: 22100 Bothell-Everett Highway Bothell Washington 98021 United States

### ISED

#### Manufacturer Information


Company Name: Philips Oral Healthcare  
Address: 22100 Bothell-Everett Highway Bothell US 98021 United States Of America (Excluding The States Of Alaska)

### EUT Information

EUT Name: 5000 Series  
Model: HX369LB  
Series Model: HX369W4  
Model Difference: Please refer to clause 5.1. Description of EUT  
Brand: Sonicare  
Sample Received Date: November 18, 2024  
Sample Status: Normal  
Sample ID: 7837255  
Date of Tested: November 20, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-210 Issue 11	PASS
ISED RSS-GEN Issue 5	PASS


Prepared By:



---

Fanny Huang  
Project Engineer

Checked By:



---

Kebo Zhang  
Senior Project Engineer

Approved By:



---

Stephen Guo  
Laboratory Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013, ISED RSS-210 Issue 11 and RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p>
---------------------------	--

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiation Emission test (include Fundamental emission) (9KHz-30MHz)	2.2 dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	4.00 dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	5.78 dB (1 GHz-18 GHz)
	5.23 dB (18 GHz-26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	5000 Series
Model	HX369LB
Series Model:	HX369W4
Model difference:	HX369W4 has the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with HX369LB. The difference lies only the color, model number.
Operation Frequency	13.56MHz
Modulation	BPSK
Battery	DC 3.6 V

### 5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Max Peak field strength @30m (dB $\mu$ V/m)
13.56	5.06

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
13.56	Enameled copper wire antenna	0

#### 5.4. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	45 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	0 ~ 40°C
Voltage:	VL	DC 3.06 V
	VN	DC 3.6 V
	VH	DC 4.14 V

Note: VL= Lower Extreme Test Voltage  
VN= Nominal Voltage  
VH= Upper Extreme Test Voltage  
TN= Normal Temperature

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	/	/	/	/

### I/O CABLES


Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	/	/	/	/	/

### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

### TEST SETUP

### SETUP DIAGRAM FOR TESTS



Note:

- 1.The EUT can't transmit the NFC signal when in charging.
- 2.New battery has been used during measurement.
- 3.Test was performed with tag and without tag, but only the worst case data (with tag) was recorded in the report.
- 4.NFC support both ISO /IEC 14443A and ISO /IEC 14443B. All lowest and highest data rates as per the standards are supported - 106 kbps, 212 kbps, 424 kbps and 848 kbps, all the modes had been tested, but only the worst data (ISO 14443A 106 kbps) was recorded in the report.

## 5.6. MEASURING INSTRUMENT AND SOFTWARE USED

Radiated Emissions						
Equipment		Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver		KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna		TDK	HLP-3003C	130959	May.08, 2023	May.07 2026
Preamplifier		HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
Loop antenna		Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier		TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Preamplifier		TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Software						
Description			Manufacturer		Name	Version
Test Software for Radiated Emissions			Farad		EZ-EMC	Ver. UL-3A1
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025

## 6. ANTENNA PORT TEST RESULTS

### 6.1. 99% & 20dB BANDWIDTH

#### LIMITS

Section	Test Item	Limit
ANSI C63.10 Section 6.9.2	20dB% Bandwidth	For reporting purposes only.
ISED RSS-Gen Clause 6.7 Issue 5	99 % Occupied Bandwidth	For reporting purposes only.


#### TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1 kHz. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

Note: Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

The type of band for the signal is narrowband.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	/	Relative Humidity	/
Atmosphere Pressure	/	Test Voltage	/

#### RESULTS

Please refer to the original report.

## 6.2. TRANSMITTER FREQUENCY STABILITY

### LIMITS

CFR 47 FCC §15.225(e)  
ISED RSS-210 Annex B B.6

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of 0 degrees to + 40 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.


### TEST SETUP AND PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	10 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	/	Relative Humidity	/
Atmosphere Pressure	/	Test Voltage	/

### RESULTS

Please refer to the original report.

## 7. RADIATED EMISSION TEST RESULTS

### LIMITS

Fundamental field strength

FCC Reference:	Part 15.225(a)(b)(c)(d) & 15.209(a)
ISED Canada Reference:	RSS-Gen 6.13 & RSS-210 B.6 & RSS-GEN Clause 8.9
Test Method Used:	ANSI C63.10 Sections 6.3, 6.4 and 6.5

Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measured Distance (Meters)
13.553-13.567	15848	84	30
13.410-13.553/13.567-13.710	334	50.47	30
13.110-13.410/13.710-14.010	106	40.51	30

Note(s):

1. The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

2. The limit is specified at a test distance of 30 meters. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).

### Radiation Disturbance Test Limit for FCC (Class B) (9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30MHz.



### Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.


<sup>2</sup>Above 38.6c

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
106 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

## TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

- The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
- The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
- The EUT was placed on a turntable with 80 cm above ground.
- The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
- The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
- For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
- Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
- The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377 \Omega$ ; For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
7. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


### **TEST ENVIRONMENT**

Temperature	22.8 °C	Relative Humidity	60 %
Atmosphere Pressure	101kPa	Test Voltage	DC 3.6 V

### **RESULTS**

## 7.1. FIELD STRENGTH OF INTENTIONAL EMISSIONS

### FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	13.1694	35.35	-47.43	-12.08	40.51	-52.59	peak
2	13.3845	35.09	-47.44	-12.35	40.51	-52.86	peak
3	13.5591	52.49	-47.43	5.06	84.00	-78.94	peak
4	13.7445	34.60	-47.43	-12.83	40.51	-53.34	peak
5	13.8957	34.55	-47.44	-12.89	40.51	-53.40	peak
6	13.9767	35.66	-47.44	-11.78	40.51	-52.29	peak


Note: 1. Result Level = Read Level + Correct Factor.

2. The test result is for 30m, the distance extrapolation factor (40dB/decade) has been considered in the test result.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

## 7.2. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz


### SPURIOUS EMISSIONS (HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	30.11	-14.34	15.77	40.00	-24.23	QP
2	202.6600	29.36	-11.23	18.13	43.50	-25.37	QP
3	292.8700	32.69	-11.04	21.65	46.00	-24.35	QP
4	599.3900	26.58	-4.98	21.60	46.00	-24.40	QP
5	747.8000	25.50	-1.25	24.25	46.00	-21.75	QP
6	855.4700	29.05	-0.76	28.29	46.00	-17.71	QP

Note: 1. Result Level = Read Level + Correct Factor.

### HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.8500	31.45	-14.31	17.14	40.00	-22.86	QP
2	350.1000	28.84	-8.48	20.36	46.00	-25.64	QP
3	444.1900	33.03	-7.47	25.56	46.00	-20.44	QP
4	532.4600	32.66	-6.14	26.52	46.00	-19.48	QP
5	878.7500	28.24	-0.21	28.03	46.00	-17.97	QP
6	928.2200	27.56	-0.07	27.49	46.00	-18.51	QP


Note: 1. Result Level = Read Level + Correct Factor.



### 7.3. SPURIOUS EMISSIONS BELOW 30MHz

#### SPURIOUS EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	64.61	-88.00	-23.39	47.60	-74.89	-3.90	-70.99	peak
2	0.0299	55.69	-88.13	-32.44	38.10	-83.94	-13.40	-70.54	peak
3	0.0499	51.51	-88.60	-37.09	33.64	-88.59	-17.86	-70.73	peak
4	0.0637	58.18	-88.32	-30.14	31.54	-81.64	-19.96	-61.68	peak
5	0.0881	42.73	-88.31	-45.58	28.71	-97.08	-22.79	-74.29	peak
6	0.1273	49.52	-88.83	-39.31	25.52	-90.81	-25.98	-64.83	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

### 150 kHz ~ 490 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1894	55.36	-89.06	-33.70	22.06	-85.20	-29.44	-55.76	peak
2	0.2360	51.53	-89.01	-37.48	20.31	-88.98	-31.19	-57.79	peak
3	0.2761	49.72	-88.99	-39.27	18.90	-90.77	-32.60	-58.17	peak
4	0.3139	48.98	-88.97	-39.99	17.71	-91.49	-33.79	-57.70	peak
5	0.3829	47.16	-88.93	-41.77	15.99	-93.27	-35.51	-57.76	peak
6	0.4458	46.53	-88.88	-42.35	14.66	-93.85	-36.84	-57.01	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

### 490kHz ~ 30MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	6.7756	36.93	-48.35	-11.42	29.54	-62.92	-21.96	-40.96	peak
2	10.0217	36.43	-47.40	-10.97	29.54	-62.47	-21.96	-40.51	peak
3	13.5629	51.71	-47.43	4.28	/	/	/	/	fundamental
4	21.4716	34.24	-46.77	-12.53	29.54	-64.03	-21.96	-42.07	peak
5	24.9833	33.58	-46.70	-13.12	29.54	-64.62	-21.96	-42.66	peak
6	29.7344	33.41	-46.42	-13.01	29.54	-64.51	-21.96	-42.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. About the Fundamental emission test result please refer to section 7.1.

## 8. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### RESULTS

Complies

---

**END OF REPORT**