

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	LED Stand Light Remote control
Model Name	TT-CL025, TT-CL028, TT-CL029, TT-CL030
FCC ID	2AVUHTT-CL00X

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

$$P_t = -6.115\text{dBm} = 0.24\text{mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.24\text{mW} / 5\text{mm}) \cdot [\sqrt{2.48(\text{GHz})}] = 0.075 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

$$P_t = -32.98\text{dBm} = 0.000503\text{mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.000503\text{mW} / 5\text{mm}) \cdot [\sqrt{0.43392(\text{GHz})}] = 0.000066 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

The BLE and 433.92MHz can transmit simultaneously

$$0.075 + 0.000066 = 0.075066 < 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$$

### 4. CONCLUSION

The SAR evaluation is not required.