

RF EXPOSURE REPORT



Report No.: 15071019-FCC-H2

Supersede Report No.: N/A

Applicant	Sun Cupid Technology (HK) Ltd.	
Product Name	LTE Moblie phone	
Model No.	N4L	
Serial No.	N/A	
Test Standard	FCC 2.1093.2014	
Test Date	July 30 to August 13, 2015	
Issue Date	November 05, 2015	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15071019-FCC-H2
Page	3 of 11

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	9
5.1 RF EXPOSURE.....	9
5.2 TEST RESULT	10

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15071019-FCC-H2	NONE	Original	November 05, 2015

2. Customer information

Applicant Name	Sun Cupid Technology (HK) Ltd.
Applicant Add	16/F, CEO Tower, 77 Wing Hong St, Cheung Sha Wan, Kowloon
Manufacturer	SUNCUPID (SHENZHEN) ELECTRONIC LTD
Manufacturer Add	Baolong Industrial City, Longgang District, Shenzhen Hi-Tech Road, Building 1, A 7

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: LTE Moblie phone

Main Model: N4L

Serial Model: N/A

Antenna Gain:

GSM850: 0.08 dBi
 PCS1900: 0.8 dBi
 UMTS-FDD Band V: 0.08 dBi
 UMTS-FDD Band IV: 0.73 dBi
 UMTS-FDD Band II: 0.89 dBi
 Bluetooth/BLE: 0.93 dBi
 WIFI(2.4G): 0.93 dBi
 WIFI(5G): 1.82 dBi
 LTE Band 2: 0.88 dBi
 LTE Band 4: 0.75 dBi
 LTE Band 5: 0.07 dBi
 LTE Band 12: -1.73 dBi
 LTE Band 17: -1.73 dBi
 GPS:-0.32dBi

Type of Modulation:

GSM / GPRS: GMSK
 EGPRS: GMSK, 8PSK
 UMTS-FDD: QPSK, 16QAM
 802.11a/b/g/n: DSSS, OFDM
 Bluetooth: GFSK, π /4DQPSK, 8DPSK
 BLE: GFSK
 LTE Band: QPSK, 16QAM
 GPS:BPSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
 UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
 UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
 RX : 2112.4 ~ 2152.6 MHz
 UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
 RX: 1932.4 ~ 1987.6 MHz

Test Report	15071019-FCC-H2
Page	7 of 11

WIFI:802.11b/g/n(20M): 2412-2462 MHz
WIFI:802.11n(40M): 2422-2452 MHz
WIFI:802.11a,n(20,40M): 5150-5250 MH
Bluetooth& BLE: 2402-2480 MHz
LTE Band 2 TX: 1852.5 ~ 1907.5 MHz; RX : 1932.5 ~ 1987.5 MHz
LTE Band 4 TX: 1712.5 ~ 1752.5 MHz; RX : 2112.5 ~ 2152.5 MHz
LTE Band 5 TX: 826.5 ~ 846.5 MHz; RX : 871.5 ~ 891.5 MHz
LTE Band 12 TX:699.7 ~ 715.3 MHz; RX : 729.7~ 745.3MHz
LTE Band 17 TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz
GPS RX:1575.42 MHz

Number of Channels:

GSM 850: 124CH
PCS1900: 299CH
UMTS-FDD Band V : 102CH
UMTS-FDD Band IV: 202CH
UMTS-FDD Band II : 277CH
WIFI :802.11b/g/n(20M): 11CH
WIFI :802.11n(40M): 7CH
Bluetooth: 79CH
BLE: 40CH
GPS:1CH

Port:

Power Port, Earphone Port, USB Port

Input Power:

Battery:
Model:NUBN4
Spec: 3.8V,2150mAh,10.0Wh
Adapter:
Model:KNC005N-050100U
Input: AC100-240V; 50/60Hz; 0.2A Max
Output: DC 5.0V,1A

Trade Name :

NUU

GPRS/EGPRS Multi-slot class

8/10/12

FCC ID:

2ADINNUUN4L

Date EUT received:

July 29, 2015

Test Report	15071019-FCC-H2
Page	8 of 11

Test Date(s): July 30 to August 13, 2015

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	7.429	7±1	8	6.310	1.96	3
	Mid	2441	7.732	7±1	8	6.310	1.97	3
	High	2480	8.055	8±1	9	7.943	2.50	3
π /4 DQPSK	Low	2402	6.679	6±1	7	5.012	1.55	3
	Mid	2441	6.969	6±1	7	5.012	1.57	3
	High	2480	7.274	7±1	8	6.310	1.99	3
8-DPSK	Low	2402	6.844	7±1	8	6.310	1.96	3
	Mid	2441	7.170	7±1	8	6.310	1.97	3
	High	2480	7.470	7±1	8	6.310	1.99	3

WIFI(2.4G) Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	9.08	8.5±1	9.5	8.913	2.77	3
	Mid	2437	9.12	8.5±1	9.5	8.913	2.78	3
	High	2462	9.01	8.5±1	9.5	8.913	2.80	3
802.11g	Low	2412	8.95	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.57	8.5±1	9.5	8.913	2.78	3
	High	2462	8.50	8.5±1	9.5	8.913	1.98	3
802.11n (20M)	Low	2412	8.40	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.80	8.5±1	9.5	8.913	2.78	3
	High	2462	8.62	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	8.98	8.5±1	9.5	8.913	2.47	3
	Mid	2437	8.97	8.5±1	9.5	8.913	2.78	3
	High	2452	9.12	8.5±1	9.5	8.913	2.79	3

WIFI (5G) Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11a	Low	5180	7.03	7±1	8	6.310	2.87	3
	Mid	5200	7.39	7±1	8	6.310	2.88	3
	High	5240	7.40	7±1	8	6.310	2.89	3
802.11g	Low	5180	7.34	7±1	8	6.310	2.87	3
	Mid	5200	7.69	7±1	8	6.310	2.88	3
	High	5240	7.49	7±1	8	6.310	2.89	3
802.11n (40M)	Low	5190	7.89	7±1	8	6.310	2.87	3
	High	5230	7.98	7±1	8	6.310	2.89	3

BLE Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	0.172	1±1	2	1.585	0.49	3
	Mid	2440	0.531	1±1	2	1.585	0.50	3
	High	2480	0.381	1±1	2	1.585	0.50	3

Result: Compliance

No SAR measurement is required.