

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093) and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Brand Name : ulefone

Model Name : GQ5007

Family Model : Armor 25T, Armor 25T Pro, Armor 25 Ultra,
Armor 25T Ultra, Armor 25, Armor 25 Lite,
Armor 25 Pro, Armor 25s, Armor 25s Pro

Report No. : S24050905706001

FCC ID : 2AOWK-5007

Prepared for

Shenzhen Gotron Electronic CO.,LTD.

7B01, Building A, Block 1, Anhongji Tianyao Plaza, Longhua District, Shenzhen City,
Guangdong Province China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name** Shenzhen Gotron Electronic CO.,LTD.Address..... 7B01, Building A, Block 1, Anhongji Tianyao Plaza, Longhua District,
Shenzhen City, Guangdong Province China**Manufacturer's Name** . Shenzhen Gotron Electronic CO.,LTD.Address..... 7B01, Building A, Block 1, Anhongji Tianyao Plaza, Longhua District,
Shenzhen City, Guangdong Province China**Product description**

Product name Mobile Phone

Brand Name ulefone

Model and/or type
reference GQ5007Family Model Armor 25T, Armor 25T Pro, Armor 25 Ultra, Armor 25T Ultra, Armor 25, Armor 25 Lite,
Armor 25 Pro, Armor 25s, Armor 25s Pro
FCC 47 CFR Part 2(2.1093)**Standards** IEEE Std 1528-2013

Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Test Sample Number S240509057006

Date of Test

Date (s) of performance of tests... May. 28, 2024 ~ Jun. 07, 2024

Date of Issue Jul. 02, 2024

Test Result **Pass**Prepared By : Jack Li
Jack Li
(Project Engineer)Reviewed By : Aaron Cheng
Aaron Cheng
(Supervisor)Approved By : Alex Li
Alex Li
(Manager)

❖ ❖ Revision History ❖ ❖

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Jul. 02, 2024	Jack Li

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability	26
5.2. SAR measurement uncertainty	26
6. RF Exposure Positions	27
6.1. Ear and handset reference point	27
6.2. Definition of the cheek position	27
6.3. Definition of the tilt position	29
6.4. Body Worn Accessory	29
6.5. Wireless Router Devices	30
7. RF Output Power	31
7.1. GSM Conducted Power	31
7.2. WCDMA Conducted Power	31
7.3. LTE Conducted Power	33

7.4. WLAN & Bluetooth Output Power	49
7.5. NFC	51
8. Antenna Location.....	51
9. Stand-alone SAR test exclusion.....	52
10. SAR Results	52
10.1. SAR measurement Result.....	52
10.1.1. SAR measurement Result of GSM850.....	53
10.1.2. SAR measurement Result of GSM1900.....	54
10.1.3. SAR measurement Result of WCDMA Band 2.....	55
10.1.4. SAR measurement Result of WCDMA Band 4.....	56
10.1.5. SAR measurement Result of WCDMA Band 5.....	57
10.1.6. SAR measurement Result of LTE Band 2	58
10.1.7. SAR measurement Result of LTE Band 4	59
10.1.8. SAR measurement Result of LTE Band 5	61
10.1.9. SAR measurement Result of LTE Band 7	63
10.1.10. SAR measurement Result of LTE Band 12	65
10.1.11. SAR measurement Result of LTE Band 17	67
10.1.12. SAR measurement Result of LTE Band 41	69
10.1.13. SAR measurement Result of LTE Band 66	71
10.1.14. SAR measurement Result of WLAN2.4G	72
10.1.15. SAR measurement Result of WLAN5.2G	73
10.1.16. SAR measurement Result of WLAN5.8G	74
10.2. Simultaneous Transmission Analysis.....	76
11. Appendix A. Photo documentation	77
12. Appendix B. System Check Plots.....	78
13. Appendix C. Plots of High SAR Measurement.....	95
14. Appendix D. Calibration Certificate	160

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
HEAD AND TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for GQ5007 are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)				Max. Reported SAR (W/kg)
		PCE	DTS	NII	DSS	
1-g Head		0.712	0.721	0.478	0.332	0.721
1-g Body-Worn (Separation distance of 10mm)		0.752	0.205	0.109	0.166	0.752
1-g Hotspot (Separation distance of 10mm)		0.752	0.205	0.109	0.166	
Max Simultaneous Tx	Head	1.433	1.433	1.190	1.044	1.433
	Body-Worn	0.957	0.957	0.861	0.918	0.957
	Hotspot	0.957	0.957	0.861	0.918	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093), and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Mobile Phone
Brand Name	uifone
Model Name	GQ5007
Family Model	Armor 25T, Armor 25T Pro, Armor 25 Ultra, Armor 25T Ultra, Armor 25, Armor 25 Lite, Armor 25 Pro, Armor 25s, Armor 25s Pro
Model Difference	All models are the same circuit and RF module, except for model names.
FCC ID	2AOWK-5007
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna Type	PIFA Antenna
Battery Information	DC 3.87V, 6500mAh, 25.155Wh
HW Version	N/A
SW Version	N/A
Device Operating Configurations	
Supporting Mode(s)	GSM850/1900,WCDMABand2/4/5,LTEBand2/4/5/7/12/17/41/66, WLAN 2.4G/5G, Bluetooth, NFC

Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK), NFC(ASK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	LTE Band 41	2535-2655	
	LTE Band 66	1710-1780	2110-2200
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	NFC	13.56	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EGPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 4)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
	3, tested with power control all Max.(LTE Band 41)		

	3, tested with power control all Max.(LTE Band 66)
--	--

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe 3423-EPGO-426 with following specifications is used



- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 2.5 mm
- Distance between probe tip and sensor center: 1 mm
- Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
- Probe linearity: ± 0.06 dB
- Axial isotropy: ± 0.01 dB
- Hemispherical Isotropy: ± 0.01 dB
- Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
- Lower detection limit: 8mW/kg

Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms

Photo of SAM phantom SN 16/15 SAM119




The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by Smart Phones.

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	3423-EPGO-426	Sep. 18, 2023	Sep. 17, 2024
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	3500 MHz Dipole	SID3500	SN 09/12 DIP 3G500-360	Oct. 15, 2022	Oct. 14, 2025
☐	MVG	3700 MHz Dipole	SID3700	SN 09/12 DIP 3G/700-361	Oct. 15, 2022	Oct. 14, 2025
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Apr. 26, 2024	Apr. 25, 2025

☒	R&S	Wideband radio communication tester	CMW500	103917	Apr. 26, 2024	Apr. 25, 2025
☒	HP	Network Analyzer	8753D	3410J01136	Apr. 26, 2024	Apr. 25, 2025
☒	Agilent	MXG Vector Signal Generator	N5182A	MY47070317	Apr. 25, 2024	Apr. 24, 2025
☒	Agilent	Power meter	E4419B	MY45102538	Apr. 25, 2024	Apr. 24, 2025
☒	Agilent	Power sensor	E9301A	MY41495644	Apr. 25, 2024	Apr. 24, 2025
☒	Agilent	Power sensor	E9301A	US39212148	Apr. 25, 2024	Apr. 24, 2025
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 04, 2023	Jul. 03, 2024
☒	N/A	Thermometer	N/A	LES-085	Mar. 27, 2023	Mar. 26, 2026
☒	MVG	SAM Phantom	SSM2	SN 16/15 SAM119	NCR	NCR
☒	MVG	Device Holder	SMPPD	SN 16/15 MSH100	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 750	Head 750	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 835	Head 835	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 1800	Head 1800	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 1900	Head 1900	NCR	NCR
☒	Shenzhen	Human	Head 2450	Head 2450	NCR	NCR

	Tianxu Communication Technology Co., Ltd.	Simulating Liquid				
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 2600	Head 2600	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 5200	Head 5200	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 5800	Head 5800	NCR	NCR

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For Wi-Fi/BT power measurement, use engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure Wi-Fi/BT output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan

above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1.6 W/kg 1 g limit, or 1.26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	≤ 1.5 · $\Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	$\sigma \text{ (S/m)} (\pm 5\%)$	ϵ_r	$\sigma \text{ (S/m)}$		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	40.88	0.90	21.5 °C	Jun. 04, 2024
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	41.53	0.91	21.5 °C	May. 30, 2024
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.34	1.40	21.7 °C	May. 28, 2024
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.78	1.44	21.5 °C	Jun. 03, 2024
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	37.72	1.76	21.5 °C	Jun. 05, 2024
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	39.17	2.02	21.4 °C	May. 29, 2024
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	34.87	4.60	21.5 °C	Jun. 07, 2024
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	34.30	5.25	21.9 °C	Jun. 06, 2024

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W)		Measured SAR		Liquid Temp.	Test Date
	(±10%)		(Normalized to 1W)			
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz	8.60 (7.74~9.46)	5.78 (5.20~6.36)	8.64	5.79	21.5 °C	Jun. 04, 2024
835MHz	9.40 (8.46~10.34)	6.28 (5.65~6.91)	9.89	6.19	21.5 °C	May. 30, 2024
1800MHz	37.06 (33.35~40.77)	20.01 (18.01~22.01)	35.65	18.62	21.7 °C	May. 28, 2024
1900MHz	39.69 (35.72~43.66)	20.92 (18.83~23.01)	43.50	22.14	21.5 °C	Jun. 03, 2024
2450MHz	50.05 (45.05~55.06)	23.80 (21.42~26.18)	47.19	22.50	21.5 °C	Jun. 05, 2024
2600MHz	54.16 (48.74~59.58)	24.85 (22.37~27.34)	57.59	25.53	21.4 °C	May. 29, 2024
5200MHz	162.59 (146.33~178.85)	56.21 (50.59~61.83)	147.84	52.17	21.5 °C	Jun. 07, 2024
5800MHz	182.20 (163.98~200.42)	61.32 (55.19~67.45)	181.97	61.09	21.9 °C	Jun. 06, 2024

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.




Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.50	32.92	33.04	32.98	24.47	23.89	24.01	23.95
GPRS(GMSK,1 Tx slot)	33.50	32.95	33.06	32.97	24.47	23.92	24.03	23.94
GPRS(GMSK,2 Tx slot)	32.00	31.87	31.98	31.89	25.98	25.85	25.96	25.87
GPRS(GMSK,3 Tx slot)	30.00	29.73	29.86	29.75	25.74	25.47	25.60	25.49
GPRS(GMSK,4 Tx slot)	29.00	28.43	28.62	28.52	25.99	25.42	25.61	25.51
EGPRS(8PSK,1 Tx slot)	28.00	27.67	27.74	27.96	18.97	18.64	18.71	18.93
EGPRS(8PSK,2 Tx slot)	27.00	26.77	26.64	26.56	20.98	20.75	20.62	20.54
EGPRS(8PSK,3 Tx slot)	25.00	24.56	24.27	24.30	20.74	20.30	20.01	20.04
EGPRS(8PSK,4 Tx slot)	23.50	23.07	23.07	23.09	20.49	20.06	20.06	20.08
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880	1909.8	(dBm)	1850.2	1880	1909.8
GSM (GMSK)	30.00	29.01	29.62	29.70	20.97	19.98	20.59	20.67
GPRS(GMSK,1 Tx slot)	30.00	28.97	29.59	29.68	20.97	19.94	20.56	20.65
GPRS(GMSK,2 Tx slot)	29.00	27.87	28.50	28.52	22.98	21.85	22.48	22.50
GPRS(GMSK,3 Tx slot)	26.50	25.76	26.36	26.41	22.24	21.50	22.10	22.15
GPRS(GMSK,4 Tx slot)	25.50	24.69	25.10	25.16	22.49	21.68	22.09	22.15
EGPRS(8PSK,1 Tx slot)	27.00	26.55	26.58	26.42	17.97	17.52	17.55	17.39
EGPRS(8PSK,2 Tx slot)	25.50	25.48	25.05	25.16	19.48	19.46	19.03	19.14
EGPRS(8PSK,3 Tx slot)	24.00	22.93	23.11	23.57	19.74	18.67	18.85	19.31
EGPRS(8PSK,4 Tx slot)	22.50	21.55	21.78	22.01	19.49	18.54	18.77	19.00

7.2. WCDMA Conducted Power

WCDMA Band 2	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC12.2K	24.00	23.00	23.34	23.50
HSDPA Sub 1	23.00	22.19	22.52	22.61
HSDPA Sub 2	22.50	21.47	21.95	22.23

HSDPA Sub 3	21.00	20.05	20.99	20.75
HSDPA Sub 4	21.50	20.67	21.38	21.12
HSUPA Sub 1	22.50	21.08	22.22	22.36
HSUPA Sub 2	23.00	21.93	22.33	22.55
HSUPA Sub 3	21.50	20.10	21.07	21.38
HSUPA Sub 4	23.00	22.08	22.44	22.57
HSUPA Sub 5	22.00	20.39	21.71	21.94
WCDMA Band 4	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC12.2K	23.50	23.36	23.24	23.02
HSDPA Sub 1	22.50	22.42	22.31	22.09
HSDPA Sub 2	22.00	21.99	21.90	21.71
HSDPA Sub 3	21.00	20.95	20.81	20.22
HSDPA Sub 4	21.50	20.66	21.26	20.96
HSUPA Sub 1	22.50	21.22	22.12	21.94
HSUPA Sub 2	22.50	22.22	22.15	22.07
HSUPA Sub 3	21.50	20.90	21.05	20.95
HSUPA Sub 4	22.50	22.42	22.34	22.10
HSUPA Sub 5	22.00	20.95	21.65	21.61
WCDMA Band 5	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	23.50	23.31	23.13	23.19
HSDPA Sub 1	22.50	22.36	22.17	22.25
HSDPA Sub 2	22.00	21.90	21.92	21.89
HSDPA Sub 3	21.00	20.86	20.54	20.77
HSDPA Sub 4	21.00	20.69	20.65	20.80
HSUPA Sub 1	22.50	21.60	21.98	22.06
HSUPA Sub 2	22.50	22.24	21.95	22.00
HSUPA Sub 3	21.00	20.89	20.76	20.93
HSUPA Sub 4	22.50	22.35	22.19	22.23
HSUPA Sub 5	22.00	20.78	21.44	21.52

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	23.00	22.35	22.53	22.86
			1	2	23.00	22.42	22.60	22.95
			1	5	23.00	22.35	22.55	22.93
			3	0	23.50	22.46	22.61	22.97
			3	1	23.50	22.49	22.66	22.99
			3	2	23.50	22.49	22.62	23.02
			6	0	22.50	21.60	21.79	22.13
		16QAM	1	0	22.50	21.61	21.89	22.10
			1	2	22.50	21.81	22.01	22.29
			1	5	22.50	21.73	21.94	22.19
			3	0	22.50	21.51	21.72	21.98
			3	1	22.50	21.57	21.73	22.08
			3	2	22.50	21.53	21.68	22.02
			6	0	21.50	20.74	20.88	21.22
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	23.50	22.53	22.47	22.73
			1	7	23.50	22.61	22.89	23.00
			1	14	23.50	22.49	22.73	23.02
			8	0	22.50	21.67	21.73	21.93
			8	4	22.50	21.68	21.88	22.07
			8	7	22.50	21.65	21.82	22.01
			15	0	22.00	21.66	21.75	21.98
		16QAM	1	0	22.50	21.83	21.86	22.10
			1	7	22.50	21.89	22.18	22.27
			1	14	22.50	21.80	22.08	22.29
			8	0	21.50	20.68	20.74	20.94
			8	4	21.50	20.69	20.90	21.10
			8	7	21.50	20.66	20.83	21.01
			15	0	21.00	20.64	20.74	20.99
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration		(dBm)			
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	23.50	22.57	22.70	22.95
			1	12	23.50	22.67	22.86	23.11
			1	24	23.50	22.58	22.76	23.08
			12	0	22.50	21.66	21.78	22.10
			12	6	22.50	21.71	21.90	22.15
			12	11	22.50	21.67	21.79	22.11
			25	0	22.50	21.66	21.79	22.11
		16QAM	1	0	22.50	21.91	21.95	22.25
			1	12	22.50	21.99	22.19	22.48
			1	24	22.50	21.85	22.06	22.37
			12	0	21.50	20.69	20.83	21.08
			12	6	21.50	20.73	20.90	21.12
			12	11	21.50	20.67	20.80	21.11
			25	0	21.50	20.68	20.83	21.14
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.50	22.65	22.72	22.94
			1	24	23.50	22.67	22.88	23.09
			1	49	23.50	22.57	22.85	23.17
			25	0	22.50	21.68	21.77	21.96
			25	12	22.50	21.71	21.86	22.09
			25	24	22.50	21.60	21.80	22.02
			50	0	22.50	21.66	21.81	22.02
		16QAM	1	0	23.00	22.02	22.04	22.21
			1	24	23.00	21.89	22.19	22.34
			1	49	23.00	21.82	22.18	22.52
			25	0	21.50	20.69	20.80	21.01
			25	12	21.50	20.74	20.89	21.14
			25	24	21.50	20.63	20.84	21.06
			50	0	21.50	20.68	20.82	21.03
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE	15MHz	QPSK	1	0	23.50	22.60	22.61	22.84

Band 2			1	37	23.50	22.66	22.92	23.07
			1	74	23.50	22.50	22.81	23.12
			36	0	22.50	21.67	21.75	21.89
			36	18	22.50	21.65	21.83	22.04
			36	37	22.50	21.57	21.85	22.01
			75	0	22.00	21.65	21.80	21.99
		16QAM	1	0	22.50	21.88	21.87	22.18
			1	37	22.50	21.90	22.14	22.35
			1	74	22.50	21.86	22.06	22.38
			36	0	21.50	20.66	20.76	20.91
			36	18	21.50	20.67	20.86	21.07
			36	37	21.50	20.60	20.86	21.04
			75	0	21.00	20.64	20.80	20.99
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.50	22.53	22.47	22.73
			1	49	23.50	22.61	22.89	23.00
			1	99	23.50	22.49	22.73	23.02
			50	0	22.50	21.67	21.73	21.93
			50	24	22.50	21.68	21.88	22.07
			50	49	22.50	21.65	21.82	22.01
			100	0	22.00	21.66	21.75	21.98
		16QAM	1	0	22.50	21.83	21.86	22.10
			1	49	22.50	21.89	22.18	22.27
			1	99	22.50	21.80	22.08	22.29
			50	0	21.50	20.68	20.74	20.94
			50	24	21.50	20.69	20.90	21.10
			50	49	21.50	20.66	20.83	21.01
			100	0	21.00	20.64	20.74	20.99

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.50	23.14	22.71	22.38
			1	2	23.50	23.20	22.78	22.41
			1	5	23.50	23.17	22.74	22.37
			3	0	23.50	23.27	22.78	22.43

			3	1	23.50	23.29	22.80	22.47
			3	2	23.50	23.30	22.82	22.47
			6	0	22.50	22.38	21.91	21.56
		16QAM	1	0	23.00	22.49	22.01	21.61
			1	2	23.00	22.65	22.02	21.77
			1	5	23.00	22.39	21.96	21.57
			3	0	22.50	22.32	21.84	21.52
			3	1	22.50	22.27	21.87	21.53
			3	2	22.50	22.34	21.83	21.50
			6	0	22.00	21.53	21.00	20.72
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.50	23.31	22.97	22.84
			1	7	23.50	23.26	23.05	22.96
			1	14	23.50	22.89	22.88	22.57
			8	0	22.50	22.29	22.01	21.93
			8	4	22.50	22.30	22.10	21.96
			8	7	22.50	22.21	21.97	21.84
			15	0	22.50	22.22	21.99	21.90
		16QAM	1	0	23.00	22.53	22.22	22.11
			1	7	23.00	22.61	22.29	22.35
			1	14	23.00	22.11	22.12	21.90
			8	0	21.50	21.30	21.00	20.97
			8	4	21.50	21.31	21.06	21.00
			8	7	21.50	21.18	21.01	20.88
			15	0	21.50	21.21	20.96	20.93
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.50	23.37	22.91	22.65
			1	12	23.50	23.47	23.01	22.74
			1	24	23.50	23.32	22.93	22.56
			12	0	23.00	22.41	21.98	21.64
			12	6	23.00	22.50	22.02	21.70
			12	11	23.00	22.43	21.93	21.61
			25	0	22.50	22.42	21.97	21.64
		16QAM	1	0	23.00	22.61	22.23	21.97

			1	12	23.00	22.71	22.26	21.93
			1	24	23.00	22.70	22.19	21.89
			12	0	22.00	21.43	20.95	20.65
			12	6	22.00	21.54	21.01	20.74
			12	11	22.00	21.46	20.90	20.66
			25	0	21.50	21.47	21.00	20.70
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.50	23.44	22.98	22.87
			1	24	23.50	23.42	23.03	22.83
			1	49	23.50	23.26	23.02	22.68
			25	0	22.50	22.35	21.97	21.74
			25	12	22.50	22.45	22.02	21.78
			25	24	22.50	22.33	21.97	21.71
			50	0	22.50	22.39	21.99	21.75
		16QAM	1	0	23.00	22.76	22.27	22.09
			1	24	23.00	22.72	22.40	22.07
			1	49	23.00	22.50	22.27	21.99
			25	0	21.50	21.38	20.99	20.84
			25	12	21.50	21.48	21.06	20.84
			25	24	21.50	21.37	20.96	20.78
			50	0	21.50	21.40	20.98	20.77
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.50	23.44	22.97	22.89
			1	37	23.50	23.36	23.05	22.89
			1	74	23.50	23.09	23.01	22.62
			36	0	22.50	22.32	21.99	21.88
			36	18	22.50	22.34	22.02	21.84
			36	37	22.50	22.26	21.95	21.73
			75	0	22.50	22.32	22.00	21.82
		16QAM	1	0	23.00	22.76	22.25	22.12
			1	37	23.00	22.63	22.38	22.18
			1	74	23.00	22.42	22.25	21.94
			36	0	21.50	21.37	20.98	20.94
			36	18	21.50	21.35	21.04	20.90

			36	37	21.50	21.24	21.01	20.77
			75	0	21.50	21.34	20.99	20.86
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.50	23.31	22.97	22.84
			1	49	23.50	23.26	23.05	22.96
			1	99	23.50	22.89	22.88	22.57
			50	0	22.50	22.29	22.01	21.93
			50	24	22.50	22.30	22.10	21.96
			50	49	22.50	22.21	21.97	21.84
			100	0	22.50	22.22	21.99	21.90
		16QAM	1	0	23.00	22.53	22.22	22.11
			1	49	23.00	22.61	22.29	22.35
			1	99	23.00	22.11	22.12	21.90
			50	0	21.50	21.30	21.00	20.97
			50	24	21.50	21.31	21.06	21.00
			50	49	21.50	21.18	21.01	20.88
			100	0	21.50	21.21	20.96	20.93

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	23.00	22.56	22.87	22.71
			1	2	23.00	22.66	22.92	22.73
			1	5	23.00	22.57	22.83	22.69
			3	0	23.00	22.67	22.93	22.77
			3	1	23.00	22.71	22.93	22.80
			3	2	23.00	22.71	22.92	22.81
			6	0	22.50	21.75	22.02	21.89
		16QAM	1	0	22.50	21.90	22.06	21.96
			1	2	22.50	21.97	22.24	22.15
			1	5	22.50	21.76	22.11	22.02
			3	0	22.00	21.62	21.98	21.79
			3	1	22.00	21.75	22.00	21.86
			3	2	22.00	21.65	21.89	21.76
			6	0	21.50	20.86	21.12	21.03
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration		(dBm)			
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	23.00	22.44	22.74	22.60
			1	7	23.00	22.61	22.83	22.67
			1	14	23.00	22.56	22.71	22.59
			8	0	22.00	21.68	21.95	21.83
			8	4	22.00	21.75	21.99	21.87
			8	7	22.00	21.72	21.94	21.81
			15	0	22.00	21.69	21.94	21.80
		16QAM	1	0	22.50	21.74	21.97	21.96
			1	7	22.50	21.89	22.09	22.05
			1	14	22.50	21.80	22.08	21.87
			8	0	21.50	20.73	21.04	20.91
			8	4	21.50	20.83	21.09	20.92
			8	7	21.50	20.79	21.02	20.88
			15	0	21.00	20.69	20.96	20.83
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	23.50	22.70	22.99	22.91
			1	12	23.50	22.91	23.09	22.98
			1	24	23.50	22.85	22.98	22.81
			12	0	22.50	21.76	22.03	21.89
			12	6	22.50	21.86	22.08	21.95
			12	11	22.50	21.87	22.01	21.83
			25	0	22.50	21.80	22.04	21.90
		16QAM	1	0	22.50	21.96	22.29	22.21
			1	12	22.50	22.27	22.42	22.33
			1	24	22.50	22.07	22.32	22.17
			12	0	21.50	20.77	21.06	20.92
			12	6	21.50	20.89	21.11	20.95
			12	11	21.50	20.88	21.02	20.85
			25	0	21.50	20.83	21.09	20.92
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE	10MHz	QPSK	1	0	23.50	22.80	23.08	23.06

Band 5			1	24	23.50	23.00	23.11	23.01
			1	49	23.50	23.10	23.00	22.93
			25	0	22.50	21.79	22.04	22.02
			25	12	22.50	21.96	22.10	22.01
			25	24	22.50	21.94	21.98	21.87
			50	0	22.50	21.89	22.05	21.98
		16QAM	1	0	22.50	22.12	22.29	22.41
			1	24	22.50	22.34	22.29	22.31
			1	49	22.50	22.33	22.35	22.24
			25	0	21.50	20.84	21.09	21.06
			25	12	21.50	21.02	21.16	21.03
			25	24	21.50	20.99	21.02	20.90
			50	0	21.50	20.88	21.06	20.98

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.50	22.50	22.69	23.24
			1	12	23.50	22.63	22.85	23.43
			1	24	23.50	22.54	22.80	23.29
			12	0	22.50	21.53	21.78	22.32
			12	6	22.50	21.62	21.86	22.41
			12	11	22.50	21.60	21.85	22.39
			25	0	22.50	21.58	21.83	22.38
		16QAM	1	0	23.00	21.78	21.88	22.51
			1	12	23.00	21.75	22.05	22.58
			1	24	23.00	21.82	21.98	22.45
			12	0	21.50	20.54	20.76	21.30
			12	6	21.50	20.63	20.85	21.38
			12	11	21.50	20.60	20.81	21.32
			25	0	21.50	20.61	20.82	21.38
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.50	22.56	22.74	23.14
			1	24	23.50	22.63	22.84	23.36
			1	49	23.50	22.66	22.92	23.38
			25	0	22.50	21.50	21.76	22.20

			25	12	22.50	21.65	21.90	22.36
			25	24	22.50	21.70	21.93	22.41
			50	0	22.50	21.65	21.89	22.33
		16QAM	1	0	23.00	21.82	22.01	22.43
			1	24	23.00	21.85	22.09	22.54
			1	49	23.00	21.87	22.07	22.57
			25	0	21.50	20.54	20.76	21.18
			25	12	21.50	20.65	20.86	21.35
			25	24	21.50	20.72	20.89	21.40
50	0	21.50	20.62	20.83	21.30			
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	23.50	22.50	22.65	22.90
			1	37	23.50	22.70	22.88	23.25
			1	74	23.50	22.72	22.89	23.31
			36	0	22.50	21.50	21.73	22.05
			36	18	22.50	21.67	21.89	22.23
			36	37	22.50	21.70	21.90	22.34
			75	0	22.50	21.62	21.84	22.21
		16QAM	1	0	23.00	21.79	21.79	22.04
			1	37	23.00	21.90	22.07	22.51
			1	74	23.00	21.87	22.09	22.54
			36	0	21.50	20.47	20.70	21.02
			36	18	21.50	20.64	20.85	21.21
			36	37	21.50	20.67	20.86	21.33
			75	0	21.50	20.60	20.79	21.16
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.50	22.41	22.55	22.79
			1	49	23.50	22.70	22.84	23.10
			1	99	23.50	22.57	22.78	23.23
			50	0	22.50	21.48	21.71	22.04
			50	24	22.50	21.76	21.93	22.21
			50	49	22.50	21.78	21.93	22.36
			100	0	22.50	21.63	21.77	22.18
		16QAM	1	0	22.50	21.67	21.83	21.99

			1	49	22.50	22.02	21.99	22.28
			1	99	22.50	21.74	22.00	22.49
			50	0	21.50	20.45	20.66	21.00
			50	24	21.50	20.71	20.87	21.17
			50	49	21.50	20.75	20.89	21.30
			100	0	21.50	20.59	20.71	21.13

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	23.00	22.66	22.54	22.57
			1	2	23.00	22.74	22.61	22.69
			1	5	23.00	22.64	22.53	22.58
			3	0	23.00	22.76	22.65	22.70
			3	1	23.00	22.76	22.64	22.73
			3	2	23.00	22.78	22.62	22.70
			6	0	22.00	21.84	21.74	21.79
		16QAM	1	0	22.50	21.88	21.88	21.75
			1	2	22.50	22.11	21.94	21.93
			1	5	22.50	21.89	21.85	21.82
			3	0	22.00	21.80	21.69	21.73
			3	1	22.00	21.82	21.62	21.76
			3	2	22.00	21.76	21.67	21.70
			6	0	21.00	20.93	20.84	20.89
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	23.00	22.88	22.86	22.80
			1	7	23.00	22.85	22.79	22.77
			1	14	23.00	22.71	22.73	22.76
			8	0	22.00	21.80	21.74	21.66
			8	4	22.00	21.81	21.82	21.78
			8	7	22.00	21.78	21.80	21.69
			15	0	22.00	21.81	21.81	21.70
		16QAM	1	0	22.50	22.06	22.05	22.01
			1	7	22.50	22.10	22.07	22.02
			1	14	22.50	22.02	22.01	22.07
			8	0	21.00	20.82	20.77	20.68

			8	4	21.00	20.87	20.84	20.80
			8	7	21.00	20.81	20.83	20.73
			15	0	21.00	20.81	20.79	20.69
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	23.00	22.77	22.72	22.65
			1	12	23.00	22.89	22.78	22.80
			1	24	23.00	22.77	22.65	22.70
			12	0	22.00	21.82	21.69	21.73
			12	6	22.00	21.82	21.76	21.80
			12	11	22.00	21.76	21.76	21.70
			25	0	22.00	21.78	21.75	21.74
		16QAM	1	0	22.50	22.12	22.05	21.92
			1	12	22.50	22.13	22.11	22.12
			1	24	22.50	22.05	21.98	21.87
			12	0	21.00	20.84	20.70	20.75
			12	6	21.00	20.85	20.79	20.78
			12	11	21.00	20.75	20.75	20.72
			25	0	21.00	20.82	20.79	20.77
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	23.00	22.88	22.86	22.80
			1	24	23.00	22.85	22.79	22.77
			1	49	23.00	22.71	22.73	22.76
			25	0	22.00	21.80	21.74	21.66
			25	12	22.00	21.81	21.82	21.78
			25	24	22.00	21.78	21.80	21.69
			50	0	22.00	21.81	21.81	21.70
		16QAM	1	0	22.50	22.06	22.05	22.01
			1	24	22.50	22.10	22.07	22.02
			1	49	22.50	22.02	22.01	22.07
			25	0	21.00	20.82	20.77	20.68
			25	12	21.00	20.87	20.84	20.80
			25	24	21.00	20.81	20.83	20.73
			50	0	21.00	20.81	20.79	20.69

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	23.00	22.65	22.66	22.66
			1	12	23.00	22.74	22.74	22.75
			1	24	23.00	22.60	22.65	22.65
			12	0	22.00	21.68	21.65	21.66
			12	6	22.00	21.75	21.75	21.75
			12	11	22.00	21.70	21.70	21.67
			25	0	22.00	21.74	21.68	21.68
		16QAM	1	0	22.50	22.00	21.87	21.87
			1	12	22.50	22.03	22.07	22.02
			1	24	22.50	21.86	21.89	22.04
			12	0	21.00	20.69	20.65	20.66
			12	6	21.00	20.73	20.74	20.78
			12	11	21.00	20.72	20.71	20.67
			25	0	21.00	20.74	20.70	20.72
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	23.00	22.76	22.76	22.74
			1	24	23.00	22.76	22.78	22.74
			1	49	23.00	22.72	22.73	22.76
			25	0	22.00	21.60	21.58	21.60
			25	12	22.00	21.75	21.75	21.73
			25	24	22.00	21.72	21.69	21.64
			50	0	22.00	21.68	21.69	21.64
		16QAM	1	0	22.50	22.08	22.02	22.00
			1	24	22.50	22.02	21.93	22.07
			1	49	22.50	21.97	21.95	22.01
			25	0	21.00	20.64	20.61	20.62
			25	12	21.00	20.79	20.79	20.77
			25	24	21.00	20.72	20.72	20.68
			50	0	21.00	20.70	20.67	20.63

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB	RB		40065/2537.	40640/259	41215/2652.5

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
Band	Band Width	Modulation	RB Size	RB Offset	Tune-up (dBm)	40090/2540	40640/2595	41190/2650
			RB Size	RB Offset		40090/2540	40640/2595	41190/2650
LTE Band 41	5MHz	QPSK	1	0	23.50	21.92	23.18	22.59
			1	12	23.50	22.15	23.32	22.70
			1	24	23.50	22.04	23.20	22.57
			12	0	22.50	20.94	22.23	21.61
			12	6	22.50	21.08	22.30	21.66
			12	11	22.50	21.08	22.27	21.62
			25	0	22.50	20.99	22.22	21.61
		16QAM	1	0	22.50	21.09	22.32	21.75
			1	12	22.50	21.32	22.49	21.88
			1	24	22.50	21.24	22.36	21.74
			12	0	21.50	19.97	21.21	20.62
			12	6	21.50	20.09	21.29	20.68
			12	11	21.50	20.08	21.25	20.63
			25	0	21.50	20.00	21.26	20.66
LTE Band 41	10MHz	QPSK	1	0	23.50	21.98	23.18	22.67
			1	24	23.50	22.14	23.27	22.69
			1	49	23.50	22.12	23.19	22.62
			25	0	22.50	20.95	22.21	21.61
			25	12	22.50	21.07	22.23	21.64
			25	24	22.50	21.11	22.19	21.62
			50	0	22.50	21.08	22.26	21.67
		16QAM	1	0	22.50	21.15	22.34	21.85
			1	24	22.50	21.34	22.44	21.89
			1	49	22.50	21.31	22.37	21.82
			25	0	21.50	19.97	21.21	20.67
			25	12	21.50	20.09	21.27	20.70
			25	24	21.50	20.13	21.22	20.65
			50	0	21.50	20.10	21.25	20.70
LTE Band 41	15MHz	QPSK	1	0	23.50	21.89	23.04	22.59
			1	37	23.50	22.13	23.27	22.67
			1	74	23.50	21.96	23.04	22.56

				36	0	22.50	20.90	22.12	21.57
				36	18	22.50	21.02	22.22	21.63
				36	37	22.50	20.97	22.12	21.58
				75	0	22.50	20.97	22.12	21.59
			16QAM	1	0	22.50	21.05	22.20	21.78
				1	37	22.50	21.29	22.41	21.84
				1	74	22.50	21.13	22.18	21.75
				36	0	21.50	19.87	21.08	20.54
				36	18	21.50	19.99	21.18	20.60
				36	37	21.50	19.95	21.10	20.56
				75	0	21.50	19.96	21.14	20.62
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		40140/2545	40640/2595	41140/2645	
LTE Band 41	20MHz	QPSK	1	0	23.50	21.78	22.89	22.63	
			1	49	23.50	22.07	23.24	22.68	
			1	99	23.50	21.99	22.83	22.48	
			50	0	22.50	20.84	22.13	21.58	
			50	24	22.50	21.02	22.25	21.65	
			50	49	22.50	21.02	22.11	21.61	
			100	0	22.50	20.92	22.12	21.59	
		16QAM	1	0	22.50	20.94	22.05	21.81	
			1	49	22.50	21.26	22.41	21.86	
			1	99	22.50	21.18	22.00	21.66	
			50	0	21.50	19.86	21.11	20.61	
			50	24	21.50	20.05	21.24	20.68	
			50	49	21.50	20.04	21.12	20.64	
			100	0	21.50	19.92	21.10	20.60	

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131979/1710.7	132322/1745	132665/1779.3
LTE Band 66	1.4MHz	QPSK	1	0	23.00	22.86	22.27	22.02
			1	2	23.00	22.90	22.31	22.01
			1	5	23.00	22.81	22.20	21.99
			3	0	23.00	23.00	22.33	22.09
			3	1	23.00	23.00	22.34	22.08
			3	2	23.00	22.99	22.33	22.07

			6	0	22.50	22.10	21.44	21.17
		16QAM	1	0	22.50	22.24	21.57	21.24
			1	2	22.50	22.28	21.66	21.26
			1	5	22.50	22.19	21.44	21.21
			3	0	22.50	22.05	21.37	21.14
			3	1	22.50	22.04	21.40	21.04
			3	2	22.50	21.96	21.34	21.06
			6	0	21.50	21.23	20.59	20.31
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131987/1711.5	132322/1745	132657/1778.5
LTE Band 66	3MHz	QPSK	1	0	23.00	22.86	22.27	22.00
			1	7	23.00	22.89	22.25	22.05
			1	14	23.00	22.65	22.07	21.86
			8	0	22.50	22.03	21.45	21.18
			8	4	22.50	22.06	21.45	21.21
			8	7	22.50	21.99	21.32	21.14
			15	0	22.00	22.00	21.40	21.17
		16QAM	1	0	22.50	22.16	21.54	21.22
			1	7	22.50	22.21	21.46	21.37
			1	14	22.50	21.97	21.38	21.14
			8	0	21.50	21.09	20.57	20.30
			8	4	21.50	21.10	20.55	20.32
			8	7	21.50	21.05	20.43	20.23
			15	0	21.00	21.00	20.42	20.22
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131997/1712.5	132322/1745	132647/1777.5
LTE Band 66	5MHz	QPSK	1	0	23.50	23.07	22.57	22.29
			1	12	23.50	23.07	22.53	22.34
			1	24	23.50	22.83	22.25	22.14
			12	0	22.50	22.05	21.55	21.32
			12	6	22.50	22.08	21.51	21.34
			12	11	22.50	21.99	21.37	21.26
			25	0	22.50	22.05	21.47	21.27
		16QAM	1	0	22.50	22.33	21.95	21.59
			1	12	22.50	22.38	21.82	21.65
			1	24	22.50	22.02	21.59	21.41

			12	0	21.50	21.07	20.58	20.36
			12	6	21.50	21.11	20.57	20.41
			12	11	21.50	21.00	20.39	20.27
			25	0	21.50	21.07	20.54	20.36
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132022/1715	132322/1745	132622/1775
LTE Band 66	10MHz	QPSK	1	0	23.50	23.16	22.78	22.17
			1	24	23.50	22.92	22.56	22.43
			1	49	23.50	22.57	22.14	22.24
			25	0	22.00	21.96	21.64	21.29
			25	12	22.00	21.89	21.53	21.40
			25	24	22.00	21.77	21.31	21.32
			50	0	22.00	21.88	21.51	21.34
		16QAM	1	0	22.50	22.42	22.05	21.52
			1	24	22.50	22.16	21.78	21.71
			1	49	22.50	21.90	21.35	21.58
			25	0	21.00	20.98	20.68	20.35
			25	12	21.00	20.92	20.61	20.46
			25	24	21.00	20.80	20.38	20.39
			50	0	21.00	20.86	20.56	20.40
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132047/1717.5	132322/1745	132597/1772.5
LTE Band 66	15MHz	QPSK	1	0	23.50	23.11	22.73	21.61
			1	37	23.50	22.73	22.58	22.29
			1	74	23.50	22.29	21.85	22.13
			36	0	22.00	21.87	21.68	20.95
			36	18	22.00	21.72	21.53	21.21
			36	37	22.00	21.49	21.19	21.24
			75	0	22.00	21.72	21.46	21.14
		16QAM	1	0	22.50	22.44	21.94	20.90
			1	37	22.50	22.02	21.80	21.63
			1	74	22.50	21.59	21.20	21.30
			36	0	21.00	20.87	20.71	20.01
			36	18	21.00	20.73	20.56	20.26
			36	37	21.00	20.50	20.22	20.28
			75	0	21.00	20.73	20.50	20.13

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132072/1720	132322/1745	132572/1770
LTE Band 66	20MHz	QPSK	1	0	23.00	22.98	22.54	21.25
			1	49	23.00	22.56	22.58	22.13
			1	99	23.00	22.26	21.56	22.07
			50	0	22.00	21.68	21.70	20.79
			50	24	22.00	21.61	21.58	21.07
			50	49	22.00	21.42	21.18	21.23
			100	0	22.00	21.54	21.42	20.99
		16QAM	1	0	22.50	22.31	21.87	21.42
			1	49	22.50	21.83	21.92	21.49
			1	99	22.50	21.58	20.90	21.30
			50	0	21.00	20.69	20.69	19.80
			50	24	21.00	20.59	20.62	20.09
			50	49	21.00	20.41	20.22	20.24
			100	0	21.00	20.51	20.44	20.01

7.4. WLAN & Bluetooth Output Power

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11b	1	2412	16.50	16.24
	6	2437	16.50	15.98
	11	2462	16.50	15.25
802.11g	1	2412	14.50	14.35
	6	2437	14.50	13.83
	11	2462	14.50	13.52
802.11n HT20	1	2412	12.50	12.38
	6	2437	12.50	11.96
	11	2462	12.50	11.39
802.11n HT40	3	2422	12.50	12.26
	6	2437	12.50	12.02
	9	2452	12.50	11.75

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power
------	---------	-----------------	---------------	--------------

				(dBm)
802.11a	36	5180	6.50	6.08
	40	5200	6.50	5.47
	48	5240	6.50	4.69
802.11n HT20	36	5180	6.00	5.96
	40	5200	6.00	5.94
	48	5240	6.00	4.98
802.11n HT40	38	5190	6.00	5.53
	46	5230	6.00	5.14
802.11ac VHT20	36	5180	6.00	5.85
	40	5200	6.00	5.94
	48	5240	6.00	4.75
802.11ac VHT40	38	5190	6.00	5.75
	46	5230	6.00	5.19
802.11ac VHT80	42	5210	6.00	5.53

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	149	5745	3.50	2.21
	157	5785	3.50	2.79
	165	5825	3.50	3.23
802.11n HT20	149	5745	3.50	2.00
	157	5785	3.50	2.64
	165	5825	3.50	3.06
802.11n HT40	151	5755	3.00	2.12
	159	5795	3.00	2.63
802.11ac VHT20	149	5745	3.00	1.69
	157	5785	3.00	2.20
	165	5825	3.00	2.72
802.11ac VHT40	151	5755	3.00	2.04
	159	5795	3.00	2.59
802.11ac VHT80	155	5775	2.50	2.23

NOTE: Power measurement results of WLAN 5.8G.

BR+EDR	Output Power (dBm)		
	Data Rates	Tune-up	Channel

		(dBm)	0CH	39CH	78CH
	1M	9.00	8.17	8.07	8.38
	2M	7.00	6.38	5.13	5.61
	3M	5.00	4.67	4.94	4.93


BLE	Channel	Tune-up (dBm)	Output Power (dBm)	
			1M	2M
	0CH	-4.00	-4.01	-4.28
	19CH	-3.00	-3.54	-3.54
	39CH	-3.00	-3.86	-4.26

NOTE: Power measurement results of Bluetooth.

7.5. NFC

The power is too low, so SAR testing is not necessary.

8. Antenna Location



Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	>25mm

Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	9.00	7.94	5	2.480	2.5	3	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	9.00	7.94	5	2.48	7.5	0.332
Bluetooth	Body	9.00	7.94	10	2.48	7.5	0.166
Bluetooth	Hotspot	9.00	7.94	10	2.48	7.5	0.166

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement Result

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	189/836.4	GPRS(GMSK 4TS)	0.325	0.240	-4.25	28.62	29.00	0.355	2024/5/30	1#
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.179	0.127	-0.21	28.62	29.00	0.195	2024/5/30	
Right Cheek	189/836.4	GPRS(GMSK 4TS)	0.280	0.205	-0.94	28.62	29.00	0.306	2024/5/30	
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.130	0.092	-0.59	28.62	29.00	0.142	2024/5/30	

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.420	0.331	0.01	28.62	29.00	0.458	2024/5/30	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.689	0.559	1.88	28.62	29.00	0.752	2024/5/30	2#

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.420	0.331	0.01	28.62	29.00	0.458	2024/5/30	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.689	0.559	1.88	28.62	29.00	0.752	2024/5/30	2#
Left Side	189/836.4	GPRS(GMSK 4TS)	0.207	0.163	1.03	28.62	29.00	0.226	2024/5/30	
Right Side	189/836.4	GPRS(GMSK 4TS)	0.210	0.165	-2.86	28.62	29.00	0.229	2024/5/30	
Bottom	189/836.4	GPRS(GMSK 4TS)	0.355	0.288	-0.81	28.62	29.00	0.387	2024/5/30	

Side

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	661/1880	GPRS(GMSK 2TS)	0.281	0.119	-2.32	28.50	29.00	0.315	2024/6/03	3#
Left Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.157	0.063	-0.96	28.50	29.00	0.176	2024/6/03	
Right Cheek	661/1880	GPRS(GMSK 2TS)	0.266	0.112	0.22	28.50	29.00	0.298	2024/6/03	
Right Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.128	0.054	2.33	28.50	29.00	0.144	2024/6/03	

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	661/1880	GPRS(GMSK 2TS)	0.168	0.098	3.95	28.50	29.00	0.188	2024/6/03	
Back Side	661/1880	GPRS(GMSK 2TS)	0.236	0.145	-3.42	28.50	29.00	0.265	2024/6/03	4#

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducte d Power (dBm)	Tune-up Power (dBm)	Scale d SAR 1-g (W/K g)	Date	Plot
			1-g	10-g						
Front Side	661/1880	GPRS(GMSK 2TS)	0.168	0.098	3.95	28.50	29.00	0.188	2024/6/03	
Back Side	661/1880	GPRS(GMSK 2TS)	0.236	0.145	-3.42	28.50	29.00	0.265	2024/6/03	4#
Left Side	661/1880	GPRS(GMSK 2TS)	0.078	0.046	0.64	28.50	29.00	0.088	2024/6/03	

Right Side	661/1880	GPRS(GMSK 2TS)	0.082	0.048	1.99	28.50	29.00	0.092	2024/6/03	
Bottom Side	661/1880	GPRS(GMSK 2TS)	0.135	0.080	2.16	28.50	29.00	0.151	2024/6/03	

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	9400/1880	RMC12.2K	0.076	0.047	3.57	23.34	24.00	0.088	2024/6/03	5#
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.040	0.024	-0.76	23.34	24.00	0.047	2024/6/03	
Right Cheek	9400/1880	RMC12.2K	0.068	0.040	-3.48	23.34	24.00	0.079	2024/6/03	
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.035	0.021	1.07	23.34	24.00	0.041	2024/6/03	

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	9400/1880	RMC12.2K	0.240	0.135	1.67	23.34	24.00	0.279	2024/6/03	
Back Side	9400/1880	RMC12.2K	0.350	0.199	0.93	23.34	24.00	0.407	2024/6/03	6#

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducte d Power (dBm)	Tune-u p Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	9400/1880	RMC12.2K	0.240	0.135	1.67	23.34	24.00	0.279	2024/6/03	
Back Side	9400/1880	RMC12.2K	0.350	0.199	0.93	23.34	24.00	0.407	2024/6/03	6#
Left Side	9400/1880	RMC12.2K	0.108	0.061	0.96	23.34	24.00	0.126	2024/6/03	

Right Side	9400/1880	RMC12.2K	0.112	0.065	-2.88	23.34	24.00	0.130	2024/6/03	
Bottom Side	9400/1880	RMC12.2K	0.298	0.161	1.83	23.34	24.00	0.347	2024/6/03	

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	1413/1732.6	RMC12.2K	0.123	0.078	2.61	23.24	23.50	0.131	2024/5/28	7#
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.066	0.042	-0.79	23.24	23.50	0.070	2024/5/28	
Right Cheek	1413/1732.6	RMC12.2K	0.115	0.069	0.79	23.24	23.50	0.122	2024/5/28	
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.058	0.036	-3.77	23.24	23.50	0.062	2024/5/28	

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	1413/1732.6	RMC12.2K	0.378	0.226	1.17	23.24	23.50	0.401	2024/5/28	
Back Side	1413/1732.6	RMC12.2K	0.610	0.365	0.36	23.24	23.50	0.648	2024/5/28	8#

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1413/1732.6	RMC12.2K	0.378	0.226	1.17	23.24	23.50	0.401	2024/5/28	

Back Side	1413/1732.6	RMC12.2K	0.610	0.365	0.36	23.24	23.50	0.648	2024/5/28	8#
Left Side	1413/1732.6	RMC12.2K	0.198	0.116	0.96	23.24	23.50	0.210	2024/5/28	
Right Side	1413/1732.6	RMC12.2K	0.202	0.119	-2.75	23.24	23.50	0.214	2024/5/28	
Bottom Side	1413/1732.6	RMC12.2K	0.330	0.192	-2.80	23.24	23.50	0.350	2024/5/28	

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	4182/836.4	RMC12.2K	0.381	0.310	3.55	23.13	23.50	0.415	2024/5/30	9#
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.214	0.165	2.85	23.13	23.50	0.233	2024/5/30	
Right Cheek	4182/836.4	RMC12.2K	0.346	0.279	3.67	23.13	23.50	0.377	2024/5/30	
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.180	0.139	3.00	23.13	23.50	0.196	2024/5/30	

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	4182/836.4	RMC12.2K	0.336	0.253	-1.77	23.13	23.50	0.366	2024/5/30	
Back Side	4182/836.4	RMC12.2K	0.533	0.409	-3.36	23.13	23.50	0.580	2024/5/30	10#

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	4182/836.4	RMC12.2K	0.336	0.253	-1.77	23.13	23.50	0.366	2024/5/30	

Back Side	4182/836.4	RMC12.2K	0.533	0.409	-3.36	23.13	23.50	0.580	2024/5/30	10#
Left Side	4182/836.4	RMC12.2K	0.162	0.118	3.36	23.13	23.50	0.176	2024/5/30	
Right Side	4182/836.4	RMC12.2K	0.172	0.123	-1.15	23.13	23.50	0.187	2024/5/30	
Bottom Side	4182/836.4	RMC12.2K	0.275	0.209	1.21	23.13	23.50	0.299	2024/5/30	

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducte d Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	18900/1880	20M QPSK(1,99)	0.442	0.320	-0.83	22.73	23.50	0.528	2024/6/03	17#
Left Tilt 15 Degree	18900/1880	20M QPSK(1,99)	0.233	0.162	3.25	22.73	23.50	0.278	2024/6/03	
Right Cheek	18900/1880	20M QPSK(1,99)	0.405	0.287	1.27	22.73	23.50	0.484	2024/6/03	
Right Tilt 15 Degree	18900/1880	20M QPSK(1,99)	0.188	0.129	-0.41	22.73	23.50	0.224	2024/6/03	
50%RB										
Left Cheek	18900/1880	20M QPSK(50,24)	0.241	0.191	-1.56	21.88	22.50	0.278	2024/6/03	
Left Tilt 15 Degree	18900/1880	20M QPSK(50,24)	0.127	0.087	-4.36	21.88	22.50	0.146	2024/6/03	
Right Cheek	18900/1880	20M QPSK(50,24)	0.220	0.153	-0.89	21.88	22.50	0.254	2024/6/03	
Right Tilt 15 Degree	18900/1880	20M QPSK(50,24)	0.106	0.066	-2.14	21.88	22.50	0.122	2024/6/03	

NOTE: Head SAR test results of LTE Band 2

NOTE: Body-Worn SAR test results of LTE Band 2

NOTE: Hotspot SAR test results of LTE Band 2

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g	Date	Plot
			1-g	10-g						

								(W/Kg)		
1RB										
Left Cheek	20175/1732.5	20M QPSK(1,0)	0.282	0.197	-2.66	22.97	23.50	0.319	2024/5/28	19#
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,0)	0.165	0.114	3.84	22.97	23.50	0.186	2024/5/28	
Right Cheek	20175/1732.5	20M QPSK(1,0)	0.264	0.183	-3.99	22.97	23.50	0.298	2024/5/28	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,0)	0.128	0.089	-3.57	22.97	23.50	0.145	2024/5/28	
50%RB										
Left Cheek	20175/1732.5	20M QPSK(50,24)	0.166	0.116	2.07	22.10	22.50	0.182	2024/5/28	
Left Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.097	0.057	-1.19	22.10	22.50	0.106	2024/5/28	
Right Cheek	20175/1732.5	20M QPSK(50,24)	0.132	0.102	-3.51	22.10	22.50	0.145	2024/5/28	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.074	0.048	2.21	22.10	22.50	0.081	2024/5/28	

NOTE: Head SAR test results of LTE Band 4

Test Position of Body- Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,0)	0.294	0.177	0.63	22.97	23.50	0.332	2024/5/28	
Back Side	20175/1732.5	20M QPSK(1,0)	0.449	0.281	0.58	22.97	23.50	0.507	2024/5/28	20#
50%RB										
Front Side	20175/1732.5	20M QPSK(50,24)	0.148	0.099	4.74	22.10	22.50	0.162	2024/5/28	

NOTE: Body-Worn SAR test results of LTE Band 4

NOTE: Hotspot SAR test results of LTE Band 4

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						

1RB										
Left Cheek	20525/836.5	10M QPSK(1,24)	0.575	0.430	-3.61	23.11	23.50	0.629	2024/5/30	21#
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.332	0.236	3.17	23.11	23.50	0.363	2024/5/30	
Right Cheek	20525/836.5	10M QPSK(1,24)	0.531	0.377	3.78	23.11	23.50	0.581	2024/5/30	
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.280	0.209	-2.79	23.11	23.50	0.306	2024/5/30	
50%RB										
Left Cheek	20525/836.5	10M QPSK(25,12)	0.318	0.229	-3.11	22.10	22.50	0.349	2024/5/30	
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,12)	0.187	0.122	2.48	22.10	22.50	0.205	2024/5/30	
Right Cheek	20525/836.5	10M QPSK(25,12)	0.305	0.223	4.71	22.10	22.50	0.334	2024/5/30	
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,12)	0.147	0.121	-2.14	22.10	22.50	0.161	2024/5/30	

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.378	0.259	-3.17	23.11	23.50	0.414	2024/5/30	
Back Side	20525/836.5	10M QPSK(1,24)	0.614	0.438	-1.67	23.11	23.50	0.672	2024/5/30	22#
50%RB										
Front Side	20525/836.5	10M QPSK(25,12)	0.202	0.147	-3.34	22.10	22.50	0.221	2024/5/30	
Back	20525/836.5	10M OPSK(25,12)	0.307	0.262	-4.22	22.10	22.50	0.337	2024/5/30	

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										

Left Cheek	21100/2535	20M QPSK(1,99)	0.052	0.033	3.37	22.78	23.50	0.061	2024/5/29	23#
Left Tilt 15 Degree	21100/2535	20M QPSK(1,99)	0.027	0.017	-3.38	22.78	23.50	0.032	2024/5/29	
Right Cheek	21100/2535	20M QPSK(1,99)	0.048	0.030	3.19	22.78	23.50	0.057	2024/5/29	
Right Tilt 15 Degree	21100/2535	20M QPSK(1,99)	0.026	0.016	-1.93	22.78	23.50	0.031	2024/5/29	
50%RB										
Left Cheek	21100/2535	20M QPSK(50,49)	0.030	0.017	-1.91	21.93	22.50	0.034	2024/5/29	
Left Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.015	0.009	0.65	21.93	22.50	0.017	2024/5/29	
Right Cheek	21100/2535	20M QPSK(50,49)	0.028	0.018	4.88	21.93	22.50	0.032	2024/5/29	
Right Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.014	0.010	-2.10	21.93	22.50	0.016	2024/5/29	

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,99)	0.066	0.036	-3.01	22.78	23.50	0.078	2024/5/29	
Back Side	21100/2535	20M QPSK(1,99)	0.096	0.055	-1.75	22.78	23.50	0.113	2024/5/29	24#
50%RB										
Front Side	21100/2535	20M QPSK(50,49)	0.033	0.019	2.99	21.93	22.50	0.038	2024/5/29	
Back Side	21100/2535	20M QPSK(50,49)	0.052	0.030	3.38	21.93	22.50	0.059	2024/5/29	

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						

10mm										
1RB										
Front Side	21100/2535	20M QPSK(1,99)	0.066	0.036	-3.01	22.78	23.50	0.078	2024/5/29	
Back Side	21100/2535	20M QPSK(1,99)	0.096	0.055	-1.75	22.78	23.50	0.113	2024/5/29	24#
Left Side	21100/2535	20M QPSK(1,99)	0.030	0.016	-1.40	22.78	23.50	0.035	2024/5/29	
Right Side	21100/2535	20M QPSK(1,99)	0.039	0.022	-0.60	22.78	23.50	0.046	2024/5/29	
Bottom Side	21100/2535	20M QPSK(1,99)	0.070	0.039	-3.07	22.78	23.50	0.083	2024/5/29	
50%RB										
Front Side	21100/2535	20M QPSK(50,49)	0.033	0.019	2.99	21.93	22.50	0.038	2024/5/29	
Back Side	21100/2535	20M QPSK(50,49)	0.052	0.030	3.38	21.93	22.50	0.059	2024/5/29	
Left Side	21100/2535	20M QPSK(50,49)	0.016	0.009	1.84	21.93	22.50	0.018	2024/5/29	
Right Side	21100/2535	20M QPSK(50,49)	0.021	0.013	1.83	21.93	22.50	0.024	2024/5/29	
Bottom Side	21100/2535	20M QPSK(50,49)	0.041	0.020	3.26	21.93	22.50	0.047	2024/5/29	

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23095/707.5	10M QPSK(1,0)	0.121	0.097	0.93	22.86	23.00	0.125	2024/6/04	25#
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.061	0.047	-2.30	22.86	23.00	0.063	2024/6/04	
Right Cheek	23095/707.5	10M QPSK(1,0)	0.109	0.087	0.69	22.86	23.00	0.113	2024/6/04	
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.059	0.045	-0.51	22.86	23.00	0.061	2024/6/04	
50%RB										
Left	23095/707.5	10M	0.071	0.049	2.31	21.82	22.00	0.074	2024/6/04	

Cheek		QPSK(25,12)								
Left Tilt 15 Degree	23095/707.5	10M QPSK(25,12)	0.035	0.026	-4.26	21.82	22.00	0.036	2024/6/04	
Right Cheek	23095/707.5	10M QPSK(25,12)	0.061	0.047	-4.84	21.82	22.00	0.064	2024/6/04	
Right Tilt 15 Degree	23095/707.5	10M QPSK(25,12)	0.032	0.024	4.12	21.82	22.00	0.033	2024/6/04	

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,0)	0.210	0.104	-3.38	22.86	23.00	0.217	2024/6/04	
Back Side	23095/707.5	10M QPSK(1,0)	0.328	0.165	-3.67	22.86	23.00	0.339	2024/6/04	26#
50%RB										
Front Side	23095/707.5	10M QPSK(25,12)	0.111	0.059	0.84	21.82	22.00	0.116	2024/6/04	
Back Side	23095/707.5	10M QPSK(25,12)	0.186	0.092	1.53	21.82	22.00	0.194	2024/6/04	

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,0)	0.210	0.104	-3.38	22.86	23.00	0.217	2024/6/04	
Back Side	23095/707.5	10M QPSK(1,0)	0.328	0.165	-3.67	22.86	23.00	0.339	2024/6/04	26#
Left Side	23095/707.5	10M QPSK(1,0)	0.108	0.053	3.09	22.86	23.00	0.112	2024/6/04	
Right Side	23095/707.5	10M QPSK(1,0)	0.112	0.059	3.35	22.86	23.00	0.116	2024/6/04	
Bottom Side	23095/707.5	10M QPSK(1,0)	0.170	0.086	-2.36	22.86	23.00	0.176	2024/6/04	

50%RB										
Front Side	23095/707.5	10M QPSK(25,12)	0.111	0.059	0.84	21.82	22.00	0.116	2024/6/04	
Back Side	23095/707.5	10M QPSK(25,12)	0.186	0.092	1.53	21.82	22.00	0.194	2024/6/04	
Left Side	23095/707.5	10M QPSK(25,12)	0.063	0.027	-4.56	21.82	22.00	0.066	2024/6/04	
Right Side	23095/707.5	10M QPSK(25,12)	0.068	0.034	0.58	21.82	22.00	0.071	2024/6/04	
Bottom Side	23095/707.5	10M QPSK(25,12)	0.097	0.044	0.91	21.82	22.00	0.101	2024/6/04	

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23790/710	10M QPSK(1,24)	0.508	0.303	-4.40	22.78	23.00	0.534	2024/6/04	27#
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.286	0.164	-3.55	22.78	23.00	0.301	2024/6/04	
Right Cheek	23790/710	10M QPSK(1,24)	0.457	0.262	-1.14	22.78	23.00	0.481	2024/6/04	
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.229	0.130	-1.12	22.78	23.00	0.241	2024/6/04	
50%RB										
Left Cheek	23790/710	10M QPSK(25,12)	0.272	0.179	-2.60	21.75	22.00	0.288	2024/6/04	
Left Tilt 15 Degree	23790/710	10M QPSK(25,12)	0.157	0.084	-0.84	21.75	22.00	0.166	2024/6/04	
Right Cheek	23790/710	10M QPSK(25,12)	0.250	0.150	-0.09	21.75	22.00	0.265	2024/6/04	
Right	23790/710	10M QPSK(25,12)	0.135	0.073	0.36	21.75	22.00	0.143	2024/6/04	

Tilt 15 Degree										
-------------------	--	--	--	--	--	--	--	--	--	--

NOTE: Head SAR test results of LTE Band 17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.264	0.169	2.94	22.78	23.00	0.278	2024/6/04	
Back Side	23790/710	10M QPSK(1,24)	0.392	0.259	-1.27	22.78	23.00	0.412	2024/6/04	28#
50%RB										
Front Side	23790/710	10M QPSK(25,12)	0.142	0.095	4.41	21.75	22.00	0.150	2024/6/04	
Back Side	23790/710	10M OPSK(25,12)	0.206	0.137	-0.22	21.75	22.00	0.218	2024/6/04	

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.264	0.169	2.94	22.78	23.00	0.278	2024/6/04	
Back Side	23790/710	10M QPSK(1,24)	0.392	0.259	-1.27	22.78	23.00	0.412	2024/6/04	28#
Left Side	23790/710	10M QPSK(1,24)	0.132	0.086	-3.05	22.78	23.00	0.139	2024/6/04	
Right Side	23790/710	10M QPSK(1,24)	0.142	0.093	2.64	22.78	23.00	0.149	2024/6/04	
Bottom Side	23790/710	10M QPSK(1,24)	0.215	0.139	-3.44	22.78	23.00	0.226	2024/6/04	
50%RB										
Front Side	23790/710	10M QPSK(25,12)	0.142	0.095	4.41	21.75	22.00	0.150	2024/6/04	
Back Side	23790/710	10M QPSK(25,12)	0.206	0.137	-0.22	21.75	22.00	0.218	2024/6/04	
Left Side	23790/710	10M QPSK(25,12)	0.075	0.050	-1.73	21.75	22.00	0.079	2024/6/04	

Right Side	23790/710	10M QPSK(25,12)	0.080	0.056	4.07	21.75	22.00	0.085	2024/6/04	
Bottom Side	23790/710	10M QPSK(25,12)	0.128	0.083	-3.80	21.75	22.00	0.136	2024/6/04	

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of LTE Band 41

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	40640/2595	20M QPSK(1,49)	0.671	0.648	1.11	23.24	23.50	0.712	2024/5/29	29#
Left Tilt 15 Degree	40640/2595	20M QPSK(1,49)	0.364	0.344	-2.59	23.24	23.50	0.386	2024/5/29	
Right Cheek	40640/2595	20M QPSK(1,49)	0.611	0.584	1.10	23.24	23.50	0.649	2024/5/29	
Right Tilt 15 Degree	40640/2595	20M QPSK(1,49)	0.294	0.273	-0.88	23.24	23.50	0.312	2024/5/29	
50%RB										
Left Cheek	40640/2595	20M QPSK(50,24)	0.401	0.352	4.43	22.25	22.50	0.425	2024/5/29	
Left Tilt 15 Degree	40640/2595	20M QPSK(50,24)	0.199	0.187	1.24	22.25	22.50	0.211	2024/5/29	
Right Cheek	40640/2595	20M QPSK(50,24)	0.359	0.309	-1.17	22.25	22.50	0.380	2024/5/29	
Right Tilt 15 Degree	40640/2595	20M QPSK(50,24)	0.152	0.151	2.40	22.25	22.50	0.161	2024/5/29	

NOTE: Head SAR test results of LTE Band 41

Test Position of Body-Worn	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g	Date	Plot
			1-g	10-g						

with 10mm								(W/Kg)		
1RB										
Front Side	40640/2595	20M QPSK(1,49)	0.366	0.208	-3.11	23.24	23.50	0.389	2024/5/29	
Back Side	40640/2595	20M QPSK(1,49)	0.605	0.351	-3.36	23.24	23.50	0.642	2024/5/29	30#
50%RB										
Front Side	40640/2595	20M QPSK(50,24)	0.190	0.116	2.53	22.25	22.50	0.201	2024/5/29	
Back Side	40640/2595	20M QPSK(50,24)	0.321	0.187	4.24	22.25	22.50	0.340	2024/5/29	

NOTE: Body-Worn SAR test results of LTE Band 41

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	40640/2595	20M QPSK(1,49)	0.366	0.208	-3.11	23.24	23.50	0.389	2024/5/29	
Back Side	40640/2595	20M QPSK(1,49)	0.605	0.351	-3.36	23.24	23.50	0.642	2024/5/29	30#
Left Side	40640/2595	20M QPSK(1,49)	0.186	0.106	-0.61	23.24	23.50	0.197	2024/5/29	
Right Side	40640/2595	20M QPSK(1,49)	0.193	0.112	-0.94	23.24	23.50	0.205	2024/5/29	
Bottom Side	40640/2595	20M QPSK(1,49)	0.325	0.185	1.54	23.24	23.50	0.345	2024/5/29	
50%RB										
Front Side	40640/2595	20M QPSK(50,24)	0.190	0.116	2.53	22.25	22.50	0.201	2024/5/29	
Back Side	40640/2595	20M QPSK(50,24)	0.321	0.187	4.24	22.25	22.50	0.340	2024/5/29	
Left Side	40640/2595	20M QPSK(50,24)	0.102	0.058	-3.97	22.25	22.50	0.108	2024/5/29	
Right Side	40640/2595	20M QPSK(50,24)	0.110	0.060	3.54	22.25	22.50	0.117	2024/5/29	
Bottom Side	40640/2595	20M QPSK(50,24)	0.176	0.099	4.61	22.25	22.50	0.186	2024/5/29	

NOTE: Hotspot SAR test results of LTE Band 41

10.1.13. SAR measurement Result of LTE Band 66

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	132322/1745	20M QPSK(1,0)	0.062	0.043	0.56	22.54	23.00	0.069	2024/5/28	31#
Left Tilt 15 Degree	132322/1745	20M QPSK(1,0)	0.033	0.022	-0.98	22.54	23.00	0.037	2024/5/28	
Right Cheek	132322/1745	20M QPSK(1,0)	0.057	0.038	1.23	22.54	23.00	0.063	2024/5/28	
Right Tilt 15 Degree	132322/1745	20M QPSK(1,0)	0.027	0.018	-2.01	22.54	23.00	0.030	2024/5/28	
50%RB										
Left Cheek	132322/1745	20M QPSK(50,0)	0.034	0.023	2.38	21.70	22.00	0.036	2024/5/28	
Left Tilt 15 Degree	132322/1745	20M QPSK(50,0)	0.020	0.012	4.97	21.70	22.00	0.021	2024/5/28	
Right Cheek	132322/1745	20M QPSK(50,0)	0.032	0.022	-2.54	21.70	22.00	0.034	2024/5/28	
Right Tilt 15 Degree	132322/1745	20M QPSK(50,0)	0.014	0.010	-4.43	21.70	22.00	0.015	2024/5/28	

NOTE: Head SAR test results of LTE Band 66

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,0)	0.246	0.141	2.04	22.54	23.00	0.273	2024/5/28	
Back Side	132322/1745	20M QPSK(1,0)	0.375	0.222	1.28	22.54	23.00	0.417	2024/5/28	32#
50%RB										
Front Side	132322/1745	20M QPSK(50,0)	0.147	0.084	-4.62	21.70	22.00	0.158	2024/5/28	
Back Side	132322/1745	20M QPSK(50,0)	0.214	0.133	1.27	21.70	22.00	0.229	2024/5/28	

NOTE: Body-Worn SAR test results of LTE Band 66

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	132322/1745	20M QPSK(1,0)	0.246	0.141	2.04	22.54	23.00	0.273	2024/5/28	
Back Side	132322/1745	20M QPSK(1,0)	0.375	0.222	1.28	22.54	23.00	0.417	2024/5/28	32#
Left Side	132322/1745	20M QPSK(1,0)	0.117	0.067	2.66	22.54	23.00	0.130	2024/5/28	
Right Side	132322/1745	20M QPSK(1,0)	0.124	0.071	-2.46	22.54	23.00	0.138	2024/5/28	
Bottom Side	132322/1745	20M QPSK(1,0)	0.200	0.118	-1.88	22.54	23.00	0.222	2024/5/28	
50%RB										
Front Side	132322/1745	20M QPSK(50,0)	0.147	0.084	-4.62	21.70	22.00	0.158	2024/5/28	
Back Side	132322/1745	20M QPSK(50,0)	0.214	0.133	1.27	21.70	22.00	0.229	2024/5/28	
Left Side	132322/1745	20M QPSK(50,0)	0.064	0.037	-3.87	21.70	22.00	0.069	2024/5/28	
Right Side	132322/1745	20M QPSK(50,0)	0.069	0.042	2.78	21.70	22.00	0.074	2024/5/28	
Bottom Side	132322/1745	20M QPSK(50,0)	0.105	0.070	0.76	21.70	22.00	0.113	2024/5/28	

NOTE: Hotspot SAR test results of LTE Band 66

10.1.14. SAR measurement Result of WLAN2.4G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left	1/2412	802.11b	0.679	0.267	1.05	16.24	16.50	0.721	2024/6/05	15#

Cheek										
Left Tilt 15 Degree	1/2412	802.11b	0.378	0.144	3.39	16.24	16.50	0.401	2024/6/05	
Right Cheek	1/2412	802.11b	0.603	0.237	-2.55	16.24	16.50	0.640	2024/6/05	
Right Tilt 15 Degree	1/2412	802.11b	0.280	0.106	-3.78	16.24	16.50	0.297	2024/6/05	

NOTE: Head SAR test results of WLAN2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.120	0.056	-0.75	16.24	16.50	0.127	2024/6/05	
Back Side	1/2412	802.11b	0.193	0.093	-1.01	16.24	16.50	0.205	2024/6/05	16#

NOTE: Body-worn SAR test results of WLAN2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.120	0.056	-0.75	16.24	16.50	0.127	2024/6/05	
Back Side	1/2412	802.11b	0.193	0.093	-1.01	16.24	16.50	0.205	2024/6/05	16#
Right Side	1/2412	802.11b	0.060	0.028	2.17	16.24	16.50	0.064	2024/6/05	
Top Side	1/2412	802.11b	0.066	0.031	-1.55	16.24	16.50	0.070	2024/6/05	

NOTE: Hotspot SAR test results of WLAN2.4G

10.1.15. SAR measurement Result of WLAN5.2G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g	Date	Plot
			1-g	10-g						

								(W/Kg)		
Left Cheek	36/5180	802.11a	0.434	0.157	-0.60	6.08	6.50	0.478	2024/6/07	11#
Left Tilt 15 Degree	36/5180	802.11a	0.234	0.080	1.96	6.08	6.50	0.258	2024/6/07	
Right Cheek	36/5180	802.11a	0.374	0.131	1.04	6.08	6.50	0.412	2024/6/07	
Right Tilt 15 Degree	36/5180	802.11a	0.170	0.058	0.25	6.08	6.50	0.187	2024/6/07	

NOTE: Head SAR test results of WLAN5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	36/5180	802.11a	0.066	0.038	-3.99	6.08	6.50	0.073	2024/6/07	
Back Side	36/5180	802.11a	0.094	0.055	3.90	6.08	6.50	0.104	2024/6/07	14#

NOTE: Body-worn SAR test results of WLAN5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	36/5180	802.11a	0.066	0.038	-3.99	6.08	6.50	0.073	2024/6/07	
Back Side	36/5180	802.11a	0.094	0.055	3.90	6.08	6.50	0.104	2024/6/07	14#
Right Side	36/5180	802.11a	0.042	0.024	-0.41	6.08	6.50	0.046	2024/6/07	
Top Side	36/5180	802.11a	0.045	0.029	2.26	6.08	6.50	0.050	2024/6/07	

NOTE: Hotspot SAR test results of WLAN5.2G

10.1.16. SAR measurement Result of WLAN5.8G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	165/5825	802.11a	0.242	0.084	0.77	3.23	3.50	0.258	2024/6/06	12#
Left Tilt 15 Degree	165/5825	802.11a	0.130	0.044	3.77	3.23	3.50	0.138	2024/6/06	
Right Cheek	165/5825	802.11a	0.209	0.070	-1.23	3.23	3.50	0.222	2024/6/06	
Right Tilt 15 Degree	165/5825	802.11a	0.095	0.032	-3.69	3.23	3.50	0.101	2024/6/06	

NOTE: Head SAR test results of WLAN5.8G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	165/5825	802.11a	0.072	0.040	2.47	3.23	3.50	0.077	2024/6/06	
Back Side	165/5825	802.11a	0.102	0.058	1.13	3.23	3.50	0.109	2024/6/06	13#

NOTE: Body-worn SAR test results of WLAN5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	165/5825	802.11a	0.072	0.040	2.47	3.23	3.50	0.077	2024/6/06	
Back Side	165/5825	802.11a	0.102	0.058	1.13	3.23	3.50	0.109	2024/6/06	13#
Right Side	165/5825	802.11a	0.045	0.026	0.61	3.23	3.50	0.048	2024/6/06	
Top Side	165/5825	802.11a	0.050	0.029	3.23	3.23	3.50	0.053	2024/6/06	

NOTE: Hotspot SAR test results of WLAN5.8G

10.2. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Head	Left Cheek	0.712	0.721	1.433	N/A	N/A
	Left Tilt 15 Degree	0.386	0.401	0.787	N/A	N/A
	Right Cheek	0.649	0.640	1.289	N/A	N/A
	Right Tilt 15 Degree	0.312	0.297	0.609	N/A	N/A
Body-Worn	Front Side	0.458	0.127	0.585	N/A	N/A
	Back Side	0.752	0.205	0.957	N/A	N/A
Hotspot	Front Side	0.458	0.127	0.585	N/A	N/A
	Back Side	0.752	0.205	0.957	N/A	N/A
	Left Side	0.226	N/A	0.226	N/A	N/A
	Right Side	0.229	0.064	0.293	N/A	N/A
	Top Side	N/A	0.070	0.070	N/A	N/A
	Bottom Side	0.388	N/A	0.388	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Head	Left Cheek	0.712	0.478	1.190	N/A	N/A
	Left Tilt 15 Degree	0.386	0.258	0.644	N/A	N/A
	Right Cheek	0.649	0.412	1.061	N/A	N/A
	Right Tilt 15 Degree	0.312	0.187	0.499	N/A	N/A
Body-Worn	Front Side	0.458	0.077	0.535	N/A	N/A
	Back Side	0.752	0.109	0.861	N/A	N/A

Hotspot	Front Side	0.458	0.077	0.535	N/A	N/A
	Back Side	0.752	0.109	0.861	N/A	N/A
	Left Side	0.226	N/A	0.226	N/A	N/A
	Right Side	0.229	0.048	0.277	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.388	N/A	0.388	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Head	Left Cheek	0.712	0.332	1.044	N/A	N/A
	Left Tilt 15 Degree	0.386	0.332	0.718	N/A	N/A
	Right Cheek	0.649	0.332	0.981	N/A	N/A
	Right Tilt 15 Degree	0.312	0.332	0.644	N/A	N/A
Body-Worn	Front Side	0.458	0.166	0.624	N/A	N/A
	Back Side	0.752	0.166	0.918	N/A	N/A
Hotspot	Front Side	0.458	0.166	0.624	N/A	N/A
	Back Side	0.752	0.166	0.918	N/A	N/A
	Left Side	0.226	N/A	0.226	N/A	N/A
	Right Side	0.229	0.166	0.395	N/A	N/A
	Top Side	N/A	0.166	0.166	N/A	N/A
	Bottom Side	0.388	N/A	0.388	N/A	N/A

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2450MHz
MEASUREMENT 6 System Performance Check - 2600MHz
MEASUREMENT 7 System Performance Check - 5200MHz
MEASUREMENT 8 System Performance Check - 5800MHz

MEASUREMENT 1

Date of measurement: 4/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.37</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	40.884891
Relative permittivity (imaginary part)	21.490463
Conductivity (S/m)	0.895436
Variation (%)	2.730000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=1.00

SAR Peak: 1.13 W/kg

SAR 10g (W/Kg)	0.579332
SAR 1g (W/Kg)	0.864321



MEASUREMENT 2

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.32</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.528502
Relative permittivity (imaginary part)	19.541862
Conductivity (S/m)	0.906525
Variation (%)	-2.720000

SURFACE SAR





VOLUME SAR



Maximum location: X=2.00, Y=2.00

SAR Peak: 1.29 W/kg

SAR 10g (W/Kg)	0.619333
SAR 1g (W/Kg)	0.989172



MEASUREMENT 3

Date of measurement: 28/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.45</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.335125
Relative permittivity (imaginary part)	13.968965
Conductivity (S/m)	1.396897
Variation (%)	2.980000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	1.862307
SAR 1g (W/Kg)	3.565066



MEASUREMENT 4

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.63</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.782481
Relative permittivity (imaginary part)	13.626018
Conductivity (S/m)	1.438302
Variation (%)	2.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.214347
SAR 1g (W/Kg)	4.350221



MEASUREMENT 5

Date of measurement: 5/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	37.717635
Relative permittivity (imaginary part)	12.931778
Conductivity (S/m)	1.760159
Variation (%)	1.290000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=-1.00

SAR Peak: 9.73 W/kg

SAR 10g (W/Kg)	2.250106
SAR 1g (W/Kg)	4.719340



MEASUREMENT 6

Date of measurement: 29/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.173484
Relative permittivity (imaginary part)	13.966388
Conductivity (S/m)	2.017367
Variation (%)	0.250000

SURFACE SAR





VOLUME SAR



Maximum location: X=1.00, Y=-11.00

SAR Peak: 9.29 W/kg

SAR 10g (W/Kg)	2.553037
SAR 1g (W/Kg)	5.759199



MEASUREMENT 7


Date of measurement: 7/6/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.07</u>

B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	34.873427
Relative permittivity (imaginary part)	15.913428
Conductivity (S/m)	4.597213
Variation (%)	2.800000




Maximum location: X=0.00, Y=6.00


SAR Peak: 40.06 W/kg

SAR 10g (W/Kg)	5.217162
SAR 1g (W/Kg)	14.784032


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SAR (W/ Kg)	37.8 91	22.3 91	11.3 77	5.66 94	2.82 91	1.40 43	0.71 50	0.36 37	0.18 02	0.10 08	0.05 27	0.03 97



3D screen shot



Hot spot position



MEASUREMENT 8


Date of measurement: 6/6/2024

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.04</u>

B. SAR Measurement Results



Frequency (MHz)	5800.000000
Relative permittivity (real part)	34.304577
Relative permittivity (imaginary part)	16.300199
Conductivity (S/m)	5.252286
Variation (%)	-0.500000



Maximum location: X=0.00, Y=6.00

SAR Peak: 57.37 W/kg

SAR 10g (W/Kg)	6.109228
SAR 1g (W/Kg)	18.197190



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 5.2G Head
MEASUREMENT 12 WLAN 5.8G Head
MEASUREMENT 13 WLAN 5.8G Body
MEASUREMENT 14 WLAN 5.2G Body
MEASUREMENT 15 WLAN 2.4G Head
MEASUREMENT 16 WLAN 2.4G Body
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 12 Head
MEASUREMENT 26 LTE Band 12 Body
MEASUREMENT 27 LTE Band 17 Head
MEASUREMENT 28 LTE Band 17 Body
MEASUREMENT 29 LTE Band 41 Head
MEASUREMENT 30 LTE Band 41 Body
MEASUREMENT 31 LTE Band 66 Head
MEASUREMENT 32 LTE Band 66 Body

MEASUREMENT 1

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>2.32</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.537582
Relative permittivity (imaginary part)	19.549063
Conductivity (S/m)	0.908380
Variation (%)	-4.250000

SURFACE SAR





VOLUME SAR



Maximum location: X=-66.00, Y=-50.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.239675
SAR 1g (W/Kg)	0.324748



MEASUREMENT 2

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>2.32</u>

B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.537582
Relative permittivity (imaginary part)	19.549063
Conductivity (S/m)	0.908380
Variation (%)	1.880000



SURFACE SAR



Maximum location: X=9.00, Y=-29.00

SAR Peak: 0.95 W/kg

SAR 10g (W/Kg)	0.558923
SAR 1g (W/Kg)	0.689185



MEASUREMENT 3

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>
<u>ConvF</u>	<u>2.63</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.857780
Relative permittivity (imaginary part)	13.673918
Conductivity (S/m)	1.428165
Variation (%)	-2.320000

SURFACE SAR





VOLUME SAR



Maximum location: X=-72.00, Y=-65.00

SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.118777
SAR 1g (W/Kg)	0.281267



MEASUREMENT 4

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>
<u>ConvF</u>	<u>2.63</u>

B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.857780
Relative permittivity (imaginary part)	13.673918
Conductivity (S/m)	1.428165
Variation (%)	-3.420000


SURFACE SAR




Maximum location: X=17.00, Y=-32.00

SAR Peak: 0.55 W/kg


SAR 10g (W/Kg)	0.144543
SAR 1g (W/Kg)	0.236040



3D screen shot



Hot spot position



MEASUREMENT 5

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.63</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.857780
Relative permittivity (imaginary part)	13.673918
Conductivity (S/m)	1.428165
Variation (%)	3.570000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-51.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.047270
SAR 1g (W/Kg)	0.076228



MEASUREMENT 6

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.63</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.857780
Relative permittivity (imaginary part)	13.673918
Conductivity (S/m)	1.428165
Variation (%)	0.930000

SURFACE SAR





VOLUME SAR



Maximum location: X=20.00, Y=-30.00

SAR Peak: 0.54 W/kg

SAR 10g (W/Kg)	0.199237
SAR 1g (W/Kg)	0.350144



MEASUREMENT 7

Date of measurement: 28/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.45</u>

B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.794827
Relative permittivity (imaginary part)	13.921265
Conductivity (S/m)	1.339535
Variation (%)	2.610000



SURFACE SAR



Maximum location: X=-52.00, Y=-52.00

SAR Peak: 0.18 W/kg

SAR 10g (W/Kg)	0.078245
SAR 1g (W/Kg)	0.122665



MEASUREMENT 8

Date of measurement: 28/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.45</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	39.794827
Relative permittivity (imaginary part)	13.921265
Conductivity (S/m)	1.339535
Variation (%)	0.360000

SURFACE SAR





VOLUME SAR



Maximum location: X=20.00, Y=-40.00

SAR Peak: 0.92 W/kg

SAR 10g (W/Kg)	0.365363
SAR 1g (W/Kg)	0.610392



MEASUREMENT 9

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.32</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.537582
Relative permittivity (imaginary part)	19.549063
Conductivity (S/m)	0.908380
Variation (%)	3.550000

SURFACE SAR





VOLUME SAR



Maximum location: X=-49.00, Y=-36.00

SAR Peak: 0.66 W/kg

SAR 10g (W/Kg)	0.310369
SAR 1g (W/Kg)	0.380780



MEASUREMENT 10

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.32</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.537582
Relative permittivity (imaginary part)	19.549063
Conductivity (S/m)	0.908380
Variation (%)	-3.360000

SURFACE SAR





VOLUME SAR



Maximum location: X=-24.00, Y=-31.00

SAR Peak: 0.77 W/kg

SAR 10g (W/Kg)	0.408940
SAR 1g (W/Kg)	0.532641



MEASUREMENT 11

Date of measurement: 7/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.07</u>


B. SAR Measurement Results

Frequency (MHz)	5180.000000
Relative permittivity (real part)	34.939580
Relative permittivity (imaginary part)	15.925478
Conductivity (S/m)	4.582999
Variation (%)	-0.600000

SURFACE SAR



VOLUME SAR




Maximum location: X=-14.00, Y=24.00


SAR Peak: 1.27 W/kg

SAR 10g (W/Kg)	0.156553
SAR 1g (W/Kg)	0.434488


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SAR (W/ Kg)	0.81 81	0.45 56	0.10 62	0.11 54	0.03 45	0.04 04	0.02 67	0.02 42	0.01 97	0.01 74	0.01 96	0.02 62



3D screen shot



Hot spot position



MEASUREMENT 12

Date of measurement: 6/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.04</u>


B. SAR Measurement Results

Frequency (MHz)	5825.000000
Relative permittivity (real part)	34.238488
Relative permittivity (imaginary part)	16.281130
Conductivity (S/m)	5.268755
Variation (%)	0.770000

SURFACE SAR



VOLUME SAR




Maximum location: X=-8.00, Y=26.00


SAR Peak: 0.76 W/kg

SAR 10g (W/Kg)	0.084270
SAR 1g (W/Kg)	0.242494


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SAR (W/ Kg)	0.46 17	0.26 48	0.11 97	0.06 58	0.04 25	0.02 65	0.02 71	0.02 71	0.02 26	0.02 03	0.02 17	0.01 96



3D screen shot



Hot spot position



MEASUREMENT 13

Date of measurement: 6/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.04</u>


B. SAR Measurement Results

Frequency (MHz)	5825.000000
Relative permittivity (real part)	34.238488
Relative permittivity (imaginary part)	16.281130
Conductivity (S/m)	5.268755
Variation (%)	1.130000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=27.00

SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.058473
SAR 1g (W/Kg)	0.102469



MEASUREMENT 14

Date of measurement: 7/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.07</u>


B. SAR Measurement Results

Frequency (MHz)	5180.000000
Relative permittivity (real part)	34.939580
Relative permittivity (imaginary part)	15.925478
Conductivity (S/m)	4.582999
Variation (%)	3.900000

SURFACE SAR





VOLUME SAR



Maximum location: X=-7.00, Y=36.00

SAR Peak: 0.24 W/kg

SAR 10g (W/Kg)	0.054547
SAR 1g (W/Kg)	0.094066



MEASUREMENT 15

Date of measurement: 5/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.85</u>


B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative permittivity (real part)	37.814335
Relative permittivity (imaginary part)	12.880978
Conductivity (S/m)	1.726051
Variation (%)	1.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=24.00

SAR Peak: 1.38 W/kg

SAR 10g (W/Kg)	0.267241
SAR 1g (W/Kg)	0.679077



MEASUREMENT 16

Date of measurement: 5/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.85</u>


B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative permittivity (real part)	37.814335
Relative permittivity (imaginary part)	12.880978
Conductivity (S/m)	1.726051
Variation (%)	-1.010000

SURFACE SAR





VOLUME SAR



Maximum location: X=9.00, Y=40.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.092896
SAR 1g (W/Kg)	0.192952



MEASUREMENT 17

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.63</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.857780
Relative permittivity (imaginary part)	13.673918
Conductivity (S/m)	1.428165
Variation (%)	-0.830000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-21.00

SAR Peak: 0.70 W/kg

SAR 10g (W/Kg)	0.320221
SAR 1g (W/Kg)	0.441962



MEASUREMENT 18

Date of measurement: 3/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.63</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.857780
Relative permittivity (imaginary part)	13.673918
Conductivity (S/m)	1.428165
Variation (%)	-1.500000

SURFACE SAR




VOLUME SAR




Maximum location: X=5.00, Y=-27.00

SAR Peak: 1.53 W/kg


SAR 10g (W/Kg)	0.448371
SAR 1g (W/Kg)	0.599666



3D screen shot



Hot spot position



MEASUREMENT 19

Date of measurement: 28/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.45</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.802727
Relative permittivity (imaginary part)	13.906115
Conductivity (S/m)	1.338464
Variation (%)	-2.660000

SURFACE SAR





VOLUME SAR



Maximum location: X=-36.00, Y=-50.00

SAR Peak: 0.68 W/kg

SAR 10g (W/Kg)	0.197303
SAR 1g (W/Kg)	0.282433



MEASUREMENT 20

Date of measurement: 28/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.45</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.802727
Relative permittivity (imaginary part)	13.906115
Conductivity (S/m)	1.338464
Variation (%)	0.580000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=-15.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.280727
SAR 1g (W/Kg)	0.449078



MEASUREMENT 21

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.32</u>


B. SAR Measurement Results



Frequency (MHz)	836.500000
Relative permittivity (real part)	42.436028
Relative permittivity (imaginary part)	19.451874
Conductivity (S/m)	0.903972
Variation (%)	-3.610000

SURFACE SAR



VOLUME SAR





MEASUREMENT 22

Date of measurement: 30/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.32</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	42.436028
Relative permittivity (imaginary part)	19.451874
Conductivity (S/m)	0.903972
Variation (%)	-1.670000

SURFACE SAR




VOLUME SAR




Maximum location: X=-14.00, Y=-29.00

SAR Peak: 0.92 W/kg


SAR 10g (W/Kg)	0.438111
SAR 1g (W/Kg)	0.614006



3D screen shot



Hot spot position



MEASUREMENT 23

Date of measurement: 29/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.65</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.508785
Relative permittivity (imaginary part)	13.834288
Conductivity (S/m)	1.948329
Variation (%)	3.370000

SURFACE SAR





VOLUME SAR



Maximum location: X=-45.00, Y=-47.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.032526
SAR 1g (W/Kg)	0.052329



MEASUREMENT 24

Date of measurement: 29/5/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.65</u>

B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.508785
Relative permittivity (imaginary part)	13.834288
Conductivity (S/m)	1.948329
Variation (%)	-1.750000



SURFACE SAR



Maximum location: X=-14.00, Y=-44.00

SAR Peak: 0.17 W/kg

SAR 10g (W/Kg)	0.054903
SAR 1g (W/Kg)	0.096460



MEASUREMENT 25

Date of measurement: 4/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.37</u>

B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	41.427540
Relative permittivity (imaginary part)	21.802214
Conductivity (S/m)	0.856948
Variation (%)	0.930000



SURFACE SAR



Maximum location: X=-52.00, Y=-24.00

SAR Peak: 0.14 W/kg

SAR 10g (W/Kg)	0.097210
SAR 1g (W/Kg)	0.121421



MEASUREMENT 26

Date of measurement: 4/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.37</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	41.427540
Relative permittivity (imaginary part)	21.802214
Conductivity (S/m)	0.856948
Variation (%)	-3.669998

SURFACE SAR





VOLUME SAR



Maximum location: X=18.00, Y=-55.00

SAR Peak: 0.75 W/kg

SAR 10g (W/Kg)	0.165149
SAR 1g (W/Kg)	0.327631



MEASUREMENT 27

Date of measurement: 4/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.37</u>

B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	41.412189
Relative permittivity (imaginary part)	21.742662
Conductivity (S/m)	0.857627
Variation (%)	-4.400000



SURFACE SAR



Maximum location: X=-22.00, Y=-22.00

SAR Peak: 1.28 W/kg

SAR 10g (W/Kg)	0.303479
SAR 1g (W/Kg)	0.508229



MEASUREMENT 28

Date of measurement: 4/6/2024


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.37</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	41.412189
Relative permittivity (imaginary part)	21.742662
Conductivity (S/m)	0.857627
Variation (%)	-1.270000

SURFACE SAR



VOLUME SAR



Maximum location: X=-11.00, Y=3.00

SAR Peak: 1.29 W/kg

SAR 10g (W/Kg)	0.259122
SAR 1g (W/Kg)	0.391823