



Project No.: TM-2208000259P
Report No.: TMWK2210004085KS

FCC ID: 2AAAS-CM01
Ref. No.: T210728W02-MF

Page: 1 / 13
Rev.: 02

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for

Ping Indoor Camera

Model Name.: CM01

Prepared for:

Vivint, Inc.

4931 N. 300 W. Provo, Utah 84604 United States

Prepared by

Compliance Certification Services Inc.

Wugu Laboratory

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)**

Issue Date: October 12, 2022

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 21, 2021	Initial Issue	ALL	Allison Chen
01	August 18, 2021	See the following note Rev.(01)	ALL	Allison Chen
02	October 12, 2022	See the following note Rev.(02)	ALL	Doris Chu

Note:

Rev.(01)

- Applicant adds 2nd source DC/DC Regulator of EUT, please refer to the following table:

Type	Vendor	Part number
DC/DC Regulator	Silergy	SY8030LDEC

DC/DC Regulator
Main Board 2CS6022M..A1G: U3
Codec board 2CS6022C..A1G: U5 U6 U8 U10
Sensor Board 1VIP5MST.B1G: U2

- After verified radiated emission below 1GHz and conduction test data, the worst case is still original test data and power no change.
- Other information, please refer to T210429W04 and this test report.

Rev.(02)

- Applicant adds two Power IC PWM, please refer to the following table:

Type	Vendor	Model
Power IC PWM	TI	TPS62140RGTR
Power IC PWM	TI	TPS62150RGTR

- Base to FCC ID:2AAAS-CM01, date of grant:07/27/2021, after verified, only retest radiated emission below 1GHz and conduction, Since the verification result is worse than the original, C2PC is performed. Other test items are identical with the original report.
- Other information, please refer to T210728W02 and this test report.



Table of Contents

1 ATTESTATION OF TEST RESULTS 4

2 TEST SPECIFICATION, METHODS AND PROCEDURES 5

3 DEVICE UNDER TEST (DUT) INFORMATION 6

 3.1 DUT DESCRIPTION 6

 3.2 WIRELESS TECHNOLOGIES 7

4 MAXIMUM PERMISSIBLE EXPOSURE 8

 4.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) 8

 4.2 MPE CALCULATION METHOD 9


 4.3 MPE EXEMPTION 10

 4.4 MULTIPLE RF SOURCES 11

5 MPE EXEMPTION OPTION B 12

6 FACILITIES 13

1 Attestation of Test Results

Applicant Name	Vivint, Inc.
Model Name	CM01
Applicable Standards	FCC 47 CFR § 2.1091 KDB 447498 D04 FCC 47 CFR § 1.1307 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures
Receive EUT Date:	August 26, 2022
<p>Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.</p>	
<p>Approved & Released By:</p> 	
<p>Sky Zhou Asst. Section Manager Compliance Certification Services Inc.</p>	



Report No.: TMWK2210004085KS

Ref. No.: T210728W02-MF

Page: 5 / 13

Rev.: 02

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Report No.: TMWK2210004085KS

Ref. No.: T210728W02-MF

Page: 6 / 13

Rev.: 02

3 Device Under Test (DUT) Information

3.1 DUT Description

Product	Ping Indoor Camera
Trade Name	Vivint
Model No.	CM01
Model Discrepancy	N/A
Sample Stage	Identical prototype

3.2 Wireless Technologies

Frequency bands	<input checked="" type="checkbox"/> 802.11b/g/n HT20: 2412 MHz ~ 2462 MHz <input checked="" type="checkbox"/> 802.11n HT40: 2422 MHz ~ 2452MHz <input type="checkbox"/> Others																	
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)																	
Antenna Specification	FPC Antenna × 1, Antenna 1(Chain 0) PIFA Antenna × 1, Antenna 2(Chain 1) Antenna 1(Chain 0), Antenna Gain: 2.61dBi Antenna 2(Chain 1), Antenna Gain: 2.46dBi Direction Gain: 5.55dBi WIFI 2.4GHz Direction Gain : 5.55 dBi (Numeric gain: 3.59) Worst																	
Maximum tune up power	<table><tr><td>2.4GHz</td><td></td><td></td></tr><tr><td>IEEE 802.11b Mode:</td><td>22.00 dBm</td><td>(158.489 mW)</td></tr><tr><td>IEEE 802.11g Mode:</td><td>18.50 dBm</td><td>(70.795 mW)</td></tr><tr><td>IEEE 802.11n HT 20 Mode:</td><td>17.50 dBm</td><td>(56.234 mW)</td></tr><tr><td>IEEE 802.11n HT 40 Mode:</td><td>17.50 dBm</td><td>(56.234 mW)</td></tr></table>			2.4GHz			IEEE 802.11b Mode:	22.00 dBm	(158.489 mW)	IEEE 802.11g Mode:	18.50 dBm	(70.795 mW)	IEEE 802.11n HT 20 Mode:	17.50 dBm	(56.234 mW)	IEEE 802.11n HT 40 Mode:	17.50 dBm	(56.234 mW)
2.4GHz																		
IEEE 802.11b Mode:	22.00 dBm	(158.489 mW)																
IEEE 802.11g Mode:	18.50 dBm	(70.795 mW)																
IEEE 802.11n HT 20 Mode:	17.50 dBm	(56.234 mW)																
IEEE 802.11n HT 40 Mode:	17.50 dBm	(56.234 mW)																

Notes:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
- The tune up power referred the AVG power of the test report T210728W02-RP for RF Exposure assessment purpose.

4 Maximum Permissible Exposure

4.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

4.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Calculation(continued)

Given $R = R_3 + 40 \log(3 / 0.2)$ or $R = R_3 + 40 \log(3 / 0.15)$

$$E = 10^{((R-12)/20)}$$

Where E = E field Strength

R₃ = Result Power on 3m

R = Result Power on 0.2m or 0.15m

4.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.
Note: R is in meters, f is in MHz.	

4.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



Report No.: TMWK2210004085KS

Ref. No.: T210728W02-MF

Page: 12 / 13

Rev.: 02

5 MPE Exemption Option B

WIFI 2.4GHz

Mode	Frequency (MHz)	R(m)	Max Tune-up EIRP(dBm)	Max Tune-up ERP(dBm)	Max Tune-up ERP(mW)	ERP Threshold(mW)	MPE Exemption
IEEE 802.11b	2462.00	0.2	27.55	25.40	346.737	3060	Complies
IEEE 802.11g	2462.00	0.2	24.05	21.90	154.882	3060	Complies
IEEE 802.11n HT 20	2462.00	0.2	23.05	20.90	123.027	3060	Complies
IEEE 802.11n HT 40	2452.00	0.2	23.05	20.90	123.027	3060	Complies



Report No.: TMWK2210004085KS

Ref. No.: T210728W02-MF

Page: 13 / 13

Rev.: 02

6 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

END OF REPORT