

FCC PART 15.247

TEST REPORT

For

**b mobile HK Limited**

Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; HONG KONG, CHINA

**FCC ID: ZSW-30-002**

|   |                                     |
|---|-------------------------------------|
| <b>Report Type:</b><br>Original Report  | <b>Product Type:</b><br>Smart phone |
| <b>Test Engineer:</b> <u>Mike Hu</u>  | <i>Mike Hu</i>                      |
| <b>Report Number:</b> <u>RSZ140905004-00C</u>   |                                     |
| <b>Report Date:</b> <u>2014-09-16</u>   |                                     |
| <b>Reviewed By:</b> <u>RF Engineer</u>  | <i>Jimmy Xiao</i>                   |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F, the 3rd Phase of WanLi Industrial Building<br>ShiHua Road, FuTian Free Trade Zone<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                     |

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

|   |           |
|---|-----------|
| <b>GENERAL INFORMATION.....</b>   | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                | 4         |
| OBJECTIVE .....   | 4         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                      | 4         |
| TEST METHODOLOGY .....  | 4         |
| TEST FACILITY .....   | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                   | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                 | 6         |
| EUT EXERCISE SOFTWARE .....   | 6         |
| SPECIAL ACCESSORIES.....  | 6         |
| EQUIPMENT MODIFICATIONS .....   | 6         |
| EXTERNAL I/O CABLE.....   | 6         |
| BLOCK DIAGRAM OF TEST SETUP .....                                       | 6         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                    | <b>7</b>  |
| <b>FCC§15.247 (i), §1.1307 (b) (1) &amp;§2.1093 – RF EXPOSURE .....</b> | <b>8</b>  |
| APPLICABLE STANDARD .....   | 8         |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                           | <b>9</b>  |
| APPLICABLE STANDARD .....   | 9         |
| ANTENNA CONNECTOR CONSTRUCTION .....                                    | 9         |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>              | <b>10</b> |
| APPLICABLE STANDARD .....   | 10        |
| MEASUREMENT UNCERTAINTY .....   | 10        |
| EUT SETUP.....  | 10        |
| EMI TEST RECEIVER SETUP.....  | 11        |
| TEST EQUIPMENT LIST AND DETAILS.....                                    | 11        |
| TEST PROCEDURE .....  | 11        |
| CORRECTED FACTOR & MARGIN CALCULATION .....                             | 11        |
| TEST RESULTS SUMMARY .....  | 12        |
| TEST DATA .....   | 12        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>  | <b>15</b> |
| APPLICABLE STANDARD .....   | 15        |
| MEASUREMENT UNCERTAINTY .....   | 15        |
| EUT SETUP .....   | 15        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                       | 16        |
| TEST PROCEDURE .....  | 16        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                          | 16        |
| TEST EQUIPMENT LIST AND DETAILS.....                                    | 16        |
| TEST RESULTS SUMMARY .....  | 17        |
| TEST DATA .....   | 17        |
| <b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>                | <b>22</b> |
| APPLICABLE STANDARD .....   | 22        |
| TEST PROCEDURE .....  | 22        |
| TEST EQUIPMENT LIST AND DETAILS.....                                    | 22        |
| TEST DATA .....   | 22        |
| <b>FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER .....</b>             | <b>25</b> |

|   |           |
|---|-----------|
| APPLICABLE STANDARD .....   | 25        |
| TEST PROCEDURE .....  | 25        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 25        |
| TEST DATA .....   | 25        |
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b> | <b>28</b> |
| APPLICABLE STANDARD .....   | 28        |
| TEST PROCEDURE .....  | 28        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 28        |
| TEST DATA .....   | 29        |
| <b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>                  | <b>31</b> |
| APPLICABLE STANDARD .....   | 31        |
| TEST PROCEDURE .....  | 31        |
| TEST EQUIPMENT LIST AND DETAILS.....                                  | 31        |
| TEST DATA .....   | 31        |

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *b mobile HK Limited* 's product, model number:AX660(FCC ID: ZSW-30-002) or the "EUT" in this report was a *Smart phone*, which was measured approximately: 125 mm (L) x64 mm (W) x 10 mm (H), rated with input voltage: DC 3.7 V rechargeable Li-ion battery or DC 5.0V from adapter.

#### Adapter Information:

Input: AC 100-240V~50/60 Hz, 0.15A

Output: DC 5.0V, 500mA

*\*All measurement and test data in this report was gathered from production sample serial number: 1409030 (Assigned by the applicant). The EUT supplied by the applicant was received on 2014-08-20.*

### Objective

This report is prepared on behalf of *b mobile HK Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS&DSS, Part 22H&24E PCE and Part 15B JBP submissions with FCC ID: ZSW-30-002.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineer mode.

EUT Exercise Software

RF test tool built-in the EUT.

Special Accessories

No special accessory.

Equipment Modifications


No modification was made to the EUT tested.

External I/O Cable

| Cable Description                | Length (m) | From Port | To      |
|----------------------------------|------------|-----------|---------|
| Unshielding Detachable USB Cable | 1.0        | EUT       | Adapter |

Block Diagram of Test Setup

For conducted emission



**SUMMARY OF TEST RESULTS**

| FCC Rules                                | Description of Test                      | Result     |
|--|--|------------|
| §15.247 (i), §1.1307 (b) (1)&<br>§2.1093 | RF Exposure                              | Compliance |
| §15.203                                  | Antenna Requirement                      | Compliance |
| §15.207 (a),                             | AC Line Conducted Emissions              | Compliance |
| §15.247(d)                               | Spurious Emissions at Antenna Port       | Compliance |
| §15.205, §15.209,<br>§15.247(d)          | Spurious Emissions                       | Compliance |
| §15.247 (a)(2)                           | 6 dB Emission Bandwidth                  | Compliance |
| §15.247(b)(3)                            | Maximum Peak Output Power                | Compliance |
| §15.247(d)                               | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e)                               | Power Spectral Density                   | Compliance |

---

## **FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE**

---

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

The SAR data please refer to the SAR report, report No.: RSZ140905004-20.

FINAL



## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement, which the antenna gain is 1 dBi, fulfill the requirement of this section. Please refer to the internal photos.

**Result:** Compliant.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207


### Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

| Port     | Measurement uncertainty                |
|----------|--|
| AC Mains | 3.26 dB (k=2, 95% level of confidence) |
| CAT 3    | 3.70 dB (k=2, 95% level of confidence) |
| CAT 5    | 3.86 dB (k=2, 95% level of confidence) |
| CAT 6    | 4.64 dB (k=2, 95% level of confidence) |

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2009. The related limit was specified in FCC Part 15.207.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

## Test Equipment List and Details

| Manufacturer    | Description       | Model  | Serial Number          | Calibration Date | Calibration Due Date |
|-----------------|-------------------|--------|------------------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 100176                 | 2014-06-17       | 2015-06-17           |
| Rohde & Schwarz | LISN              | ENV216 | 3560.6650.12-101613-Yb | 2014-05-07       | 2015-05-07           |
| Rohde & Schwarz | Transient Limiter | ESH3Z2 | DE25985                | 2013-10-15       | 2014-10-15           |
| Rohde & Schwarz | CE Test software  | EMC 32 | V8.53                  | --               | --                   |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

## Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**11.2 dB at 0.639450 MHz in the Line conducted mode**

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

in BACL.,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## Test Data

### Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25°C      |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Mike Hu on 2014-09-12.*


EUT operation mode: Charging & Transmitting

AC 120 V, 60 Hz, Line:

EMI Auto Test L



| Frequency (MHz) | Corrected Amplitude (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/Ave./QP) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.407970        | 46.0                       | 19.5                   | 57.7         | 11.7        | QP                    |
| 0.407970        | 32.9                       | 19.5                   | 47.7         | 14.7        | Ave.                  |
| 0.573270        | 42.7                       | 19.6                   | 56.0         | 13.3        | QP                    |
| 0.573270        | 27.0                       | 19.6                   | 46.0         | 19.0        | Ave.                  |
| 0.639450        | 44.8                       | 19.6                   | 56.0         | 11.2        | QP                    |
| 0.639450        | 28.0                       | 19.6                   | 46.0         | 18.0        | Ave.                  |
| 0.896470        | 42.0                       | 19.5                   | 56.0         | 14.0        | QP                    |
| 0.896470        | 24.4                       | 19.5                   | 46.0         | 21.6        | Ave.                  |
| 0.975270        | 42.8                       | 19.5                   | 56.0         | 13.2        | QP                    |
| 0.975270        | 26.3                       | 19.5                   | 46.0         | 19.7        | Ave.                  |
| 1.199850        | 42.7                       | 19.5                   | 56.0         | 13.3        | QP                    |
| 1.199850        | 26.9                       | 19.5                   | 46.0         | 19.1        | Ave.                  |

**AC 120V, 60 Hz, Neutral:****EMI Auto Test N**

| Frequency (MHz) | Corrected Amplitude (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/Ave./QP) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.395970        | 45.5                       | 19.6                   | 57.9         | 12.5        | QP                    |
| 0.395970        | 32.7                       | 19.6                   | 47.9         | 15.3        | Ave.                  |
| 0.553750        | 44.1                       | 19.6                   | 56.0         | 11.9        | QP                    |
| 0.553750        | 27.1                       | 19.6                   | 46.0         | 18.9        | Ave.                  |
| 0.648370        | 44.6                       | 19.6                   | 56.0         | 11.4        | QP                    |
| 0.648370        | 26.9                       | 19.6                   | 46.0         | 19.1        | Ave.                  |
| 0.726990        | 42.8                       | 19.6                   | 56.0         | 13.2        | QP                    |
| 0.726990        | 25.6                       | 19.6                   | 46.0         | 20.4        | Ave.                  |
| 0.868770        | 41.9                       | 19.5                   | 56.0         | 14.1        | QP                    |
| 0.868770        | 25.1                       | 19.5                   | 46.0         | 20.9        | Ave.                  |
| 0.987270        | 38.7                       | 19.5                   | 56.0         | 17.3        | QP                    |
| 0.987270        | 22.9                       | 19.5                   | 46.0         | 23.1        | Ave.                  |

**Note:**

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation  
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz. And this uncertainty will not be taken into consideration for the test data recorded in the report.

### EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz   | 120 kHz | QP       |
| Above 1 GHz       | 1 MHz   | 3 MHz     | /       | PK       |
|                   | 1 MHz   | 10 Hz     | /       | Ave.     |

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz and peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

| Manufacturer    | Description        | Model       | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|--------------------|-------------|---------------|------------------|----------------------|
| HP              | Amplifier          | 8447E       | 1937A01046    | 2014-05-06       | 2015-05-06           |
| Rohde & Schwarz | EMI Test Receiver  | ESCI        | 101120        | 2013-11-12       | 2014-11-12           |
| Sunol Sciences  | Broadband Antenna  | JB1         | A040904-2     | 2011-11-28       | 2014-11-27           |
| A.H. System     | Horn Antenna       | SAS-200/571 | 135           | 2012-02-11       | 2015-02-10           |
| Rohde & Schwarz | Signal Analyzer    | FSIQ26      | 8386001028    | 2013-11-12       | 2014-11-12           |
| Mini            | Pre-amplifier      | ZVA-183-S+  | 5969001149    | 2014-04-03       | 2015-04-03           |
| TDK             | Chamber            | Chamber A   | 2#            | 2012-10-15       | 2015-10-15           |
| TDK             | Chamber            | Chamber B   | 1#            | 2012-07-23       | 2015-07-22           |
| R&S             | Auto test Software | EMC32       | V9.10         | -                | -                    |



\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

**3.38 dB at 149.8 MHz in the Horizontal polarization**

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25°C      |
| Relative Humidity: | 51 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Mike Hu on 2014-09-10*

*EUT operation mode: Transmitting*

## 30 MHz-25 GHz

| Frequency<br>(MHz)       | Receiver          |                          | Turn<br>table<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|--------------------------|-------------------|--------------------------|-------------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                          | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                         | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| Low Channel(2402 MHz)    |                   |                          |                         |               |                |                             |                                    |                            |                |
| 149.8                    | 53.92             | QP                       | 75                      | 1.2           | H              | -13.8                       | 40.12                              | 43.5                       | 3.38           |
| 2402.0                   | 84.94             | PK                       | 244                     | 1.3           | H              | 5.48                        | 90.42                              | /                          | /              |
| 2402.0                   | 79.48             | AV                       | 244                     | 1.3           | H              | 5.48                        | 84.96                              | /                          | /              |
| 2402.0                   | 82.64             | PK                       | 355                     | 1.5           | V              | 5.48                        | 88.12                              | /                          | /              |
| 2402.0                   | 75.32             | AV                       | 355                     | 1.5           | V              | 5.48                        | 80.80                              | /                          | /              |
| 2376.0                   | 38.64             | PK                       | 316                     | 1.2           | H              | 5.48                        | 44.12                              | 74                         | 29.88          |
| 2376.0                   | 25.64             | AV                       | 316                     | 1.2           | H              | 5.48                        | 31.12                              | 54                         | 22.88          |
| 2389.7                   | 38.64             | PK                       | 97                      | 1.4           | V              | 5.48                        | 44.12                              | 74                         | 29.88          |
| 2389.7                   | 27.02             | AV                       | 97                      | 1.4           | V              | 5.48                        | 32.50                              | 54                         | 21.50          |
| 2486.5                   | 36.54             | PK                       | 292                     | 1.4           | H              | 7.21                        | 43.75                              | 74                         | 30.25          |
| 2486.5                   | 23.02             | AV                       | 292                     | 1.4           | H              | 7.21                        | 30.23                              | 54                         | 23.77          |
| 4804.0                   | 36.24             | PK                       | 144                     | 1.2           | H              | 12.44                       | 48.68                              | 74                         | 25.32          |
| 4804.0                   | 22.54             | AV                       | 144                     | 1.2           | H              | 12.44                       | 34.98                              | 54                         | 19.02          |
| 7206.0                   | 36.71             | PK                       | 70                      | 1.4           | V              | 17.06                       | 53.77                              | 74                         | 20.23          |
| 7206.0                   | 22.70             | AV                       | 70                      | 1.4           | V              | 17.06                       | 39.76                              | 54                         | 14.24          |
| 9608.0                   | 35.31             | PK                       | 197                     | 1.4           | V              | 19.28                       | 54.59                              | 74                         | 19.41          |
| 9608.0                   | 22.25             | AV                       | 197                     | 1.4           | V              | 19.28                       | 41.53                              | 54                         | 12.47          |
| Middle Channel(2440 MHz) |                   |                          |                         |               |                |                             |                                    |                            |                |
| 149.8                    | 53.20             | QP                       | 93                      | 1.2           | H              | -13.8                       | 39.40                              | 43.5                       | 4.10           |
| 2440.0                   | 84.64             | PK                       | 11                      | 1.5           | H              | 6.13                        | 90.77                              | /                          | /              |
| 2440.0                   | 79.23             | AV                       | 11                      | 1.5           | H              | 6.13                        | 85.36                              | /                          | /              |
| 2440.0                   | 83.64             | PK                       | 307                     | 1.5           | V              | 6.13                        | 89.77                              | /                          | /              |
| 2440.0                   | 78.40             | AV                       | 307                     | 1.5           | V              | 6.13                        | 84.53                              | /                          | /              |
| 2386.0                   | 36.64             | PK                       | 12                      | 1.4           | V              | 5.48                        | 42.12                              | 74                         | 31.88          |
| 2386.0                   | 22.52             | AV                       | 12                      | 1.4           | V              | 5.48                        | 28.00                              | 54                         | 26.00          |
| 2485.1                   | 36.72             | PK                       | 5                       | 1.3           | H              | 7.21                        | 43.93                              | 74                         | 30.07          |
| 2485.1                   | 22.28             | AV                       | 5                       | 1.3           | H              | 7.21                        | 29.49                              | 54                         | 24.51          |
| 2487.4                   | 36.02             | PK                       | 288                     | 1.4           | H              | 7.21                        | 43.23                              | 74                         | 30.77          |
| 2487.4                   | 22.88             | AV                       | 288                     | 1.4           | H              | 7.21                        | 30.09                              | 54                         | 23.91          |
| 4880.0                   | 35.92             | PK                       | 235                     | 1.2           | V              | 12.4                        | 48.32                              | 74                         | 25.68          |
| 4880.0                   | 22.85             | AV                       | 235                     | 1.2           | V              | 12.4                        | 35.25                              | 54                         | 18.75          |
| 7320.0                   | 36.12             | PK                       | 177                     | 1.3           | V              | 16.49                       | 52.61                              | 74                         | 21.39          |
| 7320.0                   | 23.34             | AV                       | 177                     | 1.3           | V              | 16.49                       | 39.83                              | 54                         | 14.17          |
| 9760.0                   | 35.89             | PK                       | 148                     | 1.3           | H              | 19.4                        | 55.29                              | 74                         | 18.71          |
| 9760.0                   | 23.00             | AV                       | 148                     | 1.3           | H              | 19.4                        | 42.40                              | 54                         | 11.60          |

| Frequency<br>(MHz)     | Receiver          |                          | Turn<br>table<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|------------------------|-------------------|--------------------------|-------------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                        | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                         | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| High Channel(2480 MHz) |                   |                          |                         |               |                |                             |                                    |                            |                |
| 149.8                  | 53.05             | QP                       | 120                     | 1.2           | H              | -13.8                       | 39.25                              | 43.5                       | 4.25           |
| 2480.0                 | 85.23             | PK                       | 38                      | 1.3           | H              | 7.21                        | 92.44                              | /                          | /              |
| 2480.0                 | 80.05             | AV                       | 38                      | 1.3           | H              | 7.21                        | 87.26                              | /                          | /              |
| 2480.0                 | 81.42             | PK                       | 137                     | 1.2           | V              | 7.21                        | 88.63                              | /                          | /              |
| 2480.0                 | 75.64             | AV                       | 137                     | 1.2           | V              | 7.21                        | 82.85                              | /                          | /              |
| 2389.0                 | 36.24             | PK                       | 64                      | 1.4           | H              | 5.48                        | 41.72                              | 74                         | 32.28          |
| 2389.0                 | 22.72             | AV                       | 64                      | 1.4           | H              | 5.48                        | 28.20                              | 54                         | 25.80          |
| 2483.6                 | 40.14             | PK                       | 35                      | 1.3           | V              | 7.21                        | 47.35                              | 74                         | 26.65          |
| 2483.6                 | 30.06             | AV                       | 35                      | 1.3           | V              | 7.21                        | 37.27                              | 54                         | 16.73          |
| 2490.2                 | 36.21             | PK                       | 229                     | 1.3           | V              | 7.21                        | 43.42                              | 74                         | 30.58          |
| 2490.2                 | 22.74             | AV                       | 229                     | 1.3           | V              | 7.21                        | 29.95                              | 54                         | 24.05          |
| 4960.0                 | 36.21             | PK                       | 235                     | 1.5           | V              | 12.5                        | 48.71                              | 74                         | 25.29          |
| 4960.0                 | 22.50             | AV                       | 235                     | 1.5           | V              | 12.5                        | 35.00                              | 54                         | 19.00          |
| 7440.0                 | 35.24             | PK                       | 31                      | 1.3           | H              | 15.9                        | 51.14                              | 74                         | 22.86          |
| 7440.0                 | 21.89             | AV                       | 31                      | 1.3           | H              | 15.9                        | 37.79                              | 54                         | 16.21          |
| 9920.0                 | 35.22             | PK                       | 169                     | 1.3           | V              | 19.39                       | 54.61                              | 74                         | 19.39          |
| 9920.0                 | 22.77             | AV                       | 169                     | 1.3           | V              | 19.39                       | 42.16                              | 54                         | 11.84          |

Note:


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) +cable loss – amplifier factor


Margin = Limit- Corr. Amplitude

**Conducted Spurious Emissions at Antenna Port:**


| Mode | Channel | Delta Peak to band emission (dBc) | Limit (dBc) |
|------|---------|-----------------------------------|-------------|
|      | Low     | 41.64                             | 20          |
|      | Middle  | 42.15                             | 20          |
|      | High    | 41.53                             | 20          |

**Low Channel**

### Middle Channel



### High Channel




**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH****Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Equipment List and Details**

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 837405/023    | 2014-05-31       | 2015-05-31           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 51 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Mike Hu on 2014-09-10.*


*EUT operation mode: Transmitting*

**Test Result:** Compliance


Please refer to the following tables and plots.

| Channel | Channel Frequency (MHz) | 6 dB Emission Bandwidth (kHz) | Limit (kHz) |
|---------|-------------------------|-------------------------------|-------------|
| Low     | 2402                    | 733.0                         | ≥500        |
| Middle  | 2440                    | 733.0                         | ≥500        |
| High    | 2480                    | 733.0                         | ≥500        |


### Low Channel



### Middle Channel



### High Channel





## FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER


### Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 837405/023    | 2014-05-31       | 2015-05-31           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 51 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Mike Hu on 2014-09-10.*


EUT operation mode: Transmitting

| Channel | Frequency (MHz) | Conducted Output Power (dBm) | Limit (dBm) | Result |
|---------|-----------------|------------------------------|-------------|--------|
| Low     | 2402            | -6.17                        | 30          | Pass   |
| Middle  | 2440            | -5.85                        | 30          | Pass   |
| High    | 2480            | -5.59                        | 30          | Pass   |


### RF Output Power, Low Channel



### RF Output Power, Middle Channel



### RF Output Power, High Channel



**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Equipment List and Details**

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 837405/023    | 2014-05-31       | 2015-05-31           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 °C     |
| <b>Relative Humidity:</b> | 51 %      |
| <b>ATM Pressure:</b>      | 100.0 kPa |


*The testing was performed by Mike Hu on 2014-09-10.*

*EUT operation mode: Transmitting*


*Test Result: Compliance. Please refer to following plots.*

| Mode | Band edges | Delta Peak to band emission (dBc) | Limit (dBc) |
|------|------------|-----------------------------------|-------------|
|      | Left       | 42.52                             | 20          |
|      | Right      | 44.24                             | 20          |

### Band Edge, Left Side



### Band Edge, Right Side



## FCC §15.247(e) - POWER SPECTRAL DENSITY


### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW  $\geq 3$  kHz.
4. Set the VBW  $\geq 3 \times$  RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measurement value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 837405/023    | 2014-05-31       | 2015-05-31           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 51 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Mike Hu on 2014-09-10.*


EUT operation mode: Transmitting

Test Result: Pass.

Please refer to following table and plots.


| Channel | Frequency (MHz) | Power spectral density (dBm/3kHz) | Limit (dBm/3kHz) |
|---------|-----------------|-----------------------------------|------------------|
| Low     | 2402            | -21.43                            | $\leq 8$         |
| Middle  | 2440            | -21.19                            | $\leq 8$         |
| High    | 2480            | -20.88                            | $\leq 8$         |

### Low Channel






### Middle Channel



### High Channel



\*\*\*\*\* END OF REPORT \*\*\*\*\*