
FCC Test Report

Report No.: AGC07835170401FE03

FCC ID : 2AIT8QS

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : PROFESSIONAL ACTIVE BT SPEAKER

BRAND NAME : N/A

MODEL NAME : See Page 4

CLIENT : GUANGZHOU HEADWAY I. & E. TRADING CO., LTD

DATE OF ISSUE : Apr.28, 2017

STANDARD(S) : FCC Part 15 Subpart C Section 15.249

TEST PROCEDURE(S)


REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr.28, 2017	Valid	Original Report

TABLE OF CONTENTS

1 VERIFICATION OF CONFORMITY	4
2 GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
2.2. TABLE OF CARRIER FREQUENCYS	5
3 MEASUREMENT UNCERTAINTY.....	6
4 DESCRIPTION OF TEST MODES.....	6
5 SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM.....	8
5.2. EQUIPMENT USED IN EUT SYSTEM.....	8
5.3. SUMMARY OF TEST RESULTS.....	8
6 TEST FACILITY	9
7 TEST METHOD	9
8 TEST EQUIPMENT LIST	9
9 RADIATED EMISSION	11
9.1TEST LIMIT.....	11
9.2. MEASUREMENT PROCEDURE.....	12
9.3. TEST SETUP	14
9.4. TEST RESULT	16
10 BAND EDGE EMISSION	31
10.1. MEASUREMENT PROCEDURE.....	31
10.2 TEST SETUP	31
10.3 RADIATED TEST RESULT	32
11 20DB BANDWIDTH.....	36
11.1. MEASUREMENT PROCEDURE	36
11.2. TEST SET-UP	36
11.3. LIMITS AND MEASUREMENT RESULTS.....	36
12 FCC LINE CONDUCTED EMISSION TEST	43
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	43
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	43
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	44
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	44
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	45
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	47
APPENDIX B: PHOTOGRAPHS OF EUT	50

1. VERIFICATION OF CONFORMITY

Applicant	GUANGZHOU HEADWAY I. & E. TRADING CO., LTD
Address	5F, NO.89 JIANSHE ROAD (N.) HUADU, GUANGZHOU, CHINA
Manufacturer	GUANGZHOU LEISHENG AUDIO ELECTRON EQUIPMENTS CO., LTD
Address	NO.3. Dongjing Road, Donghua Industrial Zone, Renhe Town, Baiyun District, Guangzhou
Product Designation	PROFESSIONAL ACTIVE BT SPEAKER
Brand Name	N/A
Test Model	LS-3038
Series Model	PS-91021, PS-91022, PS-91023, PS-91024, PS-91025, PS-91026, PS-91027, PS-91028, PS-91029, PS-92112, PS-92113, PS-92114, PS-92115, PS-92116, PS-92117, PS-92118, PS-92119, PS-92121, PS-92122, PS-92123, PS-12124, PS-92125, PS-92126, PS-92127, PS-92128, PS-92129, PS-91511, PS-91512, PS-91513, PS-91514, PS-91515, PS-91516, PS-91517, PS-91518, PS-91519, PS-92521, PS-92522, PS-92523, PS-92524, PS-92525, PS-92526, PS-92527, PS-92528, PS-92529.
Difference description	All the same except for the model name and appearance shape.
Date of test	Apr.15, 2017 to Apr.22, 2017
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By Strive Liang
Strive Liang(Liang Faqiang) Apr.22, 2017

Reviewed By Forrest Lei
Forrest Lei(Lei Yonggang) Apr.28, 2017

Approved By Solger Zhang
Solger Zhang(Zhang Hongyi)
Authorized Officer Apr.28, 2017

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1.63dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V2.1+EDR
Modulation	GFSK , $\pi/4$ -DQPSK, 8DPSK
Number of channels	79 for BR/EDR
Hardware Version	CW_BB_V30
Software Version	CW_BB_V30
Antenna Designation	PCB Antenna
Antenna Gain	2dBi
Power Supply	AC120V/60Hz

Note: The USB port only read data from U-disk and can't be used to transfer data with PC.

2.2. TABLE OF CARRIER FREQUENCIES

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHz	0	2402MHz
	1	2403MHz
	:	:
	38	2440 MHz
	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	BT Link

Software Setting

AppoTech RF Control Kit V4.0

IC Model: CW66xx

COM Port Info: Port: COM1 Rate: 921600

DUT MODE: FCC Mode

RF Trim: ☐ Fix_RX_24xx ☐ SingleTone Hopping: OFF

☒ Channel: 41 (2-80) Tx Modulation: ON

☒ Power: 6 (0-7) Packet Type: 3DH5

Test scenario: 3 Transmitter test - 1010 pattern

Specification:

FIX RX mode: (1)check FIX_RX_24xx (2)check channel to set channel number

FIX TX mode: (1)unchecked FIX_RX_24xx (2)check channel to set channel number (3)check power to set TX signal amplitude (4)Modulation Enable OFF

TX Modulation mode: (1)unchecked FIX_RX_24xx (2)check channel to set channel number (3)check power to set TX signal amplitude (4)Modulation Enable ON (5)select Packet Type

Hopping mode: (1)unchecked FIX_RX_24xx (2)unchecked channel to enable Hopping ON and TX Modulation OFF (3)check power (4)select Packet Type

Language: 语言

RF: R12 60BD Write Read Address: 0206 Val: 04 Write_xSFR Read_xSFR

01 19 FC 40 0F 40 B2 41 04 06 A0 40 00 81 00 00 80 0

04 0E 04 01 19 FC 00

01 08 FC 03 68 4F 00

04 0E 04 01 08 FC 00

01 0F FC 0A 02 03 00 27 00 06 28 2F FD 03

04 0E 04 01 0F FC 00

01 09 FC 01 0C

04 0E 07 01 09 FC 00 0C BD 60

☒ Show HCI Clear Save Read MROM

Enable Patch 1: 00C845 00C0CF 019E68 019E69

048280 0482AE 048040 048073


PFile: ...

Send


5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	PROFESSIONAL ACTIVE BT SPEAKER	LEISHENG	LS-3038	EUT
2	PC	Sony	E1412AYCW	A.E
3	PC Adapter	Sony	AC-L100	A.E
4	Control box	GZU	USB_TTL	A.E
5	USB Cable	N/A	1m unshielded	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a) §15.209	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	Bandwidth	Compliant

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

7.TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

8. TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHz)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101417	July 4, 2016	July 3, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2016	July 3, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2016	July 3, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	MAX-FULL	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	SCHWARZBECK	FMZB1519	1519-038	June 6, 2016	June 5, 2017
Spectrum analyzer	AGILENT	E4407B	MY46185649	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

FOR RADIATED EMISSION TEST (1GHz ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101417	July 4, 2016	July 3, 2017
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2016	July 10, 2017
Spectrum Analyzer	AGILENT	E4411B	MY4511453	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2016	July 6, 2017
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2016	July 7, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	MAX-FULL	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101417	July 4, 2016	July 3, 2017
Artificial Mains Network	NARDA	L2-16B	000WX31025	July 8, 2016	July 7, 2017
Artificial Mains Network (AUX)	NARDA	L2-16B	000WX31026	July 8, 2016	July 7, 2017
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2016	July 3, 2017
Shielded Room	CHENGYU	843	PTS-002	June 6, 2016	June 5, 2017
Conduction Cable	MXT	SE1	S003	June 6, 2016	June 5, 2017

9. RADIATED EMISSION

9.1 TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark: (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

9.2. MEASUREMENT PROCEDURE

1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 1.5MHz/10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

9.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



9.4. TEST RESULT

(Worst modulation:GFSK)


FOR BR/EDR

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: PROFESSIONAL ACTIVE BT SPEAKER
M/N: LS3038
Mode: Low Channel TX
Note:


Polarization: **Horizontal**
Power:
Distance:

Temperature: 23.5
Humidity: 53.3 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	131.8498	26.99	11.39	38.38	43.50	-5.12	peak			
2	!	227.2333	31.20	9.22	40.42	46.00	-5.58	peak			
3	!	324.2332	24.57	17.02	41.59	46.00	-4.41	peak			
4	!	372.7332	22.00	18.89	40.89	46.00	-5.11	peak			
5	*	492.3666	21.07	21.05	42.12	46.00	-3.88	peak			
6	!	684.7500	16.00	24.78	40.78	46.00	-5.22	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



Site: site #1
 Limit: FCC Class B 3M Radiation
 EUT: PROFESSIONAL ACTIVE BT SPEAKER
 M/N: LS3038
 Mode: Low Channel TX
 Note:

Polarization: **Vertical**
 Power:
 Distance:

Temperature: 23.5
 Humidity: 53.3 %


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	131.8499	25.85	11.80	37.65	43.50	-5.85	peak			
2	!	251.4833	26.26	13.94	40.20	46.00	-5.80	peak			
3	*	443.8666	21.50	20.40	41.90	46.00	-4.10	peak			
4	!	560.2667	18.98	22.53	41.51	46.00	-4.49	peak			
5		679.8999	14.54	24.65	39.19	46.00	-6.81	peak			
6		948.2667	8.75	29.95	38.70	46.00	-7.30	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 23.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 53.3 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N: LS3038


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		107.5999	21.68	8.72	30.40	43.50	-13.10	peak			
2		227.2333	30.04	9.22	39.26	46.00	-6.74	peak			
3	!	324.2332	23.09	17.02	40.11	46.00	-5.89	peak			
4	!	440.6333	20.25	20.31	40.56	46.00	-5.44	peak			
5	*	519.8500	19.17	21.67	40.84	46.00	-5.16	peak			
6		679.8999	15.08	24.65	39.73	46.00	-6.27	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 23.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 53.3 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N: LS3038

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	107.5999	38.06	0.68	38.74	43.50	-4.76	peak			
2	*	156.0997	24.44	15.30	39.74	43.50	-3.76	peak			
3	!	299.9832	26.60	15.41	42.01	46.00	-3.99	peak			
4	!	443.8666	21.11	20.40	41.51	46.00	-4.49	peak			
5		660.5000	15.63	24.13	39.76	46.00	-6.24	peak			
6		948.2667	8.03	29.95	37.98	46.00	-8.02	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 23.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 53.3 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N: LS3038


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	227.2333	28.61	9.22	37.83	46.00	-8.17	peak			
2		299.9832	21.60	15.41	37.01	46.00	-8.99	peak			
3		372.7332	15.92	18.89	34.81	46.00	-11.19	peak			
4		516.6167	14.97	21.58	36.55	46.00	-9.45	peak			
5		684.7500	10.67	24.78	35.45	46.00	-10.55	peak			
6		851.2667	7.01	27.34	34.35	46.00	-11.65	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 23.5

Limit: FCC Class B 3M Radiation

Power:

Humidity: 53.3 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N: LS3038


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	120.5332	30.53	7.08	37.61	43.50	-5.89	peak			
2		227.2333	25.12	11.67	36.79	46.00	-9.21	peak			
3		299.9832	23.95	15.41	39.36	46.00	-6.64	peak			
4	!	519.8500	18.66	21.67	40.33	46.00	-5.67	peak			
5	*	560.2667	19.17	22.53	41.70	46.00	-4.30	peak			
6	!	679.8999	16.19	24.65	40.84	46.00	-5.16	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHz**(Worst modulation: GFSK)****FOR BR/EDR****RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL**

Site: site #1

Polarization: *Horizontal*

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N:LS-3038


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	83.19	10.32	93.51	114.00	-20.49	peak			
2		4804.000	41.24	7.69	48.93	74.00	-25.07	peak			
3		5441.667	48.20	-0.64	47.56	74.00	-26.44	peak			
4	*	2402.000	74.01	10.32	84.33	94.00	-9.67	AVG	100	178	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N:LS-3038


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	83.30	10.32	93.62	114.00	-20.38	peak			
2		4804.000	40.88	7.69	48.57	74.00	-25.43	peak			
3		5591.667	49.27	-1.77	47.50	74.00	-26.50	peak			
4	*	2402.000	74.24	10.32	84.56	94.00	-9.44	AVG	100	324	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N:LS-3038


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	86.25	10.36	96.61	114.00	-17.39	peak			
2		4882.000	40.38	7.89	48.27	74.00	-25.73	peak			
3		5608.333	48.89	-1.76	47.13	74.00	-26.87	peak			
4	*	2441.000	77.06	10.36	87.42	94.00	-6.58	AVG	100	154	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N:LS-3038


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	86.47	10.36	96.83	114.00	-17.17	peak			
2		4882.000	41.31	7.89	49.20	74.00	-24.80	peak			
3		5550.000	49.69	-1.79	47.90	74.00	-26.10	peak			
4	*	2441.000	77.22	10.36	87.58	94.00	-6.42	AVG	100	339	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:

M/N:LS-3038


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	85.93	10.41	96.34	114.00	-17.66	peak			
2		4960.000	41.51	8.09	49.60	74.00	-24.40	peak			
3		5475.000	49.87	-1.31	48.56	74.00	-25.44	peak			
4	*	2480.000	76.75	10.41	87.16	94.00	-6.84	AVG	100	161	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: *Horizontal* Temperature: 22.7
Limit: FCC Class B 3M Radiation above 1GHz(PK)- Power: Humidity: 53.6 %
EUT: PROFESSIONAL ACTIVE BT SPEAKER Distance:
M/N: LS-3038
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	85.97	10.41	96.38	114.00	-17.62	peak			
2		4960.000	41.01	8.09	49.10	74.00	-24.90	peak			
3		5375.000	47.41	0.69	48.10	74.00	-25.90	peak			
4	*	2480.000	76.83	10.41	87.24	94.00	-6.76	AVG	100	352	

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	83.19	10.32	93.51	114	-20.49	Horizontal
2402	83.30	10.32	93.62	114	-20.38	Vertical
2441	86.25	10.36	96.61	114	-17.39	Horizontal
2441	86.47	10.36	96.83	114	-17.17	Vertical
2480	85.93	10.41	96.34	114	-17.66	Horizontal
2480	85.97	10.41	96.38	114	-17.62	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	74.01	10.32	84.33	94	-9.67	Horizontal
2402	74.24	10.32	84.56	94	-9.44	Vertical
2441	77.06	10.36	87.42	94	-6.58	Horizontal
2441	77.22	10.36	87.58	94	-6.42	Vertical
2480	76.75	10.41	87.16	94	-6.84	Horizontal
2480	76.83	10.41	87.24	94	-6.76	Vertical

2Mbps Result:**Peak value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	82.72	10.32	93.04	114	-20.96	Horizontal
2402	82.73	10.32	93.05	114	-20.95	Vertical
2441	85.75	10.36	96.11	114	-17.89	Horizontal
2441	85.79	10.36	96.15	114	-17.85	Vertical
2480	85.38	10.41	95.79	114	-18.21	Horizontal
2480	85.40	10.41	95.81	114	-18.19	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	73.54	10.32	83.86	94	-10.14	Horizontal
2402	73.60	10.32	83.92	94	-10.08	Vertical
2441	76.58	10.36	86.94	94	-7.06	Horizontal
2441	76.63	10.36	86.99	94	-7.01	Vertical
2480	76.28	10.41	86.69	94	-7.31	Horizontal
2480	76.31	10.41	86.72	94	-7.28	Vertical

3Mbps Result:**Peak value**

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	82.23	10.32	92.55	114	-21.45	Horizontal
2402	82.24	10.32	92.56	114	-21.44	Vertical
2441	85.28	10.36	95.64	114	-18.36	Horizontal
2441	85.30	10.36	95.66	114	-18.34	Vertical
2480	84.91	10.41	95.32	114	-18.68	Horizontal
2480	84.95	10.41	95.36	114	-18.64	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	73.15	10.32	83.47	94	-10.53	Horizontal
2402	73.18	10.32	83.50	94	-10.50	Vertical
2441	76.11	10.36	86.47	94	-7.53	Horizontal
2441	76.16	10.36	86.52	94	-7.48	Vertical
2480	75.83	10.41	86.24	94	-7.76	Horizontal
2480	75.87	10.41	86.28	94	-7.72	Vertical


10. BAND EDGE EMISSION

10.1. MEASUREMENT PROCEDURE

- 1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission

10.2 TEST SETUP

RADIATED EMISSION TEST SETUP




10.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1	Polarization: Horizontal	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHz(PK)	Power:	Humidity: 60 %
EUT: PROFESSIONAL ACTIVE BT SPEAKER	Distance:	
M/N:LS-3038		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.000	83.22	10.32	93.54	74.00	19.54	peak			
2		2390.000	31.00	10.31	41.31	74.00	-32.69	peak			
3		2366.050	31.63	10.28	41.91	74.00	-32.09	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1

Polarization: Vertical

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHz(PK)

Power:

Humidity: 60 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:


M/N:LS-3038

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.000	83.09	10.32	93.41	74.00	19.41	peak			
2		2390.000	32.71	10.31	43.02	74.00	-30.98	peak			
3		2342.133	32.54	10.26	42.80	74.00	-31.20	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHz(PK)

Power:

Humidity: 60 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

Distance:


M/N: LS-3038

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.55	10.41	95.96	74.00	21.96	peak			
2		2483.500	32.19	10.41	42.60	74.00	-31.40	peak			
3		2494.500	30.03	10.42	40.45	74.00	-33.55	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHz(PK) Power: Humidity: 60 %
EUT: PROFESSIONAL ACTIVE BT SPEAKER Distance:
M/N: LS-3038
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.82	10.41	96.23	74.00	22.23	peak			
2		2483.530	31.68	10.41	42.09	74.00	-31.91	peak			
3		2494.170	31.97	10.42	42.39	74.00	-31.61	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


Hopping on mode and Hopping off mode have been tested, but only worst case reported.

11. 20DB BANDWIDTH

11.1. MEASUREMENT PROCEDURE

1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
3. Set SPA Trace 1 Max hold, then View.

11.2. TEST SET-UP




11.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	0.934	1.110	PASS
	Middle Channel	0.930	1.076	PASS
	High Channel	0.923	1.087	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.211	1.353	PASS
	Middle Channel	1.210	1.334	PASS
	High Channel	1.209	1.364	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.201	1.371	PASS
	Middle Channel	1.207	1.344	PASS
	High Channel	1.211	1.349	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



12. FCC LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received AC 120V voltage by adapter which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

By adapter(worst case)

FOR BR/EDR

Line Conducted Emission Test Line 1-L



Site: Conduction

Phase: L1

Temperature: 23.9

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 55.2 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

M/N:LS-3038

Mode:BT Link

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1965	43.33		26.56	10.21	53.54		36.77	63.75	53.75	-10.21	-16.98	P	
2	0.2459	37.58		21.58	10.27	47.85		31.85	61.89	51.89	-14.04	-20.04	P	
3	0.6058	33.69		16.56	10.31	44.00		26.87	56.00	46.00	-12.00	-19.13	P	
4	3.0659	32.82		14.93	10.54	43.36		25.47	56.00	46.00	-12.64	-20.53	P	
5	16.0731	28.61		9.59	10.11	38.72		19.70	60.00	50.00	-21.28	-30.30	P	
6	20.0180	34.78		14.06	10.11	44.89		24.17	60.00	50.00	-15.11	-25.83	P	

Line Conducted Emission Test Line 2-N



Site: Conduction

Phase: **N**

Temperature: 23.9

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 55.2 %

EUT: PROFESSIONAL ACTIVE BT SPEAKER

M/N:LS-3038


Mode:BT Link

Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1621	38.91		25.87	10.17	49.08		36.04	65.35	55.35	-16.27	-19.31	P	
2	0.2589	34.60		15.90	10.27	44.87		26.17	61.46	51.46	-16.59	-25.29	P	
3	0.6018	34.81		18.01	10.31	45.12		28.32	56.00	46.00	-10.88	-17.68	P	
4	1.3580	34.19		12.73	10.38	44.57		23.11	56.00	46.00	-11.43	-22.89	P	
5	3.8620	34.25		19.42	10.45	44.70		29.87	56.00	46.00	-11.30	-16.13	P	
6	8.2698	28.24		10.60	10.34	38.58		20.94	60.00	50.00	-21.42	-29.06	P	



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP







APPENDIX B: PHOTOGRAPHS OF EUT


WHOLE VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



VIEW OF EUT (PORT)-1




VIEW OF EUT (PORT)-2




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




OPEN VIEW OF EUT-3




OPEN VIEW OF EUT-4




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4




INTERNAL VIEW OF EUT-5




INTERNAL VIEW OF EUT-6




INTERNAL VIEW OF EUT-7




INTERNAL VIEW OF EUT-8




INTERNAL VIEW OF EUT-9




INTERNAL VIEW OF EUT-10




INTERNAL VIEW OF EUT-11




INTERNAL VIEW OF EUT-12




INTERNAL VIEW OF EUT-13




INTERNAL VIEW OF EUT-14




INTERNAL VIEW OF EUT-15




INTERNAL VIEW OF EUT-16




INTERNAL VIEW OF EUT-17



INTERNAL VIEW OF EUT-18



INTERNAL VIEW OF EUT-19



----END OF REPORT----