

MPE Calculation : Bluetooth

RF function or Mode	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
Bluetooth(1Mbps)	2402.00	~	2480.00	1.50	-0.05	1.45	1.397	0.0003	1.000
Bluetooth(2Mbps)	2402.00	~	2480.00	0.00	-0.05	-0.05	0.989	0.0002	1.000
		~							
		~							
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 1.397 / (4 \times 20^2 \times \pi) \\
 &= 0.0003 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenn

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averageing time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC

MPE Calculation : LTE, CDMA

RF function or Mode	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirment (mW/cm ²)
LTE(Band 13)	776.00	~	787.00	25.00	0.42	25.42	348.338	0.0693	0.517
LTE(Band 4)	1710.70	~	1755.00	25.00	-0.65	24.35	272.271	0.0542	1.000
CDMA(Band 850)	824.70	~	848.31	26.00	1.51	27.51	563.638	0.1122	0.549
CDMA(Band 1900)	1851.25	~	1908.75	26.00	3.13	29.13	818.465	0.1629	1.000
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 348.338 / (4 \times 20^2 \times \pi) \\
 &= 0.0693 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenn

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averageing time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC

RF Exposure Compliance for simultaneous operations

▪ Configurations for simultaneous operations

- Configuration 1: BT + LTE, CDMA Module

▪ Configurations for simultaneous operations(LTE, CDMA Module)

- LTE Band 13 + CDMA 850(Cellular)
- LTE Band 4 + CDMA 850(Cellular)
- LTE Band 4 + CDMA 1900(PCS)
- LTE Band 13 + CDMA 1900(PCS)

Note: Above configuration was declared from applicant.

▪ Configurations for simultaneous operation

RF function or mode	BT	LTE		CDMA		-		Σ of MPE ratios
Band	2.4GHz	Band 13	Band 4	Cellular	PCS	-	-	
Power Density (mW/cm ²)	0.0003	0.0693	0.0542	0.1122	0.1629			
Requirement (mW/cm ²)	1.0000	0.5170	1.0000	0.5490	1.0000			
MPE ratio (Power Density/Requirement)	0.0003	0.1340	0.0542	0.2044	0.1629			
Configuration 1 (MPE ratio)	0.0003	0.1340		0.2044				0.3387
	0.0003		0.0542	0.2044				0.2589
	0.0003		0.0542		0.1629			0.2174
	0.0003	0.1340			0.1629			0.2972

Note: The maximum power density in each RF function was used for above table.

- Requirement = Σ of MPE ratios ≤ 1

Conclusion : The exposure condition of this device is compliant with FCC rules.