

# Beijing Roborock Technology Co., Ltd.

## MPE ASSESSMENT REPORT

**Report Type:**

FCC MPE assessment report

**Model:**

X170RR

**REPORT NUMBER:**

210600064SHA-002

**ISSUE DATE:**

July 30, 2021

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



## TEST REPORT

**Applicant:** Beijing Roborock Technology Co., Ltd.  
Floor 6, Suite 6016, 6017, 6018, Building C, Kangjian Baosheng  
Plaza, No.8 Heiquan Road, Haidian District, Beijing, P.R. China

**Manufacturer:** Beijing Roborock Technology Co., Ltd.  
Floor 6, Suite 6016, 6017, 6018, Building C, Kangjian Baosheng  
Plaza, No.8 Heiquan Road, Haidian District, Beijing, P.R. China

**FCC ID:** 2AN2O-GTW01

## SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06  
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

## PREPARED BY:

## REVIEWED BY:

---

Project Engineer  
Sky Yang

---

Reviewer  
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

Report No.	Version	Description	Issued Date
210600064SHA-002	Rev. 01	Initial issue of report	July 30, 2021

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	Robotic Vacuum Cleaner
Type/Model:	X170RR
Description of EUT:	The EUT is an automatic battery-operated cleaner which contains a 2.4GHz WIFI module. 2.4GHz WIFI module: F89FTSM13
Rating:	Rated input: 20VDC, 1.8A; Docking station: Input:100-240VAC,50-60Hz, 42W; Output: 20VDC, 1.8A
EUT type:	<input type="checkbox"/> Table top <input checked="" type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	June 04, 2021
Date of test:	June 07, 2021 ~ June 21, 2021

### 1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20), IEEE 802.11n(HT40)
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20) 2422MHz to 2452MHz for IEEE 802.11n(HT40)
Type of Modulation:	IEEE 802.11b: CCK, QPSK, BPSK IEEE 802.11g: OFDM IEEE 802.11n-HT20: OFDM IEEE 802.11n-HT40: OFDM
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20) 7 Channels for 802.11n(HT40)
Channel Separation:	5 MHz
Antenna:	The EUT will use two types antenna. This two types antenna can be used with WIFI module separately, so the EUT has two WIFI configurations.

Antenna information:			
No.	Antenna Type	Gain (dBi)	Note
Antenna 1	Internal PCB Antenna	1.43	-
Alternative Antenna2:	Internal PCB Antenna	2.02	-

### 1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 MPE Assessment

Test result: Pass

### 2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$**

## TEST REPORT

### 2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = P / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = Radiated transmit power in mW

R = distance (cm)

As we can see from the test report 210600064SHA-001:

The maximum radiated power = 20.54dBm = 113.24 mW;

Here R is chosen to be 20cm,

Frequency Range	Power		R	S	Limits
(MHz)	dBm	mW	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2412 - 2462	20.54	113.24	20	0.0225	1

## Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

\*\*\*\*\* END \*\*\*\*\*