

MPE TEST REPORT

Applicant Quectel Wireless Solutions Co., Ltd.
FCC ID XMR2023BG773AGL
Product LTE Module
Brand Quectel
Model BG773A-GL
Report No. R2211A1099-M1
Issue Date March 21, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Wei Fangying

Fan Guangchang

Prepared by: Wei Fangying

Approved by: Fan Guangchang

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

| | | |
|------|--|----|
| 1 | Test Laboratory..... | 3 |
| 1.1 | Notes of the Test Report | 3 |
| 1.2. | Test facility | 3 |
| 1.3 | Testing Location..... | 3 |
| 1.4 | Laboratory Environment..... | 4 |
| 2 | Description of Equipment under Test..... | 5 |
| 3 | Maximum conducted output power (measured) and antenna Gain | 7 |
| 4 | Test Result | 8 |
| | ANNEX A: The EUT Appearance..... | 12 |
| | ANNEX B: Product Change Description (Variant 1)..... | 13 |
| | ANNEX C: Product Change Description (Variant 2) | 14 |

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Fan Guangchang
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: fanguangchang@ta-shanghai.com

1.4 Laboratory Environment

| | |
|---|---------------------------|
| Temperature | Min. = 18°C, Max. = 25 °C |
| Relative humidity | Min. = 30%, Max. = 70% |
| Ground system resistance | < 0.5 Ω |
| Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards. | |

2 Description of Equipment under Test

Client Information

| | |
|-----------------------------|--|
| Applicant | Quectel Wireless Solutions Co., Ltd |
| Applicant address | Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233 China |
| Manufacturer | Quectel Wireless Solutions Co., Ltd |
| Manufacturer address | Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233 China |

General Technologies

| | |
|---|---------------------------|
| Model | BG773A-GL |
| IMEI | Original: 863593050006733 |
| Hardware Version | R1.1 |
| Software Version | BG773AGLAAR02A01 |
| Date of Testing: | May 19, 2021 |
| Date of Sample Received: | April 16, 2021 |
| <p>Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.</p> <p>2. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.</p> | |

BG773A-GL (Report No.: R2211A1099-M1) is a variant model (Variant 2) of BG770A-GL (Report No.: R2207A0656-M1V1). Test values all duplicated from Original for variant. There is no test for variant in this report.

The detailed product change description please refers to following table:

| Module | BG770A-GL | BG773A-GL |
|------------------------|---|---|
| BB Chip | ALT1250 | ALT1250 |
| Category | Cat M1 /NB2/GNSS | Cat M1 /NB2/GNSS |
| Frequency Bands | Cat M1 LTE-HD-FDD: B2/B4/B5 /B12/B13/B25/B26/B66 Cat NB2 LTE-HD-FDD: B2/B4/B5/B12/B13/B17/ B25/B66 | Cat M1 LTE-HD-FDD: B2/B4/B5 /B12/B13/B25/B26/B66 Cat NB2 LTE-HD-FDD: B2/B4/B5/B12/B13/B17/ B25/B66 |
| GNSS | GPS, GLONASS | GPS, GLONASS |
| iSIM | N/A | Supported |

The detailed product change description please refers to the ***Difference Declaration Letter (Variant 2)***.

BG770A-GL (Report No.: R2207A0656-M1V1) is a variant model (Variant 1) of BG770A-GL (Report No.: R2104A0331-M1). Test values all duplicated from Original for variant. There is no test for variant in this report. BG770A-GL supports from Cat NB1 (3GPP R13) to Cat NB2 (3GPP R14) only by FW updating, the hardware remains the same.

The detailed product change description please refers to following table:

| Module | BG770A-GL (Cat NB1) | BG770A-GL (Cat NB2) |
|-----------------|---|---|
| Category | Cat M1 & NB1 | Cat M1 & NB2 |
| Frequency Bands | Cat M1 LTE-HD-FDD: B2/B4/B5 /B12/B13/B25/B26/B66 Cat NB1 LTE-HD-FDD: B2/B4/B5/B12/B13/B17/ B25/B66 | Cat M1 LTE-HD-FDD: B2/B4/B5 /B12/B13/B25/B26/B66 Cat NB2 LTE-HD-FDD: B2/B4/B5/B12/B13/B17/ B25/B66 |
| Others | The same | |

The detailed product change description please refers to the *Difference Declaration Letter (Variant 1)*.

3 Maximum conducted output power (measured) and antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)=10^(antenna gain/10)

| Band | Maximum Conducted Output Power (dBm) | |
|------------------|--------------------------------------|---------|
| | (dBm) | (mW) |
| LTE eMTC Band 2 | 25.70 | 371.535 |
| LTE eMTC Band 4 | 25.70 | 371.535 |
| LTE eMTC Band 5 | 25.70 | 371.535 |
| LTE eMTC Band 12 | 25.70 | 371.535 |
| LTE eMTC Band 13 | 25.70 | 371.535 |
| LTE eMTC Band 25 | 25.70 | 371.535 |
| LTE eMTC Band 26 | 25.70 | 371.535 |
| LTE eMTC Band 66 | 25.70 | 371.535 |
| NB-IoT Band 2 | 25.70 | 371.535 |
| NB-IoT Band 4 | 25.70 | 371.535 |
| NB-IoT Band 5 | 25.70 | 371.535 |
| NB-IoT Band 12 | 25.70 | 371.535 |
| NB-IoT Band 13 | 25.70 | 371.535 |
| NB-IoT Band 17 | 25.70 | 371.535 |
| NB-IoT Band 25 | 25.70 | 371.535 |
| NB-IoT Band 66 | 25.70 | 371.535 |

4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
|---|-------------------------------------|-------------------------------------|--|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | 6 |
| 3-30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | f/300 | 6 |
| 1500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | f/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

Note1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is f/1500, for 1500~100,000MHz is 1.0. So

| Band | The maximum permissible exposure (mW/cm ²) |
|------------------|--|
| LTE eMTC Band 2 | 1.000 |
| LTE eMTC Band 4 | 1.000 |
| LTE eMTC Band 5 | 0.566 |
| LTE eMTC Band 12 | 0.477 |
| LTE eMTC Band 13 | 0.525 |
| LTE eMTC Band 25 | 1.000 |
| LTE eMTC Band 26 | 0.566 |
| LTE eMTC Band 66 | 1.000 |
| NB-IoT Band 2 | 1.000 |
| NB-IoT Band 4 | 1.000 |
| NB-IoT Band 5 | 0.566 |
| NB-IoT Band 12 | 0.477 |
| NB-IoT Band 13 | 0.525 |
| NB-IoT Band 17 | 0.469 |
| NB-IoT Band 25 | 1.000 |
| NB-IoT Band 66 | 1.000 |

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

| Band | Maximum Conducted Output Power (dBm) | EIRP limit (dBm) | Margin1 (dB) | Power density Limit | | Margin2 (dB) | Final Margin (dB) | Gain (dBi) |
|------------------|--------------------------------------|------------------|--------------|-----------------------|--------|--------------|-------------------|------------|
| | | | | (mW/cm ²) | (dBm) | | | |
| LTE eMTC Band 2 | 25.70 | 33.000 | 7.300 | 1.000 | 37.013 | 11.313 | 7.300 | 7.300 |
| LTE eMTC Band 4 | 25.70 | 30.000 | 4.300 | 1.000 | 37.013 | 11.313 | 4.300 | 4.300 |
| LTE eMTC Band 5 | 25.70 | 38.450 | 12.750 | 0.566 | 34.541 | 8.841 | 8.841 | 8.841 |
| LTE eMTC Band 12 | 25.70 | 34.770 | 9.070 | 0.477 | 33.798 | 8.098 | 8.098 | 8.098 |
| LTE eMTC Band 13 | 25.70 | 34.770 | 9.070 | 0.525 | 34.214 | 8.514 | 8.514 | 8.514 |
| LTE eMTC Band 25 | 25.70 | 33.000 | 7.300 | 1.000 | 37.013 | 11.313 | 7.300 | 7.300 |
| LTE eMTC Band 26 | 25.70 | 38.450 | 12.750 | 0.566 | 34.541 | 8.841 | 8.841 | 8.841 |
| LTE eMTC Band 66 | 25.70 | 30.000 | 4.300 | 1.000 | 37.013 | 11.313 | 4.300 | 4.300 |
| NB-IoT Band 2 | 25.70 | 33.000 | 7.300 | 1.000 | 37.013 | 11.313 | 7.300 | 7.300 |
| NB-IoT Band 4 | 25.70 | 30.000 | 4.300 | 1.000 | 37.013 | 11.313 | 4.300 | 4.300 |
| NB-IoT Band 5 | 25.70 | 38.450 | 12.750 | 0.566 | 34.541 | 8.841 | 8.841 | 8.841 |
| NB-IoT Band 12 | 25.70 | 34.770 | 9.070 | 0.477 | 33.798 | 8.098 | 8.098 | 8.098 |
| NB-IoT Band 13 | 25.70 | 34.770 | 9.070 | 0.525 | 34.214 | 8.514 | 8.514 | 8.514 |
| NB-IoT Band 17 | 25.70 | 34.770 | 9.070 | 0.469 | 33.724 | 8.024 | 8.024 | 8.024 |
| NB-IoT Band 25 | 25.70 | 33.000 | 7.300 | 1.000 | 37.013 | 11.313 | 7.300 | 7.300 |
| NB-IoT Band 66 | 25.70 | 30.000 | 4.300 | 1.000 | 37.013 | 11.313 | 4.300 | 4.300 |

Note: 1. The Maximum allowed antenna gain per Band should be less than or equal to the **Final Margin** which is the allowable maximum gain value to comply with limits for maximum permissible exposure (MPE).

2. The Final Margin is determined and selected to the worst-case of Margin1 and Margin2.

3. Margin1=EIRP Limit(dBm)-Maximum Conducted Power (dBm). EIRP limit reference standard part22/part24/part27 for each band, EIRP = ERP + 2.15 (dB).

4. Margin2=Power density Limit(dBm)-Maximum Conducted Power (dBm). Power density Limit(dBm): The max. obtained by MPE with 20cm.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

| Band | PG (mW) | Test Result (mW/cm ²) | Limit Value (mW/cm ²) | Conclusion |
|---|----------|-----------------------------------|-----------------------------------|------------|
| LTE eMTC Band 2 | 1995.262 | 0.397 | 1.000 | Pass |
| LTE eMTC Band 4 | 1000.000 | 0.199 | 1.000 | Pass |
| LTE eMTC Band 5 | 2845.116 | 0.566 | 0.566 | Pass |
| LTE eMTC Band 12 | 2397.728 | 0.477 | 0.477 | Pass |
| LTE eMTC Band 13 | 2638.761 | 0.525 | 0.525 | Pass |
| LTE eMTC Band 25 | 1995.262 | 0.397 | 1.000 | Pass |
| LTE eMTC Band 26 | 2845.116 | 0.566 | 0.566 | Pass |
| LTE eMTC Band 66 | 1000.000 | 0.199 | 1.000 | Pass |
| NB-IoT Band 2 | 1995.262 | 0.397 | 1.000 | Pass |
| NB-IoT Band 4 | 1000.000 | 0.199 | 1.000 | Pass |
| NB-IoT Band 5 | 2845.116 | 0.566 | 0.566 | Pass |
| NB-IoT Band 12 | 2397.728 | 0.477 | 0.477 | Pass |
| NB-IoT Band 13 | 2638.761 | 0.525 | 0.525 | Pass |
| NB-IoT Band 17 | 2357.219 | 0.469 | 1.000 | Pass |
| NB-IoT Band 25 | 1995.262 | 0.397 | 1.000 | Pass |
| NB-IoT Band 66 | 1000.000 | 0.199 | 1.000 | Pass |
| Note: $R = 20\text{cm}$ $\pi = 3.1416$ | | | | |

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

*****END OF REPORT *****

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

ANNEX B: Product Change Description (Variant 1)

The Product Change Description are submitted separately.

ANNEX C: Product Change Description (Variant 2)

The Product Change Description are submitted separately.