

HYUNDAI CURITEL INC.

San 136-1, Ami-Ri, Bubal-Eub, Ichon-Si, Kyoungki-Do, 467-701, Korea

Date : February 20, 2004

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046, U.S.A.

Subject: **FCC E911 Requirements Per §22.921**

HYUNDAI CURITEL INC.

FCC ID : PP4TX-130CA

Part 22/24 Certification

Gentlemen :

Hyundai Curitel Inc. hereby certifies that the **tri-mode phone**(FCC ID : **PP4TX-130CA**), using the Automatic A/B Roaming - Intelligent Retry Method, meets the E911 requirements specified in Section 22.921 of the FCC Rules. This procedure recognizes when a "9-1-1" call is made and, at such time, will override any programming in the mobile unit that determines the handling of a non-911 call and permits the call to be handled by other analog carriers.

Should you have any questions or comments concerning the above, please contact the undersigned.

Sincerely Yours,



Eui-Kwon Park - Project Manager
R & D Center

HYUNDAI CURITEL INC.

San 136-1, Ami-Ri, Bubal-Eub, Ichon-Si, Kyoungki-Do, 467-701, Korea

Date : February 20, 2004

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046, U.S.A.

Subject: **User's Manual RF Exposure Warning Statement**

HYUNDAI CURITEL INC.
FCC ID: PP4TX-130CA
Part 22/24 Certification

Gentlemen:

Hyundai Curitel Inc. hereby confirms that the attached RF exposure warning page will be readily visible to the user, and will be placed at a prominent location in the front section of the user's manual.

Should you have any questions or comments concerning the above, please do not hesitate contact me.

Sincerely Yours,



Eui-Kwon Park - Project Manager
R & D Center

HYUNDAI CURITEL INC.

San 136-1, Ami-Ri, Bubal-Eub, Ichon-Si, Kyoungki-Do, 467-701, Korea

Date : February 20, 2004

**AFFIDAVIT FOR ESN PROTECTION
OF CELLULAR MOBILE TELEPHONES**

We hereby certify that the **tri-mode phone** (FCC ID: **PP4TX-130CA**) is so designed that it complies with all the requirements for ESN protection specified in Section 22.919 of the FCC Rules.

a) The transmitter in service has a unique ESN.

b) The ESN host component is permanently attached to a main circuit board of the mobile transmitter and the integrity of the unit operating software cannot be altered. The ESN is plated from fraudulent contact and tampering. The ESN is encoded using multiplication by a polynomial and the ESN data programmed in the memory with other information.

c) The ESN is factory-set and cannot be altered, transferred, removed or otherwise able to be manipulated. Cellular mobile equipment is specifically designed such that any attempt to remove, tamper with, or change the ESN chip, its logic system, or firmware originally programmed by the manufacturer will render the mobile transmitter inoperative.

Sincerely Yours,



Eui-Kwon Park - Project Manager
R & D Center