

TEST REPORT

Application No.: SZCR2106021345AT
Applicant: SKULLCANDY, INC.
Address of Applicant: 6301 N Landmark Dr Park City UT 84098, Utah United States of America
Manufacturer: SKULLCANDY, INC.
Address of Manufacturer: 6301 N Landmark Dr Park City UT 84098, Utah United States of America
Equipment Under Test (EUT):
EUT Name: Indy Fuel/IndyXT Fuel
Model No.: S11FW
Trade Mark:  Skullcandy
FCC ID: Y22- S11FW
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2021-06-02
Date of Test: 2021-06-13 to 2021-06-29
Date of Issue: 2021-07-02

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-07-02		Original

Authorized for issue by:				
		Benson Wang		
		Benson Wang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	6
4.4 TEST LOCATION	7
4.5 TEST FACILITY	7
4.6 DEVIATION FROM STANDARDS	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST	8
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	11
6.1 ANTENNA REQUIREMENT	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 RADIO SPECTRUM MATTER TEST RESULTS	12
7.1 CONDUCTED PEAK OUTPUT POWER	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	13
7.2 MINIMUM 6DB BANDWIDTH	14
7.2.1 E.U.T. Operation	14
7.2.2 Test Mode Description	14
7.2.3 Test Setup Diagram	14
7.2.4 Measurement Procedure and Data	14
7.3 POWER SPECTRUM DENSITY	15
7.3.1 E.U.T. Operation	15
7.3.2 Test Mode Description	15
7.3.3 Test Setup Diagram	15
7.3.4 Measurement Procedure and Data	15
7.4 CONDUCTED BAND EDGES MEASUREMENT	16
7.4.1 E.U.T. Operation	16
7.4.2 Test Mode Description	16
7.4.3 Test Setup Diagram	17
7.4.4 Measurement Procedure and Data	17
7.5 CONDUCTED SPURIOUS EMISSIONS	18
7.5.1 E.U.T. Operation	18
7.5.2 Test Mode Description	18
7.5.3 Test Setup Diagram	19



7.5.4	Measurement Procedure and Data.....	19
7.6	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	20
7.6.1	E.U.T. Operation.....	20
7.6.2	Test Mode Description.....	20
7.6.3	Test Setup Diagram.....	21
7.6.4	Measurement Procedure and Data.....	21
7.7	RADIATED SPURIOUS EMISSIONS BELOW 1GHz.....	38
7.7.1	E.U.T. Operation.....	38
7.7.2	Test Mode Description.....	38
7.7.3	Test Setup Diagram.....	39
7.7.4	Measurement Procedure and Data.....	39
7.8	RADIATED SPURIOUS EMISSIONS ABOVE 1GHz.....	52
7.8.1	E.U.T. Operation.....	52
7.8.2	Test Mode Description.....	52
7.8.3	Test Setup Diagram.....	52
7.8.4	Measurement Procedure and Data.....	53
8	TEST SETUP PHOTO.....	78
9	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	78
10	APPENDIX.....	79



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Left earbuds: Li-Ion Polymer Battery 3.7V 40mAh (Charge by travel case) Right earbuds: Li-Ion Polymer Battery 3.7V 40mAh (Charge by travel case) travel case with backup battery: Li-Ion Polymer Battery 3.7V 500mAh (Charged by Type-C port or WPC charging pad)
Cable(s):	Type-C cable: 13cm unshielded
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.2 Dual mode
Data Rate:	Support 1M and 2M/bit
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Integral Antenna
Antenna Gain:	Left earbuds: 3.11dBi; Right earbuds: 4.59dBi

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 4.5\text{dB}$
Radiated Spurious Emissions Above 1GHz	$\pm 4.8\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI (Member No. 1937)**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-17	2021-04-08	2022-04-07
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07



Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-17	2021-04-08	2022-04-07
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-17	2021-04-08	2022-04-07
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2021-02-01	2022-01-31
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2021-04-14	2024-04-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2020-11-14	2023-11-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2021-03-24	2022-03-23



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2021-03-27	2024-03-26
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2020-11-02	2021-11-01
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2019-08-08	2022-08-07
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2021-04-08	2022-04-07
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2020-08-14	2023-08-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2020-07-10	2021-07-09

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2021-02-01	2022-01-31
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2021-04-14	2024-04-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2020-09-15	2021-09-14
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2020-09-15	2021-09-14
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2021-03-30	2022-03-29



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, China SGS-CSTC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna: Left earbuds: 3.11dBi; Right earbuds: 4.59dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 22.2 °C Humidity: 41.1 % RH Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 21.1 °C Humidity: 48.7 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 21.1 °C Humidity: 48.7 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 22.2 °C Humidity: 41.1 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22.2 °C

Humidity: 41.1 % RH


Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C

Humidity: 54.3 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2374.919	4.32	28.85	40.41	58.25	51.01	74.00	-22.99	peak
2	2390.000	4.34	28.88	40.42	56.37	49.17	74.00	-24.83	peak
3	2402.000	4.36	28.90	40.43	111.64	104.47	74.00	30.47	peak



Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-L

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2381.470	4.33	28.86	40.42	58.60	51.37	74.00	-22.63 peak
2	2390.000	4.34	28.88	40.42	56.61	49.41	74.00	-24.59 peak
3	2402.000	4.36	28.90	40.43	104.47	97.30	74.00	23.30 peak



Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-L

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	110.04	103.12	74.00	29.12	peak
2 2483.500	4.49	29.07	40.47	56.93	50.02	74.00	-23.98	peak
3 2487.469	4.50	29.08	40.47	58.50	51.61	74.00	-22.39	peak



Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-L

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	103.26	96.34	74.00	22.34	peak
2 2483.500	4.49	29.07	40.47	56.61	49.70	74.00	-24.30	peak
3 2484.995	4.50	29.07	40.47	58.13	51.23	74.00	-22.77	peak



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-L 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2320.400	4.23	28.73	40.38	58.68	51.26	74.00	-22.74	peak
2	2390.000	4.34	28.88	40.42	56.34	49.14	74.00	-24.86	peak
3	2402.000	4.36	28.90	40.43	111.63	104.46	74.00	30.46	peak



Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-L 2M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2384.096	4.33	28.87	40.42	58.26	51.04	74.00	-22.96 peak
2	2390.000	4.34	28.88	40.42	56.45	49.25	74.00	-24.75 peak
3	2402.000	4.36	28.90	40.43	104.55	97.38	74.00	23.38 peak



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-L 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	110.01	103.09	74.00	29.09	peak
2 2483.500	4.49	29.07	40.47	59.83	52.92	74.00	-21.08	peak
3 2483.996	4.49	29.07	40.47	59.77	52.86	74.00	-21.14	peak



Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-L 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	103.27	96.35	74.00	22.35	peak
2 2483.500	4.49	29.07	40.47	57.54	50.63	74.00	-23.37	peak
3 2485.869	4.50	29.07	40.47	58.46	51.56	74.00	-22.44	peak



Test Mode: 09; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2356.173	4.29	28.81	40.40	58.11	50.81	74.00	-23.19	peak
2	2390.000	4.34	28.88	40.42	57.52	50.32	74.00	-23.68	peak
3	2402.000	4.36	28.90	40.43	107.70	100.53	74.00	26.53	peak



Test Mode: 09; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-R

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2326.998	4.24	28.75	40.39	58.29	50.89	74.00	-23.11 peak
2 2390.000	4.34	28.88	40.42	56.92	49.72	74.00	-24.28 peak
3 . 2402.000	4.36	28.90	40.43	101.89	94.72	74.00	20.72 peak



Test Mode: 09; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-R

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	106.17	99.25	74.00	25.25	peak
2 2483.500	4.49	29.07	40.47	57.87	50.96	74.00	-23.04	peak
3 2492.398	4.51	29.08	40.47	58.86	51.98	74.00	-22.02	peak



Test Mode: 09; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-R

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	101.11	94.19	74.00	20.19	peak
2 2483.500	4.49	29.07	40.47	56.58	49.67	74.00	-24.33	peak
3 2492.899	4.51	29.09	40.47	58.01	51.14	74.00	-22.86	peak



Test Mode: 10; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-R 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2313.233	4.22	28.72	40.38	58.06	50.62	74.00	-23.38	peak
2	2390.000	4.34	28.88	40.42	56.64	49.44	74.00	-24.56	peak
3	2402.000	4.36	28.90	40.43	107.74	100.57	74.00	26.57	peak



Test Mode: 10; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 Band edge
Note : BLE-R 2M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2382.379	4.33	28.86	40.42	58.31	51.08	74.00	-22.92 peak
2	2390.000	4.34	28.88	40.42	56.94	49.74	74.00	-24.26 peak
3	2402.000	4.36	28.90	40.43	101.93	94.76	74.00	20.76 peak



Test Mode: 10; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-R 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	106.22	99.30	74.00	25.30	peak
2 2483.500	4.49	29.07	40.47	58.56	51.65	74.00	-22.35	peak
3 2494.278	4.51	29.09	40.47	59.01	52.14	74.00	-21.86	peak



Test Mode: 10; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 Band edge
Note : BLE-R 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	101.19	94.27	74.00	20.27	peak
2 2483.500	4.49	29.07	40.47	56.74	49.83	74.00	-24.17	peak
3 2498.518	4.52	29.10	40.47	58.71	51.86	74.00	-22.14	peak



7.7 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Measurement Distance: 10m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C


Humidity: 50.1 % RH

Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, CSTC Standards Technical Services Co., Ltd. Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:High



Condition: 10m HORIZONTAL


Job No. : 21345AT

Test Mode: 04

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	44.431	20.34	32.50	0.94	26.69	15.47	29.50	-14.03	QP
2	53.882	20.09	32.49	1.00	26.56	15.16	29.50	-14.34	QP
3	149.486	20.18	32.42	1.48	26.94	16.18	33.00	-16.82	QP
4	299.316	19.49	32.40	2.06	28.19	17.34	35.60	-18.26	QP
5	582.743	25.41	32.30	3.08	27.06	23.25	35.60	-12.35	QP
6 pp	851.035	28.71	31.84	3.37	27.65	27.89	35.60	-7.71	QP



Test Mode: 04; Polarity: Vertical; Modulation: GFSK; Channel: High



Condition: 10m VERTICAL

Job No. : 21345AT

Test Mode: 04

	Freq	Ant Factor	Preamp Factor	Cable Loss	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	43.506	20.32	32.50	0.94	26.09	14.85	29.50	-14.65	QP
2	52.391	19.94	32.50	0.98	26.24	14.66	29.50	-14.84	QP
3	138.874	19.55	32.43	1.44	27.32	15.88	33.00	-17.12	QP
4	269.428	18.94	32.40	2.00	27.51	16.05	35.60	-19.55	QP
5	510.044	24.20	32.30	2.85	26.65	21.40	35.60	-14.20	QP
6 pp	922.516	29.80	31.39	3.50	26.20	28.11	35.60	-7.49	QP



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L_3 : Level @ 3m distance. Unit: $\mu\text{V/m}$;

L_{10} : Level @ 10m distance. Unit: $\mu\text{V/m}$;

D_3 : 3m distance. Unit: m


D_{10} : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m ($\mu\text{V/m}$)	Level @ 3m ($\mu\text{V/m}$)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
43.506	14.85	5.53	18.42	25.31	40.00	-14.69	V
52.391	14.66	5.41	18.03	25.12	40.00	-14.88	V
138.874	15.88	6.22	20.74	26.34	43.50	-17.16	V
269.428	16.05	6.35	21.15	26.51	46.00	-19.49	V
510.044	21.40	11.75	39.16	31.86	46.00	-14.14	V
922.516	28.11	25.44	84.80	38.57	46.00	-7.43	V
44.431	15.47	5.94	19.79	25.93	40.00	-14.07	H
53.882	15.16	5.73	19.09	25.62	40.00	-14.38	H
149.486	16.18	6.44	21.47	26.64	43.50	-16.86	H
299.316	17.34	7.36	24.54	27.80	46.00	-18.20	H
582.743	23.25	14.54	48.46	33.71	46.00	-12.29	H
851.035	27.89	24.80	82.68	38.35	46.00	-7.65	H



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High



Condition: 10m HORIZONTAL


Job No. : 21345AT

Test Mode: 05

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	37.945	19.99	32.50	0.92	26.86	15.27	29.50	-14.23	QP
2	50.232	20.25	32.50	0.96	26.40	15.11	29.50	-14.39	QP
3	141.826	19.79	32.42	1.46	27.33	16.16	33.00	-16.84	QP
4	270.375	19.01	32.40	2.00	28.55	17.16	35.60	-18.44	QP
5	508.258	24.17	32.30	2.84	28.02	22.73	35.60	-12.87	QP
6 pp	785.093	28.45	32.13	3.33	28.29	27.94	35.60	-7.66	QP



Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: High



Condition: 10m VERTICAL

Job No. : 21345AT

Test Mode: 05

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	38.346	20.00	32.50	0.92	27.31	15.73	29.50	-13.77	QP
2	45.217	20.42	32.50	0.95	27.23	16.10	29.50	-13.40	QP
3	145.351	19.97	32.42	1.47	27.78	16.80	33.00	-16.20	QP
4	324.456	20.39	32.37	2.21	27.68	17.91	35.60	-17.69	QP
5	578.670	25.27	32.30	3.07	29.19	25.23	35.60	-10.37	QP
6 pp	958.794	29.89	31.06	3.58	27.58	29.99	35.60	-5.61	QP



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m


D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
38.346	15.73	6.12	20.39	26.19	40.00	-13.81	V
45.217	16.10	6.38	21.28	26.56	40.00	-13.44	V
145.351	16.80	6.92	23.06	27.26	43.50	-16.24	V
324.456	17.91	7.86	26.20	28.37	46.00	-17.63	V
578.670	25.23	18.26	60.87	35.69	46.00	-10.31	V
958.794	29.99	31.59	105.29	40.45	46.00	-5.55	V
37.945	15.27	5.80	19.34	25.73	40.00	-14.27	H
50.232	15.11	5.70	18.98	25.57	40.00	-14.43	H
141.826	16.16	6.43	21.42	26.62	43.50	-16.88	H
270.375	17.16	7.21	24.04	27.62	46.00	-18.38	H
508.258	22.73	13.69	45.64	33.19	46.00	-12.81	H
785.093	27.94	24.95	83.15	38.40	46.00	-7.60	H



Test Mode: 09; Polarity: Horizontal; Modulation:GFSK; Channel:High



Condition: 10m HORIZONTAL


Job No. : 21345AT

Test Mode: 09

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	37.945	19.99	32.50	0.92	26.79	15.20	29.50	-14.30	QP
2	58.613	19.51	32.49	1.04	27.95	16.01	29.50	-13.49	QP
3	144.842	19.95	32.42	1.47	27.05	16.05	33.00	-16.95	QP
4	375.939	21.38	32.32	2.35	27.45	18.86	35.60	-16.74	QP
5 pp	605.659	26.33	32.30	3.10	26.75	23.88	35.60	-11.72	QP
6	972.337	30.09	30.94	3.63	26.81	29.59	44.40	-14.81	QP



Test Mode: 09; Polarity: Vertical; Modulation: GFSK; Channel: High



Condition: 10m VERTICAL

Job No. : 21345AT

Test Mode: 09

	Ant Freq	Preamp Factor	Cable Factor	Cable Loss	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	42.600	20.37	32.50	0.94	26.07	14.88	29.50	-14.62	QP
2	50.586	20.18	32.50	0.97	26.71	15.36	29.50	-14.14	QP
3	140.835	19.74	32.43	1.45	27.22	15.98	33.00	-17.02	QP
4	340.782	20.50	32.36	2.31	27.22	17.67	35.60	-17.93	QP
5	603.539	26.24	32.30	3.09	27.48	24.51	35.60	-11.09	QP
6 pp	935.546	29.80	31.27	3.52	27.03	29.08	35.60	-6.52	QP



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m


D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
42.600	14.88	5.55	18.49	25.34	40.00	-14.66	V
50.586	15.36	5.86	19.54	25.82	40.00	-14.18	V
140.835	15.98	6.30	20.98	26.44	43.50	-17.06	V
340.782	17.67	7.65	25.49	28.13	46.00	-17.87	V
603.539	24.51	16.81	56.02	34.97	46.00	-11.03	V
935.546	29.08	28.44	94.82	39.54	46.00	-6.46	V
37.945	15.20	5.75	19.18	25.66	40.00	-14.34	H
58.613	16.01	6.32	21.06	26.47	40.00	-13.53	H
144.842	16.05	6.35	21.15	26.51	43.50	-16.99	H
375.939	18.86	8.77	29.23	29.32	46.00	-16.68	H
605.659	23.88	15.63	52.10	34.34	46.00	-11.66	H
972.337	29.59	30.16	100.55	40.05	54.00	-13.95	H



Test Mode: 10; Polarity: Horizontal; Modulation:GFSK; Channel:High



Condition: 10m HORIZONTAL


Job No. : 21345AT

Test Mode: 10

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	42.900	20.35	32.50	0.94	25.41	14.20	29.50	-15.30	QP
2	54.452	19.96	32.49	1.00	25.38	13.85	29.50	-15.65	QP
3	163.182	19.64	32.41	1.52	27.11	15.86	33.00	-17.14	QP
4	642.861	26.36	32.30	3.14	27.57	24.77	35.60	-10.83	QP
5 pp	726.805	27.77	32.24	3.32	27.43	26.28	35.60	-9.32	QP
6	972.337	30.09	30.94	3.63	25.81	28.59	44.40	-15.81	QP



Test Mode: 10; Polarity: Vertical; Modulation:GFSK; Channel:High



Condition: 10m VERTICAL

Job No. : 21345AT

Test Mode: 10

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	36.895	19.73	32.50	0.91	28.13	16.27	29.50	-13.23	QP
2	43.966	20.30	32.50	0.94	27.05	15.79	29.50	-13.71	QP
3	141.330	19.77	32.43	1.45	27.66	16.45	33.00	-16.55	QP
4	463.970	23.64	32.30	2.67	28.28	22.29	35.60	-13.31	QP
5	609.922	26.50	32.30	3.10	27.35	24.65	35.60	-10.95	QP
6 pp	929.008	29.80	31.33	3.51	27.19	29.17	35.60	-6.43	QP



The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
36.895	16.27	6.51	21.70	26.73	40.00	-13.27	V
43.966	15.79	6.16	20.53	26.25	40.00	-13.75	V
141.330	16.45	6.65	22.15	26.91	43.50	-16.59	V
463.970	22.29	13.02	43.39	32.75	46.00	-13.25	V
609.922	24.65	17.08	56.93	35.11	46.00	-10.89	V
929.008	29.17	28.74	95.80	39.63	46.00	-6.37	V
42.900	14.20	5.13	17.10	24.66	40.00	-15.34	H
54.452	13.85	4.93	16.42	24.31	40.00	-15.69	H
163.182	15.86	6.21	20.70	26.32	43.50	-17.18	H
642.861	24.77	17.32	57.73	35.23	46.00	-10.77	H
726.805	26.28	20.61	68.69	36.74	46.00	-9.26	H
972.337	28.59	26.88	89.61	39.05	54.00	-14.95	H



7.8 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C


Humidity: 54.7 % RH

Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	09	TX mode(1Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	10	TX mode(2Mbps)(Right earubds)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1620.431	3.36	26.32	40.02	45.66	35.32	74.00	-38.68	peak
2	4254.921	6.53	32.81	41.65	48.97	46.66	74.00	-27.34	peak
3	4804.000	7.10	33.62	42.14	47.51	46.09	74.00	-27.91	peak
4	6914.763	8.50	35.35	41.76	47.13	49.22	74.00	-24.78	peak
5	7206.000	8.74	35.67	41.50	46.87	49.78	74.00	-24.22	peak
6	9608.000	10.81	37.34	37.76	42.13	52.52	74.00	-21.48	peak



Test Mode: 04; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.43	26.71	40.06	46.16	36.24	74.00	-37.76	peak
2	4443.453	6.71	32.96	41.82	47.49	45.34	74.00	-28.66	peak
3	4804.000	7.10	33.62	42.14	47.72	46.30	74.00	-27.70	peak
4	6995.172	8.54	35.49	41.70	47.51	49.84	74.00	-24.16	peak
5	7206.000	8.74	35.67	41.50	47.17	50.08	74.00	-23.92	peak
6	9608.000	10.81	37.34	37.76	42.27	52.66	74.00	-21.34	peak



Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.42	26.64	40.05	45.88	35.89	74.00	-38.11	peak
2	4392.376	6.66	32.92	41.78	48.16	45.96	74.00	-28.04	peak
3	4880.000	7.18	33.77	42.20	47.42	46.17	74.00	-27.83	peak
4	6874.906	8.48	35.28	41.78	47.65	49.63	74.00	-24.37	peak
5	7320.000	8.84	35.76	41.40	46.93	50.13	74.00	-23.87	peak
6	9760.000	10.76	37.41	37.50	42.12	52.79	74.00	-21.21	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-L

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.59	40.05	45.36	35.31	74.00	-38.69	peak
2	4443.453	6.71	32.96	41.82	48.10	45.95	74.00	-28.05	peak
3	4880.000	7.18	33.77	42.20	46.57	45.32	74.00	-28.68	peak
4	6018.999	8.26	34.60	42.39	49.80	50.27	74.00	-23.73	peak
5	7320.000	8.84	35.76	41.40	46.76	49.96	74.00	-24.04	peak
6	9760.000	10.76	37.41	37.50	42.08	52.75	74.00	-21.25	peak



Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-L

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.39	26.48	40.04	46.34	36.17	74.00	-37.83	peak
2	6.67	32.93	41.79	47.59	45.40	74.00	-28.60	peak
3	7.26	33.92	42.27	47.30	46.21	74.00	-27.79	peak
4	8.25	34.55	42.39	48.64	49.05	74.00	-24.95	peak
5	8.96	35.85	41.29	47.42	50.94	74.00	-23.06	peak
6	10.71	37.47	37.23	42.50	53.45	74.00	-20.55	peak



Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-L

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1574.265	3.33	26.09	39.99	46.73	36.16	74.00	-37.84	peak
2	4392.376	6.66	32.92	41.78	48.30	46.10	74.00	-27.90	peak
3	4960.000	7.26	33.92	42.27	47.12	46.03	74.00	-27.97	peak
4	6995.172	8.54	35.49	41.70	47.16	49.49	74.00	-24.51	peak
5	7440.000	8.96	35.85	41.29	48.73	52.25	74.00	-21.75	peak
6	9920.000	10.71	37.47	37.23	42.67	53.62	74.00	-20.38	peak



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-L 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.41	26.57	40.05	47.22	37.15	74.00	-36.85	peak
2	6.71	32.96	41.82	47.57	45.42	74.00	-28.58	peak
3	7.10	33.62	42.14	48.08	46.66	74.00	-27.34	peak
4	8.27	34.60	42.24	48.82	49.45	74.00	-24.55	peak
5	8.74	35.67	41.50	46.90	49.81	74.00	-24.19	peak
6	10.81	37.34	37.76	42.31	52.70	74.00	-21.30	peak



Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-L 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.35	26.22	40.01	46.84	36.40	74.00	-37.60	peak
2	6.73	32.98	41.85	48.55	46.41	74.00	-27.59	peak
3	7.10	33.62	42.14	48.45	47.03	74.00	-26.97	peak
4	8.46	35.21	41.81	47.81	49.67	74.00	-24.33	peak
5	8.74	35.67	41.50	46.73	49.64	74.00	-24.36	peak
6	10.81	37.34	37.76	42.80	53.19	74.00	-20.81	peak



Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-L 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	3.40	26.50	40.04	46.35	36.21	74.00	-37.79	peak
2	4482.150	6.74	32.99	41.86	48.13	46.00	74.00	-28.00	peak
3	4880.000	7.18	33.77	42.20	47.03	45.78	74.00	-28.22	peak
4	5535.047	8.19	34.23	42.36	50.38	50.44	74.00	-23.56	peak
5	7320.000	8.84	35.76	41.40	47.10	50.30	74.00	-23.70	peak
6	9760.000	10.76	37.41	37.50	42.41	53.08	74.00	-20.92	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: middle




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-L 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1667.951	3.40	26.55	40.04	46.08	35.99	74.00	-38.01	peak
2	4367.058	6.64	32.90	41.75	48.75	46.54	74.00	-27.46	peak
3	4880.000	7.18	33.77	42.20	47.23	45.98	74.00	-28.02	peak
4	6776.265	8.43	35.11	41.85	47.69	49.38	74.00	-24.62	peak
5	7320.000	8.84	35.76	41.40	47.66	50.86	74.00	-23.14	peak
6	9760.000	10.76	37.41	37.50	42.13	52.80	74.00	-21.20	peak



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-L 2M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1639.274	3.38	26.41	40.03	46.40	36.16	74.00	-37.84	peak
2	4469.214	6.73	32.98	41.85	49.98	47.84	74.00	-26.16	peak
3	4960.000	7.26	33.92	42.27	47.62	46.53	74.00	-27.47	peak
4	6679.040	8.38	34.93	41.91	48.11	49.51	74.00	-24.49	peak
5	7440.000	8.96	35.85	41.29	47.98	51.50	74.00	-22.50	peak
6	9920.000	10.71	37.47	37.23	42.44	53.39	74.00	-20.61	peak



Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-L 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.69	40.06	45.39	35.45	74.00	-38.55 peak
2	4495.125	6.76	33.00	41.87	48.68	46.57	74.00	-27.43 peak
3	4960.000	7.26	33.92	42.27	47.09	46.00	74.00	-28.00 peak
4	6995.172	8.54	35.49	41.70	47.27	49.60	74.00	-24.40 peak
5	7440.000	8.96	35.85	41.29	48.43	51.95	74.00	-22.05 peak
6	9920.000	10.71	37.47	37.23	42.42	53.37	74.00	-20.63 peak



Test Mode: 09; Polarity: Horizontal; Modulation:GFSK; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-R

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1629.825	3.37	26.36	40.02	45.91	35.62	74.00	-38.38	peak
2	4392.376	6.66	32.92	41.78	47.67	45.47	74.00	-28.53	peak
3	4804.000	7.10	33.62	42.14	46.85	45.43	74.00	-28.57	peak
4	6914.763	8.50	35.35	41.76	47.86	49.95	74.00	-24.05	peak
5	7206.000	8.74	35.67	41.50	46.63	49.54	74.00	-24.46	peak
6	9608.000	10.81	37.34	37.76	42.62	53.01	74.00	-20.99	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 09; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1406.443	3.12	25.53	39.90	47.44	36.19	74.00	-37.81	peak
2	4304.400	6.58	32.85	41.70	47.47	45.20	74.00	-28.80	peak
3	4804.000	7.10	33.62	42.14	48.18	46.76	74.00	-27.24	peak
4	6795.879	8.44	35.14	41.83	47.63	49.38	74.00	-24.62	peak
5	7206.000	8.74	35.67	41.50	46.74	49.65	74.00	-24.35	peak
6	9608.000	10.81	37.34	37.76	42.42	52.81	74.00	-21.19	peak



Test Mode: 09; Polarity: Horizontal; Modulation: GFSK; Channel: middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1667.951	3.40	26.55	40.04	45.69	35.60	74.00	-38.40	peak
2	4482.150	6.74	32.99	41.86	48.10	45.97	74.00	-28.03	peak
3	4880.000	7.18	33.77	42.20	47.97	46.72	74.00	-27.28	peak
4	6036.421	8.26	34.60	42.37	49.56	50.05	74.00	-23.95	peak
5	7320.000	8.84	35.76	41.40	48.01	51.21	74.00	-22.79	peak
6	9760.000	10.76	37.41	37.50	42.96	53.63	74.00	-20.37	peak



Test Mode: 09; Polarity: Vertical; Modulation:GFSK; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-R

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1634.543	3.38	26.39	40.03	46.07	35.81	74.00	-38.19	peak
2	4304.400	6.58	32.85	41.70	48.49	46.22	74.00	-27.78	peak
3	4880.000	7.18	33.77	42.20	47.03	45.78	74.00	-28.22	peak
4	6795.879	8.44	35.14	41.83	48.83	50.58	74.00	-23.42	peak
5	7320.000	8.84	35.76	41.40	46.21	49.41	74.00	-24.59	peak
6	9760.000	10.76	37.41	37.50	42.16	52.83	74.00	-21.17	peak



Test Mode: 09; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.59	40.05	46.53	36.48	74.00	-37.52	peak
2	4495.125	6.76	33.00	41.87	48.21	46.10	74.00	-27.90	peak
3	4960.000	7.26	33.92	42.27	48.02	46.93	74.00	-27.07	peak
4	6995.172	8.54	35.49	41.70	46.94	49.27	74.00	-24.73	peak
5	7440.000	8.96	35.85	41.29	47.68	51.20	74.00	-22.80	peak
6	9920.000	10.71	37.47	37.23	42.60	53.55	74.00	-20.45	peak



Test Mode: 09; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.59	40.05	46.08	36.03	74.00	-37.97	peak
2	4495.125	6.76	33.00	41.87	47.68	45.57	74.00	-28.43	peak
3	4960.000	7.26	33.92	42.27	46.63	45.54	74.00	-28.46	peak
4	6855.063	8.47	35.25	41.80	47.37	49.29	74.00	-24.71	peak
5	7440.000	8.96	35.85	41.29	47.82	51.34	74.00	-22.66	peak
6	9920.000	10.71	37.47	37.23	41.76	52.71	74.00	-21.29	peak



Test Mode: 10; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-R 2M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1551.677	3.31	25.97	39.98	46.33	35.63	74.00	-38.37	peak
2	4291.977	6.57	32.84	41.68	47.55	45.28	74.00	-28.72	peak
3	4804.000	7.10	33.62	42.14	47.71	46.29	74.00	-27.71	peak
4	6545.263	8.30	34.68	42.01	48.53	49.50	74.00	-24.50	peak
5	7206.000	8.74	35.67	41.50	46.86	49.77	74.00	-24.23	peak
6	9608.000	10.81	37.34	37.76	43.02	53.41	74.00	-20.59	peak



Test Mode: 10; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2402 TX RSE
Note : BLE-R 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.43	26.69	40.06	45.80	35.86	74.00	-38.14	peak
2	6.66	32.92	41.78	48.15	45.95	74.00	-28.05	peak
3	7.10	33.62	42.14	47.82	46.40	74.00	-27.60	peak
4	8.44	35.14	41.83	47.93	49.68	74.00	-24.32	peak
5	8.74	35.67	41.50	47.17	50.08	74.00	-23.92	peak
6	10.81	37.34	37.76	42.72	53.11	74.00	-20.89	peak



Test Mode: 10; Polarity: Horizontal; Modulation:GFSK; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-R 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.42	26.64	40.05	45.72	35.73	74.00	-38.27	peak
2	4109.872	6.39	32.69	41.51	49.30	46.87	74.00	-27.13	peak
3	4880.000	7.18	33.77	42.20	47.40	46.15	74.00	-27.85	peak
4	6855.063	8.47	35.25	41.80	48.22	50.14	74.00	-23.86	peak
5	7320.000	8.84	35.76	41.40	46.07	49.27	74.00	-24.73	peak
6	9760.000	10.76	37.41	37.50	42.72	53.39	74.00	-20.61	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 10; Polarity: Vertical; Modulation:GFSK; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2440 TX RSE
Note : BLE-R 2M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.69	40.06	46.34	36.40	74.00	-37.60	peak
2	4430.628	6.70	32.95	41.81	47.60	45.44	74.00	-28.56	peak
3	4880.000	7.18	33.77	42.20	46.61	45.36	74.00	-28.64	peak
4	6974.982	8.53	35.46	41.72	47.32	49.59	74.00	-24.41	peak
5	7320.000	8.84	35.76	41.40	46.09	49.29	74.00	-24.71	peak
6	9760.000	10.76	37.41	37.50	42.40	53.07	74.00	-20.93	peak



Test Mode: 10; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-R 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1615.754	3.36	26.29	40.02	46.68	36.31	74.00	-37.69	peak
2	4482.150	6.74	32.99	41.86	47.93	45.80	74.00	-28.20	peak
3	4960.000	7.26	33.92	42.27	47.19	46.10	74.00	-27.90	peak
4	6974.982	8.53	35.46	41.72	46.92	49.19	74.00	-24.81	peak
5	7440.000	8.96	35.85	41.29	47.68	51.20	74.00	-22.80	peak
6	9920.000	10.71	37.47	37.23	42.24	53.19	74.00	-20.81	peak



Test Mode: 10; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 21345AT/21346AT
Mode : 2480 TX RSE
Note : BLE-R 2M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1507.470	3.27	25.74	39.96	47.04	36.09	74.00	-37.91	peak
2	4379.699	6.65	32.91	41.77	48.61	46.40	74.00	-27.60	peak
3	4960.000	7.26	33.92	42.27	46.45	45.36	74.00	-28.64	peak
4	6835.278	8.46	35.21	41.81	47.47	49.33	74.00	-24.67	peak
5	7440.000	8.96	35.85	41.29	48.41	51.93	74.00	-22.07	peak
6	9920.000	10.71	37.47	37.23	42.56	53.51	74.00	-20.49	peak



8 Test Setup Photo

Refer to Setup Photos

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2106021345AT



10 Appendix

Appendix for 15.247

For Right earbuds



1. Duty Cycle



1.1 Test Result



Test Mode	Channel Frequency (MHz)	TX Type	ANT No.	T _{on} (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.378	0.625	60.48	2.18
	2440	SISO	1	0.378	0.625	60.48	2.18
	2480	SISO	1	0.378	0.626	60.38	2.19
2M	2402	SISO	1	0.194	0.625	31.04	5.08
	2440	SISO	1	0.193	0.625	30.88	5.10
	2480	SISO	1	0.194	0.625	31.04	5.08



1.2 Test Graph







2. Bandwidth



2.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.714	PASS
	2440	SISO	1	0.715	PASS
	2480	SISO	1	0.715	PASS
2M	2402	SISO	1	1.251	PASS
	2440	SISO	1	1.252	PASS
	2480	SISO	1	1.246	PASS



Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.041	Only for Report Use
	2440	SISO	1	1.041	Only for Report Use
	2480	SISO	1	1.041	Only for Report Use
2M	2402	SISO	1	2.063	Only for Report Use
	2440	SISO	1	2.063	Only for Report Use
	2480	SISO	1	2.066	Only for Report Use





2.2 Test Graph - 6dB Bandwidth











2.3 Test Graph - 99% Occupied Bandwidth










3. Maximum Conducted Output Power



3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	2.72	30	PASS
	2440	SISO	2.24	30	PASS
	2480	SISO	1.56	30	PASS
2M	2402	SISO	2.76	30	PASS
	2440	SISO	2.28	30	PASS
	2480	SISO	1.59	30	PASS

3.2 Test Graph












4. Maximum Power Spectral Density (PSD)



4.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-12.57	≤8	PASS
	2440	SISO	-13.04	≤8	PASS
	2480	SISO	-13.72	≤8	PASS
2M	2402	SISO	-14.74	≤8	PASS
	2440	SISO	-15.16	≤8	PASS
	2480	SISO	-15.96	≤8	PASS

4.2 Test Graph












5. Unwanted Emissions in Non-restricted Frequency Bands

5.1 Test Result

Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-18.08	PASS
	2440	SISO	1	Refer to test graph	-18.08	PASS
	2480	SISO	1	Refer to test graph	-18.08	PASS
2M	2402	SISO	1	Refer to test graph	-18.42	PASS
	2440	SISO	1	Refer to test graph	-18.42	PASS
	2480	SISO	1	Refer to test graph	-18.42	PASS



5.2 Test Graph











Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com












For Left earbuds



1. Duty Cycle



1.1 Test Result

Test Mode	Channel Frequency (MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.378	0.625	60.48	2.18
	2440	SISO	1	0.378	0.625	60.48	2.18
	2480	SISO	1	0.378	0.625	60.48	2.18
2M	2402	SISO	1	0.194	0.625	31.04	5.08
	2440	SISO	1	0.193	0.625	30.88	5.10
	2480	SISO	1	0.194	0.625	31.04	5.08

1.2 Test Graph








Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com





2. Bandwidth



2.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.714	PASS
	2440	SISO	1	0.712	PASS
	2480	SISO	1	0.715	PASS
2M	2402	SISO	1	1.252	PASS
	2440	SISO	1	1.254	PASS
	2480	SISO	1	1.243	PASS

Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.042	Only for Report Use
	2440	SISO	1	1.042	Only for Report Use
	2480	SISO	1	1.042	Only for Report Use
2M	2402	SISO	1	2.065	Only for Report Use
	2440	SISO	1	2.065	Only for Report Use
	2480	SISO	1	2.065	Only for Report Use



2.2 Test Graph - 6dB Bandwidth











2.3 Test Graph - 99% Occupied Bandwidth










3. Maximum Conducted Output Power



3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	2.83	30	PASS
	2440	SISO	2.30	30	PASS
	2480	SISO	1.58	30	PASS
2M	2402	SISO	2.89	30	PASS
	2440	SISO	2.36	30	PASS
	2480	SISO	1.63	30	PASS

3.2 Test Graph












4. Maximum Power Spectral Density (PSD)



4.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3kHz)	Verdict
			Ant 1		
1M	2402	SISO	-12.38	≤8	PASS
	2440	SISO	-12.99	≤8	PASS
	2480	SISO	-13.57	≤8	PASS
2M	2402	SISO	-14.65	≤8	PASS
	2440	SISO	-15.11	≤8	PASS
	2480	SISO	-15.79	≤8	PASS

4.2 Test Graph












5. Unwanted Emissions in Non-restricted Frequency Bands



5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-17.94	PASS
	2440	SISO	1	Refer to test graph	-17.94	PASS
	2480	SISO	1	Refer to test graph	-17.94	PASS
2M	2402	SISO	1	Refer to test graph	-18.28	PASS
	2440	SISO	1	Refer to test graph	-18.28	PASS
	2480	SISO	1	Refer to test graph	-18.28	PASS



5.2 Test Graph


















- End of the Report -

