

## FCC RF Exposure

EUT Description: Intelligent connected aromatherapy machine

Test type.: JD01

Series model: N/A

FCC ID: 2BEDL-JD01

Equipment type: Mobile equipment

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

| Frequency range<br>(MHz)                                | Electric field<br>strength<br>(V/m) | Magnetic field strength<br>(A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|---------------------------------------------------------|-------------------------------------|----------------------------------|----------------------------------------|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                                     |                                  |                                        |                             |
| 0.3–3.0                                                 | 614                                 | 1.63                             | *(100)                                 | 6                           |
| 3.0–30                                                  | 1842/f                              | 4.89/f                           | *(900/f <sup>2</sup> )                 | 6                           |
| 30–300                                                  | 61.4                                | 0.163                            | 1.0                                    | 6                           |
| 300–1500                                                |                                     |                                  | f/300                                  | 6                           |
| 1500–100,000                                            |                                     |                                  | 5                                      | 6                           |
| (B) Limits for General Population/Uncontrolled Exposure |                                     |                                  |                                        |                             |
| 0.3–1.34                                                | 614                                 | 1.63                             | *(100)                                 | 30                          |
| 1.34–30                                                 | 824/f                               | 2.19/f                           | *(180/f <sup>2</sup> )                 | 30                          |
| 30–300                                                  | 27.5                                | 0.073                            | 0.2                                    | 30                          |
| 300–1500                                                |                                     |                                  | f/1500                                 | 30                          |
| 1500–100,000                                            |                                     |                                  | 1.0                                    | 30                          |

F = frequency in MHz

Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where :

$P_d$  = power density in mW/cm<sup>2</sup>,

$P_{out}$  = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi$  = 3.14;

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3. Test Result of RF Exposure Evaluation

| Modulation | Channel Freq. (MHz) | Conduct ed power (dBm) | Max tune-up power (mW) | Antenna Gain (dBi) | Antenna gain numeric | Evaluation result (mW/cm2 ) | Power density Limits (mW/cm2) |
|------------|---------------------|------------------------|------------------------|--------------------|----------------------|-----------------------------|-------------------------------|
| GFSK       | 2402                | 2.49                   | 1.77                   | 1.35               | 1.36                 | 0.00047914                  | 1                             |
|            | 2440                | 2.41                   | 1.74                   | 1.35               | 1.36                 | 0.000471019                 | 1                             |
|            | 2480                | 2.94                   | 1.97                   | 1.35               | 1.36                 | 0.00053328                  | 1                             |

Conclusion: the max result :  $0.00053328 \leq 1.0$  compliance with FCC's RF Exposure.

Conclusion: No SAR is required